

# L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021

This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



# Configuration File Formats

- 1 Configuration File Formats
- 2 Command-line Arguments
- 3 Environment Variables
- 4 Abstractions
- 5 Complexity
  - Trend
  - Calculation
- 6 Meeting

# Learning Outcomes

Students will be able to

- differentiate between configuration sources
- unify configuration sources via specifications
- (calculate complexity of configuration settings)

# Definition

A ***configuration file*** is a file containing configuration settings.

# Definition

A ***configuration file*** is a file containing configuration settings.  
A Web server configuration file:

```
1 port=80 ; comment
2 address=127.0.0.1
```

## Question

What are keys? What are configuration values? What is metadata?

# Definition

A ***configuration file*** is a file containing configuration settings.

A Web server configuration file:

```
1 port=80 ; comment
2 address=127.0.0.1
```

The configuration values are 80 and 127.0.0.1, respectively.  
Other information in the configuration file is metadata for the configuration settings (such as the comment).

# Configuration File Formats

- CSV (comma-separated values)
- semi-structured
- programming language
- literate

# CSV formats

- passwd: 3<sup>rd</sup> November, 1971
- passwd and group use : as separator
- are difficult to extend (e.g., GECOS)
- today mostly used for legacy reasons
- are replaced one-by-one (e.g., inetd, crontab)



# Programming Language

- + trivial for developers (source the file)
- + above-average quality of error message
- makes automatic change of individual values harder
- very hard to use for people who do not know the programming language
- does not separate code and data

# Trends

- away from CSV
- towards general-purpose serialization formats (INI, JSON)
- human-read/writable (YAML, TOML)
- programming language as configuration file

# Method

What do FLOSS developers say?

**Q:** survey with 672 persons visiting, 162 persons completing the survey [4]

**S:** source code analysis of 16 applications, comprising 50 million lines of code [4]

# Why are so many formats present?

*Q: "In which way have you used or contributed to the configuration system/library/API in your previously mentioned FLOSS project(s)?" [4]*

- 19 % persons ( $n = 251$ ) have introduced a configuration file format.
- 29 % implemented a configuration file parser.
- 15 % introduced a configuration system/library/API.
- 34 % used external configuration access APIs.

# Multitude of Formats

- on every system a multitude of (legacy) configuration file formats exist
- the number grows fast
- thus applications usually have to deal with some legacy formats

## Requirement

*A configuration library must be able to integrate (legacy) systems and must fully support (legacy) configuration files.*


## L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021

This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



# Command-line Arguments

- 1 Configuration File Formats
- 2 Command-line Arguments**
- 3 Environment Variables
- 4 Abstractions
- 5 Complexity
  - Trend
  - Calculation
- 6 Meeting

# Is there something else?

- configuration files are the most researched of all configuration sources [2]
- but it is neither the most used nor most popular [4]



*Q: "Which configuration systems/libraries/APIs have you already used or would like to use in one of your FLOSS project(s)?"*

- command-line arguments (92 %,  $n = 222$ )
- environment variables (79 %,  $n = 218$ )
- S: API `getenv` is used omnipresently with 2,683 occurrences
- configuration files (74 %,  $n = 218$ ))

*Q: "What is your experience with the following configuration systems/libraries/APIs?"*

- getenv (10 %,  $n = 198$ )
- configuration files (6 %,  $n = 190$ )
- command-line options (4 %,  $n = 210$ )
- X/Q/GSettings (41 %, 14 %, 35 %)
- KConfig (21 %)
- dconf (42 %)
- plist (32 %)
- Windows Registry (69 %)

# Semantics

- passed by main for a new process via  
(int argc, char \*\* argv)
- visible from other processes (e.g., via ps aux)
- could be passed along to subprocesses but hardly done
- need to be parsed by process
- portability: differences in parsing
- cannot be changed from outside (requires restart, no IPC)

## L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021

This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



# Environment Variables

- 1 Configuration File Formats
- 2 Command-line Arguments
- 3 Environment Variables**
- 4 Abstractions
- 5 Complexity
  - Trend
  - Calculation
- 6 Meeting

# Usage

- 1 bypassing other configuration accesses (Q: 45 %)
- 2 locating configuration files
- 3 debugging and testing (Q: 55 %, S: 1,152, i. e. 43 %)
- 4 sharing configuration settings across applications (Q: 53 %, S: 716, i. e. 47 %)
- 5 for configuration settings unlikely to be changed by a user (Q: 20 %)
- 6 *“even when it is used inside a loop”* (Q: 2 %)

# Semantics

- are also per-process (`/proc/self/envron`)
- are not visible from other processes
- are automatically inherited by subprocesses
- need to be parsed by process (`[extern] char **environ`) but API is provided (`getenv`)
- cannot be changed from outside (requires restart or an additional IPC mechanism)

# getenv

- is widely standardized, including SVr4, POSIX.1-2001, 4.3BSD, C89, C99 [1],
- is supported by many programming languages, and
- enforces key=value convention.



# Portability

- no separators for values defined
- case sensitivity problems
- often many environment variables for the same purpose:  
TMP, TEMP, or TMPDIR
- sometimes one environment variable for different purposes:  
PATH

## L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021

This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



# Abstractions

- 1 Configuration File Formats
- 2 Command-line Arguments
- 3 Environment Variables
- 4 Abstractions**
- 5 Complexity
  - Trend
  - Calculation
- 6 Meeting

# User View

- command-line for trying out configuration settings
- environment variables for configuration settings within a shell
- configuration files for persistent configuration settings

# Abstraction

## Requirement

*A configuration library must be able to integrate (legacy) systems and must fully support (legacy) configuration files.*

How can we deal with the many formats?


# Key-Value

A key-value pair is the simplest generic data structure [7]. While all these formats above have many differences, all of them represent configuration settings as **key-value pairs** [2, 3, 6, 8].

For configuration as program you need to execute them first.


# KeySet (Recapitulation)

The common data structure between plugins:



# Mounting

**Mounting** integrates a backend into the key database [5]. Hence, ELEKTRA allows several backends to deal with configuration files at the same time. Each backend is responsible for its own subtree of the key database.





# Elektra

```
1 [kdb/printversion]
2 description = "print version information"
3 opt = v
4 opt/long = version
5 opt/arg = none
```

- gopts puts Keys in the proc namespace
- <https://www.libelektra.org/tutorials/command-line-options>

```
kdb -v      kdb --version      VERSION=1 kdb
```

How can we deal with the many sources?

## Requirement


*A configuration library must support all three popular ways for configuration access: configuration files, command-line options, and environment variables.*

# Plugins


Different backends can use different plugins:

`/sw` in the INI file `config.ini`

`/sw/libreoffice` in the XML file `libreoffice.xml`



# Cascading



# Conclusion

- three different configuration sources widely used
- all three used for different reasons but often for the same configuration settings
- many different configuration file formats
- abstractions: key-value, mounting, and cascading

## L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021


This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



# Complexity


- 1 Configuration File Formats
- 2 Command-line Arguments
- 3 Environment Variables
- 4 Abstractions
- 5 Complexity**
  - Trend
  - Calculation
- 6 Meeting

# Trend Firefox









# Trend Chromium



# Trend Configuration Files



# Types of Complexity

- complexity in access:
  - many different formats
  - non-uniformity
  - transformations
- configuration settings
  - number of settings  $s$
  - number of values  $n$
  - dependences between settings

# Calculation of Complexity

Using enumerative combinatorics:

- number of configurations:  $n^s$
- for  $N$  groups of different  $n$  and  $s$  (i.e.,  $n_1 \dots n_N$  with  $s_1 \dots s_N$  occurrences):

$$\prod_{i=1}^N n_i^{s_i}$$

- more difficult to calculate (or unbounded) for dependences, module instantiations, arrays, ...

# Calculation of Complexity

Examples:

- 600 boolean settings in Apache httpd (let us assume  $n = 2$ ):

# Calculation of Complexity

Examples:

- 600 boolean settings in Apache httpd (let us assume  $n = 2$ ):  
 $2^{600} \approx 10^{180}$
- 19 integer settings:

# Calculation of Complexity

## Examples:

- 600 boolean settings in Apache httpd (let us assume  $n = 2$ ):  
 $2^{600} \approx 10^{180}$
- 19 integer settings:  $2^{32^{19}} = 2^{32 \cdot 19} = 2^{609} \approx 10^{183}$
- for 20 boolean and 20 enums with 5 possibilities:

# Calculation of Complexity

Examples:

- 600 boolean settings in Apache httpd (let us assume  $n = 2$ ):  
 $2^{600} \approx 10^{180}$
- 19 integer settings:  $2^{32^{19}} = 2^{32 \cdot 19} = 2^{609} \approx 10^{183}$
- for 20 boolean and 20 enums with 5 possibilities:

$$2^{20} * 5^{20} = 10^{20}$$



# Calculation of Complexity (cont.)

Examples:

- an array with 1 – 20 boolean settings:

---

<sup>1</sup><https://downloads.mysql.com/docs/refman-5.7-en.pdf>

# Calculation of Complexity (cont.)

## Examples:

- an array with 1 – 20 boolean settings:  $2^{20}$
- MySQL has 461 settings, of which 216 are non-simple types [9]  
(let us assume  $n = \{3, 20\}$ ):

---

<sup>1</sup><https://downloads.mysql.com/docs/refman-5.7-en.pdf>

# Calculation of Complexity (cont.)

## Examples:

- an array with 1 – 20 boolean settings:  $2^{20}$
- MySQL has 461 settings, of which 216 are non-simple types [9]  
(let us assume  $n = \{3, 20\}$ ):  $3^{245} * 20^{216} \approx 10^{397}$   
(settings are explained in 5560 pages<sup>1</sup>)

---

<sup>1</sup><https://downloads.mysql.com/docs/refman-5.7-en.pdf>

# Calculation of Complexity (cont.) [2]

Examples:

- in Firefox resulting in 846 boolean options and 1,111 options of either integer or string, each with three values

# Calculation of Complexity (cont.) [2]

## Examples:

- in Firefox resulting in 846 boolean options and 1,111 options of either integer or string, each with three values

$$2^{846} * 3^{1111} \approx 6.46 * 10^{259}$$

- LibreOffice

# Calculation of Complexity (cont.) [2]

## Examples:

- in Firefox resulting in 846 boolean options and 1,111 options of either integer or string, each with three values

$$2^{846} * 3^{1111} \approx 6.46 * 10^{259}$$

- LibreOffice

$$2^{4433} * 3^{31889}$$

## L04 Configuration Sources

Markus Raab

Institute of Information Systems Engineering, TU Wien

14.04.2021

This work is licensed under a Creative Commons “*Attribution-ShareAlike 4.0 International*” license.



# Meeting

- 1 Configuration File Formats
- 2 Command-line Arguments
- 3 Environment Variables
- 4 Abstractions
- 5 Complexity
  - Trend
  - Calculation
- 6 Meeting



## Task

Calculate complexity of your teamwork and add to PR.

See `scripts/complexity.rb`

# Introduce somebody

## Task

Talk with someone about your favourite configuration file format.

## Task

Did you implement a configuration file parser and/or invented a new configuration file format?

## Task

Explain to everyone about the other person and his/her favourite configuration file format.

## Task

Discuss the differences of mounting and cascading with your neighbor.

Task

Break.

# Outlook

- Challenges in Configuration Management

# Outlook

- Challenges in Configuration Management
- Properties: self-describing, idempotent, round-tripping

# Outlook

- Challenges in Configuration Management
- Properties: self-describing, idempotent, round-tripping
- **Validation**

# Outlook

- Challenges in Configuration Management
- Properties: self-describing, idempotent, round-tripping
- Validation
- Configuration management languages



- [1] *getenv(3) Linux User's Manual*, March 2017.
- [2] Dongpu Jin, Xiao Qu, Myra B. Cohen, and Brian Robinson. Configurations everywhere: Implications for testing and debugging in practice. In *Companion Proceedings of the 36th International Conference on Software Engineering, ICSE Companion 2014*, pages 215–224, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2768-8. doi: 10.1145/2591062.2591191. URL <http://dx.doi.org/10.1145/2591062.2591191>.
- [3] Neal Lathia, Kiran Rachuri, Cecilia Mascolo, and George Roussos. Open source smartphone libraries for computational social science. In *Proceedings of the 2013 ACM Conference on Pervasive and Ubiquitous Computing Adjunct Publication, UbiComp '13 Adjunct*, pages 911–920, New York, NY, USA, 2013. ACM. ISBN 978-1-4503-2215-7. doi:

10.1145/2494091.2497345. URL

<http://dx.doi.org/10.1145/2494091.2497345>.

- [4] Markus Raab and Gergő Barany. *Challenges in Validating FLOSS Configuration*, pages 101–114. Springer International Publishing, Cham, 2017. ISBN 978-3-319-57735-7. doi: 10.1007/978-3-319-57735-7\_11. URL [http://dx.doi.org/10.1007/978-3-319-57735-7\\_11](http://dx.doi.org/10.1007/978-3-319-57735-7_11).
- [5] Markus Raab and Patrick Sabin. Implementation of Multiple Key Databases for Shared Configuration. <ftp://www.markus-raab.org/elektra.pdf>, March 2008. Accessed February 2014.
- [6] Ariel Rabkin and Randy Katz. Static extraction of program configuration options. In *Software Engineering (ICSE), 2011 33rd International Conference on*, pages 131–140. IEEE, 2011.

- [7] Thomas Strang and Claudia Linnhoff-Popien. A context modeling survey. In *First International Workshop on Advanced Context Modelling, Reasoning And Management at UbiComp 2004*, September 2004. URL <http://elib.dlr.de/7444/>.
- [8] Tianyin Xu, Jiaqi Zhang, Peng Huang, Jing Zheng, Tianwei Sheng, Ding Yuan, Yuanyuan Zhou, and Shankar Pasupathy. Do not blame users for misconfigurations. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 244–259. ACM, 2013.
- [9] Tianyin Xu, Long Jin, Xuepeng Fan, Yuanyuan Zhou, Shankar Pasupathy, and Rukma Talwadker. Hey, you have given me too many knobs! Understanding and dealing with over-designed configuration in system software. In *Proceedings of the 2015 10th Joint Meeting on Foundations of Software Engineering, ESEC/FSE 2015*, pages 307–319, New York, NY, USA, 2015. ACM. ISBN 978-1-4503-3675-8. doi:

10.1145/2786805.2786852. URL  
<http://dx.doi.org/10.1145/2786805.2786852>.