

Configuration Management

Markus Raab

Institute of Information Systems Engineering, TU Wien

22.05.2018



Lecture is every week Wednesday 09:00 - 11:00.

06.03.2019: topic, teams

13.03.2019: TISS registration, initial PR

20.03.2019: other registrations, guest lecture

27.03.2019: PR for first issue done, second started

03.04.2019: first issue done, PR for second

10.04.2019: mid-term submission of exercises

08.05.2019: different location: Complang Library

15.05.2019:

22.05.2019: all 5 issues done

29.05.2019:

05.06.2019: final submission of exercises

12.06.2019:

19.06.2019: last corrections of exercises

26.06.2019: exam

Tasks for today

(until 22.05.2019 23:59)

Task

All issues done.

Tasks for today

(until 22.05.2019 23:59)

Task

Continue teamwork and homework.

Popular Topics

14	tools	4	design
9	testability	4	cascading
9	code-generation	4	architecture of access
7	context-awareness	3	configuration sources
6	specification	3	config-less systems
6	misconfiguration	2	secure conf
6	complexity reduction	2	architectural decisions
5	validation	1	push vs. pull
5	points in time	1	infrastructure as code
5	error messages	1	full vs. partial
5	auto-detection	1	convention over conf
4	user interface	1	CI/CD
4	introspection	0	documentation

Goals for today

learning outcome:

- remember how to use configuration specification as documentation
- remember requirement for synchronization
- remember example of 3-way merge
- remember types of configuration

Modularity (Recapitulation)

Vertical modularity describes how strongly separated the configuration accesses of different applications is.

Horizontal modularity describes how strongly separated modules implementing configuration access for a single application is.

Introspection (Recapitulation)

Task

What is internal and external specification? What is introspection?

- internal: within applications' source code
- unified get/set access to (meta*)-key/values
- access via applications, CLI, GUI, web-UI, ...
- access via any programming language (similar to file systems)
- GUI, web-UI can semantically interpret metadata
- needed as communication of producers and consumers of configuration
- essential for *no-futz computing* Holland et al. [4]

Guarantees (Recapitulation)

Question

How to ensure that configuration access points match with present configuration settings?

Configuration Specification:

- without specification you and others do not even know which settings are available
- needed for any further techniques we will discuss:
 - code generation guarantees that configuration access points match with specification
 - validation guarantees that configuration settings match with specification

Testing (Recapitulation)

Question

What do we want to test? What do we ask ourselves?

- That settings do what they should (devs and admins)
- That settings are properly validated (devs [12])
- Regression tests [10]
- Are all settings implemented?
- Are all settings used in tests?
- Are there unused settings in the code?

When are settings used? (Recapitulation)

- Implementation-time** configuration accesses are hard-coded settings in the source code repository. For example, architectural decisions [3] lead to implementation-time settings.
- Compile-time** configuration accesses are configuration accesses resolved by the build system while compiling the code.
- Deployment-time** configuration accesses are configuration accesses while the software is installed.
- Load-time** configuration accesses are configuration accesses during the start of applications.
- Run-time** configuration accesses are configuration accesses during execution not limited to the startup procedure.

Latent Misconfiguration (Recapitulation)

Phases when we can detect misconfigurations:

- Compilation stage in configuration management tool
- Writing configuration settings on nodes
- Starting applications (load-time)
- When configuration setting is actually used (run-time)

Problem

More context vs. easier to detect and fix.

Documentation

- 1 Documentation
- 2 3-way merge
- 3 Team Work
- 4 Context-Awareness

Q: In detail, persons found it very important that (multiple choice, $n \geq 150$, “You want to configure a FLOSS application. How important are the following ways for you?”):

- 48 % documentation is shipped with the application
- 36 % configuration examples are shipped with the applications
- 17 % “google, stackoverflow... (looking for my problem)”
- 14 % looking at the website of the application
- 14 % use UIs that help them
- 14 % look into the source code
- 11 % “wiki, tutorials... (looking for complete solutions)”
- 5 % look into the configuration specification
- 2 % ask colleagues and friends

There are at least two forms of documentation necessary:

- Explanations
- Examples

Generation helps to avoid duplication:

Requirement

There must be a support for shipping correct documentation and examples generated from the configuration specifications.

Question

How to avoid duplication between description text and other parts?

- Render type and defaults into the documentation
- Render requirements and rationale into the documentation
- Use visibility to only show relevant configuration settings

Example

```
1 [slapd/threads/listener]
2   check/range := 1,2,4,8,16
3   default := 1
4   description := adjust to use more threads
5   rationale := needed for many-core systems
6   requirement := 1234
7   visibility := user
```

Reevaluate specifications (Recapitulation)

In which situations should you reevaluate if a configuration setting (specification) is needed?

- ① a requirement,
- ② an architectural decision,
- ③ a technical need, and
- ④ an ad hoc decision.

3-way merge

- 1 Documentation
- 2 3-way merge
- 3 Team Work
- 4 Context-Awareness

Synchronization

Problem: transient and persistent configuration settings might be out-of-sync [5]

Requirement

Configuration libraries must provide ways to keep transient and persistent views consistent.

Solutions:

- Often write out configuration settings.
- Many conflicts can be resolved with a semantic 3-way merge.

Semantic 3-way merge

We can resolve many conflicts automatically, if we consider:

- the key/value structure (vs. line-based)
- the origin of both files
- the type of settings

For example, when upgrading slapd:

- System administrator changed the file (Ours).
- Package maintainer changed the file (Theirs).

Conflicts Example

Ours:

```
1 slapd/threads/listener=4
2
3 abc = \
4     def
```

Theirs:

```
1 abc = def
2 slapd/threads/listener=8
```

Origin:

```
1 slapd/threads/listener=8
2 abc=def
```

Team Work

- 1 Documentation
- 2 3-way merge
- 3 Team Work
- 4 Context-Awareness

Step 1 (5 min)

Familiarize yourself with one of the configuration systems:

- 1 environment variables (Factor 12)
- 2 QSettings
- 3 Apache Commons Configurations
- 4 plist
- 5 Windows Registry
- 6 any other system you want to... (laptop)

Step 2 (45 min)

Come together in a group

- ① decide who will create flip chart, moderate, and present
- ② explain the system you looked into
- ③ explain what the system could do for the task
- ④ create together an architecture that fulfils the goals

Goals

- 1 configuration-management friendly
- 2 early detection of misconfiguration
- 3 smooth upgrades
- 4 transient and persistent configuration consistent
- 5 consistent documentation
- 6 suitable and context-aware configurations
- 7 reuse software as much as possible but integrate them nicely

Requirements

Design a camera system:

- 1 that is able to take single pictures and streams
- 2 pluggable camera modules (lenses, image sensor, ...)
- 3 should have camera profiles for different vendors
- 4 a Web-UI that shows all configuration settings
- 5 support remote configuration protocol (Web, SNMP, CMs, ...)
- 6 time synchronization via NTP
- 7 should be easily upgradeable (with fallback if the upgrade fails)

Tasks

- 1 design and architecture of configuration settings
- 2 design and architecture of configuration access
- 3 design decisions (which languages, which software)
- 4 explain how to ensure smooth upgrades
- 5 provide documentation for operators (via IP)
- 6 ensure synchronized, suitable and context-aware configuration
- 7 reuse software as much as possible but integrate them nicely

Outlook

- ① design and architecture of configuration settings
- ② design and architecture of configuration access
- ③ design decisions (which languages, which software)
- ④ explain how to ensure smooth upgrades
- ⑤ provide documentation for operators (via IP)
- ⑥ ensure synchronized, suitable and context-aware configuration
- ⑦ reuse software as much as possible but integrate them nicely

Context-Awareness

- 1 Documentation
- 2 3-way merge
- 3 Team Work
- 4 Context-Awareness

If you're a baker, making bread, you're a baker. If you make the best bread in the world, you're not an artist, but if you bake the bread in the gallery, you're an artist. So the context makes the difference.

— Marina Abramovic

As adapted from Chalmers [1]:


***Context** is the circumstances relevant to the configuration settings of the application.*

We extend the definition with:

***Context-aware configurations** are configuration settings that are consistent with its context. **Context-aware configuration access** is configuration access providing context-aware configuration.*

Types of Configuration


- Valid configuration** does not contradict the present validation specifications. With a valid configuration, applications can start but they may not do what the user wanted or may be inconsistent with context.
- Suitable configuration** is valid with respect to additional specifications from the user that describe the system the user requires [9].
- Optimal configuration** is optimal with respect to given optimization criteria. Optimization criteria are important if managing configuration of many computers but are rarely needed for configuration access discussed in this book.
- Context-aware configuration** is in accordance with its context. Unlike configuration settings, the context changes in ways outside of our control.



Viewpoints

- Sensors:** derive context from information sources of the system. Adding new context sensors increases the context available in a system.
- Users:** Context awareness can be subjective with respect to the needs of a user. For different users, we may need different context specifications. Configuration that is context aware for one user, can be context unaware regarding the wishes of another user. According to Khalil and Connelly [7, 8] personalization is essential.
- Time:** Because context varies in time, on changes, we need to renew the context awareness of configuration settings. In such situations we speak of *context changes* [2, 6].

Cascading (Recapitulation)



Context-aware Lookup

- Determine threads from CPUs:

```
1 [env/layer/cpu]
2   type := long
3 [slapd/threads/listener]
4   context := /slapd/threads/%cpu%/listener
```

- Determine vibration from sensors:

```
1 [phone/call/vibration]
2   type := boolean
3   context := /phone/call/%inocket%/vibration
```

- Determine proxy settings from network:

```
1 [env/override/http_proxy]
2   context := /http_proxy/%interface%/%network%
```

- [1] Daniel Chalmers. *Contextual mediation to support ubiquitous computing*. PhD thesis, University of London, 2002.
- [2] Kurt Geihs, Paolo Barone, Frank Eliassen, Jacqueline Floch, Rolf Fricke, Eli Gjølven, Svein O. Hallsteinsen, Geir Horn, Mohammad Ullah Khan, Alessandro Mamelli, George A. Papadopoulos, Nearchos Paspallis, Roland Reichle, and Erlend Stav. A comprehensive solution for application-level adaptation. *Software: Practice and Experience*, 39(4): 385–422, 2009. ISSN 1097-024X. URL <http://dx.doi.org/10.1002/spe.900>.
- [3] Neil B Harrison, Paris Avgeriou, and Uwe Zdun. Using patterns to capture architectural decisions. *Software, IEEE*, 24(4): 38–45, 2007. ISSN 0740-7459. doi: 10.1109/MS.2007.124.

- [4] David A. Holland, William Josephson, Kostas Magoutis, Margo I. Seltzer, Christopher A. Stein, and Ada Lim. Research issues in no-futz computing. In *Hot Topics in Operating Systems, 2001. Proceedings of the Eighth Workshop on*, pages 106–110. IEEE, May 2001. doi: 10.1109/HOTOS.2001.990069.
- [5] Dongpu Jin, Xiao Qu, Myra B. Cohen, and Brian Robinson. Configurations everywhere: Implications for testing and debugging in practice. In *Companion Proceedings of the 36th International Conference on Software Engineering, ICSE Companion 2014*, pages 215–224, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2768-8. doi: 10.1145/2591062.2591191. URL <http://dx.doi.org/10.1145/2591062.2591191>.

- [6] Tetsuo Kamina, Tomoyuki Aotani, Hidehiko Masuhara, and Tetsuo Tamai. Context-oriented software engineering: A modularity vision. In *Proceedings of the 13th International Conference on Modularity, MODULARITY '14*, pages 85–98, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2772-5.
- [7] Ashraf Khalil and Kay Connelly. *Context-Aware Configuration: A Study on Improving Cell Phone Awareness*, pages 197–209. Springer Berlin Heidelberg, Berlin, Heidelberg, 2005. ISBN 978-3-540-31890-3. doi: 10.1007/11508373_15. URL http://dx.doi.org/10.1007/11508373_15.
- [8] Ashraf Khalil and Kay Connelly. *Improving Cell Phone Awareness by Using Calendar Information*, pages 588–600. Springer Berlin Heidelberg, Berlin, Heidelberg, 2005. ISBN 978-3-540-31722-7. doi: 10.1007/11555261_48. URL http://dx.doi.org/10.1007/11555261_48.

- [9] Manuele Kirsch-Pinheiro, Raúl Mazo, Carine Souveyet, and Danillo Sprovieri. Requirements analysis for context-oriented systems. *Procedia Computer Science*, 83:253–261, 2016. ISSN 1877-0509. doi: <http://dx.doi.org/10.1016/j.procs.2016.04.123>. URL <http://www.sciencedirect.com/science/article/pii/S1877050916301466>. The 7th International Conference on Ambient Systems, Networks and Technologies (ANT 2016) / The 6th International Conference on Sustainable Energy Information Technology (SEIT-2016) / Affiliated Workshops.
- [10] Xiao Qu, Myra B. Cohen, and Gregg Rothermel. Configuration-aware regression testing: An empirical study of sampling and prioritization. In *Proceedings of the 2008 International Symposium on Software Testing and Analysis, ISSTA '08*, pages 75–86, New York, NY, USA, 2008. ACM.

ISBN 978-1-60558-050-0. doi: 10.1145/1390630.1390641.
URL <http://doi.acm.org/10.1145/1390630.1390641>.

- [11] Markus Raab and Gergő Barany. Introducing context awareness in unmodified, context-unaware software. In *Proceedings of the 12th International Conference on Evaluation of Novel Approaches to Software Engineering - Volume 1: ENASE*, pages 218–225. INSTICC, ScitePress, 2017. ISBN 978-989-758-250-9. doi: 10.5220/0006326602180225.
- [12] Tianyin Xu, Jiaqi Zhang, Peng Huang, Jing Zheng, Tianwei Sheng, Ding Yuan, Yuanyuan Zhou, and Shankar Pasupathy. Do not blame users for misconfigurations. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 244–259. ACM, 2013.