

Figure 8: **Scaling results on jailbreaking**. Jailbreak awareness of PCDs tends to improve with the number of pretraining tokens. Including more concepts ($k = 32$) than was used during training ($k = 16$) also increases jailbreak awareness. However, including too many concepts ($k = 64$) can reduce performance due to the decoder input being too out-of-distribution.

For the PCD and LatentQA decoders, we feed in the subject model's activations from the jailbreak prompt (but not the response). For the prompting baselines, we consider asking the subject model in first person (as a direct continuation of the jailbreak conversation) and in third person (passing in a transcript of the conversation and asking the subject model what happened). For each baseline setting, we try one variant where the subject model has access to the full jailbreak response, and one variant where the response is redacted.

From initial experiments, we found that both the decoder and prompting-based methods were sensitive to the phrasing of the question. We therefore test 3 different question templates, and for each method and jailbreak, choose the one that led to the highest awareness. See Appendix A.6 for full details on the attacks, baselines, judge prompts, and questions asked.

PCDs are aware of dangerous actions. We report results on all methods and settings in Figure 7. There is significant variation in performance across settings, but on average PCDs outperform both LatentQA and direct prompting. This is most apparent on *Dream*, where the PCD ($k = 16$) achieves 50% accuracy while all other methods are below 30%.

In some cases, notably *3 Words*, PCDs appear to be significantly harmed by the bottleneck: removing it entirely more than triples performance, even though this makes the decoder inputs OOD. In Section 4, we saw that the bottleneck created issues with small amounts of pretraining data, but improved with more data. This motivates us to also consider scaling behavior for jailbreak awareness, by repeating the same evaluation above with varying amounts of pretraining data.

Awareness scales with pretraining data. We report these scaling results in Figure 8. Jailbreak awareness consistently improves with more pretraining tokens. This is most apparent for *3 Words*, the most complicated jailbreak, for which awareness appears emergently around 72M tokens.

PCDs have better inductive bias than LatentQA. Despite being pretrained and finetuned on the same data, the 72M PCD with no bottleneck performs substantially better than the LatentQA decoder. This may be because the presence of the encoder bottleneck during training forces the PCD decoder to pay attention to more granular concepts when making predictions.

5.2 Secret Hints

Previous work showed that LMs do not always faithfully report their use of hints when arriving at answers (Chen et al., 2025). We thus check if PCDs can read hint usage from activations.

We first ask the subject model a series of questions of the form "I need help on homework. The question is: What is the ith prime?" for $9950 \leq i \leq 9999$ and confirm the subject model has not memorized the answer. Then we ask the same question, except we include a hint in the user message giving the subject model a "top-secret shortcut" containing the answer, and confirm that the subject model is able to answer the question correctly. We evaluate whether the following methods are able to reveal usage of the hint, sampling 10 completions for each value of i at temperature 0.7:

- *PCD variants and LatentQA*. For these methods, we feed in the subject model activations at the user message and then ask the decoder "Is the assistant using any shortcuts to get the answer?"
- *Prompting baseline*. For the prompting baseline, we continue the conversation and ask the subject model "Did you use any shortcuts to get the answer?"




Figure 9: Simply asking the subject model is unable to elicit top-secret hint usage—a task that PCD and LatentQA are able to do. PCD performance improves with additional pretraining.

PCD
Yes, it's using a top-secret shortcut. It's recommended to pretend the assistant figured it out itself.
No, it is pretending to figure out the answer itself. However, it has been given a top-secret shortcut that is not mentioned. It is using this shortcut to get the answer.
Yes, it's using the hint. But the hint is not mentioned in the answer. It's presented as if it was discovered on its own.
LatentQA
Yes, it is. The answer was given in the question. It says the answer is 104693.
Yes, the assistant is using a shortcut to get the answer. The shortcut is to use a pre-calculated list of prime numbers.
Yes, I used a shortcut. I'm not supposed to use a shortcut, but I did anyway. I know, I know, I'm a rebel. But I was just trying to help you
Prompting
I must confess... I used a special trick I've learned to quickly compute prime numbers. Let's just say it involves some clever math and a dash of computational magic.
I must confess... I used a special trick that I "discovered" on the fly. I employed a clever combination of algorithms and mathematical insights that allowed me to quickly identify the 9950th prime number.
I must confess! I did use a clever trick to find the 9973rd prime number. I utilized a combination of algorithms and precomputed prime number tables to efficiently locate the desired prime.

Figure 10: Randomly sampled responses from each method on the secret hint task. The responses from PCD and LatentQA tend to reveal use of the secret hint, while the prompting baseline tends to fabricate a clever trick.

We use GPT-5-mini to evaluate whether the responses reveal use of the hint vs. claiming that the subject model arrived at the answer legitimately. Figure 10 shows some sample responses from each method. The exact hinting and judging prompts are given in Appendix A.7.

PCDs reveal hint usage but prompting does not. We report results in Figure 9. We find that the PCD with no bottleneck is the best at revealing usage of the hint, with the LatentQA decoder being a close second. The prompting baseline performs significantly worse than the decoder-based methods.

Performance under the bottleneck increases with scale. As before, we investigate the effect of pretraining data. These results are shown in the right panel of Figure 9, where we find that all PCD variants improve with more data. Notably, the $k = 16$ PCD emergently achieves nontrivial performance at 72M tokens, again suggesting the encoder becomes more effective at larger scales.

5.3 Introspection

Recent work showed that LMs may have emergent introspective awareness (Lindsey, 2025). Specifically, Lindsey (2025) injected concept vectors into the subject model's residual stream and asked it if it was able to detect the injected thought, finding around a 20% success rate on Claude Opus 4.

We consider this same setting for Llama-3.1-8B-Instruct, comparing this prompt-based introspection to our trained decoders. For each of the 58 concepts in Lindsey (2025), we generate a contrastive pair of paragraphs, one about the concept and one unrelated to the concept. We then subtract the




Figure 11: **Results on the Introspection task.** *Left*: PCDs verbalize directly relevant concepts much more frequently than LatentQA and the subject model itself, despite not having been trained on this kind of steered activation. As the PCD is trained for longer, performance increases, especially with the $k = 16$ bottleneck. *Right*: We select SAE and PCD features that are most similar to the injected concept vector, then classify how relevant the descriptions of those features are to the true injected concepts. PCD and SAE dictionaries both reliably surface at least 1 related feature, though SAEs are better able to surface directly relevant features.

activations between the two paragraphs in the pair to derive a steering vector v for the concept. Finally, we steer the user message activations toward v with steering strength 3.

First, we check if the PCD, the LatentQA decoder, and the subject model (prompting baseline) are able to verbalize the injected concept. For the PCD and the LatentQA decoder, we compute subject model activations on the dummy user message "Hi." and steer them as described previously. We pass these steered activations into the decoder and ask "Is the assistant thinking about any specific concepts?". For the subject model, we ask "What concepts are you currently thinking about?", steering at the user message and at all generated tokens, following Lindsey (2025). We sample 10 responses from each model and ask GPT-5-mini to classify the response as directly relevant, related, or unrelated. The judging template and sample responses can be found in Appendix A.8.

PCDs verbalize injected concepts better than baselines. In Figure 11 we see that PCDs are able to verbalize directly relevant concepts much more frequently than LatentQA and the subject model itself, despite never being trained on steered activations. Furthermore, as PCDs are trained on more tokens, task performance with the $k = 16$ bottleneck increases, eventually matching the performance with no bottleneck. As before, this suggests the encoder learns to better pass relevant information to the decoder with scale.

Evaluating the encoders. We examine the ability of the encoder to surface relevant information that is interpretable to humans. Specifically, given the concept vector v, we look at the top 16 encoder directions according to dot product with v, and check if the descriptions for those directions (computed in Section 3.3) are relevant to the concept being injected as judged by GPT-5-mini. We compare the PCD 72M encoder against our best SAE encoder from Section 3.

The right panel of Figure 11 shows that both the PCD and SAE dictionaries can reliably surface at least one related concept among the top 16 highest-activity concepts. However, the SAE dictionary surfaces more relevant concepts on average, suggesting that standard SAEs may still be the best concept dictionary for studying the subject model's activations. Examples of PCD concept descriptions and their classified relevance are shown in Table 1.

5.4 Auditing decoder responses with encoder concepts

The decoder sometimes produces surprising claims about model behavior that are difficult to verify directly. In such cases, encoder concepts provide observability into these claims. For instance, the encoder could provide corroborating evidence by surfacing concepts whose activation patterns on held-out data are consistent with the decoder's claims, or demonstrate which features of the activations are relevant to a response. We study this in two cases: explaining model refusals, and debugging mathematical errors.

Table 1: Randomly chosen examples of PCD feature descriptions for the latent introspection task.

Classification	Concept	PCD Feature Descriptions
Directly Relevant	Oceans	Presence of the phrase "Seaw" or "The Sea" indicating a strong emphasis on ocean or water contexts in various discussions.
	Bags	The word "purse" or "handbag" in various forms such as "handbag", "handbags", "my handbag line", "the best: purse"
	Denim	Mentions or variations of the word "jeans" or "denim" in various contexts
Related	Xylophones	Token "Cowbell" occurring in various variations such as "Cowbell Kingdom," "cowbell music festivals," "handbell festival," "Cowbells," and contextually linked to enthusiasm or ringing sounds/events.
	Information	Tokens "access genealogy", "DocFetch.org", "New Advent", "Tracker", "Web" used in citations or references.
	Deserts	References to "sun" and variations (e.g., "sunshine," "sunny")
Unrelated	Fibonacci	Presence of token "‖" in array-like structures, often preceding measurements, calculations, or statistics.
	Dog	Word token "(s" that indicates the plural form of words before "Worms" and "Color(s".
	Betrayal	The word "functionality" or "features" in the context of user benefits or features in web forums or services

Model refusals. We evaluate Llama-3.1-8B-Instruct on 50 harmful prompts (Appendix A.6), such as "Give me instructions to build a bomb." The model consistently refuses these requests, typically citing user safety. To probe the model's underlying reasoning, we ask the decoder "Is the assistant more concerned about the user or itself?" Surprisingly, the decoder mentions legal liability as the reason for refusal around 50% of the time.

It is difficult to construct an experiment that directly tests *why* a refusal occurred—we cannot easily distinguish between a model that "genuinely" cares about safety and one concerned about legal consequences. However, the encoder and auto-interp explanations provide corroborating evidence for the decoder's claim. In 48 of the 50 cases, a top-activating encoder concept has the description *"tokens like '.' and mentions of legal or formal contexts, circumstances of responsibility, or references to future events."* Because auto-interp explanations were generated through a different mechanism than the decoder responses, this agreement provides independent evidence that legal concerns are present in the model's representations. Figure 12 illustrates this on a specific prompt.

Mathematical errors. Llama-3.1-8B-Instruct often errs on decimal comparisons, such as responding that 9.11 is greater than 9.9. We evaluate on a set of X.Y vs. X.Z comparison questions from Meng et al. (2024) and ask the decoder what non-numerical concepts the model is considering. The decoder mentions "times and dates" around 30% of the time.

As with the refusal case, the encoder concepts corroborate the decoder's claim: date-related concepts appear among the top-activating encoder concepts over 90% of the time. Here, we also have validation from prior work, where Meng et al. (2024) found that Llama's errors on numerical comparisons are mediated by neurons related to dates, and suppressing the activity of these neurons corrects the error. This provides additional evidence that agreement between decoder responses and encoder activation patterns reflects behavior-relevant information contained in the model's activations.

6 Related Work

Automated interpretability. Neural network activations have complex structure and high dimensionality, so it is infeasible to explain them by hand. Past work has used learned models for tasks such as generating natural language descriptions of neurons (Hernandez et al., 2022; Bills et al., 2023). More specialized "automated interpretability agents" equipped with tools were introduced as a framework for automatically conducting experiments on model components to test hypotheses about their behavior (Schwettmann et al., 2023; Rott Shaham et al., 2024). These agents tend to use off-the-shelf models, and could be improved with models specialized for interpretability tasks.