

INGENIERÍA DE SERVIDORES (2016-2017)  
GRADO EN INGENIERÍA INFORMÁTICA  
UNIVERSIDAD DE GRANADA

---

## Memoria Práctica 4

---

Elena María Gómez Ríos

22 de diciembre de 2016

## Índice

<b>1. Cuestión 1:</b>	<b>4</b>
1.1. a) ¿Selecione, instale y ejecute uno, comente los resultados. Atención: no es lo mismo un benchmark que una suite, instale un benchmark. . . . .	4
<b>2. Cuestión 2:</b>	<b>12</b>
2.1. De los parámetros que le podemos pasar al comando ¿Qué significa -c 5? ¿y -n 100? Monitorice la ejecución de ab contra alguna máquina (cualquiera) ¿cuántas “tarefas” crea ab en el cliente? . . . . .	12
<b>3. Cuestión 3:</b>	<b>15</b>
3.1. Ejecute ab contra a las tres máquinas virtuales (desde el SO anfitrión a las máquina virtuales de la red local) una a una (arrancadas por separado).¿Cuál es la que proporciona mejores resultados? Muestre y coméntelos. (Use como máquina de referencia Ubuntu Server para la comparativa). . .	15
<b>4. Cuestión opcional 1:</b>	<b>19</b>
4.1. ¿Qué es Scala? Instale Gatling y pruebe los escenarios por defecto. . . . .	19
<b>5. Cuestión 4:</b>	<b>19</b>
5.1. Instale y siga el tutorial en <a href="http://jmeter.apache.org/usermanual/build-web-test-plan.html">http://jmeter.apache.org/usermanual/build-web-test-plan.html</a> [1] realizando capturas de pantalla y comentándolas. En vez de usar la web de jmeter, haga el experimento usando sus máquinas virtuales ¿coincide con los resultados de ab? . . . . .	19
<b>6. Cuestión 5:</b>	<b>19</b>
6.1. Programe un benchmark usando el lenguaje que desee. El benchmark debe incluir: . . . . .	19

## Índice de figuras

1.1. CentOS, instalación de Phoronix Suite. . . . .	5
1.2. CentOS, listado de benchmarks. . . . .	5
1.3. CentOS, instalación del benchmark Blender. . . . .	6
1.4. CentOS, Phoronix Suite GUI. . . . .	6
1.5. CentOS, Phoronix Suite GUI web. . . . .	7
1.6. CentOS, Phoronix Suite, listado de benchmarks. . . . .	7
1.7. CentOS, Phoronix Suite, listado de benchmarks instalados. . . . .	8
1.8. CentOS, Phoronix Suite, ejecución de benchmarks. . . . .	8
1.9. CentOS, Phoronix Suite, ejecución de benchmarks. . . . .	9
1.10. CentOS, Phoronix Suite, problemas con benchmark Blender. . . . .	9
1.11. CentOS, Phoronix Suite, ejecución de benchmark GLmark2. . . . .	10
1.12. CentOS, Phoronix Suite, ejecución de benchmark GLmark2. . . . .	10

1.13. CentOS, Phoronix Suite, benchmark GLmark2 finalizado. . . . .	11
1.14. CentOS, Phoronix Suite, resultado de benchmark GLmark2. . . . .	11
1.15. CentOS, Phoronix Suite, resultado de benchmark GLmark2. . . . .	12
2.1. CentOS, ab contra Windows Server. . . . .	13
2.2. CentOS, ab contra Windows Server. . . . .	13
2.3. CentOS, número de tareas de ab. . . . .	14
2.4. Windows, Administrador de tareas durante ejecución ab desde CentOS. . .	14
3.1. CentOS, resultado ab contra Windows. . . . .	16
3.2. CentOS, resultado ab contra Windows. . . . .	16
3.3. CentOS, desactivación del firewall. . . . .	17
3.4. CentOS, resultado ab contra CentOS. . . . .	17
3.5. CentOS, resultado ab contra CentOS. . . . .	18
3.6. CentOS, resultado ab contra Ubuntu Server. . . . .	18
3.7. CentOS, resultado ab contra Ubuntu Server. . . . .	19

## Índice de tablas

3.1. Resultados de ab. . . . .	15
--------------------------------	----

## 1. Cuestión 1:

- 1.1. a) ¿Seleccione, instale y ejecute uno, comente los resultados.  
**Atención: no es lo mismo un benchmark que una suite, instale un benchmark.**

Para instalar Phoronix Suite en CentOS [3] se utiliza el comando `yum install phoronix-test-suite` (figura 1.1). Con el comando `phoronix-test-suite list-tests` se obtiene una lista de los benchmarks disponibles (figura 1.2). Para instalar un benchmark de la lista se utiliza el comando `phoronix-test-suite install <test>` (figura 1.3). La documentación utilizada para los comandos de phoronix ha sido [2], aunque podemos obtener la misma información con `man phoronix-test-suite`.

Podemos iniciar el cliente web con el comando `phoronix-test-suite gui` (figura 1.4), el cual abrirá una nueva ventana como se muestra en la figura 1.5 en la que aparece la monitorización de nuestro sistema. Desde aquí también podemos listar los test disponibles (figura 1.6) e instalarlos. En la pestaña de “Installed Tests” podemos ver los benchmarks ya instalados, en mi caso, como se muestra en la figura 1.7, aparece el “Blender” que es el benchmark que he instalado anteriormente.

Ejecutar el benchmark desde la GUI es muy sencillo, simplemente debemos pulsar sobre el benchmark que queremos ejecutar y nos saldrá una pantalla como la de la figura 1.8, si el benchmark no está instalado se instalará previamente. Mientras que se ejecuta el benchmark se muestra la siguiente pantalla de información, figura 1.9, donde informa del tiempo aproximado que va a tardar en completarse.


Debido a que mi máquina virtual no es capaz de finalizar el benchmark de Blender, he decidido cancelar la ejecución tras unos 46 minutos (figura 1.10) y probar con otro que requiera menos requisitos y tarde menos en finalizar la ejecución, como por ejemplo “GLmark2” (figura 1.11 y 1.12).

Una vez finalizado el benchmark de “GLmark2”, como se muestra en la figura 1.13, accedemos a los resultados donde podemos ver un listado de las especificaciones de nuestro sistema y una puntuación del test realizado (figuras 1.14 y 1.15).



```
Archivo Editar Ver Buscar Terminal Ayuda
[elena@localhost ~]$ sudo yum install phoronix-test-suite
[sudo] password for elena:
Complementos cargados:fastestmirror, langpacks
Loading mirror speeds from cached hostfile
* base: ftp.cica.es
* epel: mirror.airenetworks.es
* extras: ftp.cica.es
* updates: ftp.cica.es
Resolviendo dependencias
--> Ejecutando prueba de transacción
--> Paquete phoronix-test-suite.noarch 0:6.6.0-1.el7 debe ser instalado
--> Procesando dependencias: /usr/bin/ruby para el paquete: phoronix-test-suite-6.6.0-1.el7.noarch
--> Ejecutando prueba de transacción
--> Paquete ruby.x86_64 0:2.0.0.648-29.el7 debe ser instalado
--> Procesando dependencias: ruby-libs(x86_64) = 2.0.0.648-29.el7 para el paquete: ruby-2.0.0.648-29.el7.x86_64
--> Procesando dependencias: rubygem(bigdecimal) >= 1.2.0 para el paquete: ruby-2.0.0.648-29.el7.x86_64
--> Procesando dependencias: ruby(rubygems) >= 2.0.14.1 para el paquete: ruby-2.0.0.648-29.el7.x86_64
--> Procesando dependencias: libruby.so.2.0()(64bit) para el paquete: ruby-2.0.0.648-29.el7.x86_64
--> Ejecutando prueba de transacción
--> Paquete ruby-libs.x86_64 0:2.0.0.648-29.el7 debe ser instalado
--> Paquete rubygem-bigdecimal.x86_64 0:1.2.0-29.el7 debe ser instalado
--> Paquete rubygems.noarch 0:2.0.14.1-29.el7 debe ser instalado
--> Procesando dependencias: rubygem(rdoc) >= 4.0.0 para el paquete: rubygems-2.0.14.1-29.el7.noarch
--> Procesando dependencias: rubygem(psych) >= 2.0.0 para el paquete: rubygems-2.0.14.1-29.el7.noarch
--> Procesando dependencias: rubygem(io-console) >= 0.4.2 para el paquete: rubygems-2.0.14.1-29.el7.noarch
--> Ejecutando prueba de transacción
--> Paquete rubygem-io-console.x86_64 0:0.4.2-29.el7 debe ser instalado
--> Paquete rubygem-psych.x86_64 0:2.0.0-29.el7 debe ser instalado
--> Procesando dependencias: libyaml-0.so.2()(64bit) para el paquete: rubygem-psych-2.0.0-29.el7.x86_64
--> Paquete rubygem-rdoc.noarch 0:4.0.0-29.el7 debe ser instalado
--> Procesando dependencias: rubygem(irb) = 2.0.0.648 para el paquete: rubygem-rdoc-4.0.0-29.el7.noarch
--> Procesando dependencias: rubygem(json) >= 1.7.7 para el paquete: rubygem-rdoc-4.0.0-29.el7.noarch
```


Figura 1.1: CentOS, instalación de Phoronix Suite.



```
Available Tests

pts/aio-stress          - AIO-Stress          Disk
pts/apache              - Apache Benchmark    System
pts/apitest             - APITest             Graphics
pts/apitrace            - APITrace            Graphics
pts/askap               - ASKAP tConvolveCuda Graphics
pts/battery-power-usage - Battery Power Usage System
pts/bioshock-infinite   - BioShock Infinite  Graphics
pts/blake2              - BLAKE2              Processor
pts/blender             - Blender             System
pts/blogbench           - BlogBench           Disk
pts/bork                - Bork File Encrypter Processor
pts/botan               - Botan               Processor
pts/build-apache        - Timed Apache Compilation Processor
pts/build-boost-interprocess - Timed Boost Interprocess Compilation Processor
pts/build-eigen         - Timed Eigen Compilation Processor
pts/build-firefox       - Timed Firefox Compilation Processor
pts/build-imagemagick   - Timed ImageMagick Compilation Processor
pts/build-linux-kernel - Timed Linux Kernel Compilation Processor
pts/build-mplayer       - Timed MPlayer Compilation Processor
pts/build-php           - Timed PHP Compilation Processor
pts/build-webkitgtk     - Timed WebKitGTK Compilation Processor
pts/bullet              - Bullet Physics Engine Processor
pts/byte                - BYTE Unix Benchmark Processor
pts/c-ray               - C-Ray               Processor
pts/cachebench          - CacheBench          Processor
pts/caffe               - Caffe AlexNet       System
pts/cairo-demos         - Cairo Performance Demos Graphics
pts/cairo-perf-trace    - cairo-perf-trace    Graphics
```

Figura 1.2: CentOS, listado de benchmarks.



```
elena@localhost:~$ phoronix-test-suite install pts/blender


[NOTICE] chmod(): Operation not permitted in pts_client:42

The following dependencies are needed and will be installed:

- bzip2-devel
- freeglut-devel
- xorg-x11-server-devel
- opengl-headers
- pocl

This process may take several minutes.
Please enter your root password below:
Contraseña:
There are unfinished transactions remaining. You might consider running yum-complete-transaction, or "yum-complete-transaction --cleanup-only" and "yum history redo last", first to finish them. If those don't work you'll have to try removing/installing packages by hand (maybe package-clean up can help).
Advertencia: Las bases de datos (RPMDB) han sido modificadas por un elemento ajeno a yum.
** Se ha encontrado 4 problema(s) pre existentes en la base de datos RPM, este es el resultado de 'yum check':
ipa-client-4.4.0-14.el7.centos.x86_64 se ha instalado choca con freeipa-client: ipa-client-4.4.0-14.el7.centos.x86_64
ipa-client-common-4.4.0-14.el7.centos.noarch se ha instalado choca con freeipa-client-common: ipa-client-common-4.4.0-14.el7.centos.noarch
ipa-common-4.4.0-14.el7.centos.noarch se ha instalado choca con freeipa-common: ipa-common-4.4.0-14.el7.centos.noarch
ipa-python-compat-4.4.0-14.el7.centos.noarch se ha instalado choca con freeipa-python-compat: ipa-python-compat-4.4.0-14.el7.centos.noarch
Complementos cargados:fastestmirror, langpacks
Loading mirror speeds from cached hostfile
* base: mirror.trueinter.net
* epel: ftp.cica.es
* extras: mirror.trueinter.net
* updates: mirror.trueinter.net
No existe disponible ningún paquete pocl.
Resolviendo dependencias
```

Figura 1.3: CentOS, instalación del benchmark Blender.



```
1 File Needed [0.17 MB]
Downloading: llcbench.tar.gz [0.17MB]
Downloaded: .....
Installation Size: 0.5 MB
Installing Test @ 17:03:51
The installer exited with a non-zero exit status.
LOG: /var/lib/phoronix-test-suite/installed-tests/pts/cachebench-1.0.0/install-failed.log

[elena@localhost ~]$ phoronix-test-suite gui
To start server run new script: /tmp/tmp.2mBPBkups/web-server-launcher
PHP 5.4.16 Development Server started at Wed Dec 14 17:05:12 2016
Listening on http://localhost:5342
Document root is /usr/share/phoronix-test-suite/pts-core/web-interface
Press Ctrl-C to quit.
Launching Browser
WebSocket Server Active: localhost:5341

127.0.0.1: Connecting

127.0.0.1: Sending: {"pts":{"msg":{"name":"user_session_start"},"status":{"current":"Starting Session","full":"Starting Session"}}}

127.0.0.1: Sending: {"pts":{"msg":{"name":"user_session_start"},"status":{"current":"Generating Phodevi Cache + VFS","full":"Starting Session\nGenerating Phodevi Cache + VFS"}}}

127.0.0.1: Sending: {"pts":{"msg":{"name":"user_session_start"},"status":{"current":"Starting Phodevi Sensor Handler","full":"Starting Session\nGenerating Phodevi Cache + VFS\nStarting Phodevi Sensor Handler"}}}

127.0.0.1: Sending: {"pts":{"msg":{"name":"user_session_start"},"status":{"current":"Downloading Test Information","full":"Starting Session\nGenerating Phodevi Cache + VFS\nStarting Phodevi Sensor Handler\nDownloading Test Information"}}}
1481731768554 addons.update-checker WARN Update manifest for {972ce4c6-7e08-4474-a285-3208198ce6fd} did not contain an updates property
```

Figura 1.4: CentOS, Phoronix Suite GUI.




Figura 1.5: CentOS, Phoronix Suite GUI web.




Figura 1.6: CentOS, Phoronix Suite, listado de benchmarks.




Figura 1.7: CentOS, Phoronix Suite, listado de benchmarks instalados.




Figura 1.8: CentOS, Phoronix Suite, ejecución de benchmarks.






Figura 1.9: CentOS, Phoronix Suite, ejecución de benchmarks.




Figura 1.10: CentOS, Phoronix Suite, problemas con benchmark Blender.




Figura 1.11: CentOS, Phoronix Suite, ejecución de benchmark GLmark2.




Figura 1.12: CentOS, Phoronix Suite, ejecución de benchmark GLmark2.




Figura 1.13: CentOS, Phoronix Suite, benchmark GLmark2 finalizado.




Figura 1.14: CentOS, Phoronix Suite, resultado de benchmark GLmark2.





Figura 1.15: CentOS, Phoronix Suite, resultado de benchmark GLmark2.

## 2. Cuestión 2:

### 2.1. De los parámetros que le podemos pasar al comando ¿Qué significa -c 5? ¿y -n 100? Monitoree la ejecución de ab contra alguna máquina (cualquiera) ¿cuántas “tareas” crea ab en el cliente?

Tal y como se indica en el man de `ab` la opción `-c 5` indica que se podrán ejecutar concurrentemente 5 solicitudes y la opción `-n 100` significa que se harán 100 peticiones en el benchmarking actual.

He monitorizado la ejecución de `ab` desde una máquina virtual con CentOS hacia otra con Windows Server, el resultado de la ejecución se muestra en las figuras 2.1 y 2.2. El comando `ab` crea 1 tarea en el cliente como se muestra en la figura 2.3. En el servidor se puede ver un claro aumento del uso de la CPU durante la ejecución de `ab` (figura 2.4).



A terminal window titled 'Aplicaciones Lugares terminal' with a status bar showing 'jue, 22 de dic, 16:04'. The prompt is 'elena@localhost:~'. The user has run the command 'ab -c 5 -n 100 http://10.0.2.9/'. The output shows ApacheBench version 2.3 results for a Microsoft-IIS/7.5 server. The benchmarking process is complete, showing various performance metrics.

```
elena@localhost:~$ ab -c 5 -n 100 http://10.0.2.9/
This is ApacheBench, Version 2.3 <$Revision: 1430300 $>
Copyright 1996 Adam Twiss, Zeus Technology Ltd, http://www.zeustech.net/
Licensed to The Apache Software Foundation, http://www.apache.org/

Benchmarking 10.0.2.9 (be patient).....done



Server Software:      Microsoft-IIS/7.5
Server Hostname:      10.0.2.9
Server Port:          80

Document Path:        /
Document Length:      689 bytes

Concurrency Level:     5
Time taken for tests:  1.101 seconds
Complete requests:     100
Failed requests:        0
Write errors:           0
Total transferred:     93200 bytes
HTML transferred:      68900 bytes
Requests per second:   90.80 [#/sec] (mean)
Time per request:      55.068 [ms] (mean)
Time per request:      11.014 [ms] (mean, across all concurrent requests)
Transfer rate:         82.64 [Kbytes/sec] received

Connection Times (ms)
              min      mean[+/-sd] median   max
Connect:        0        1   0.9      1      10
Processing:      1       13 100.0      2     1001
Waiting:        1       13  99.8      1     1000
```

Figura 2.1: CentOS, ab contra Windows Server.



A terminal window titled 'Aplicaciones Lugares terminal' with a status bar showing 'jue, 22 de dic, 16:05'. The prompt is 'elena@localhost:~'. The output continues from the previous figure, showing connection times and a percentage of requests served within a certain time.

```
Document Length:      689 bytes

Concurrency Level:     5
Time taken for tests:  1.101 seconds
Complete requests:     100
Failed requests:        0
Write errors:           0
Total transferred:     93200 bytes
HTML transferred:      68900 bytes
Requests per second:   90.80 [#/sec] (mean)
Time per request:      55.068 [ms] (mean)
Time per request:      11.014 [ms] (mean, across all concurrent requests)
Transfer rate:         82.64 [Kbytes/sec] received

Connection Times (ms)
              min      mean[+/-sd] median   max
Connect:        0        1   0.9      1      10
Processing:      1       13 100.0      2     1001
Waiting:        1       13  99.8      1     1000
Total:          2       14 100.9      3     1011

Percentage of the requests served within a certain time (ms)
 50%    3
 66%    3
 75%    3
 80%    3
 90%    5
 95%   29
 98%   31
 99%  1011
100%  1011 (longest request)
elena@localhost:~$
```

Figura 2.2: CentOS, ab contra Windows Server.




Figura 2.3: CentOS, número de tareas de ab.




Figura 2.4: Windows, Adminitrador de tareas durante ejecución ab desde CentOS.

### 3. Cuestión 3:

#### 3.1. Ejecute **ab** contra a las tres máquinas virtuales (desde el SO anfitrión a las máquinas virtuales de la red local) una a una (arrancadas por separado). ¿Cuál es la que proporciona mejores resultados? Muestre y coméntelos. (Use como máquina de referencia Ubuntu Server para la comparativa).

En primer lugar comentar que este ejercicio lo voy a realizar desde una máquina virtual CentOS en vez de utilizar el SO anfitrión ya que tengo un problema con los puertos, como ya dije en prácticas anteriores, y me es imposible realizar la redirección de puertos de VirtualBox.


En primer lugar voy a ejecutar **ab** contra Windows, los resultados se muestran en las figuras 3.1 y 3.2. Para hacerlo contra CentOS he tenido que desactivar el firewall como se muestra en la figura 3.3 ya que por defecto el firewall bloquea todo el tráfico impidiendo ejecutar **ab**. Los resultados de **ab** contra CentOS se muestran en las figuras 3.4 y 3.5. Por último he realizado el test **ab** contra Ubuntu Server como se muestra en las figuras 3.6 y 3.7. Igualmente en Ubuntu he tenido que deshabilitar el firewall con el comando `sudo ufw disable`.

Para una fácil comparación entre los resultados de **ab** contra las diferentes máquinas virtuales voy a mostrar los resultados en la tabla 3.1.

Tabla 3.1: Resultados de **ab**.

SO	Tamaño web	Tiempo (s)	Datos Transferidos	Respuestas/s	Ratio Transferencia
CentOS	4897 bytes	64.347	493.90 MB	1554.08	7859.94 KB/s
Ubuntu	11510 bytes	54.763	1123.71 MB	1826.06	21012.13 KB/s
Windows	689 bytes	31.895	88.882 MB	3135.33	2853.64 KB/s

Como se puede observar mirando la columna correspondiente al ratio de transferencia, la máquina virtual que proporciona mejores resultados es Ubuntu, seguida de CentOS y por último Windows. Ubuntu tiene un ratio de transferencia 7.3632 veces mejor que Windows, y 2.67 veces mejor que CentOS.



Aplicaciones Lugares terminal jue, 22 de dic, 16:32

elena@localhost:~\$

```
Archivo Editar Ver Buscar Terminal Ayuda
elena@localhost:~$ ab -c 5 -n 100000 http://10.0.2.9/
This is ApacheBench, Version 2.3 <$Revision: 1430300 $>
Copyright 1996 Adam Twiss, Zeus Technology Ltd, http://www.zeustech.net/
Licensed to The Apache Software Foundation, http://www.apache.org/

Benchmarking 10.0.2.9 (be patient)
Completed 10000 requests
Completed 20000 requests
Completed 30000 requests
Completed 40000 requests
Completed 50000 requests
Completed 60000 requests
Completed 70000 requests
Completed 80000 requests
Completed 90000 requests
Completed 100000 requests
Finished 100000 requests

Server Software:      Microsoft-IIS/7.5
Server Hostname:      10.0.2.9
Server Port:          80


Document Path:        /
Document Length:      689 bytes

Concurrency Level:     5
Time taken for tests:  31.895 seconds
Complete requests:     100000
Failed requests:       0
Write errors:          0
Total transferred:     93200000 bytes
```

elena@localhost:~\$

1 / 4

Figura 3.1: CentOS, resultado ab contra Windows.



Aplicaciones Lugares terminal jue, 22 de dic, 16:32

elena@localhost:~\$

```
Archivo Editar Ver Buscar Terminal Ayuda
Document Length:      689 bytes

Concurrency Level:     5
Time taken for tests:  31.895 seconds
Complete requests:     100000
Failed requests:       0
Write errors:          0
Total transferred:     93200000 bytes
HTML transferred:     68900000 bytes
Requests per second:   3135.33 [#/sec] (mean)
Time per request:      1.595 [ms] (mean)
Time per request:      0.319 [ms] (mean, across all concurrent requests)
Transfer rate:         2853.64 [Kbytes/sec] received

Connection Times (ms)
      min  mean[+/-sd] median  max
Connect:    0    1  0.7      1    33
Processing:  0    1  0.9      1    29
Waiting:    0    1  0.9      1    29
Total:      1    1  1.2      1    47

Percentage of the requests served within a certain time (ms)
 50%    1
 66%    1
 75%    1
 80%    2
 90%    2
 95%    2
 98%    2
 99%    2
100%   47 (longest request)
elena@localhost:~$
```

elena@localhost:~\$

1 / 4

Figura 3.2: CentOS, resultado ab contra Windows.



```
elena@localhost:~$ systemctl disable firewalld
Removed symlink /etc/systemd/system/dbus-org.fedoraproject.FirewallD1.service.
Removed symlink /etc/systemd/system/basic.target.wants/firewalld.service.
elena@localhost:~$ systemctl status firewalld
● firewalld.service - firewalld - dynamic firewall daemon
   Loaded: loaded (/usr/lib/systemd/system/firewalld.service; disabled; vendor preset: enabled)
   Active: active (running) since jue 2016-12-22 16:50:33 CET; 11min ago
     Docs: man:firewalld(1)
   Main PID: 722 (firewalld)
   CGroup: /system.slice/firewalld.service
           └─722 /usr/bin/python -Es /usr/sbin/firewalld --nofork --nopid

dic 22 16:50:23 localhost.localdomain systemd[1]: Starting firewalld - dynami...
dic 22 16:50:33 localhost.localdomain systemd[1]: Started firewalld - dynamic...
Hint: Some lines were ellipsized, use -l to show in full.
elena@localhost:~$ systemctl stop firewalld
elena@localhost:~$ systemctl status firewalld
● firewalld.service - firewalld - dynamic firewall daemon
   Loaded: loaded (/usr/lib/systemd/system/firewalld.service; disabled; vendor preset: enabled)
   Active: inactive (dead)
     Docs: man:firewalld(1)

dic 22 16:50:23 localhost.localdomain systemd[1]: Starting firewalld - dynami...
dic 22 16:50:33 localhost.localdomain systemd[1]: Started firewalld - dynamic...
dic 22 17:02:35 localhost.localdomain systemd[1]: Stopping firewalld - dynami...
dic 22 17:02:35 localhost.localdomain systemd[1]: Stopped firewalld - dynamic...
Hint: Some lines were ellipsized, use -l to show in full.
elena@localhost:~$
```

Figura 3.3: CentOS, desactivación del firewall.

```
elena@localhost:~$ ab -c 5 -n 100000 http://10.0.2.10/
This is ApacheBench, Version 2.3 <$Revision: 1430300 $>
Copyright 1996 Adam Twiss, Zeus Technology Ltd, http://www.zeustech.net/
Licensed to The Apache Software Foundation, http://www.apache.org/

Benchmarking 10.0.2.10 (be patient)
Completed 10000 requests
Completed 20000 requests
Completed 30000 requests
Completed 40000 requests
Completed 50000 requests
Completed 60000 requests
Completed 70000 requests
Completed 80000 requests
Completed 90000 requests
Completed 100000 requests
Finished 100000 requests


Server Software:      Apache/2.4.6
Server Hostname:      10.0.2.10
Server Port:          80

Document Path:        /
Document Length:      4897 bytes

Concurrency Level:    5
Time taken for tests:  64.347 seconds
Complete requests:    100000
Failed requests:       0
Write errors:          0
Non-2xx responses:    100000
```

Figura 3.4: CentOS, resultado ab contra CentOS.

The screenshot shows a terminal window titled 'terminal' with the user 'elena@localhost'. The terminal displays the output of an ApacheBench test. The results show a concurrency level of 5, a total time of 64.347 seconds, and 100,000 complete requests. The transfer rate is 7859.94 Kbytes/sec. The connection times table shows a median of 0.3 ms for connect, 1.9 ms for processing, and 2.0 ms for total. The percentage of requests served within a certain time shows that 99% of requests were served within 8 ms, and the longest request took 474 ms.

```
Concurency Level:      5
Time taken for tests:  64.347 seconds
Complete requests:     100000
Failed requests:       0
Write errors:          0
Non-2xx responses:    100000
Total transferred:     517900000 bytes
HTML transferred:     489700000 bytes
Requests per second:   1554.08 [#/sec] (mean)
Time per request:      3.217 [ms] (mean)
Time per request:      0.643 [ms] (mean, across all concurrent requests)
Transfer rate:         7859.94 [Kbytes/sec] received

Connection Times (ms)
              min      mean[+/-sd] median    max
Connect:      0       0   0.3      0       29
Processing:    1       3   1.9      3      474
Waiting:       0       3   1.8      3      474
Total:         1       3   2.0      3      474

Percentage of the requests served within a certain time (ms)
 50%    3
 66%    3
 75%    3
 80%    3
 90%    3
 95%    3
 98%    4
 99%    8
100%   474 (longest request)
elena@localhost:~$
```

Figura 3.5: CentOS, resultado ab contra CentOS.

The screenshot shows a terminal window titled 'terminal' with the user 'elena@localhost'. The terminal displays the output of an ApacheBench test. The results show a concurrency level of 5, a total time of 54.763 seconds, and 100,000 complete requests. The transfer rate is 1178300000 bytes. The connection times table shows a median of 0.3 ms for connect, 1.9 ms for processing, and 2.0 ms for total. The percentage of requests served within a certain time shows that 99% of requests were served within 8 ms, and the longest request took 474 ms.


```
Benchmarking 10.0.2.11 (be patient)
Completed 10000 requests
Completed 20000 requests
Completed 30000 requests
Completed 40000 requests
Completed 50000 requests
Completed 60000 requests
Completed 70000 requests
Completed 80000 requests
Completed 90000 requests
Completed 100000 requests
Finished 100000 requests

Server Software:      Apache/2.4.7
Server Hostname:      10.0.2.11
Server Port:          80

Document Path:        /
Document Length:      11510 bytes

Concurency Level:      5
Time taken for tests:  54.763 seconds
Complete requests:     100000
Failed requests:       0
Write errors:          0
Total transferred:     1178300000 bytes
```

Figura 3.6: CentOS, resultado ab contra Ubuntu Server.

A screenshot of a terminal window on a CentOS system. The window title is 'Aplicaciones Lugares terminal'. The terminal shows the output of a JMeter test. The top part shows summary statistics: Document Length (11510 bytes), Concurrency Level (5), Time taken for tests (54.763 seconds), Complete requests (100000), Failed requests (0), Write errors (0), Total transferred (1178300000 bytes), HTML transferred (1151000000 bytes), Requests per second (1826.06 [#/sec] (mean)), Time per request (2.738 [ms] (mean)), Time per request (0.548 [ms] (mean, across all concurrent requests)), and Transfer rate (21012.13 [Kbytes/sec] received). Below this is a table of Connection Times (ms) with columns for min, mean[+/-sd], median, and max. The rows are Connect, Processing, Waiting, and Total. The bottom part shows the Percentage of the requests served within a certain time (ms) for various percentiles from 50% to 100%. The 100th percentile is 188 (longest request). The prompt 'elena@localhost:~\$' is visible at the bottom.

```
Document Length:      11510 bytes

Concurrency Level:      5
Time taken for tests:   54.763 seconds
Complete requests:      100000
Failed requests:         0
Write errors:            0
Total transferred:      1178300000 bytes
HTML transferred:       1151000000 bytes
Requests per second:    1826.06 [#/sec] (mean)
Time per request:        2.738 [ms] (mean)
Time per request:        0.548 [ms] (mean, across all concurrent requests)
Transfer rate:           21012.13 [Kbytes/sec] received

Connection Times (ms)
      min      mean[+/-sd] median    max
Connect:    0       0   0.5      0      25
Processing:  0       2   3.9      1     188
Waiting:    0       1   1.8      1      49
Total:       1       3   4.0      2     188

Percentage of the requests served within a certain time (ms)
 50%      2
 66%      2
 75%      2
 80%      2
 90%      3
 95%      7
 98%     14
 99%     19
100%    188 (longest request)
elena@localhost:~$
```

Figura 3.7: CentOS, resultado ab contra Ubuntu Server.

## 4. Cuestión opcional 1:

4.1. ¿Qué es Scala? Instale Gatling y pruebe los escenarios por defecto.

## 5. Cuestión 4:

5.1. Instale y siga el tutorial en <http://jmeter.apache.org/usermanual/build-web-test-plan.html> [1] realizando capturas de pantalla y comentándolas. En vez de usar la web de jmeter, haga el experimento usando sus máquinas virtuales ¿coincide con los resultados de ab?

## 6. Cuestión 5:

6.1. Programe un benchmark usando el lenguaje que desee. El benchmark debe incluir:

1. Objetivo del benchmark.
2. Métricas (unidades, variables, puntuaciones, etc.).
3. Instrucciones para su uso.
4. Ejemplo de uso analizando los resultados.

Tenga en cuenta que puede comparar varios gestores de BD, lenguajes de programación web (tiempos de ejecución, gestión de memoria, ...), duración de la batería, servidor DNS, etc. . Alternativamente, puede descargar alguno de algún repositorio en github y modificarlo según sus necesidades.

## Referencias

- [1] <http://jmeter.apache.org/usermanual/build-web-test-plan.html>, consultado el 14 de Diciembre de 2016. Tutorial ejercicio 4.
- [2] <http://www.phoronix-test-suite.com/documentation/phoronix-test-suite.html>, consultado el 14 de Diciembre de 2016. Comandos de Phoronix.
- [3] [http://www.phoronix.com/scan.php?page=news\\_item&px=NzIwMQ](http://www.phoronix.com/scan.php?page=news_item&px=NzIwMQ), consultado el 14 de Diciembre de 2016. Phoronix.