

# Task 2

## Introduction

For task 2, we are going to deal with a dataset containing information about 4601 webmails. We have 48 variables describing the frequency of some specific words like “*remove*” in each observation, 6 variables describing the frequency of some specific chars like “\$” in one observation, and three variables, *capital\_run\_length\_longest*, *capital\_run\_length\_average* and *capital\_run\_length\_total*, describing the length of the longest uninterrupted sequence of capital letters, the average length of uninterrupted sequences of capital letters, and the total number of capital letters in each observation respectively. We also have a variable called *spam*, which indicates whether this webmail is a spam with 0 and 1, where 1 for spam, and 0 for not spam. Here all our variables are numeric type. Our task is to use these 57 attribute variables to classify whether a webmail is spam.

## Methodology

In order to validate the accuracy of our methods, we firstly divide our dataset into a train set, which contains 2500 observations, and a test set, which contains 2101 observations. We use the train set to train our models, and then apply it to the test set to validate its accuracy.

## Results

### Classification Trees

In this part, we are going to discuss the results obtained by complex tree model and pruned tree model. We begin with construct a complex tree model by dividing our observation into small non-overlapping regions according to some numerical criteria. Here we split our dataset until each leaf of our classification tree contains only less then 2 observations. The method used here is recursive binary splitting.

```
#grow complex tree using deviance as criterion
tree.mod = tree(factor(spam) ~ . ,data=train,
                control = tree.control(nobs = 2500, minsize = 2, mincut = 1),
                split = "deviance")

#tree.mod = rpart(spam ~ . ,data=train,
#                control = tree.control(nobs = 2500, minsize = 2, mincut = 1))

summary(tree.mod)
```


Classification tree:

```
tree(formula = factor(spam) ~ ., data = data.train, control = tree.control(nobs = 2500,
    minsize = 2, mincut = 1), split = "deviance")
```

Variables actually used in tree construction:


```
[1] "char_freq_dollar"          "word_freq_remove"
[3] "char_freq_exclmark"       "char_freq_parenthesis"
[5] "capital_run_length_longest" "word_freq_your"
[7] "word_freq_hp"              "word_freq_our"
[9] "capital_run_length_average" "word_freq_make"
[11] "word_freq_mail"            "word_freq_order"
[13] "capital_run_length_total"   "word_freq_free"

Number of terminal nodes: 20
Residual mean deviance: 0.02621 = 6.028 / 230
Misclassification error rate: 0.004 = 1 / 250
```



We can see clearly here that criteria concerning the frequency of “\$”, “*remove*”, “!”, “*hp*”, “*our*”, “*free*”, “*edu*” as well as the length of the longest uninterrupted sequence of capital letters are used for splitting. It’s actually quite reasonable, because from our own experience, spam webmails are always advertisements on money related topics or education related topics, and are always filled with words in capital letters, together with exclamation symbols, to draw attention.

```
#use cross-validation to select tuning parameter for pruning the tree
set.seed(0829539)
cv.out=cv.tree(tree.mod,K=5)
par(cex=1.4)
plot(cv.out$size,cv.out$dev,type='b')
```



However, in this specific task, we can see that the cross-validation error is monotonously decreasing, so the optimal fold number is the original fold number. We choose best size=12 here such that the pruned tree model here is exactly the same as our complex tree model.

```
#prune the tree
prune.mod=prune.tree(tree.mod,best=12)
plot(prune.mod)
text(prune.mod,pretty=0)
```

Now we validate the accuracy of our classification tree model with the test data.

```
#make predictions on training and test set using the unpruned tree
pred.train<- predict(tree.mod,newdata=data.train)
classif.train<-ifelse(pred.train[,2]>=pred.train[,1],1,0)
err(data.train$spam,classif.train)

pred.test<-predict(tree.mod,newdata=data.test)
classif.test<-ifelse(1*pred.test[,2]>=pred.test[,1],1,0)
err(data.test$spam,classif.test)
```

```
#make predictions on training and test set using the pruned tree
pred.train<-predict(prune.mod,newdata=data.train)
classif.train<-ifelse(pred.train[,2]>=pred.train[,1],1,0)
err(data.train$spam,classif.train)
pred.test<-predict(prune.mod,newdata=data.test)
classif.test<-ifelse(1*pred.test[,2]>=pred.test[,1],1,0)
err(data.test$spam,classif.test)
```

We can conclude that our classification model performs very well. since the complex tree is the same as pruned tree here, we can see that the test error is just very slightly higher than the train error. There is not much overfitting here.

## Different Classification Models

Now for this part, we are going to compare different classification models using two different classification scenarios.

Firstly, we consider the scenario where we have different prior probabilities and equal classification costs. We use the entire dataset to figure out the prior probability.

```
#(a)Account for different prior probabilities and equal classification costs
# (1) linear discriminant analysis
set.seed(0829539)
ldaS.out<-lda(spam~.,data=spamdata)
print(ldaS.out$prior)
```

```
      0      1
0.6059552 0.3940448
```

So, we take  $P(\text{is spam})=0.394$ ,  $P(\text{not spam})=0.606$  as our prior probability, and we can verify that their sum equals 1.

The four classification models we are going to compare is 1) Linear Discriminant Analysis, 2) Bagging, 3) Random Forests and 4) Gradient Boosting. Since the dimension here is very high and the mathematical assumption of our dataset is very weak, we do not suppose that Linear Discriminant Analysis without Principal Component analysis here will have very good performance. We just take it as a baseline. The three other methods are all methods used to improve the classification tree model, as tree models are always with high variance, thus high probability to cause overfitting.

The results are listed as below:

### 1) Linear Discriminant Analysis

```
lda.out<-lda(spam~.,prior=c(0.606,0.394),data=data.train)
```

Warning in lda.default(x, grouping, ...): variables are collinear

```
scaling <- lda.out$scaling %>% as.data.frame() %>% mutate(name = rownames(lda.out$scaling))
scaling %>% filter(name %in% c("char_freq_dollar", "word_freq_remove", "word_freq_table",
                             "word_freq_conference", "char_freq_dotcomma",
                             "char_freq_parenthesis", "char_freq_bracket", "char_freq_exclmark" ))
```

	LD1	name
1	0.6815563	word_freq_remove
2	-0.4296151	word_freq_table
3	-0.4725607	word_freq_conference
4	-0.5919005	char_freq_dotcomma
5	-0.4811911	char_freq_parenthesis
6	-1.3138634	char_freq_bracket
7	0.2859002	char_freq_exclmark
8	0.9359106	char_freq_dollar

Here we can see that the three attributes highly correlated with spam webmails—the frequency of “\$”, “!” and “remove”, are exactly the same as what we have got from our classification tree model. What is interesting here is we can also see that the frequency of “table”, “;” and “parenthesis” shows strong negative correlation with spam webmails.

```
pred.train<-predict(lda.out,data.train)
err(data.train$spam,pred.train$class)
```

```
pred.test<-predict(lda.out,data.test)
err(data.test$spam,pred.test$class)
```

## 2) Bagging just some test


```
#(2) Bagging
set.seed(0829539)
bag.mod=randomForest(spam ~ ., data = data.train,
                      classwt=c(0.606,0.394),
                      mtry=57, ntree=nrotree, importance=TRUE)
bag.mod
```

Call:

```
randomForest(formula = spam ~ ., data = data.train, classwt = c(0.606, 0.394), mtry = 57, ntree = 
  Type of random forest: regression
  Number of trees: 500
No. of variables tried at each split: 57
```

```
Mean of squared residuals: 0.07989729
% Var explained: 66.82
```

```
#plot variable importance
varImpPlot(bag.mod,type=2,cex=.8)
```



```
pred.train<-predict(bag.mod,newdata=data.train)
err(data.train$spam,pred.train)

pred.test<-predict(bag.mod,newdata=data.test)
err(data.test$spam,pred.test)
```

Actually, with the *MeanDecreaseGini* graph we can see that the frequency of “\$”, “!” and “remove” made evidently the most contribution. This is the same conclusion we have drawn from our classification tree model and Linear Discriminant Analysis. Here Out Of Bag error rate is 6.76%, which is acceptable.

### 3) Random Forests just some text.

```
# (3) random forests
set.seed(0829539)
rf.mod=randomForest(spam~.,data=data.train,classwt=c(0.606,0.394),mtry=5,ntree=nrotree,importance=TRUE)
rf.mod
```

Call:

```
randomForest(formula = spam ~ ., data = data.train, classwt = c(0.606, 0.394), mtry = 5, ntree = 1000)
Type of random forest: regression
```

Number of trees: 500

No. of variables tried at each split: 5

Mean of squared residuals: 0.07646554

% Var explained: 68.24

```
pred.train<-predict(rf.mod,newdata=data.train)
err(data.train$spam,pred.train)
```

```
pred.test<-predict(rf.mod,newdata=data.test)
err_1 <- err(data.test$spam,pred.test)
```

```
kable(err_1$table)
```


Warning in kable\_pipe(x = structure(character(0), .Dim = c(0L, 0L), .Dimnames =  
list(: The table should have a header (column names)

```
kable(err_1$numeric)
```

Warning in kable\_pipe(x = structure(character(0), .Dim = c(0L, 0L), .Dimnames =  
list(: The table should have a header (column names)

```
#variable importance plot
#two measures are reported:
#increase in MSE computed on OOB samples when removing variable
#decrease in node impurity (or increase in node purity) resulting from splits on the variable
importance(rf.mod)
```

```
varImpPlot(rf.mod,type=2,cex=.7)
```



Random Forests Model is also based on the idea of decorrelating trees. Here we choose  $m=5$  for the size of our predictor set. can see that although there is slightly difference, “\$”, “!” and “remove” still stand for spam webmails, as well as the length of the longest uninterrupted sequence of capital letters.


**4) Gradient Boosting** Different from Bagging and Random Forests, the number of trees for Gradient Boosting is not expected to be as large as possible, since using too many trees may cause overfitting for Gradient Boosting. We start with deciding the optimal number of trees by cross-validation, for the same reason explained before.

Note that since we are going to suppose Bernoulli distribution in our gbm function, we should firstly make sure that our variable for classification is numeric type.

```
# (4) gradient boosting
set.seed(0829539)
data.train$spam<-ifelse(data.train$spam=="1_yes",1,0)
data.test$spam<-ifelse(data.test$spam=="1_yes",1,0)
spamdata$spam<-ifelse(spamdata$spam=="1_yes",1,0)

#use distribution="bernoulli" for binary target
#interaction.depth=4, means that we fit a tree that uses 4 splits
#(and that includes at most a 4-th order interaction)

#data.train$spam <- as.factor(data.train$spam)
#boost.mod=gbm(spam~., distribution="bernoulli", data=data.train, n.trees=20000, interaction.depth=4,
#              shrinkage=0.001,cv.folds=5)
#boost.mod=gbm::gbm(spam~., distribution="bernoulli", data=data.train, n.trees=20000, interaction.depth=4,
#                  shrinkage=0.001,cv.folds=1)
load("~/GitHub/kul-multivariate-a2/save_objects.Rdata")
gbm.perf(boost.mod_save,method="cv")
```






```
## [1] 19932
```

So here we get that the optimal number of trees is 19932. We use this parameter to continue our analysis.

```
#relative influence plot  
par(cex=1.2)  
summary(boost.mod_save,n.trees=19932)
```



	var	rel.inf
char_freq_dollar	char_freq_dollar	2.285917e+01
char_freq_exclmark	char_freq_exclmark	1.965558e+01
word_freq_remove	word_freq_remove	9.933912e+00
word_freq_hp	word_freq_hp	6.371358e+00
word_freq_your	word_freq_your	6.075841e+00
word_freq_free	word_freq_free	5.428856e+00
capital_run_length_longest	capital_run_length_longest	4.344714e+00
capital_run_length_average	capital_run_length_average	3.937332e+00
capital_run_length_total	capital_run_length_total	3.391273e+00
word_freq_george	word_freq_george	2.866851e+00
word_freq_edu	word_freq_edu	2.308666e+00
word_freq_our	word_freq_our	1.976375e+00
word_freq_money	word_freq_money	1.743456e+00
word_freq_000	word_freq_000	1.559673e+00
word_freq_you	word_freq_you	1.013728e+00
word_freq_meeting	word_freq_meeting	7.223353e-01

word_freq_re	word_freq_re	6.227953e-01
word_freq_internet	word_freq_internet	5.493848e-01
word_freq_1999	word_freq_1999	4.530588e-01
word_freq_business	word_freq_business	4.244831e-01
word_freq_over	word_freq_over	3.985102e-01
word_freq_email	word_freq_email	3.710928e-01
word_freq_receive	word_freq_receive	3.484809e-01
word_freq_will	word_freq_will	3.377431e-01
char_freq_dotcomma	char_freq_dotcomma	3.321253e-01
char_freq_parenthesis	char_freq_parenthesis	2.853891e-01
word_freq_report	word_freq_report	2.587867e-01
word_freq_technology	word_freq_technology	2.084485e-01
word_freq_mail	word_freq_mail	1.903978e-01
word_freq_hpl	word_freq_hpl	1.677002e-01
word_freq_650	word_freq_650	1.504262e-01
word_freq_3d	word_freq_3d	1.131915e-01
word_freq_all	word_freq_all	1.063984e-01
word_freq_font	word_freq_font	8.440753e-02
word_freq_project	word_freq_project	7.595445e-02
word_freq_make	word_freq_make	6.275894e-02
word_freq_pm	word_freq_pm	4.042293e-02
word_freq_address	word_freq_address	3.613297e-02
word_freq_order	word_freq_order	3.496306e-02
word_freq_parts	word_freq_parts	2.876464e-02
word_freq_conference	word_freq_conference	2.842824e-02
word_freq_credit	word_freq_credit	2.467152e-02
word_freq_people	word_freq_people	2.197801e-02
word_freq_85	word_freq_85	1.685307e-02
char_freq_pound	char_freq_pound	1.468910e-02
word_freq_data	word_freq_data	1.128843e-02
word_freq_labs	word_freq_labs	4.584238e-03
char_freq_bracket	char_freq_bracket	3.254895e-03
word_freq_direct	word_freq_direct	2.550972e-03
word_freq_lab	word_freq_lab	4.378566e-04
word_freq_original	word_freq_original	1.606371e-04
word_freq_addresses	word_freq_addresses	9.088811e-05
word_freq_table	word_freq_table	7.843543e-05
word_freq_telnet	word_freq_telnet	0.000000e+00
word_freq_857	word_freq_857	0.000000e+00
word_freq_415	word_freq_415	0.000000e+00
word_freq_cs	word_freq_cs	0.000000e+00

We can actually get nearly the same result as we obtained from all the former models concerning the variable most correlated to spam webmails here, that the frequency of “\$”, “!” and “remove” come top.

```

pred.train<-predict(boost.mod_save,n.trees=19932,newdata=data.train,type="response")
classif.train<-ifelse(pred.train>=1-pred.train,1,0)
err(data.train$spam,classif.train)
pred.test<-predict(boost.mod_save,n.trees=19932,newdata=data.test,type="response")
classif.test<-ifelse(pred.test>=1-pred.test,1,0)
err(data.test$spam,classif.test)

```

Then, we consider the scenario where we have different prior probabilities and unequal classification costs:  $C(spam|email) = 10 * C(email|spam)$ . Actually, the models here remain the same, and we just need to

do some reclassification based on the posterior probabilities obtained from our built models and a criterion taking the classification costs as weights for posterior probabilities.

## 1) Linear Discriminant Analysis some text

```
#(b)Account for different prior probabilities and unequal classification costs: C(spam/email)=10*C(email/spam)  
# (1) linear discriminant analysis  
set.seed(0829539)  
data.train$spam<-factor(ifelse(data.train$spam==1,"1_yes","0_no"))  
data.test$spam<-factor(ifelse(data.test$spam==1,"1_yes","0_no"))  
spamdata$spam<-factor(ifelse(spamdata$spam==1,"1_yes","0_no"))  
print(data.train$spam)
```

```
[1] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[16] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[31] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[46] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[61] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[76] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[91] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[106] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[121] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[136] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[151] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[166] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[181] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[196] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[211] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[226] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
[241] 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no 0_no  
Levels: 0_no
```

```
#lda.out<- MASS::lda(spam~.,prior=c(0.606,0.394),data=data.train)  
#print(lda.out)  
  
#pred.train<-predict(lda.out,data.train)  
#classif.train<-ifelse(1*pred.train$posterior[,2]>=10*pred.train$posterior[,1],1,0)  
#err(data.train$spam, classif.train)  
  
#pred.test<-predict(lda.out,data.test)  
#classif.test<-ifelse(1*pred.test$posterior[,2]>=10*pred.test$posterior[,1],1,0)  
#err(data.test$spam,classif.test)
```