

# Machine Learning

## Lecture 9:


# Introduction to Deep Learning


Harbour.Space University  
February 2020

**Radoslav Neychev**


1. Neural Networks in different areas. Historical overview.
2. Backpropagation.
3. Playground.
4. More on backpropagation.
5. Activation functions.
6. PyTorch practice

# Deep Learning Timeline






Spectrogram




MFCC

- Object detection
- Action classification
- Image captioning
- ...



"man in black shirt is playing guitar."


# Logistic regression




$$P(y|x) = \sigma(w \cdot x + b)$$

$$L = - \sum_i y_i \log P(y|x_i) + (1 - y_i) \log (1 - P(y|x_i))$$

# Problem: nonlinear dependencies



What we have




What we want

Logistic regression  
(generally, linear model)  
need feature engineering  
to show good results.


And feature engineering is  
*an art.*

# Classic pipeline



Handcrafted features, generated by experts.


# NN pipeline



Automatically extracted features.




# NN pipeline: example




E.g. two logistic regressions one after another.

# NN pipeline: example




Actually, it's a neural network.

# XOR problem




This 2-layer NN (on the left) implements XOR with only  $x^1$  and  $x^2$  features.


1-layer NN also can succeed, but only with extra feature  $x^1 * x^2$ .




AND



OR



XOR(with  $x^1 * x^2$ )



XOR


# Activation functions: nonlinearities

$$f(a) = \frac{1}{1 + e^a}$$

$$f(a) = \tanh(a)$$


$$f(a) = \max(0, a)$$

$$f(a) = \log(1 + e^a)$$




# Some generally accepted terms

- Layer – a building block for NNs :
  - Dense layer:  $f(x) = Wx+b$
  - Nonlinearity layer:  $f(x) = \sigma(x)$
  - Input layer, output layer
  - A few more we will cover later
- Activation function – function applied to layer output
  - Sigmoid
  - tanh
  - ReLU
  - Any other function to get nonlinear intermediate signal in NN
- Backpropagation – a fancy word for “chain rule”




“Train it via backprop!”

Actually, it can be deeper



# Much deeper...



## How to train it?






# Backpropagation and chain rule

Chain rule is just simple math:  $\frac{\partial L}{\partial x} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial x}$


Backprop is just way to use it in NN training.



# Backpropagation example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$



# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

A magenta arrow points from this box to the  $z$  input of the multiplication node in the computational graph above.

# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$





# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}$ ,  $\frac{\partial f}{\partial y}$ ,  $\frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

$$\frac{\partial f}{\partial y}$$

# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



# Backpropagation example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial x}$$

Chain rule:

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$

# Practice time: interactive playground

## DATA

Which dataset do you want to use?



Ratio of training to test data: 50%



Noise: 0



Batch size: 10



REGENERATE

## FEATURES

Which properties do you want to feed in?



+ - 1 HIDDEN LAYER

+ -


2 neurons

This is the output from one **neuron**.  
Hover to see it larger.


## OUTPUT

Test loss 0.208

Training loss 0.207



Colors shows data, neuron and weight values.



☐ Show test data ☐ Discretize output


<https://playground.tensorflow.org/>

# Backpropagation and chain rule

Chain rule is just simple math:


$$\frac{\partial L}{\partial x} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial x}$$

Backprop is just way to use it in NN training.



# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$





# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		<div style="border: 1px solid red; padding: 5px;"><math>f_c(x) = c + x</math></div>	$\rightarrow$	<div style="border: 1px solid red; padding: 5px;"><math>\frac{df}{dx} = 1</math></div>

# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$




$$\boxed{\begin{array}{l} f(x) = e^x \quad \rightarrow \quad \frac{df}{dx} = e^x \\ f_a(x) = ax \quad \rightarrow \quad \frac{df}{dx} = a \end{array}}$$

$$\begin{array}{l} f(x) = \frac{1}{x} \quad \rightarrow \quad \frac{df}{dx} = -1/x^2 \\ f_c(x) = c + x \quad \rightarrow \quad \frac{df}{dx} = 1 \end{array}$$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

$$f_c(x) = c + x$$

$\rightarrow$


$$\frac{df}{dx} = -1/x^2$$

$\rightarrow$

$$\frac{df}{dx} = 1$$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$


$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$



# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$

$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

$$f_c(x) = c + x$$

→


$$\frac{df}{dx} = -1/x^2$$

→

$$\frac{df}{dx} = 1$$

# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$$\begin{array}{lcl}
 f(x) = e^x & \rightarrow & \frac{df}{dx} = e^x \\
 f_a(x) = ax & \rightarrow & \frac{df}{dx} = a
 \end{array}
 \quad \Bigg| \quad
 \begin{array}{lcl}
 f(x) = \frac{1}{x} & \rightarrow & \frac{df}{dx} = -1/x^2 \\
 f_c(x) = c + x & \rightarrow & \frac{df}{dx} = 1
 \end{array}$$

# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	$\rightarrow$	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	$\rightarrow$	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	$\rightarrow$	$\frac{df}{dx} = a$		$f_c(x) = c + x$	$\rightarrow$	$\frac{df}{dx} = 1$

# Backpropagation example


Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



$$\begin{array}{lcl}
 f(x) = e^x & \rightarrow & \frac{df}{dx} = e^x \\
 f_a(x) = ax & \rightarrow & \frac{df}{dx} = a
 \end{array}
 \quad \Bigg| \quad
 \begin{array}{lcl}
 f(x) = \frac{1}{x} & \rightarrow & \frac{df}{dx} = -1/x^2 \\
 f_c(x) = c + x & \rightarrow & \frac{df}{dx} = 1
 \end{array}$$

# Backpropagation example

Another example:  $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$



[local gradient] x [its gradient]

$$x_0: [2] \times [0.2] = 0.4$$

$$w_0: [-1] \times [0.2] = -0.2$$


$$\begin{array}{lcl} f(x) = e^x & \rightarrow & \frac{df}{dx} = e^x \\ f_a(x) = ax & \rightarrow & \frac{df}{dx} = a \end{array} \quad \left| \quad \begin{array}{lcl} f(x) = \frac{1}{x} & \rightarrow & \frac{df}{dx} = -1/x^2 \\ f_c(x) = c + x & \rightarrow & \frac{df}{dx} = 1 \end{array} \right.$$

# Backpropagation example

$$f(w, x) = \frac{1}{1 + e^{-(w_0 x_0 + w_1 x_1 + w_2)}}$$

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad \text{sigmoid function}$$



$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left( \frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left( \frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$



# Gradient optimization

Stochastic gradient descent (and variations)  
is used to optimize NN parameters.

$$x_{t+1} = x_t - \text{learning rate} \cdot dx$$




# Once more: nonlinearities

$$f(a) = \frac{1}{1 + e^a}$$

$$f(a) = \tanh(a)$$


$$f(a) = \max(0, a)$$

$$f(a) = \log(1 + e^a)$$





# Activation functions



## Sigmoid


$$f(a) = \frac{1}{1 + e^a}$$

- Squashes numbers to range [0,1]
- Historically popular since they have nice interpretation as a saturating “firing rate” of a neuron

3 problems:

1. Saturated neurons “kill” the gradients
2. Sigmoid outputs are not zero-centered
3.  $\exp()$  is a bit compute expensive

# Activation functions




**$\tanh(x)$**

- Squashes numbers to range  $[-1,1]$
- zero centered (nice)
- still kills gradients when saturated :(

$$f(a) = \tanh(a)$$

# Activation functions



## ReLU


(Rectified Linear Unit)

$$f(a) = \max(0, a)$$

- Does not saturate (in +region)
- Very computationally efficient
- Converges much faster than sigmoid/tanh in practice (e.g. 6x)
- Not zero-centered output
- An annoyance:

hint: what is the gradient when  $x < 0$ ?

# Activation functions




- Does not saturate
- Computationally efficient
- Converges much faster than sigmoid/tanh in practice! (e.g. 6x)
- **will not “die”.**

## Leaky ReLU

$$f(x) = \max(0.01x, x)$$

# Activation functions

- Does not saturate
- Computationally efficient
- Converges much faster than sigmoid/tanh in practice! (e.g. 6x)
- **will not “die”.**



## Leaky ReLU

$$f(x) = \max(0.01x, x)$$


## Parametric Rectifier (PReLU)

$$f(x) = \max(\alpha x, x)$$

backprop into  $\alpha$   
(parameter)



## Exponential Linear Units (ELU)



$$f(x) = \begin{cases} x & \text{if } x > 0 \\ \alpha (\exp(x) - 1) & \text{if } x \leq 0 \end{cases}$$

- All benefits of ReLU
- Does not die
- Closer to zero mean outputs
- Computation requires  $\exp()$

# Activation functions: sum up

- Use **ReLU** as baseline approach
- Be careful with the learning rates
- Try out **Leaky ReLU** or **ELU**
- Try out **tanh** but do not expect much from it
- Do not use **Sigmoid**

That's all. Time to build some NN.







Backup

# Optimizers

Stochastic gradient descent is used to optimize NN parameters.


$$x_{t+1} = x_t - \text{learning rate} \cdot dx$$



# Optimizers

There are much more optimizers:

- Momentum
- Adagrad
- Adadelata
- RMSprop
- Adam
- ...
- even other NNs




# Optimization: SGD

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(x_i, y_i, W)$$

$$\nabla_W L(W) = \frac{1}{N} \sum_{i=1}^N \nabla_W L_i(x_i, y_i, W)$$

Averaging over minibatches ---> noisy gradient



# First idea: momentum


Simple SGD

$$x_{t+1} = x_t - \alpha \nabla f(x_t)$$

SGD with momentum


$$v_{t+1} = \rho v_t + \nabla f(x_t)$$

$$x_{t+1} = x_t - \alpha v_{t+1}$$



# Nesterov momentum


Momentum update:



$$v_{t+1} = \rho v_t + \nabla f(x_t)$$

$$x_{t+1} = x_t - \alpha v_{t+1}$$


Nesterov Momentum



$$v_{t+1} = \rho v_t - \alpha \nabla f(x_t + \rho v_t)$$

$$x_{t+1} = x_t + v_{t+1}$$

# Comparing momentums



## Second idea: different dimensions are different

Adagrad: SGD with cache

$$\text{cache}_{t+1} = \text{cache}_t + (\nabla f(x_t))^2$$

$$x_{t+1} = x_t - \alpha \frac{\nabla f(x_t)}{\text{cache}_{t+1} + \varepsilon}$$



## Second idea: different dimensions are different

Adagrad: SGD with cache

$$\text{cache}_{t+1} = \text{cache}_t + (\nabla f(x_t))^2$$

$$x_{t+1} = x_t - \alpha \frac{\nabla f(x_t)}{\text{cache}_{t+1} + \varepsilon}$$

*Problem: gradient fades with time*

# Second idea: different dimensions are different

Adagrad: SGD with cache


$$\text{cache}_{t+1} = \text{cache}_t + (\nabla f(x_t))^2$$

$$x_{t+1} = x_t - \alpha \frac{\nabla f(x_t)}{\text{cache}_{t+1} + \varepsilon}$$




RMSProp: SGD with cache with exp. Smoothing

$$\text{cache}_{t+1} = \beta \text{cache}_t + (1 - \beta)(\nabla f(x_t))^2$$

$$x_{t+1} = x_t - \alpha \frac{\nabla f(x_t)}{\text{cache}_{t+1} + \varepsilon}$$


Slide 29 Lecture 6 of Geoff Hinton's Coursera class

[http://www.cs.toronto.edu/~tijmen/csc321/slides/lecture\\_slides\\_lec6.pdf](http://www.cs.toronto.edu/~tijmen/csc321/slides/lecture_slides_lec6.pdf)



— SGD

— SGD+Momentum

— RMSProp

Let's combine the momentum idea and RMSProp normalization:

$$\begin{aligned}v_{t+1} &= \gamma v_t + (1 - \gamma) \nabla f(x_t) \\ \text{cache}_{t+1} &= \beta \text{cache}_t + (1 - \beta) (\nabla f(x_t))^2 \\ x_{t+1} &= x_t - \alpha \frac{v_{t+1}}{\text{cache}_{t+1} + \varepsilon}\end{aligned}$$


Adam full form involves bias correction term. See <http://cs231n.github.io/neural-networks-3/> for more info.

Let's combine the momentum idea and RMSProp normalization:

$$\begin{aligned}v_{t+1} &= \gamma v_t + (1 - \gamma) \nabla f(x_t) \\ \text{cache}_{t+1} &= \beta \text{cache}_t + (1 - \beta) (\nabla f(x_t))^2 \\ x_{t+1} &= x_t - \alpha \frac{v_{t+1}}{\text{cache}_{t+1} + \varepsilon}\end{aligned}$$



*Actually, that's not quite Adam.*

# Comparing optimizers



- SGD
- SGD+Momentum
- RMSProp
- Adam


# Once more: learning rate




# Sum up: optimization

- Adam is great basic choice
- Even for Adam/RMSProp learning rate matters
- Use learning rate decay
- Monitor your model quality





Better optimization algorithms  
help reduce training loss



But we really care about error on new  
data - how to reduce the gap?