

Database Basics MS SQL Exam – 13 October 2019

Exam problems for the [“Database Basics” course @ SoftUni](#).


Submit your solutions in the SoftUni Judge system at <https://judge.softuni.bg/>

Bitbucket

You’ve most likely heard of Github. Well ... There is a side project called “Bitbucket” which is the back-up data of Github. You are one of the few selected to work in the multi-billion company, as one of the back-up database managers. You’ll need to prove your skills by designing and manipulating data in the Instagram prototype.

Section 1. DDL (30 pts)

You are given an E/R Diagram of the Trip Service:



Create a database called **Bitbucket**. You need to create **6 tables**:

- **Users** – contains information about the **users**.
- **Repositories** – contains information about the **repositories**.
- **RepositoriesContributors** – a **many to many mapping** table between the **repositories** and the **users**.
- **Issues** – contains information about the **issues**.
 - Each **issue** has a **repository**.
 - Each **issue** has an **assignee (user)**.
- **Commits** – contains information about the **commits**.
 - Each **commit** **MAY** have an **issue**.
 - Each **commit** has a **repository**.
 - Each **commit** has a **contributor (user)**.
- **Files** – contains information about the **files**.
 - Each **file** **MAY** have a **parent (file)**.

- Each **file** has a **commit**.

Users

Column Name	Data Type	Constraints
Id	Integer from 0 to 2,147,483,647	Unique table identifier , Identity
Username	String up to 30 symbols	NULL is not allowed
Password	String up to 30 symbols	NULL is not allowed
Email	String up to 50 symbols	NULL is not allowed

Repositories

Column Name	Data Type	Constraints
Id	Integer from 0 to 2,147,483,647	Unique table identifier , Identity
Name	String up to 50 symbols	NULL is not allowed

RepositoriesContributors

Column Name	Data Type	Constraints
RepositoryId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Repositories
ContributorId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Users

Issues

Column Name	Data Type	Constraints
Id	Integer from 0 to 2,147,483,647	Unique table identifier , Identity
Title	String up to 255 symbols	NULL is not allowed
IssueStatus	String with exactly 6 symbols	NULL is not allowed
RepositoryId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Repositories
AssigneeId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Users

Commits

Column Name	Data Type	Constraints
Id	Integer from 0 to 2,147,483,647	Unique table identifier , Identity
Message	String up to 255 symbols	NULL is not allowed
IssuedId	Integer from 0 to 2,147,483,647	Relationship with table Issues
RepositoryId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Repositories
ContributorId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Users

Files

Column Name	Data Type	Constraints
Id	Integer from 0 to 2,147,483,647	Unique table identifier , Identity
Name	String up to 100 symbols	NULL is not allowed
Size	Decimal number with two-digit precision	NULL is not allowed
ParentId	Integer from 0 to 2,147,483,647	Relationship with table Files
CommitId	Integer from 0 to 2,147,483,647	NULL is not allowed, Relationship with table Commits

1. Database Design

Submit all of yours **create statements** to Judge (only creation of tables).

Section 2. DML (10 pts)

Before you start, you must import "DataSet-Bitbucket.sql". If you have created the structure correctly, the data should be successfully inserted without any errors.

In this section, you have to do some data manipulations:

2. Insert

Insert some sample data into the database. Write a query to add the following records into the corresponding tables. **All Ids should be auto-generated.**

Files

Name	Size	ParentId	CommitId
Trade.idk	2598.0	1	1
menu.net	9238.31	2	2
Administrat .sosh	1246.93	3	3
Controller.ph p	7353.15	4	4
Find.java	9957.86	5	5
Controller.js on	14034.87	3	6
Operate.xix	7662.92	7	7

Issues

Title	IssueStatus	RepositoryId	AssigneeId
Critical Problem with HomeController.cs file	open	1	4
Typo fix in Judge.html	open	4	3
Implement documentation for UsersService.cs	closed	8	2
Unreachable code in Index.cs	open	9	8

3. Update

Make issue status 'closed' where Assignee Id is 6.

4. Delete

Delete repository "**Softuni-Teamwork**" in repository **contributors** and **issues**.

Section 3. Querying (40 pts)

You need to start with a fresh dataset, so recreate your DB and import the sample data again ([DataSet - Bitbucket.sql](#)).

5. Commits

Select all commits from the database. Order them by **id** (ascending), **message** (ascending), **repository id** (ascending) and **contributor id** (ascending).

Examples

Id	Message	RepositoryId	ContributorId
1	Deleted deprecated functionality from index.cpp	17	8
2	Created README.MD	14	8
3	Initial Commit	24	1
4	Implemented config.json functionality	10	12
...

6. Heavy HTML

Select all of the **files**, which have **size**, **greater** than **1000**, and their **name** contains "**html**". Order them by **size** (descending), **id** (ascending) and by **file name** (ascending)

Examples

Id	Name	Size
49	compile.html	27402.59
17	Login.html	2863.23
...

7. Issues and Users

Select all of the **issues**, and the **users** that are **assigned** to them, so that they end up in the following format: **{username} : {issueTitle}**. Order them by **issue id** (descending) and **issue assignee** (ascending).

Examples

Id	IssueAssignee
75	TheDivineBel : Critical bug in Controller.php ruins application when executed
74	DarkImmagidsa : Compilation failed while trying to execute init.xml
73	ScoreAntigarein : Loose Cohesion and Strong Coupling in Beat.html

...	...
-----	-----

8. Non-Directory Files

Examples

Select all of the **files**, which are NOT a **parent** to any other file. Select their size of the file and add "**KB**" to the end of it. Order them file **id** (ascending), **file name** (ascending) and **file size** (descending).

Id	Name	Size
6	Controller.json	14034.87KB
12	Model.MD	4753.67KB
17	Login.html	2863.23KB
...

9. Most Contributed Repositories

Select the **top 5** repositories in terms of **count** of **commits**. Order them by **commits count** (descending), **repository id** (ascending) then by **repository name** (ascending).

Examples

Id	Name	Commits
1	WorkWork	20
7	DundaApp	16
10	SortedTupleJS	12
...

10. User and Files

Select all users which have **commits**. Select their username and average size of the file, which were uploaded by them. Order the results by **average upload size** (descending) and by **username** (ascending).

Examples

Username	Size
RoundIns pecindi	19506.877500
BlaAntiga dsa	18397.434000
...	...

Section 4. Programmability (20 pts)

11. User Total Commits

Create a **user defined function**, named `udf_UserTotalCommits(@username)` that receives a username.

The function must return count of all commits for the user:

Example:

Query
<code>SELECT dbo.udf_UserTotalCommits('UnderSinduxrein')</code>
Output
6

12. Find by Extensions

Create a **user defined stored procedure**, named `usp_FindByExtension(@extension)`, that receives a files extensions.

The procedure must print the **id**, **name** and **size** of the file. Add "KB" in the end of the size. Order them by **id** (ascending), **file name** (ascending) and **file size** (descending)

Example:

Query		
<code>EXEC usp_FindByExtension 'txt'</code>		
Output		
Id	Name	Size
28	Jason.txt	10317.54KB
31	file.txt	5514.02KB
43	init.txt	16089.79KB