

1 Surroundings

1.1 setup

```
1 測機 (test on C++ and Python)
2 AC : 好好寫
3 WA : cout << "0\n" / 結尾多印一行;
4 RE : 空間越界/除0
5 TLE : while(true);
6 CE : empty code
7 OLE : 瘋狂Hello World
8 NO Output : default code
9 待測 : stack深度、judge速度、陣列MAX
10 開賽
11 1. bash.rc打ac
12 2. 調gedit設定
13 3. 打default_code
14 4. 測試ac
```

1.2 bashrc

```
1 oj() {
2   ext=${1##*.}           #空格敏感
3   filename=${1##*/}      #空格敏感
4   filename=${filename%. *} #空格敏感
5   case $ext in
6     cpp ) g++ -o "/tmp/$filename" "$1" && "/tmp/$filename" ;;
7     py   ) python3 "$1" ;;
8
9   esac
10 }
```

1.3 vimrc

```
1 set tabstop=4
2 set shiftwidth=4
3 set softtabstop=4
4 set expandtab
5 set autoindent
6 set number
```

2 Data_Structure

2.1 Sparse Table

```
1 // https://judge.yosupo.jp/problem/staticrmq 214 ms
2
3 template<typename T, int RANGE>
4 struct Sparse_Table {
```

```
5     struct Node {
6         T val;
7
8         Node(): val(INF) {}
9
10        Node operator +(const Node &rhs) {
11            Node ret;
12            ret.val = min(val, rhs.val);
13            return ret; // 視情況修改
14        }
15    };
16    vector<vector<Node>> arr;
17
18    Sparse_Table() {
19        arr.resize(__lg(RANGE) + 1, vector<Node>(RANGE, Node()));
20    }
21
22    void build(auto &v) {
23        for (int i = 1; i <= n; i++) {
24            arr[0][i].val = v[i];
25        }
26        for (int i = 1; i <= __lg(n); i++)
27            for (int j = 1; j + (1 << (i - 1)) <= n; j++)
28                arr[i][j] = arr[i - 1][j] + arr[i - 1][j + (1 << (i - 1))];
29    }
30
31    Node query(int ql, int qr) {
32        int lg = __lg(qr - ql + 1);
33        return arr[lg][ql] + arr[lg][qr - (1 << lg) + 1];
34    }
35    };
```

2.2 Fenwick Tree

```
1 /** 普通 BIT ，為了加速打字只支援 1-based **/
2 const int MAXN = ? ; // 開全域加速打字
3 #define lowbit(x & (-x))
4
5 template<typename T>
6 struct Fenwick_Tree { // 1 based
7     // 二維：陣列開二維，修改跟查詢就是對 (x, y) 各自 +- lowbit
8     T arr[MAXN];
9     void init(int _n = MAXN) {
10         for (int i = 0; i < _n; i++)
11             arr[i] = 0;
12     }
13     void update(int i, T val) {
14         for (; i < MAXN; i += lowbit(i))
15             arr[i] += val;
16     }
17     T query(int i) {
18         T ret = 0;
19         for (; i; i -= lowbit(i))
20             ret += arr[i];
21         return ret;
22     }
23 };
24 };
```

2.3 線段樹

```
1 /** 普通線段樹，為了加速打字時間，所以只支援 1-based 。 **/
2 /**
3  * 把 df 設為：
4  * 0 for 區間和/gcd/bit-or/bit-xor
5  * 1 for 區間積/lcm
6  * 9e18 for 區間最小值
7  * -9e18 for 區間最大值
8  * -1 for 區間 bit-and
9  */
10 const ll df = 0;
11 const int N = ? ; // maxn
12 #define ls i << 1 // 加速打字
13 #define rs i << 1 | 1
14 struct SegmentTree {
15     ll a[N << 2];
16     inline ll cal(ll a, ll b) {
17         /**
18          * 把回傳值設為對應的操作，例如 a+b 為區間和，還有像
19          * 是
20          * a*b, min(a,b), max(a,b), gcd(a,b), lcm(a,b),
21          * a|b, a&b, a^b 等等。 */
22         return a + b;
23     }
24     // 單點設置。外部呼叫的時候後三個參數不用填。注意只支援
25     // 1-based !
26     ll set(int q, ll v, int i = 1, int l = 1, int r = N) {
27         if (r < q || l > q) return a[i];
28         if (l == r) return a[i] = v;
29         int m = (l + r) >> 1;
30         ll lo = set(q, v, ls, l, m);
31         ll ro = set(q, v, rs, m + 1, r);
32         return a[i] = cal(lo, ro);
33     }
34     // 查詢區間 [l, r] 總和
35     // (或極值等等，看你怎麼寫)。外部呼叫的時
36     // 候後三個參數不用填。注意只支援 1-based !
37     ll query(int ql, int qr, int i = 1, int l = 1,
38             int r = N) {
39         if (r < ql || l > qr) return df;
40         if (ql <= l && r <= qr) return a[i];
41         int m = (l + r) >> 1;
42         ll lo = query(ql, qr, ls, l, m);
43         ll ro = query(ql, qr, rs, m + 1, r);
44         return cal(lo, ro);
45     }
46     // 建立 size = N 的空線段樹，所有元素都是 0 。注意只支援
47     // 1-based !
48     SegmentTree() { memset(a, 0, sizeof(a)); }
49 };
```

2.4 單點修改、區間查詢線段樹

```
1 // https://judge.yosupo.jp/problem/point_add_range_sum 331 ms
2 // https://judge.yosupo.jp/problem/staticrmq 359 ms
3 template<typename T, int RANGE>
4 struct Segment_Tree {
5     struct Node {
6         T val;
```

```

7 Node (): val(0) {} // mx: -INF, mn: INF, sum: 0, gcd: 1,
8   lcm: 1
9
10 Node operator +(const Node &rhs) {
11   Node ret;
12   ret.val = val + rhs.val; // 對應不同操作修改
13
14   return ret;
15 }
16
17 void update(int _val) {
18   val += _val;
19 }
20
21 };
22
23 vector<Node> arr;
24
25 Segment_Tree() {
26   arr.resize(RANGE << 2);
27 }
28
29 void build(vector<int> &v, int i = 1, int l = 1, int r = n)
30 {
31   if (l == r) {
32     arr[i].val = v[l];
33     return;
34   }
35   int mid = (l + r) >> 1;
36   build(v, i << 1, l, mid);
37   build(v, i << 1 | 1, mid + 1, r);
38   arr[i] = arr[i << 1] + arr[i << 1 | 1];
39 }
40
41 void update(int pos, int val, int i = 1, int l = 1, int r =
42   n) {
43   if (l == r) {
44     arr[i].update(val);
45     return;
46   }
47   int mid = (l + r) >> 1;
48   if (pos <= mid) update(pos, val, i << 1, l, mid);
49   else update(pos, val, i << 1 | 1, mid + 1, r);
50   arr[i] = arr[i << 1] + arr[i << 1 | 1];
51 }
52
53 Node query(int ql, int qr, int i = 1, int l = 1, int r = n)
54 {
55   if (l > qr || r < ql)
56     return Node();
57   if (ql <= l && r <= qr)
58     return arr[i];
59   int mid = (l + r) >> 1;
60   return query(ql, qr, i << 1, l, mid) + query(ql, qr, i <<
61     1 | 1, mid + 1, r);
62 }
63
64 };

```

2.5 最大區間和線段樹

```

1 /** 計算最大子區間連續和的線段樹，限定 1-based 。
2  * 複雜度 O(Q*log(N)) **/

```

```

3 #define ls i << 1
4 #define rs i << 1 | 1
5 class MaxSumSegmentTree {
6   private:
7     struct node {
8       ll lss, rss, ss, ans;
9       void set(ll v) { lss = rss = ss = ans = v; }
10    };
11    int n;
12    vector<node> a; // 萬萬不可用普通陣列，要用 vector
13    vector<ll> z;
14    void pull(int i) {
15      a[i].ss = a[ls].ss + a[rs].ss;
16      a[i].lss = max(a[ls].lss, a[ls].ss + a[rs].lss);
17      a[i].rss = max(a[rs].rss, a[rs].ss + a[ls].rss);
18      a[i].ans = max(max(a[ls].ans, a[rs].ans),
19        a[ls].rss + a[rs].lss);
20    }
21    void build(int i, int l, int r) {
22      if (l == r) return a[i].set(z[l]), void();
23      int m = (l + r) >> 1;
24      build(ls, l, m), build(rs, m + 1, r), pull(i);
25    }
26    void set(int i, int l, int r, int q, ll v) {
27      if (l == r) return a[i].set(v), void();
28      int m = (l + r) >> 1;
29      if (q <= m) set(ls, l, m, q, v);
30      else set(rs, m + 1, r, q, v);
31      pull(i);
32    }
33    node query(int i, int l, int r, int ql, int qr) {
34      if (ql <= l && r <= qr) return a[i];
35      int m = (l + r) >> 1;
36      if (qr <= m) return query(ls, l, m, ql, qr);
37      if (m < ql) return query(rs, m + 1, r, ql, qr);
38      node lo = query(ls, l, m, ql, qr),
39        ro = query(rs, m + 1, r, ql, qr), ans;
40      ans.ss = lo.ss + ro.ss;
41      ans.lss = max(lo.lss, lo.ss + ro.lss);
42      ans.rss = max(ro.rss, ro.ss + lo.rss);
43      ans.ans = max(max(lo.ans, ro.ans), lo.rss + ro.lss);
44      return ans;
45    }
46  public:
47    MaxSumSegmentTree(int n) : n(n) {
48      a.resize(n << 2), z.resize(n << 2);
49      build(1, 1, n);
50    }
51    // 單點設置。限定 1-based 。
52    inline void set(int i, ll v) { set(1, 1, n, i, v); }
53    // 問必區間 [1, r] 的最大子區間連續和。限定 1-based 。
54    inline ll query(int l, int r) {
55      return query(1, 1, n, l, r).ans;
56    }
57  };

```

2.6 懶標線段樹

```

1 struct Node {
2   int sum, tag;
3   Node(): sum(0), tag(0) {}

```

```

4 void update(int val, int l, int r) {
5   sum += (val) * (r - l + 1);
6   tag += val;
7 }
8
9 Node operator +(const Node &rhs) {
10   Node ret;
11   ret.sum = sum + rhs.sum;
12   return ret;
13 }
14 void operator *=(const Node &rhs) {
15   sum = rhs.sum;
16 }
17 };
18
19 template<typename T>
20 struct Segment_Tree {
21   vector<T> arr;
22
23   void init() {
24     arr.resize(MAXN << 2, Node());
25   }
26
27   void push(int i, int l, int r) {
28     if (l == r || arr[i].tag == 0)
29       return;
30     int mid = (l + r) / 2;
31     arr[i * 2].update(arr[i].tag, l, mid);
32     arr[i * 2 + 1].update(arr[i].tag, mid + 1, r);
33     arr[i].tag = 0;
34   }
35
36   void update(int ql, int qr, int val, int i = 1, int l =
37     1, int r = n) {
38     if (ql <= l && r <= qr) {
39       arr[i].update(val, l, r);
40       return;
41     }
42     if (l > qr || r < ql)
43       return;
44     int mid = (l + r) / 2;
45     push(i, l, r);
46     update(ql, qr, val, i * 2, l, mid);
47     update(ql, qr, val, i * 2 + 1, mid + 1, r);
48     arr[i].sum = (arr[i * 2] + arr[i * 2 + 1]).sum;
49   }
50
51   T query(int ql, int qr, int i = 1, int l = 1, int r = n)
52   {
53     if (ql <= l && r <= qr)
54       return arr[i];
55     if (l > qr || r < ql)
56       return T();
57     int mid = (l + r) / 2;
58     auto q1 = query(ql, qr, i * 2, l, mid);
59     auto q2 = query(ql, qr, i * 2 + 1, mid + 1, r);
60     return q1 + q2;
61   }
62 };

```

2.7 持久化線段樹

```

1 int a[maxn], b[maxn], root[maxn], cnt;
2 struct node {
3     int sum, L_son, R_son;
4 } tree[maxn << 5];
5 int create(int _sum, int _L_son, int _R_son) {
6     int idx = ++cnt;
7     tree[idx].sum = _sum, tree[idx].L_son = _L_son, tree[idx].R_son = _R_son;
8     return idx;
9 }
10 void Insert(int &root, int pre_rt, int pos, int L, int R) {
11     root = create(tree[pre_rt].sum+1, tree[pre_rt].L_son, tree[pre_rt].R_son);
12     if(L==R) return;
13     int M = (L+R)>>1;
14     if(pos<=M) Insert(tree[root].L_son, tree[pre_rt].L_son, pos, L, M);
15     else Insert(tree[root].R_son, tree[pre_rt].R_son, pos, M+1, R);
16 }
17 int query(int L_id, int R_id, int L, int R, int K) {
18     if(L==R) return L;
19     int M = (L+R)>>1;
20     int s = tree[tree[R_id].L_son].sum - tree[tree[L_id].L_son].sum;
21     if(K<=s) return query(tree[L_id].L_son, tree[R_id].L_son, L, M, K);
22     return query(tree[L_id].R_son, tree[R_id].R_son, M+1, R, K-s);
23 }
24 int main() {
25     int n,m; cin >> n >> m;
26     for(int i=1; i<=n; i++) {
27         cin >> a[i]; b[i] = a[i];
28     } sort(b+1,b+1+n); //離散化
29     int b_sz = unique(b+1, b+1+n) - (b+1);
30     cnt = root[0] = 0;
31     for(int i=1; i<=n; i++) {
32         int pos = lower_bound(b+1, b+1+b_sz, a[i]) - b;
33         Insert(root[i], root[i-1], pos, 1, b_sz);
34     }
35     while(m--) {
36         int l, r, k; cin >> l >> r >> k;
37         int pos = query(root[l-1], root[r], l, b_sz, k);
38         cout << b[pos] << endl;
39     } return 0;
40 }

```

2.8 李超線段樹

```

1 template<typename T>
2 struct LiChao_SegTree {
3     T arr[MAXM << 2];
4
5     void init() {
6         for (int i = 0; i < (MAXM << 2); i++) {
7             arr[i] = {m, 0};
8         }
9     }
10
11     void insert(int i, int l, int r, T x) {
12         if (l == r) {
13             if (x(l) < arr[i](l)) {

```

```

14         arr[i] = x;
15     }
16     return;
17 }
18 if (arr[i].a > x.a) {
19     swap(arr[i], x);
20 }
21 }
22 int mid = (l + r) / 2;
23
24 if (x(mid) > arr[i](mid)) {
25     insert(i * 2, l, mid, x);
26 }
27 else {
28     swap(arr[i], x);
29     insert(i * 2 + 1, mid + 1, r, x);
30 }
31 }
32 }
33
34 int query(int i, int l, int r, int pos) {
35     if (l == r)
36         return arr[i](pos);
37     int mid = (l + r) / 2;
38     int res;
39     if (pos <= mid) {
40         res = query(i * 2, l, mid, pos);
41     }
42     else {
43         res = query(i * 2 + 1, mid + 1, r, pos);
44     }
45     return min(res, arr[i](pos));
46 }
47 };

```

2.9 Treap

```

1 // 支援區間加值、區間反轉、區間 rotate、區間刪除、插入元素、求區間
2 // 最小值的元素的 Treap。使用前建議 srand(time(0)); 除了 size()
3 // 方法以外，所有操作都是 O(log N)。所有 public 方法各自獨立，請
4 // 斟酌要使用到哪些方法，有需要的才抄。
5 class Treap {
6 private:
7     struct Node {
8         int pri = rand(), size = 1;
9         ll val, mn, inc = 0;
10         bool rev = 0;
11         Node *lc = 0, *rc = 0;
12         Node(ll v) { val = mn = v; }
13     };
14     Node* root = 0;
15     void rev(Node* t) {
16         if (!t) return;
17         swap(t->lc, t->rc), t->rev ^= 1;
18     }
19     void update(Node* t, ll v) {
20         if (!t) return;
21         t->val += v, t->inc += v, t->mn += v;
22     }

```

```

23 void push(Node* t) {
24     if (t->rev) rev(t->lc), rev(t->rc), t->rev = 0;
25     update(t->lc, t->inc), update(t->rc, t->inc);
26     t->inc = 0;
27 }
28 void pull(Node* t) {
29     t->size = 1 + size(t->lc) + size(t->rc);
30     t->mn = t->val;
31     if (t->lc) t->mn = min(t->mn, t->lc->mn);
32     if (t->rc) t->mn = min(t->mn, t->rc->mn);
33 }
34 // 看你要不要釋放記憶體
35 void discard(Node* t) {
36     if (!t) return;
37     discard(t->lc), discard(t->rc);
38     delete t;
39 }
40 void split(Node* t, Node*& a, Node*& b, int k) {
41     if (!t) return a = b = 0, void();
42     push(t);
43     if (size(t->lc) < k) {
44         a = t;
45         split(t->rc, a->rc, b, k - size(t->lc) - 1);
46         pull(a);
47     } else {
48         b = t;
49         split(t->lc, a, b->lc, k);
50         pull(b);
51     }
52 }
53 Node* merge(Node* a, Node* b) {
54     if (!a || !b) return a ? a : b;
55     if (a->pri > b->pri) {
56         push(a);
57         a->rc = merge(a->rc, b);
58         pull(a);
59         return a;
60     } else {
61         push(b);
62         b->lc = merge(a, b->lc);
63         pull(b);
64         return b;
65     }
66 }
67 inline int size(Node* t) { return t ? t->size : 0; }
68 public:
69     int size() { return size(root); }
70     void add(int l, int r, ll val) {
71         Node *a, *b, *c, *d;
72         split(root, a, b, r);
73         split(a, c, d, l - 1);
74         update(d, val);
75         root = merge(merge(c, d), b);
76     }
77     // 反轉區間 [l, r]
78     void reverse(int l, int r) {
79         Node *a, *b, *c, *d;
80         split(root, a, b, r);
81         split(a, c, d, l - 1);
82         swap(d->lc, d->rc);
83         d->rev ^= 1;
84         root = merge(merge(c, d), b);
85     }
86     // 區間 [l, r] 向右 rotate k 次，k < 0 表向左 rotate
87     void rotate(int l, int r, int k) {

```

```

88     int len = r - l + 1;
89     Node *a, *b, *c, *d, *e, *f;
90     split(root, a, b, r);
91     split(a, c, d, l - 1);
92     k = (k + len) % len;
93     split(d, e, f, len - k);
94     root = merge(merge(c, merge(f, e)), b);
95 }
96 // 插入一個元素 val 使其 index = i
97 // 注意 i <= size
98 void insert(int i, ll val) {
99     if (i == size() + 1) {
100         push_back(val);
101         return;
102     }
103     assert(i <= size());
104     Node *a, *b;
105     split(root, a, b, i - 1);
106     root = merge(merge(a, new Node(val)), b);
107 }
108 void push_back(ll val) {
109     root = merge(root, new Node(val));
110 }
111 void remove(int l, int r) {
112     int len = r - l + 1;
113     Node *a, *b, *c, *d;
114     split(root, a, b, l - 1);
115     split(b, c, d, len);
116     discard(c); // 看你要不要釋放記憶體
117     root = merge(a, d);
118 }
119 ll minn(int l, int r) {
120     Node *a, *b, *c, *d;
121     split(root, a, b, r);
122     split(a, c, d, l - 1);
123     int ans = d->mn;
124     root = merge(merge(c, d), b);
125     return ans;
126 }
127 };

```

2.10 Dynamic_KD_tree

```

1 template<typename T, size_t kd> // 有kd個維度
2 struct kd_tree {
3     struct point {
4         T d[kd];
5         T dist(const point &x) const {
6             T ret=0;
7             for(size_t i=0; i<kd; ++i) ret+=abs(d[i]-x.d[i]);
8             return ret;
9         }
10        bool operator==(const point &p) {
11            for(size_t i=0; i<kd; ++i)
12                if(d[i]!=p.d[i]) return 0;
13            return 1;
14        }
15        bool operator<(const point &b) const {
16            return d[0]<b.d[0];
17        }
18    };
19 private:

```

```

20 struct node {
21     node *l, *r;
22     point pid;
23     int s;
24     node(const point &p): l(0), r(0), pid(p), s(1) {}
25     ~node() { delete l; delete r; }
26     void up() { s=(l?l->s:0)+1+(r?r->s:0); }
27 } *root;
28 const double alpha, loga;
29 const T INF; // 記得要給INF, 表示極大值
30 int maxn;
31 struct __cmp {
32     int sort_id;
33     bool operator()(const node *x, const node *y) const {
34         return operator()(x->pid, y->pid);
35     }
36     bool operator()(const point &x, const point &y) const {
37         if(x.d[sort_id]!=y.d[sort_id])
38             return x.d[sort_id]<y.d[sort_id];
39         for(size_t i=0; i<kd; ++i)
40             if(x.d[i]!=y.d[i]) return x.d[i]<y.d[i];
41         return 0;
42     }
43 } cmp;
44 int size(node *o) { return o?o->s:0; }
45 vector<node*> A;
46 node* build(int k, int l, int r) {
47     if(l>r) return 0;
48     if(k==kd) k=0;
49     int mid=(l+r)/2;
50     cmp.sort_id = k;
51     nth_element(A.begin()+l, A.begin()+mid, A.begin()+r+1, cmp);
52     node *ret=A[mid];
53     ret->l = build(k+1, l, mid-1);
54     ret->r = build(k+1, mid+1, r);
55     ret->up();
56     return ret;
57 }
58 bool isbad(node *o) {
59     return size(o->l)>alpha*o->s || size(o->r)>alpha*o->s;
60 }
61 void flatten(node *u, typename vector<node*>::iterator &it) {
62     if(!u) return;
63     flatten(u->l, it);
64     *it=u;
65     flatten(u->r, ++it);
66 }
67 void rebuild(node *u, int k) {
68     if((int)A.size()<u->s) A.resize(u->s);
69     auto it=A.begin();
70     flatten(u, it);
71     u=build(k, 0, u->s-1);
72 }
73 bool insert(node *u, int k, const point &x, int dep) {
74     if(!u) return u=new node(x), dep<=0;
75     ++u->s;
76     cmp.sort_id=k;
77     if(insert(cmp(x, u->pid)?u->l:u->r, (k+1)%kd, x, dep-1)) {
78         if(!isbad(u)) return 1;
79         rebuild(u, k);
80     }
81     return 0;
82 }
83 node *findmin(node *o, int k) {
84     if(!o) return 0;

```

```

85     if(cmp.sort_id==k) return o->l?findmin(o->l, (k+1)%kd):o;
86     node *l=findmin(o->l, (k+1)%kd);
87     node *r=findmin(o->r, (k+1)%kd);
88     if(l&&!r) return cmp(l, o)?l:o;
89     if(!l&&r) return cmp(r, o)?r:o;
90     if(!l&&!r) return o;
91     if(cmp(l, r)) return cmp(l, o)?l:o;
92     return cmp(r, o)?r:o;
93 }
94 bool erase(node *u, int k, const point &x) {
95     if(!u) return 0;
96     if(u->pid==x) {
97         if(u->r)
98             else if(u->l) u->r=u->l, u->l=0;
99         else return delete(u), u=0, 1;
100         --u->s;
101         cmp.sort_id=k;
102         u->pid=findmin(u->r, (k+1)%kd)->pid;
103         return erase(u->r, (k+1)%kd, u->pid);
104     }
105     cmp.sort_id=k;
106     if(erase(cmp(x, u->pid)?u->l:u->r, (k+1)%kd, x))
107         return --u->s, 1;
108     return 0;
109 }
110 T heuristic(const T h[]) const {
111     T ret=0;
112     for(size_t i=0; i<kd; ++i) ret+=h[i];
113     return ret;
114 }
115 int qM;
116 priority_queue<pair<T, point>> pQ;
117 void nearest(node *u, int k, const point &x, T *h, T &mndist) {
118     if(u==0 || heuristic(h)>=mndist) return;
119     T dist=u->pid.dist(x), old=h[k];
120     /*mndist=std::min(mndist, dist);*/
121     if(dist<mndist) {
122         pQ.push(std::make_pair(dist, u->pid));
123         if((int)pQ.size()==qM+1)
124             mndist=pQ.top().first, pQ.pop();
125     }
126     if(x.d[k]<u->pid.d[k]) {
127         nearest(u->l, (k+1)%kd, x, h, mndist);
128         h[k] = abs(x.d[k]-u->pid.d[k]);
129         nearest(u->r, (k+1)%kd, x, h, mndist);
130     } else {
131         nearest(u->r, (k+1)%kd, x, h, mndist);
132         h[k] = abs(x.d[k]-u->pid.d[k]);
133         nearest(u->l, (k+1)%kd, x, h, mndist);
134     }
135     h[k]=old;
136 }
137 vector<point> in_range;
138 void range(node *u, int k, const point &mi, const point &ma) {
139     if(!u) return;
140     bool is=1;
141     for(int i=0; i<kd; ++i)
142         if(u->pid.d[i]<mi.d[i] || ma.d[i]<u->pid.d[i])
143             { is=0; break; }
144     if(is) in_range.push_back(u->pid);
145     if(mi.d[k]<u->pid.d[k]) range(u->l, (k+1)%kd, mi, ma);
146     if(ma.d[k]>u->pid.d[k]) range(u->r, (k+1)%kd, mi, ma);
147 }
148 public:
149 kd_tree(const T &INF, double a=0.75):
150     root(0), alpha(a), loga(log2(1.0/a)), INF(INF), maxn(1) {}

```

```

151 ~kd_tree(){delete root;}
152 void clear(){delete root,root=0,maxn=1;}
153 void build(int n,const point *p){
154     delete root,A.resize(maxn=n);
155     for(int i=0;i<n;++i)A[i]=new node(p[i]);
156     root=build(0,0,n-1);
157 }
158 void insert(const point &x){
159     insert(root,0,x,_lg(size(root))/loga);
160     if(root->s>maxn)maxn=root->s;
161 }
162 bool erase(const point &p){
163     bool d=erase(root,0,p);
164     if(root&&root->s<alpha*maxn)rebuild();
165     return d;
166 }
167 void rebuild(){
168     if(root)rebuild(root,0);
169     maxn=root->s;
170 }
171 T nearest(const point &x,int k){
172     qM=k;
173     T mndist=INF,h[kd]={};
174     nearest(root,0,x,h,mndist);
175     mndist=pQ.top().first;
176     pQ = priority_queue<pair<T,point>>());
177     return mndist;//回傳離x第k近的點的距離
178 }
179 const vector<point> &range(const point&mi,const point&ma){
180     in_range.clear();
181     range(root,0,mi,ma);
182     return in_range;//回傳介於mi到ma之間的點vector
183 }
184 int size(){return root?root->s:0;}
185 };

```

2.11 Heavy Light

```

1 #include<vector>
2 #define MAXN 100005
3 int siz[MAXN],max_son[MAXN],pa[MAXN],dep[MAXN];
4 int link_top[MAXN],link[MAXN],cnt;
5 vector<int> G[MAXN];
6 void find_max_son(int u){
7     siz[u]=1;
8     max_son[u]=-1;
9     for(auto v:G[u]){
10         if(v==pa[u])continue;
11         pa[v]=u;
12         dep[v]=dep[u]+1;
13         find_max_son(v);
14         if(max_son[u]==-1||siz[v]>siz[max_son[u]])max_son[u]=v;
15         siz[u]+=siz[v];
16     }
17 }
18 void build_link(int u,int top){
19     link[u]=++cnt;
20     link_top[u]=top;
21     if(max_son[u]==-1)return;
22     build_link(max_son[u],top);
23     for(auto v:G[u]){
24         if(v==max_son[u]||v==pa[u])continue;

```

```

25     build_link(v,v);
26 }
27 }
28 int find_lca(int a,int b){
29     //求LCA，可以在過程中對區間進行處理
30     int ta=link_top[a],tb=link_top[b];
31     while(ta!=tb){
32         if(dep[ta]<dep[tb]){
33             swap(ta,tb);
34             swap(a,b);
35         }
36         //這裡可以對a所在的鏈做區間處理
37         //區間為(link[ta],link[a])
38         ta=link_top[a=pa[ta]];
39     }
40     //最後a,b會在同一條鏈，若a!=b還要在進行一次區間處理
41     return dep[a]<dep[b]?a:b;
42 }

```

2.12 HLD By Koying

```

1 // https://cses.fi/problemset/task/1137/
2
3 struct HLD {
4     struct Info {
5         int sub, mxsub, dep, fa, root, id;
6     } arr[MAXN];
7
8     int index = 0;
9
10    void find_son(int i, int fa) {
11        pii mx(0, i);
12        arr[i].sub = 1;
13        for (auto it: G[i]) if (it != fa) {
14            arr[it].dep = arr[i].dep + 1;
15            arr[it].fa = i;
16            find_son(it, i);
17            cmax(mx, pii(arr[it].sub, it));
18            arr[i].sub += arr[it].sub;
19        }
20        arr[i].mxsub = mx.S;
21    }
22
23    void build(int i, int root) {
24        arr[i].root = root;
25        arr[i].id = ++index;
26        y[arr[i].id] = x[i];
27
28        if (arr[i].mxsub != i) {
29            build(arr[i].mxsub, root);
30            y[arr[i].id] += y[arr[arr[i].mxsub].id];
31        }
32
33        for (auto it: G[i]) if (it != arr[i].fa && it != arr[
34            i].mxsub) {
35            build(it, it);
36            y[arr[i].id] += y[arr[it].id];
37        }
38    }
39
40    void jump(int a, int b) { // from a to b (dep(a) > dep(b)
41    }

```

```

40     while (arr[a].root != arr[b].root) {
41         if (arr[arr[a].root].dep < arr[arr[b].root].dep)
42             a = arr[arr[a].root].fa;
43     }
44
45     if (arr[a].dep < arr[b].dep)
46         swap(a, b);
47
48     return mx;
49 }
50 } HLD;

```

2.13 Link Cut Tree

```

1 struct splay_tree{
2     int ch[2],pa;//子節點跟父母
3     bool rev;//反轉的懶惰標記
4     splay_tree():pa(0),rev(0){ch[0]=ch[1]=0;}
5 };
6 vector<splay_tree> nd;
7 //有的時候用vector會TLE，要注意
8 //這邊以node[0]作為null節點
9 bool isroot(int x){//判斷是否為這棵splay tree的根
10     return nd[nd[x].pa].ch[0]!=x&&nd[nd[x].pa].ch[1]!=x;
11 }
12 void down(int x){//懶惰標記下推
13     if(nd[x].rev){
14         if(nd[x].ch[0]nd[nd[x].ch[0]].rev^=1;
15         if(nd[x].ch[1]nd[nd[x].ch[1]].rev^=1;
16         swap(nd[x].ch[0],nd[x].ch[1]);
17         nd[x].rev=0;
18     }
19 }
20 void push_down(int x){//所有祖先懶惰標記下推
21     if(!isroot(x))push_down(nd[x].pa);
22     down(x);
23 }
24 void up(int x){//將子節點的資訊向上更新
25 void rotate(int x){//旋轉，會自行判斷轉的方向
26     int y=nd[x].pa,z=nd[y].pa,d=(nd[y].ch[1]==x);
27     nd[x].pa=z;
28     if(!isroot(y))nd[z].ch[nd[z].ch[1]==y]=x;
29     nd[y].ch[d]=nd[x].ch[d^1];
30     nd[nd[y].ch[d]].pa=y;
31     nd[y].pa=x,nd[x].ch[d^1]=y;
32     up(y),up(x);
33 }
34 void splay(int x){//將x伸展到splay tree的根
35     push_down(x);
36     while(!isroot(x)){
37         int y=nd[x].pa;
38         if(!isroot(y)){
39             int z=nd[y].pa;
40             if((nd[z].ch[0]==y)^(nd[y].ch[0]==x))rotate(y);
41             else rotate(x);
42         }
43         rotate(x);
44     }
45 }
46 int access(int x){
47     int last=0;

```

```

48 while(x){
49     splay(x);
50     nd[x].ch[1]=last;
51     up(x);
52     last=x;
53     x=nd[x].pa;
54 }
55 return last; //access後splay tree的根
56 }
57 void access(int x, bool is=0) { //is=0就是一般的access
58     int last=0;
59     while(x){
60         splay(x);
61         if(is && !nd[x].pa){
62             //printf("%d\n", max(nd[last].ma, nd[nd[x].ch[1]].ma));
63         }
64         nd[x].ch[1]=last;
65         up(x);
66         last=x;
67         x=nd[x].pa;
68     }
69 }
70 void query_edge(int u, int v){
71     access(u);
72     access(v, 1);
73 }
74 void make_root(int x){
75     access(x), splay(x);
76     nd[x].rev ^= 1;
77 }
78 void make_root(int x){
79     nd[access(x)].rev ^= 1;
80     splay(x);
81 }
82 void cut(int x, int y){
83     make_root(x);
84     access(y);
85     splay(y);
86     nd[y].ch[0] = 0;
87     nd[x].pa = 0;
88 }
89 void cut_parents(int x){
90     access(x);
91     splay(x);
92     nd[nd[x].ch[0]].pa = 0;
93     nd[x].ch[0] = 0;
94 }
95 void link(int x, int y){
96     make_root(x);
97     nd[x].pa = y;
98 }
99 int find_root(int x){
100     x = access(x);
101     while(nd[x].ch[0]) x = nd[x].ch[0];
102     splay(x);
103     return x;
104 }
105 int query(int u, int v){
106     //傳回uv路徑splay tree的根結點
107     //這種寫法無法求LCA
108     make_root(u);
109     return access(v);
110 }
111 int query_lca(int u, int v){
112     //假設求鏈上點權的總和，sum是子樹的權重和，data是節點的權重

```

```

113     access(u);
114     int lca = access(v);
115     splay(u);
116     if(u == lca){
117         //return nd[lca].data + nd[nd[lca].ch[1]].sum
118     } else {
119         //return nd[lca].data + nd[nd[lca].ch[1]].sum + nd[u].sum
120     }
121 }
122 struct EDGE {
123     int a, b, w;
124 } e[10005];
125 int n;
126 vector<pair<int, int>> G[10005];
127 //first表示子節點，second表示邊的編號
128 int pa[10005], edge_node[10005];
129 //pa是父母節點，暫存用的，edge_node是每個編號被存在哪個點裡面的
    陣列
130 void bfs(int root){
131     //在建構的時候把每個點都設成一個splay tree
132     queue<int> q;
133     for(int i=1; i<=n; ++i) pa[i] = 0;
134     q.push(root);
135     while(q.size()){
136         int u = q.front();
137         q.pop();
138         for(auto P: G[u]){
139             int v = P.first;
140             if(v != pa[u]){
141                 pa[v] = u;
142                 nd[v].pa = u;
143                 nd[v].data = e[P.second].w;
144                 edge_node[P.second] = v;
145                 up(v);
146                 q.push(v);
147             }
148         }
149     }
150 }
151 void change(int x, int b){
152     splay(x);
153     //nd[x].data = b;
154     up(x);
155 }

```

3 DP

3.1 LCIS

```

3 vector<int> LCIS(vector<int> a, vector<int> b) {
4     int n = a.size(), m = b.size();
5     int dp[LEN][LEN] = {}, pre[LEN][LEN] = {};
6     for(int i=1; i<=n; i++) {
7         int p = 0;
8         for(int j=1; j<=m; j++) {
9             if(a[i-1] != b[j-1]) {
10                 dp[i][j] = dp[i-1][j], pre[i][j] = j;
11                 if(a[i-1] > b[j-1] && dp[i-1][j] > dp[i-1][p])
12                     p = j;
13             } else {

```

```

12         dp[i][j] = dp[i-1][p] + 1, pre[i][j] = p;
13     }
14 }
15 int len = 0, p = 0;
16 for(int j=1; j<=m; j++)
17     if(dp[n][j] > len) len = dp[n][j], p = j;
18 vector<int> ans;
19 for(int i=n; i>=1; i--) {
20     if(a[i-1] == b[p-1]) ans.push_back(b[p-1]);
21     p = pre[i][p];
22 }
23 reverse(ans.begin(), ans.end());
24 return ans;
25 }

```

3.2 Bounded_Knapsack

```

1 namespace {
2     static const int MAXW = 1000005;
3     static const int MAXN = 1005;
4     struct BB {
5         int w, v, c;
6         BB(int w = 0, int v = 0, int c = 0): w(w), v(v), c(c) {}
7         bool operator<(const BB &x) const {
8             return w * c < x.w * x.c;
9         }
10    };
11    static int run(BB A[], int dp[], int W, int N) {
12        static int MQ[MAXW][2];
13        for(int i = 0, sum = 0; i < N; i++) {
14            int w = A[i].w, v = A[i].v, c = A[i].c;
15            sum = min(sum + w * c, W);
16            for(int j = 0; j < w; j++) {
17                int l = 0, r = 0;
18                MQ[l][0] = 0, MQ[l][1] = dp[j];
19                for(int k = 1, tw = w + j, tv = v; tw <= sum
20                    && k <= c; k++, tw += w, tv += v) {
21                    int dpv = dp[tw] - tv;
22                    while(1 <= r && MQ[r][1] <= dpv) r--;
23                    r++;
24                    MQ[r][0] = k, MQ[r][1] = dpv;
25                    dp[tw] = max(dp[tw], MQ[l][1] + tv);
26                }
27                for(int k = c + 1, tw = (c + 1) * w + j, tv = (c + 1) *
28                    v; tw <= sum; k++, tw += w, tv += v) {
29                    if(k - MQ[l][0] > c) l++;
30                    int dpv = dp[tw] - tv;
31                    while(1 <= r && MQ[r][1] <= dpv) r--;
32                    r++;
33                    MQ[r][0] = k, MQ[r][1] = dpv;
34                    dp[tw] = max(dp[tw], MQ[l][1] + tv);
35                }
36            }
37        }
38        static int knapsack(int C[][3], int N, int W) { // O(WN)
39            vector<BB> A;
40            for(int i = 0; i < N; i++) {
41                int w = C[i][0], v = C[i][1], c = C[i][2];
42                A.push_back(BB(w, v, c));
43            }
44            assert(N < MAXN);

```



```

44 static int dp1[MAXW+1], dp2[MAXW+1];
45 BB Ar[2][MAXN];
46 int ArN[2] = {};
47 memset(dp1, 0, sizeof(dp1[0])*(W+1));
48 memset(dp2, 0, sizeof(dp2[0])*(W+1));
49 sort(A.begin(), A.end());
50 int sum[2] = {};
51 for (int i = 0; i < N; i++) {
52     int ch = sum[1] < sum[0];
53     Ar[ch][ArN[ch]] = A[i];
54     ArN[ch]++;
55     sum[ch] = min(sum[ch] + A[i].w*A[i].c, W);
56 }
57 run(Ar[0], dp1, W, ArN[0]);
58 run(Ar[1], dp2, W, ArN[1]);
59 int ret = 0;
60 for (int i = 0, j = W, mx = 0; i <= W; i++, j--) {
61     mx = max(mx, dp2[i]);
62     ret = max(ret, dp1[j] + mx);
63 }
64 return ret;
65 }
66 }
67 int main() {
68     int W, N;
69     assert(scanf("%d %d", &W, &N) == 2);
70     int C[MAXN][3];
71     for (int i = 0; i < N; i++)
72         assert(scanf("%d %d %d", &C[i][1], &C[i][0], &C[i][2]) == 3);
73     printf("%d\n", knapsack(C, N, W));
74     return 0;
75 }

```

3.3 1D1D

```

1 int t, n, L, p;
2 char s[MAXN][35];
3 ll sum[MAXN] = {0};
4 long double dp[MAXN] = {0};
5 int prevd[MAXN] = {0};
6 long double pw(long double a, int n) {
7     if (n == 1) return a;
8     long double b = pw(a, n/2);
9     if (n & 1) return b*b*a;
10    else return b*b;
11 }
12 long double f(int i, int j) {
13     // cout << (sum[i] - sum[j]+i-j-1-L) << endl;
14     return pw(abs(sum[i] - sum[j]+i-j-1-L), p) + dp[j];
15 }
16 struct INV {
17     int L, R, pos;
18 };
19 INV stk[MAXN*10];
20 int top = 1, bot = 1;
21 void update(int i) {
22     while (top > bot && i < stk[top].L && f(stk[top].L, i) <
23             f(stk[top].L, stk[top].pos) ) {
24         stk[top-1].R = stk[top].R;
25         top--;
26     }

```

```

26 int lo = stk[top].L, hi = stk[top].R, mid, pos = stk[top]
    ].pos;
27 // if ( i >= lo ) lo = i + 1;
28 while ( lo != hi ) {
29     mid = lo + (hi - lo) / 2;
30     if ( f(mid, i) < f(mid, pos) ) hi = mid;
31     else lo = mid + 1;
32 }
33 if ( hi < stk[top].R ) {
34     stk[top+1] = (INV) { hi, stk[top].R, i };
35     stk[top++].R = hi;
36 }
37 }
38 int main() {
39     cin >> t;
40     while ( t-- ) {
41         cin >> n >> L >> p;
42         dp[0] = sum[0] = 0;
43         for ( int i = 1; i <= n; i++ ) {
44             cin >> s[i];
45             sum[i] = sum[i-1] + strlen(s[i]);
46             dp[i] = numeric_limits<long double>::max();
47         }
48         stk[top] = (INV) {1, n+1, 0};
49         for ( int i = 1; i <= n; i++ ) {
50             if ( i >= stk[bot].R ) bot++;
51             dp[i] = f(i, stk[bot].pos);
52             update(i);
53             // cout << (ll) f(i, stk[bot].pos) << endl;
54         }
55         if ( dp[n] > 1e18 ) {
56             cout << "Too hard to arrange" << endl;
57         } else {
58             vector<PI> as;
59             cout << (ll)dp[n] << endl;
60         }
61     } return 0;
62 }

```

4 Graph

4.1 Dijkstra

```

1 /** 問某點到所有圖上的點的最短距離。0/1-based 都安全。 edge
    要
2 * 是 {cost, dest} 格式。回傳的陣列若含有 -1 表示 src 到該位
    置
3 * 不連通 **/
4 typedef pair<ll, int> pii;
5 vector<ll> dijkstra(int src, vector<vector<pii>>& edge) {
6     vector<ll> sum(edge.size(), -1);
7     priority_queue<pii, vector<pii>, greater<pii>> q;
8     q.emplace(0, src);
9     while (q.size()) {
10         int v = q.top().second; ll d = q.top().first;
11         q.pop();
12         if (sum[v] != -1) continue;
13         sum[v] = d;
14         for (auto& e : edge[v])
15             if (sum[e.second] == -1)

```

```

16         q.emplace(d + e.first, e.second);
17     } return sum;
18 }

```

4.2 Bellman Ford

```

1 vector<pii> G[maxn];
2 int dis[maxn];
3 bool BellmanFord(int n, int s) {
4     for (int i=1; i<=n; i++) dis[i] = INF;
5     dis[s] = 0;
6     bool relax;
7     for (int r=1; r<=n; r++) { //O(VE)
8         relax = false;
9         for (int i=1; i<=n; i++)
10             for (pii e:G[i])
11                 if (dis[i] + e.second < dis[e.first])
12                     dis[e.first] = dis[i] + e.second, relax = true;
13     }
14     return relax; //有負環
15 }

```

4.3 SPFA

```

1 vector<pii> G[maxn]; int dis[maxn];
2 void SPFA(int n, int s) { //O(kE) k~2.
3     for (int i=1; i<=n; i++) dis[i] = INF;
4     dis[s] = 0;
5     queue<int> q; q.push(s);
6     bool inque[maxn] = {};
7     while (!q.empty()) {
8         int u = q.front(); q.pop();
9         inque[u] = false;
10        for (pii e:G[u]) {
11            int v = e.first, w = e.second;
12            if (dis[u] + w < dis[v]) {
13                if (!inque[v]) q.push(v), inque[v] = true;
14                dis[v] = dis[u] + w;
15            }
16        }
17    }
18 }

```

4.4 Prim

```

1 /** 0/1-based 安全， n 是節點數量 (必須剛好)。 edge 格式為
2 * {cost, dest}，回傳 -1 表示圖不連通。*/
3 typedef pair<ll, int> pii;
4 ll minpath(vector<vector<pii>>& edge, int n) {
5     vector<bool> vis(n+1);
6     priority_queue<pii, vector<pii>, greater<pii>> q;
7     q.emplace(0, 1);
8     ll ret = 0; int nvis = 0;
9     while (nvis < n && q.size()) {
10         ll d = q.top().first;

```

```

11     int v = q.top().second; q.pop();
12     if (vis[v]) continue;
13     vis[v] = 1; ret += d;
14     if (++nvis == n) return ret;
15     for (auto& e : edge[v])
16         if (!vis[e.second]) q.push(e);
17 } return -1;
18 }

```

4.5 Mahattan MST

```

1 #define REP(i,n) for(int i=0;i<n;i++)
2 typedef long long LL;
3 const int N=200100;
4 int n,m;
5 struct PT {int x,y,z,w,id;} p[N];
6 inline int dis(const PT &a,const PT &b){return abs(a.x-b.x)+
7     abs(a.y-b.y);}
8 inline bool cpx(const PT &a,const PT &b)
9 {return a.x!=b.x? a.x>b.x:a.y>b.y;}
10 inline bool cpz(const PT &a,const PT &b){return a.z<b.z;}
11 struct E{int a,b,c;}e[8*N];
12 bool operator<(const E&a,const E&b){return a.c<b.c;}
13 struct Node{ int L,R,key; } node[4*N];
14 int s[N];
15 int F(int x) {return s[x]==x? x : s[x]=F(s[x]); }
16 void U(int a,int b) {s[F(b)]=F(a);}
17 void init(int id,int L,int R) {
18     node[id] = (Node){L,R,-1};
19     if(L==R)return;
20     init(id*2,L,(L+R)/2);
21     init(id*2+1,(L+R)/2+1,R);
22 }
23 void ins(int id,int x) {
24     if(node[id].key==-1 || p[node[id].key].w>p[x].w)
25         node[id].key=x;
26     if(node[id].L==node[id].R) return;
27     if(p[x].z<=(node[id].L+node[id].R)/2) ins(id*2,x);
28     else ins(id*2+1,x);
29 }
30 int Q(int id,int L,int R){
31     if(R<node[id].L || L>node[id].R)return -1;
32     if(L<=node[id].L && node[id].R<=R)return node[id].key;
33     int a=Q(id*2,L,R),b=Q(id*2+1,L,R);
34     if(b!=-1 || (a!=-1 && p[a].w<p[b].w)) return a;
35     else return b;
36 }
37 void calc() {
38     REP(i,n) {
39         p[i].z = p[i].y-p[i].x;
40         p[i].w = p[i].x+p[i].y;
41     }
42     sort(p,p+n,cpz);
43     int cnt = 0, j, k;
44     for(int i=0; i<n; i=j){
45         for(j=i+1; p[j].z==p[i].z && j<n; j++);
46         for(k=i, cnt++; k<j; k++) p[k].z = cnt;
47     }
48     init(1,1,cnt);
49     sort(p,p+n,cpx);
50     REP(i,n) {
51         j=Q(1,p[i].z,cnt);

```

```

51         if(j!=-1) e[m++] = (E){p[i].id, p[j].id, dis(p[i],p[j]
52             )});
53         ins(1,i);
54     }
55 }
56 LL MST() {
57     LL r=0;
58     sort(e, e+m);
59     REP(i, m) {
60         if(F(e[i].a)==F(e[i].b)) continue;
61         U(e[i].a, e[i].b);
62         r += e[i].c;
63     }
64     return r;
65 }
66 int main() {
67     int ts;
68     scanf("%d", &ts);
69     while (ts--) {
70         m = 0;
71         scanf("%d",&n);
72         REP(i,n) {scanf("%d",&p[i].x,&p[i].y);p[i].id=s[i]=
73             i;}
74         calc();
75         REP(i,n)p[i].y= -p[i].y;
76         calc();
77         REP(i,n)swap(p[i].x,p[i].y);
78         calc();
79         REP(i,n)p[i].x=-p[i].x;
80         calc();
81         printf("%lld\n",MST()*2);
82     }
83     return 0;
84 }

```

4.6 LCA

```

1 /** 所有 LCA 都是 0/1-based 安全的。建構式 edge 表示 adj
2  * 邊資訊。 只支援無向樹。這三個類別各有優缺點。*/
3
4 /** 最快的 LCA O(N+Q) ，但非常吃記憶體 O(N^2) 。支援非離線。*
5  */
6 class SsadbTarjan {
7 private:
8     int n;
9     vector<int> par, dep; vector<vector<int>>> ca;
10     int dfs(int u, vector<vector<int>>& edge, int d) {
11         dep[u] = d;
12         for (int a = 0; a < n; a++)
13             if (dep[a] != -1)
14                 ca[a][u] = ca[u][a] = parent(a);
15         for (int a : edge[u]) {
16             if (dep[a] != -1) continue;
17             dfs(a, edge, d + 1);
18             par[a] = u;
19         }
20     }
21     int parent(int x) {
22         if (par[x] == x) return x;
23         return par[x] = parent(par[x]);
24     }

```

```

25 public:
26     SsadbTarjan(vector<vector<int>>& edge, int root)
27         : n(edge.size()) {
28         dep.assign(n, -1); par.resize(n);
29         ca.assign(n, vector<int>(n));
30
31         for (int i = 0; i < n; i++) par[i] = i;
32         dfs(root, edge, 0);
33     }
34     int lca(int a, int b) { return ca[a][b]; }
35     int dist(int a, int b) {
36         return dep[a] + dep[b] - 2 * dep[ca[a][b]];
37     }
38 };
39
40 /** 最快的 LCA O(N+Q) 且最省記憶體 O(N+Q) 。但必須離線。*/
41 #define x first // 加速
42 #define y second
43 class OfflineTarjan {
44 private:
45     vector<int> par, anc, dep, ans, rank;
46     vector<vector<pii>> qry;
47     // 出於安全考量你可以把 & 去掉
48     vector<vector<int>>& edge;
49     int root, n;
50
51     void merge(int a, int b) {
52         a = parent(a), b = parent(b);
53         if (rank[a] < rank[b]) swap(a, b);
54         par[b] = a;
55         if (rank[a] == rank[b]) rank[a]++;
56     }
57     void dfs(int u, int d) {
58         anc[parent(u)] = u, dep[u] = d;
59         for (int a : edge[u]) {
60             if (dep[a] != -1) continue;
61             dfs(a, d + 1);
62             merge(a, u);
63             anc[parent(u)] = u;
64         }
65         for (auto q : qry[u]) {
66             if (dep[q.first] != -1)
67                 ans[q.second] = anc[parent(q.first)];
68         }
69     }
70     int parent(int x) {
71         if (par[x] == x) return x;
72         return par[x] = parent(par[x]);
73     }
74     void solve(vector<pii>& query) {
75         dep.assign(n, -1), rank.assign(n, 0);
76         par.resize(n), anc.resize(n);
77         for (int i = 0; i < n; i++) anc[i] = par[i] = i;
78         ans.resize(query.size());
79         qry.resize(n);
80         for (int i = 0; i < query.size(); i++) {
81             auto& q = query[i];
82             qry[q.first].emplace_back(q.second, i);
83             qry[q.second].emplace_back(q.first, i);
84         }
85         dfs(root, 0);
86     }
87 }
88 public:
89     // edge 是傳 reference ，完成所有查詢前萬萬不可以改。

```



```

90 OfflineTarjan(vector<vector<int>>& edge, int root)
91 : edge(edge), root(root), n(edge.size()) {}
92 // 離線查詢， query 陣列包含所有詢問 {src, dst}。呼叫一
    次無
93 // 論 query 量多少，複雜度都是 O(N)。所以應盡量只呼叫一
    次。
94 vector<int> lca(vector<pii>& query) {
95     solve(query);
96     return ans;
97 }
98 vector<int> dist(vector<pii>& query) {
99     solve(query);
100     for (int i = 0; i < query.size(); i++) {
101         auto& q = query[i];
102         ans[i] = dep[q.first] + dep[q.second] -
103             2 * dep[ans[i]];
104     }
105     return ans;
106 }
107 };
108
109 /** 威達的 LCA，時間普通 O(Q*log(N))，記憶體需求也普通
110 * O(N*log(N))。支援非離線。*/
111 class SparseTableTarjan {
112 private:
113     int maxlg;
114     vector<vector<int>> anc;
115     vector<int> dep;
116
117     void dfs(int u, vector<vector<int>>& edge, int d) {
118         dep[u] = d;
119         for (int i = 1; i < maxlg; i++)
120             if (anc[u][i - 1] == -1) break;
121         else anc[u][i] = anc[anc[u][i - 1]][i - 1];
122         for (int a : edge[u]) {
123             if (dep[a] != -1) continue;
124             anc[a][0] = u;
125             dfs(a, edge, d + 1);
126         }
127     }
128
129 public:
130     SparseTableTarjan(vector<vector<int>>& edge, int root) {
131         int n = edge.size();
132         maxlg = ceil(log2(n));
133         anc.assign(n, vector<int>(maxlg, -1));
134         dep.assign(n, -1);
135         dfs(root, edge, 0);
136     }
137
138     int lca(int a, int b) {
139         if (dep[a] > dep[b]) swap(a, b);
140         for (int k = 0; dep[b] - dep[a]; k++)
141             if (((dep[b] - dep[a]) >> k) & 1) b = anc[b][k];
142
143         if (a == b) return a;
144         for (int k = maxlg - 1; k >= 0; k--)
145             if (anc[a][k] != anc[b][k])
146                 a = anc[a][k], b = anc[b][k];
147         return anc[a][0];
148     }
149
150     int dist(int a, int b) {
151         return dep[a] + dep[b] - 2 * dep[lca(a, b)];
152     }
153 };

```

4.7 Tarjan

```

1 割點
2 點 u 為割點 if and only if 滿足 1. or 2.
3 1. u 為樹根，且 u 有多於一個子樹。
4 2. u 不為樹根，且滿足存在 (u,v) 為樹枝邊（或稱父子邊，即 u 為
    v 在搜索樹中的父親），使得 DFN(u) <= Low(v)。
5 -----
6 橋
7 一條無向邊 (u,v) 是橋 if and only if (u,v) 為樹枝邊，且滿足
    DFN(u) < Low(v)。
8 // 0 base
9 struct TarjanSCC{
10     static const int MAXN = 1000006;
11     int n, dfn[MAXN], low[MAXN], scc[MAXN], scn, count;
12     vector<int> G[MAXN];
13     stack<int> stk;
14     bool ins[MAXN];
15     void tarjan(int u) {
16         dfn[u] = low[u] = ++count;
17         stk.push(u);
18         ins[u] = true;
19         for(auto v:G[u]) {
20             if(!dfn[v]) {
21                 tarjan(v);
22                 low[u] = min(low[u], low[v]);
23             } else if(ins[v]) {
24                 low[u] = min(low[u], dfn[v]);
25             }
26         }
27         if(dfn[u] == low[u]) {
28             int v;
29             do {
30                 v = stk.top(); stk.pop();
31                 scc[v] = scn;
32                 ins[v] = false;
33             } while(v != u);
34             scn++;
35         }
36     }
37     void getSCC(){
38         memset(dfn,0,sizeof(dfn));
39         memset(low,0,sizeof(low));
40         memset(ins,0,sizeof(ins));
41         memset(scc,0,sizeof(scc));
42         count = scn = 0;
43         for(int i = 0 ; i < n ; i++ )
44             if(!dfn[i]) tarjan(i);
45     }
46 } SCC;

```

4.8 BCC_edge

```

1 邊雙連通
2 任意兩點間至少有兩條不重疊的路徑連接，找法：
3 1. 標記出所有的橋
4 2. 對全圖進行 DFS，不走橋，每一次 DFS 就是一個新的邊雙連通
5 // from BCW
6 struct BccEdge {
7     static const int MXN = 100005;

```

```

8 struct Edge { int v,eid; };
9 int n,m,step,par[MXN],dfn[MXN],low[MXN];
10 vector<Edge> E[MXN];
11 DisjointSet djs;
12 void init(int _n) {
13     n = _n; m = 0;
14     for (int i=0; i<n; i++) E[i].clear();
15     djs.init(n);
16 }
17 void add_edge(int u, int v) {
18     E[u].PB({v, m});
19     E[v].PB({u, m});
20     m++;
21 }
22 void DFS(int u, int f, int f_eid) {
23     par[u] = f;
24     dfn[u] = low[u] = step++;
25     for (auto it:E[u]) {
26         if (it.eid == f_eid) continue;
27         int v = it.v;
28         if (dfn[v] == -1) {
29             DFS(v, u, it.eid);
30             low[u] = min(low[u], low[v]);
31         } else {
32             low[u] = min(low[u], dfn[v]);
33         }
34     }
35 }
36 void solve() {
37     step = 0;
38     memset(dfn, -1, sizeof(int)*n);
39     for (int i=0; i<n; i++) {
40         if (dfn[i] == -1) DFS(i, i, -1);
41     }
42     djs.init(n);
43     for (int i=0; i<n; i++) {
44         if (low[i] < dfn[i]) djs.uni(i, par[i]);
45     }
46 }
47 } graph;

```

4.9 最小平均環

```

1 #include<cstdio> //for DBL_MAX
2 int dp[MAXN][MAXN]; // 1-base,0(NM)
3 vector<tuple<int,int,int>> edge;
4 double mmc(int n){ //allow negative weight
5     const int INF = 0x3f3f3f3f;
6     for(int t=0; t<n; ++t){
7         memset(dp[t+1],0x3f,sizeof(dp[t+1]));
8         for(const auto &e:edge) {
9             int u, v, w; tie(u,v,w) = e;
10             dp[t+1][v] = min(dp[t+1][v],dp[t][u]+w);
11         }
12     }
13     double res = DBL_MAX;
14     for(int u=1; u<=n; ++u) {
15         if(dp[n][u]==INF) continue;
16         double val = -DBL_MAX;
17         for(int t=0;t<n;++t)
18             val = max(val,(dp[n][u]-dp[t][u])*1.0/(n-t));
19         res = min(res,val);
20     } return res;

```

21 }

4.10 2-SAT

```

1 const int MAXN = 2020;
2 struct TwoSAT{
3     static const int MAXv = 2*MAXN;
4     vector<int> GO[MAXv],BK[MAXv],stk;
5     bool vis[MAXv];
6     int SC[MAXv];
7     void imply(int u,int v){ // u imply v
8         GO[u].push_back(v);
9         BK[v].push_back(u);
10    }
11    int dfs(int u,vector<int>*G,int sc){
12        vis[u]=1, SC[u]=sc;
13        for (int v:G[u])if (!vis[v])
14            dfs(v,G,sc);
15        if (G==GO) stk.push_back(u);
16    }
17    int scc(int n=MAXv){
18        memset(vis,0,sizeof(vis));
19        for (int i=0; i<n; i++)
20            if (!vis[i]) dfs(i,GO,-1);
21        memset(vis,0,sizeof(vis));
22        int sc=0;
23        while (!stk.empty()){
24            if (!vis[stk.back()])
25                dfs(stk.back(),BK,sc++);
26            stk.pop_back();
27        }
28    } SAT;
29    int main(){
30        SAT.scc(2*n);
31        bool ok = 1;
32        for (int i=0; i<n; i++){
33            if (SAT.SC[2*i]==SAT.SC[2*i+1]) ok = 0;
34        }
35        if (ok) {
36            for (int i=0; i<n; i++)
37                if (SAT.SC[2*i]>SAT.SC[2*i+1])
38                    cout << i << endl;
39        }
40        else puts("NO");
41    }
42 }
43 void warshall(){
44     bitset<2003> d[2003];
45     for (int k=0; k<n; k++){
46         for (int i=0; i<n; i++)
47             if (d[i][k]) d[i] |= d[k];
48 }

```

4.11 生成樹數量

```

1 // D : degree-matrix
2 // A : adjacent-matrix
3 // 無向圖
4 // (u,v)

```

```

5 // A[u][v]++, A[v][u]++
6 // D[u][u]++, D[v][v]++
7 // G = D-A
8 // abs(det(G去掉i-col和i-row))
9 // 生成樹的數量
10 // 有向圖
11 // A[u][v]++
12 // D[v][v]++ (in-deg)
13 // 以i為root的樹形圖數量
14 // 所有節點都能到達root

```

5 Flow_Matching

5.1 Dinic

```

1 // 一般來說複雜度遠低於 O(EV^2) , 二分圖約 O(E * sqrt(v)) 。
2 // 0/1-based 都安全。
3 class Dinic {
4     struct edge {
5         int d, r; ll c;
6         edge(int d, ll c, int r) : d(d), c(c), r(r){};
7     };
8     private:
9     vector<vector<edge>> adj; vector<int> lv, ve; int n;
10    bool mklv(int s, int d) {
11        lv.assign(n, -1); lv[s] = 0;
12        queue<int> q; q.push(s);
13        while (!q.empty()) {
14            int v = q.front(); q.pop();
15            for (auto& e : adj[v]) {
16                if (e.c == 0 || lv[e.d] != -1) continue;
17                lv[e.d] = lv[v] + 1, q.push(e.d);
18            }
19        }
20        return lv[d] > 0;
21    }
22    ll aug(int v, ll f, int d) {
23        if (v == d) return f;
24        for (; ve[v] < adj[v].size(); ve[v]++) {
25            auto& e = adj[v][ve[v]];
26            if (lv[e.d] != lv[v] + 1 || !e.c) continue;
27            ll sent = aug(e.d, min(f, e.c), d);
28            if (sent > 0) {
29                e.c -= sent, adj[e.d][e.r].c += sent;
30                return sent;
31            }
32        }
33        return 0;
34    }
35    public:
36    // 建立空圖, n 是節點 (包含 source, sink) 數量
37    Dinic(int n) : n(n+1) { clear(); }
38    // 清空整個圖, 這需要重複使用 dinic 時 (如二分搜) 很方便
39    void clear() { adj.assign(n, vector<edge>()); }
40    // 加有向邊 src->dst, cap 是容量
41    void add_edge(int src, int dst, ll cap) {
42        edge ss(dst, cap, adj[dst].size());
43        edge dd(src, 0, adj[src].size());
44        adj[src].push_back(ss), adj[dst].push_back(dd);

```

```

45    }
46    ll max_flow(int s, int d) {
47        ll ret = 0;
48        while (mklv(s, d)) {
49            ve.assign(n, 0);
50            while (ll f = aug(s, 9e18, d)) ret += f;
51        }
52        return ret;
53    }
54 };

```

5.2 Min Cost Max Flow

```

1 /** Min cost max flow 0/1-based 都安全。 */
2 class MCMF {
3     private:
4     struct edge { int to, r; ll rest, c; };
5     int n; ll f = 0, c = 0;
6     vector<vector<edge>> g;
7     vector<int> pre, prel;
8     bool run(int s, int t) {
9         vector<ll> dis(n, inf); vector<bool> vis(n);
10        dis[s] = 0; queue<int> q; q.push(s);
11        while (q.size()) {
12            int u = q.front(); q.pop(); vis[u] = 0;
13            for (int i = 0; i < g[u].size(); i++) {
14                int v = g[u][i].to; ll w = g[u][i].c;
15                if (g[u][i].rest <= 0 ||
16                    dis[v] <= dis[u] + w)
17                    continue;
18                pre[v] = u, prel[v] = i;
19                dis[v] = dis[u] + w;
20                if (!vis[v]) vis[v] = 1, q.push(v);
21            }
22        }
23        if (dis[t] == inf) return 0;
24        ll tf = inf;
25        for (int v = t, u, l; v != s; v = u) {
26            u = pre[v], l = prel[v];
27            tf = min(tf, g[u][l].rest);
28        }
29        for (int v = t, u, l; v != s; v = u) {
30            u = pre[v], l = prel[v], g[u][l].rest -= tf;
31            g[v][g[u][l].r].rest += tf;
32        }
33        c += tf * dis[t], f += tf;
34        return 1;
35    }
36    public:
37    // 建立空圖, n 是節點數量 (包含 source 和 sink)
38    MCMF(int n) : n(n+1), g(n+1), pre(n+1), prel(n+1) {}
39    // 加有向邊 u->v, cap 容量 cost 成本
40    void add_edge(int u, int v, ll cap, ll cost) {
41        g[u].push_back({v, (int)g[v].size(), cap, cost});
42        g[v].push_back({u, (int)g[u].size() - 1, 0, -cost});
43    }
44    pair<ll, ll> query(int src, int sink) {
45        while (run(src, sink));
46        return {f, c}; // {min cost, max flow}
47    }
48 }
49 };

```

5.3 Ford Fulkerson

```

1 const int maxn = 1e5 + 10, INF = 1e9;
2 const long long INF64 = 1e18;
3 struct edge{ int to, cap, rev; };
4 vector<edge> G[maxn];
5 int n, m, s, t, a, b, c;
6 bool vis[maxn];
7 int dfs(int v, int t, int f) {
8     cout << v << ' ' << t << ' ' << f << '\n';
9     if (v == t) return f;
10    vis[v] = true;
11    for (edge &e: G[v]) {
12        if (!vis[e.to] && e.cap > 0) {
13            int d = dfs(e.to, t, min(f, e.cap));
14            if (d > 0) {
15                e.cap -= d, G[e.to][e.rev].cap += d;
16                return d;
17            }
18        }
19    }
20    return 0;
21 }
22 int ford_fulkerson(int s, int t) {
23     int flow = 0, f;
24     for (int i = 0; i < n; i++) {
25         cout << i << " : ";
26         for (edge e: G[i])
27             cout << '(' << e.to << ', ' << e.cap << ')' << ' ';
28         cout << '\n';
29     }
30     do {
31         memset(vis, false, sizeof(vis));
32         f = dfs(s, t, INF);
33         for (int i = 0; i < n; i++) {
34             cout << i << " : ";
35             for (edge e: G[i])
36                 cout << '(' << e.to << ', ' << e.cap << ')' << ' ';
37             cout << '\n';
38         }
39         cout << f << '\n';
40         flow += f;
41     } while (f > 0);
42     return flow;
43 }
44 void init(int n) {
45     for (int i = 0; i < n; i++) G[i].clear();
46 }
47 int main() {
48     cin >> n >> m >> s >> t;
49     init(n);
50     while (m--) {
51         cin >> a >> b >> c;
52         G[a].push_back((edge){b, c, (int)G[b].size()});
53         G[b].push_back((edge){a, 0, (int)G[a].size() - 1});
54     }
55     cout << ford_fulkerson(s, t) << '\n';
56     return 0;
57 }

```

5.4 KM

```

1 /** 二分圖最大權值匹配 KM 演算法，複雜度 O(n^3)*/
2 #define inf 5e18
3 class KM {
4 private:
5     const vector<vector<ll>>& e;
6     int xx, yy;
7     vector<ll> cx, cy, wx, wy;
8     vector<bool> vx, vy;
9     ll z;
10
11     bool dfs(int u) {
12         vx[u] = 1;
13         for (int v = 0; v < yy; v++) {
14             if (vy[v] || e[u][v] == inf) continue;
15             ll t = wx[u] + wy[v] - e[u][v];
16             if (t == 0) {
17                 vy[v] = 1;
18                 if (cy[v] == -1 || dfs(cy[v])) {
19                     cx[u] = v, cy[v] = u;
20                     return 1;
21                 }
22             } else if (t > 0)
23                 z = min(z, t);
24         }
25         return 0;
26     }
27 public:
28     // 問最大匹配權重。
29     ll max_weight() {
30         for (int i = 0; i < xx; i++)
31             for (int j = 0; j < yy; j++) {
32                 if (e[i][j] == inf) continue;
33                 wx[i] = max(wx[i], e[i][j]);
34             }
35         for (int i = 0; i < xx; i++) {
36             while (1) {
37                 z = inf, vx.assign(xx, 0), vy.assign(yy, 0);
38                 if (dfs(i)) break;
39                 for (int j = 0; j < xx; j++)
40                     if (vx[j] && wx[j] == z)
41                         for (int j = 0; j < yy; j++)
42                             if (vy[j] && wy[j] == z)
43                                 z += z;
44             }
45             ll ans = 0;
46             for (int i = 0; i < xx; i++)
47                 if (cx[i] != -1) ans += e[i][cx[i]];
48             return ans;
49         }
50     }
51
52     // 給他 n * m 的權重表 (n <= m)，求最大完全匹配權重，權重
53     // 可以
54     // 是負數。注意 n > m 會導致無窮迴圈。
55     KM(vector<vector<ll>>& e) : e(e) {
56         xx = e.size(), yy = e[0].size(); // xx 要 <= yy !!
57         cx.assign(xx, -1), cy.assign(yy, -1);
58         wx.assign(xx, 0), wy.assign(yy, 0);
59     }
60 };

```

5.5 Hopcroft Karp

```

1 int n, m, vis[maxn], level[maxn], pr[maxn], pr2[maxn];
2 vector<int> edge[maxn]; // for Left
3 bool dfs(int u) {
4     vis[u] = true;
5     for (vector<int>::iterator it = edge[u].begin();
6         it != edge[u].end(); ++it) {
7         int v = pr2[*it];
8         if (v == -1 ||
9             (!vis[v] && level[u] < level[v] && dfs(v))) {
10             pr[u] = *it, pr2[*it] = u;
11             return true;
12         }
13     }
14     return false;
15 }
16 int hopcroftKarp() {
17     memset(pr, -1, sizeof(pr));
18     memset(pr2, -1, sizeof(pr2));
19     for (int match = 0; ; ) {
20         queue<int> Q;
21         for (int i = 1; i <= n; ++i) {
22             if (pr[i] == -1) {
23                 level[i] = 0;
24                 Q.push(i);
25             } else
26                 level[i] = -1;
27         }
28         while (!Q.empty()) {
29             int u = Q.front();
30             Q.pop();
31             for (vector<int>::iterator it = edge[u].begin();
32                 it != edge[u].end(); ++it) {
33                 int v = pr2[*it];
34                 if (v != -1 && level[v] < 0) {
35                     level[v] = level[u] + 1;
36                     Q.push(v);
37                 }
38             }
39         }
40         for (int i = 1; i <= n; ++i) vis[i] = false;
41         int d = 0;
42         for (int i = 1; i <= n; ++i)
43             if (pr[i] == -1 && dfs(i)) ++d;
44         if (d == 0) return match;
45         match += d;
46     }
47 }

```

5.6 SW-MinCut

```

1 // all pair min cut
2 // global min cut
3 struct SW { // O(V^3)
4     static const int MXN = 514;
5     int n, vst[MXN], del[MXN];
6     int edge[MXN][MXN], wei[MXN];
7     void init(int _n){
8         n = _n; FZ(edge); FZ(del);
9     }
10    void addEdge(int u, int v, int w) {

```

```

11     edge[u][v] += w; edge[v][u] += w;
12 }
13 void search(int &s, int &t) {
14     FZ(vst); FZ(wei);
15     s = t = -1;
16     while (true){
17         int mx=-1, cur=0;
18         for (int i=0; i<n; i++)
19             if (!del[i] && !vst[i] && mx<wei[i])
20                 cur = i, mx = wei[i];
21         if (mx == -1) break;
22         vst[cur] = 1;
23         s = t; t = cur;
24         for (int i=0; i<n; i++)
25             if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
26     }
27 }
28 int solve() {
29     int res = 2147483647;
30     for (int i=0, x, y; i<n-1; i++) {
31         search(x,y);
32         res = min(res,wei[y]);
33         del[y] = 1;
34         for (int j=0; j<n; j++)
35             edge[x][j] = (edge[j][x] += edge[y][j]);
36     }
37     return res;
38 }
39 } graph;

```

5.7 Stable Marriage

```

1 // 演算法筆記
2 1. N位男士各自向自己最喜愛的女士求婚。
3 2. N位女士各自從自己的求婚者中，挑最喜愛的那位男士訂婚，但是
4   往後可背約。
5   沒有求婚者的女士，就只好等等。
6 3. 失敗的男士們，只好各自向自己次喜愛的女士求婚。
7 4. N位女士各自從自己的求婚者中，挑最喜歡的那位男士訂婚，但是
8   往後可背約。
9   已訂婚卻有更喜愛的女士求婚的女士，就毀約，改為與此男士訂
10  婚。
11   沒有求婚者的女士，就只好再等等。
12 5. 重複3. 4.直到形成N對伴侶為止。
13 // Jinkela
14 queue<int> Q;
15 for ( i : 所有考生 ) {
16     設定在第0志願;
17     Q.push(考生i);
18 }
19 while(Q.size()){
20     當前考生=Q.front();Q.pop();
21     while ( 此考生未分發 ) {
22         指標移到下一志願;
23         if ( 已經沒有志願 or 超出志願總數 ) break;
24         計算該考生在該科系加權後的總分;
25         if ( 不符合科系需求 ) continue;
26         if ( 目前科系有餘額 ) {

```

```

24         依加權後分數高低順序將考生id加入科系錄取名單中;
25         break;
26     }
27     if ( 目前科系已額滿 ) {
28         if ( 此考生成績比最低分數還高 ) {
29             依加權後分數高低順序將考生id加入科系錄取名單;
30             Q.push(被踢出的考生);
31         }
32     }
33 }
34 }

```

6 Math

6.1 快速冪

```

1 // 問  $a^p$ 
2 ll fastpow(ll a, int p) {
3     ll ret = 1;
4     while (p) {
5         if (p & 1) ret *= a;
6         a *= a, p >>= 1;
7     } return ret;
8 }
9 // 問  $(a^p) \bmod m$ 
10 ll fastpow(ll a, ll p, ll m) {
11     ll ret = 1;
12     while (p) {
13         if (p & 1) ret = ret * a % m;
14         a = a * a % m, p >>= 1;
15     } return ret;
16 }

```

6.2 模逆元

```

1 // 解  $(ax \equiv 1) \bmod p$  。p 必須是質數，a 是正整數。
2 ll modinv(ll a, ll p) {
3     if (p == 1) return 0;
4     ll pp = p, y = 0, x = 1;
5     while (a > 1) {
6         ll q = a / p, t = p;
7         p = a % p, a = t, t = y, y = x - q * y, x = t;
8     }
9     if (x < 0) x += pp;
10    return x;
11 }
12 // 解  $(ax \equiv b) \bmod p$  。p 必須是質數，a 和 b 是正整數。
13 ll modinv(ll a, ll b, ll p) {
14     ll ret = modinv(a, p);
15     return ret * b % p;
16 }

```

6.3 離散根號

```

1 int order(ll b, ll p) {
2     if (__gcd(b, p) != 1) return -1;
3     int ret = 2;
4     while (++ret)
5         if (fastpow(b, ret, p) == 1) break;
6     return ret;
7 }
8 // 把 fastpow 也抄過來，會用到。
9 // 問  $(x^2 = y) \bmod p$  的解。回傳 -1 表示 x 無解。
10 ll dsqrt(ll y, ll p) {
11     if (__gcd(y, p) != 1) return -1;
12     if (fastpow(y, (p - 1) / 2, p) == p - 1) return -1;
13     int e = 0;
14     ll s = p - 1;
15     while (!(s & 1)) s >>= 1, e++;
16     int q = 2;
17     while (1)
18         if (fastpow(q, (p - 1) / 2, p) == p - 1)
19             break;
20     else q++;
21     ll x = fastpow(y, (s + 1) / 2, p);
22     ll b = fastpow(y, s, p);
23     ll g = fastpow(q, s, p);
24     while (1) {
25         int m;
26         for (m = 0; m < e; m++) {
27             int o = order(p, b);
28             if (o == -1) return -1;
29             if (o == fastpow(2, m, p)) break;
30         }
31         if (m == 0) return x;
32         x = x * fastpow(g, fastpow(2, e - m - 1, p) % p);
33         g = fastpow(g, fastpow(2, e - m, p), p);
34         b = b * g % p;
35         if (b == 1) return x;
36         e = m;
37     }
38 }

```

6.4 外星模運算

```

1 //a[0]^(a[1]^a[2]^...)
2 #define maxn 1000000
3 int euler[maxn+5];
4 bool is_prime[maxn+5];
5 void init_euler(){
6     is_prime[1] = 1; //—不是質數
7     for(int i=1; i<=maxn; i++) euler[i]=i;
8     for(int i=2; i<=maxn; i++) {
9         if(!is_prime[i]) { //是質數
10             euler[i]--;
11             for(int j=i<<1; j<=maxn; j+=i) {
12                 is_prime[j]=1;
13                 euler[j] = euler[j]/i*(i-1);
14             }
15         }
16     }
17 }
18 LL pow(LL a, LL b, LL mod) { //a^b%mod
19     LL ans=1;
20     for(; b; a=a*a%mod, b>>=1)
21         if(b&1) ans = ans*a%mod;

```

```

22     return ans;
23 }
24 bool isless(LL *a, int n, int k) {
25     if(*a==1)return k>1;
26     if(--n==0)return *a<k;
27     int next=0;
28     for(LL b=1;b<k;++next)
29         b *= *a;
30     return isless(a+1, n, next);
31 }
32 LL high_pow(LL *a, int n, LL mod){
33     if(*a==1||--n==0)return *a%mod;
34     int k = 0, r = euler[mod];
35     for(LL tma=1;tma!=pow(*a,k+r,mod);++k)
36         tma = tma*(*a)%mod;
37     if(isless(a+1,n,k))return pow(*a,high_pow(a+1,n,k),mod);
38     int tmd = high_pow(a+1,n,r), t = (tmd-k+r)%r;
39     return pow(*a,k+t,mod);
40 }
41 LL a[1000005]; int t,mod;
42 int main(){
43     init_euler();
44     scanf("%d", &t);
45     #define n 4
46     while(t--){
47         for(int i=0;i<n;++i)scanf("%lld", &a[i]);
48         scanf("%d", &mod);
49         printf("%lld\n", high_pow(a,n,mod));
50     }
51     return 0;
52 }

```

6.5 SG

1 Anti Nim (取走最後一個石子者敗) :

2 先手必勝 **if and only if**

1. 「所有」堆的石子數都為 1 且遊戲的 SG 值為 0。
2. 「有些」堆的石子數大於 1 且遊戲的 SG 值不為 0。

6 Anti-SG (決策集合為空的遊戲者贏) :

7 定義 SG 值為 0 時, 遊戲結束,

8 則先手必勝 **if and only if**

1. 遊戲中沒有單一遊戲的 SG 函數大於 1 且遊戲的 SG 函數為 0。
2. 遊戲中某個單一遊戲的 SG 函數大於 1 且遊戲的 SG 函數不為 0。

12 Sprague-Grundy :

1. 雙人、回合制
2. 資訊完全公開
3. 無隨機因素
4. 可在有限步內結束
5. 沒有和局
6. 雙方可採取的行動相同

20 SG(S) 的值為 0 : 後手(P)必勝

21 不為 0 : 先手(N)必勝

```

22 int mex(set S) {
23     // find the min number >= 0 that not in the S
24     // e.g. S = {0, 1, 3, 4} mex(S) = 2
25 }

```

```

26 state = []
27 int SG(A) {
28     if (A not in state) {
29         S = sub_states(A)
30         if( len(S) > 1 ) state[A] = reduce(operator.xor, [SG(B)
31             for B in S])
32         else state[A] = mex(set(SG(B) for B in next_states(A)))
33     } return state[A]
34 }

```

6.6 Matrix

```

1 struct Matrix {
2     int r, c;
3     vector<vector<ll>> m;
4     Matrix(int r, int c): r(r), c(c), m(r, vector<ll>(c)) {}
5     vector<ll> &operator[](int i) { return m[i]; }
6     Matrix operator+(const Matrix &a) {
7         Matrix rev(r, c);
8         for (int i = 0; i < r; ++i)
9             for (int j = 0; j < c; ++j)
10                 rev[i][j] = m[i][j] + a.m[i][j];
11         return rev;
12     }
13     Matrix operator-(const Matrix &a) {
14         Matrix rev(r, c);
15         for (int i = 0; i < r; ++i)
16             for (int j = 0; j < c; ++j)
17                 rev[i][j] = m[i][j] - a.m[i][j];
18         return rev;
19     }
20     Matrix operator*(const Matrix &a) {
21         Matrix rev(r, a.c);
22         Matrix tmp(a.c, a.r);
23         for (int i = 0; i < a.r; ++i)
24             for (int j = 0; j < a.c; ++j)
25                 tmp[j][i] = a.m[i][j];
26         for (int i = 0; i < r; ++i)
27             for (int j = 0; j < a.c; ++j)
28                 for (int k = 0; k < c; ++k)
29                     rev.m[i][j] += m[i][k] * tmp[j][k];
30         return rev;
31     }
32     // 回傳反矩陣。注意這是 const 方法所以原矩陣不受影響。
33     Matrix inverse() const {
34         Matrix t(r, r + c);
35         for (int y = 0; y < r; y++) {
36             t.m[y][c + y] = 1;
37             for (int x = 0; x < c; x++) t.m[y][x] = m[y][x];
38         }
39         if (!t.gauss()) return Matrix(0, 0);
40         Matrix ret(c, r);
41         for (int y = 0; y < r; y++)
42             for (int x = 0; x < c; x++)
43                 ret[y][x] = t.m[y][c + x] / t.m[y][y];
44         return ret;
45     }
46     // 做高斯消去 (最高次係數應置於最左, 常數應置於最右) 並回傳 det
47     // 行列式值。複雜度 O(n^3)。如果不是方陣, 回傳值無意義。
48     ll gauss() {
49         vector<ll> lazy(r, 1);

```

```

50     bool sign = false;
51     for (int i = 0; i < r; ++i) {
52         if (m[i][i] == 0) {
53             int j = i + 1;
54             while (j < r && !m[j][i]) j++;
55             if (j == r) continue;
56             m[i].swap(m[j]); sign = !sign;
57         }
58         for (int j = 0; j < r; ++j) {
59             if (i == j) continue;
60             lazy[j] = lazy[j] * m[i][i];
61             ll mx = m[j][i];
62             for (int k = 0; k < c; ++k)
63                 m[j][k] =
64                     m[j][k] * m[i][i] - m[i][k] * mx;
65         }
66         ll det = sign ? -1 : 1;
67         for (int i = 0; i < r; ++i) {
68             det = det * m[i][i] / lazy[i];
69             for (auto &j : m[i]) j /= lazy[i];
70         }
71         return det;
72     }
73 }
74 };

```

6.7 Karatsuba

```

1 // N is power of 2
2 template<typename Iter>
3 void DC(int N, Iter tmp, Iter A, Iter B, Iter res){
4     fill(res,res+2*N,0);
5     if (N<=32){
6         for (int i=0;i<N;i++)
7             for (int j=0;j<N;j++)
8                 res[i+j] += A[i]*B[j];
9         return;
10    }
11    int n = N/2;
12    auto a = A+n, b = A;
13    auto c = B+n, d = B;
14    DC(n,tmp+N,a,c,res+2*N);
15    for (int i=0;i<N;i++){
16        res[i+n] += res[2*N+i];
17        res[i+n] -= res[2*N+i];
18    }
19    DC(n,tmp+N,b,d,res+2*N);
20    for (int i=0;i<N;i++){
21        res[i] += res[2*N+i];
22        res[i+n] -= res[2*N+i];
23    }
24    auto x = tmp;
25    auto y = tmp+n;
26    for (int i=0;i<n;i++) x[i] = a[i]+b[i];
27    for (int i=0;i<n;i++) y[i] = c[i]+d[i];
28    DC(n,tmp+N,x,y,res+2*N);
29    for (int i=0;i<N;i++)
30        res[i+n] += res[2*N+i];
31 }
32 // DC(1<<16,tmp.begin(),A.begin(),B.begin(),res.begin());

```

6.8 Euler Function

```

1 // 查詢 phi(x) 亦即比 x 小且與 x 互質的數的數量。
2 int phi(int x) {
3     int r = x;
4     for (int p = 2; p * p <= x; p++) {
5         if (x % p == 0) {
6             while (x % p == 0) x /= p;
7             r -= r / p;
8         }
9     }
10    if (x > 1) r -= r / x;
11    return r;
12 }
13 // 查詢所有 phi(x) , 且 x in [0, n) 。注意右開區間, 回傳陣
    列。
14 vector<int> phi_in(int n) {
15     vector<bool> p(n, 1); vector<int> r(n);
16     p[0] = p[1] = 0;
17     for (int i = 0; i < n; i++) r[i] = i;
18     for (int i = 2; i < n; i++) {
19         if (!p[i]) continue;
20         r[i]--;
21         for (int j = i * 2; j < n; j += i)
22             p[j] = 0, r[j] = r[j] / i * (i - 1);
23     }
24     r[1] = 0;
25     return r;
26 }

```

6.9 Miller Rabin

```

1 //From jacky860226
2 typedef long long LL;
3 inline LL mul(LL a, LL b, LL m) { //a*b%m
4     return (a%m)*(b%m)%m;
5 }
6 /*LL mul(LL a, LL b, LL m) { //a*b%m
7     a %= m, b %= m;
8     LL y = (LL)((double)a*b/m+0.5); //fast for m < 2^58
9     LL r = (a*b-y*m)%m;
10    return r<0 ? r+m : r;
11 }*/
12 template<typename T> T pow(T a, T b, T mod) { //a^b%mod
13     T ans = 1;
14     while(b) {
15         if(b&1) ans = mul(ans, a, mod);
16         a = mul(a, a, mod);
17         b >>= 1;
18     } return ans;
19 }
20 template<typename T> bool isprime(T n, int num) { //num = 3,7
21     int sprp[3] = {2,7,61}; //int範圍可解
22     //int llsprp[7] =
23         {2,325,9375,28178,450775,9780504,1795265022}; //至少
24         unsigned long long範圍
25     if(n==2) return true;
26     if(n<2 || n%2==0) return false;
27     //n-1 = u * 2^t
28     int t = 0; T u = n-1;
29     while(u%2==0) u >>= 1, t++;

```

```

28     for(int i=0; i<num; i++) {
29         T a = sprp[i]%n;
30         if(a==0 || a==1 || a==n-1) continue;
31         T x = pow(a,u,n);
32         if(x==1 || x==n-1) continue;
33         for(int j=1; j<t; j++) {
34             x = mul(x,x,n);
35             if(x==1) return false;
36             if(x==n-1) break;
37         }
38         if(x!=n-1) return false;
39     } return true;
40 }

```

6.10 質因數分解

```

1 typedef __int128 ll;
2 vector<ll> vv;
3
4 /* fastoi here */
5
6 ll abs(ll x){
7     return (x>0?x:-x);
8 }
9 ll power(ll x, ll y, ll p){
10    ll res = 1;
11    x = x % p;
12    while (y > 0){
13        if (y & 1)
14            res = (res*x) % p;
15        y = y>>1;
16        x = (x*x) % p;
17    }
18    return res;
19 }
20 bool miillerTest(ll d, ll n){
21     ll a = 2 + rand() % (n - 4);
22     ll x = power(a, d, n);
23     if (x == 1 || x == n-1)
24         return true;
25     while (d != n-1){
26         x = (x * x) % n;
27         d *= 2;
28         if (x == 1) return false;
29         if (x == n-1) return true;
30     }
31     return false;
32 }
33 bool isPrime(ll n, ll k){
34     if (n <= 1 || n == 4) return false;
35     if (n <= 3) return true;
36     ll d = n - 1;
37     while (d % 2 == 0)
38         d /= 2;
39     for (ll i = 0; i < k; i++)
40         if (!miillerTest(d, n))
41             return false;
42     return true;
43 }
44 ll func(ll t, ll c, ll x) {
45     return (t*t+c)%x;
46 }
47 ll Pollard_Rho(ll x) {

```

```

48     ll t = 0;
49     ll c = rand() % (x - 1) + 1;
50     for (int i = 1; i < 1145; ++i) t = func(t, c, x);
51     ll s = t;
52     int step = 0, goal = 1;
53     ll val = 1;
54     for (goal = 1; goal <= 1, s = t, val = 1) {
55         for (step = 1; step <= goal; ++step) {
56             t = func(t, c, x);
57             val = val * abs(t - s) % x;
58             if (!val) return x;
59             if (step % 127 == 0) {
60                 ll d = __gcd(val, x);
61                 if (d > 1) return d;
62             }
63         }
64         ll d = __gcd(val, x);
65         if (d > 1) return d;
66     }
67 }
68 void prefactor(ll &n, vector<ll> &v) {
69     ll prime[12] = {2,3,5,7,11,13,17,19,23,29,31,37};
70     for(int i=0;i<12;++i) {
71         while(n%prime[i]==0) {
72             v.push_back(prime[i]);
73             n/=prime[i];
74         }
75     }
76 }
77 void comfactor(const ll &n, vector<ll> &v) {
78     if(isPrime(n,15)) {
79         v.push_back(n);
80         return;
81     }
82     ll d = Pollard_Rho(n);
83     comfactor(d,v);
84     comfactor(n/d,v);
85 }
86 void Factor(const ll &x, vector<ll> &v) {
87     ll n = x;
88     if(n==1) { puts("Factor 1"); return; }
89     prefactor(n,v);
90     if(n==1) return;
91     comfactor(n,v);
92     sort(v.begin(),v.end());
93 }
94 void AllFactor(const ll &n,vector<ll> &v) {
95     vector<ll> tmp;
96     Factor(n,tmp);
97     v.clear();
98     v.push_back(1);
99     ll len;
100    ll now=1;
101    ll lentmp = tmp.size();
102    for(int i=0;i<lentmp;++i) {
103        if(i==0 || tmp[i]!=tmp[i-1]) {
104            len = v.size();
105            now = 1;
106        }
107        now*=tmp[i];
108        for(int j=0;j<len;++j)
109            v.push_back(v[j]*now);
110    }
111 }
112 void prime_factorization(){
113     srand(time(NULL));

```



```

114 ll n = read();
115 AllFactor(n,vv);
116 sort(vv.begin(),vv.end());
117 for(auto i:vv){
118     print(i); putchar(' ');
119 }
120 }

```

6.11 質數

```

1 12721      13331      14341      75577
2 123457     222557     556679     880301
3 999983     1e6+99      1e9+9      2e9+99
4 1e12+39    1e15+37      1e9+7      1e7+19
5 1097774749 1076767633 100102021
6 999997771 1001010013 1000512343
7 987654361 999991231 999888733
8 98789101 987777733 999991921
9 1010101333 1010102101
10 2305843009213693951 4611686018427387847
11 9223372036854775783 18446744073709551557

```

6.12 實根

```

1 // an*x^n + ... + a1x + a0 = 0;
2 int sign(double x){
3     return x < -eps ? -1 : x > eps;
4 }
5 double get(const vector<double>&coef, double x){
6     double e = 1, s = 0;
7     for(auto i : coef) s += i*e, e *= x;
8     return s;
9 }
10 double find(const vector<double>&coef, int n, double lo,
11             double hi){
12     double sign_lo, sign_hi;
13     if( !(sign_lo = sign(get(coef,lo))) ) return lo;
14     if( !(sign_hi = sign(get(coef,hi))) ) return hi;
15     if(sign_lo * sign_hi > 0) return INF;
16     for(int stp = 0; stp < 100 && hi - lo > eps; ++stp){
17         double m = (lo+hi)/2.0;
18         int sign_mid = sign(get(coef,m));
19         if(!sign_mid) return m;
20         if(sign_lo*sign_mid < 0) hi = m;
21         else lo = m;
22     }
23     return (lo+hi)/2.0;
24 }
25 vector<double> cal(vector<double>coef, int n){
26     vector<double>res;
27     if(n == 1){
28         if(sign(coef[1])) res.pb(-coef[0]/coef[1]);
29         return res;
30     }
31     vector<double>dcoef(n);
32     for(int i = 0; i < n; ++i) dcoef[i] = coef[i+1]*(i+1);
33     vector<double>droot = cal(dcoef, n-1);
34     droot.insert(droot.begin(), -INF);
35     droot.pb(INF);
36     for(int i = 0; i+1 < droot.size(); ++i){

```

```

36 double tmp = find(coef, n, droot[i], droot[i+1]);
37 if(tmp < INF) res.pb(tmp);
38 }
39 return res;
40 }
41 int main () {
42     vector<double>ve;
43     vector<double>ans = cal(ve, n);
44     // 視情況把答案 +eps，避免 -0
45 }

```

6.13 FFT

```

1 template<typename T,typename VT=vector<complex<T> > >
2 struct FFT{
3     const T pi;
4     FFT(const T pi=acos((T)-1)):pi(pi){}
5     unsigned bit_reverse(unsigned a,int len){
6         a=((a&0x55555555U)<<1)|((a&0xAAAAAAAAU)>>1);
7         a=((a&0x33333333U)<<2)|((a&0xCCCCCCCCU)>>2);
8         a=((a&0x0F0F0F0FU)<<4)|((a&0xFF0F0F0FU)>>4);
9         a=((a&0x00FF00FFU)<<8)|((a&0xFF00FF00U)>>8);
10        a=((a&0x0000FFFFU)<<16)|((a&0xFFFF0000U)>>16);
11        return a>>(32-len);
12    }
13    void fft(bool is_inv,VT &in,VT &out,int N){
14        int bitlen=__lg(N),num=is_inv?-1:1;
15        for(int i=0;i<N;++i) out[bit_reverse(i,bitlen)]=in[i];
16    }
17    for(int step=2; step<=N; step<<=1){
18        const int mh = step>>1;
19        for(int i=0; i<mh; ++i){
20            complex<T> wi = exp(complex<T>(0,i*num*pi/mh));
21            for(int j=i; j<N; j+=step){
22                int k = j+mh;
23                complex<T> u = out[j], t = wi*out[k];
24                out[j] = u+t;
25                out[k] = u-t;
26            }
27        }
28        if(is_inv) for(int i=0;i<N;++i) out[i]/=N;
29    }
30 };

```

6.14 NTT

```

1 template<typename T,typename VT=std::vector<T> >
2 struct NTT{
3     const T P,G;
4     NTT(T p=(1<<23)*7*17+1,T g=3):P(p),G(g){}
5     inline unsigned int bit_reverse(unsigned int a,int len){
6         a=((a&0x55555555U)<<1)|((a&0xAAAAAAAAU)>>1);
7         a=((a&0x33333333U)<<2)|((a&0xCCCCCCCCU)>>2);
8         a=((a&0x0F0F0F0FU)<<4)|((a&0xFF0F0F0FU)>>4);
9         a=((a&0x00FF00FFU)<<8)|((a&0xFFFF00FFU)>>8);
10        a=((a&0x0000FFFFU)<<16)|((a&0xFFFF0000U)>>16);
11        return a>>(32-len);

```

```

12 }
13 inline T pow_mod(T n,T k,T m){
14     T ans=1;
15     for(n=(n>=m?n%m:n);k;k>>=1){
16         if(k&1)ans=ans*n%m;
17         n=n*n%m;
18     } return ans;
19 }
20 inline void ntt(bool is_inv,VT &in,VT &out,int N){
21     int bitlen=std::__lg(N);
22     for(int i=0;i<N;++i)out[bit_reverse(i,bitlen)]=in[i];
23     for(int step=2,id=1;step<=N;step<<=1,++id){
24         T wn=pow_mod(G,(P-1)>>id,P),wi=1,u,t;
25         const int mh=step>>1;
26         for(int i=0;i<mh;++i){
27             for(int j=i;j<N;j+=step){
28                 u = out[j], t = wi*out[j+mh]%P;
29                 out[j] = u+t;
30                 out[j+mh] = u-t;
31                 if(out[j]>=P)out[j]-=P;
32                 if(out[j+mh]<0)out[j+mh]+=P;
33             }
34             wi = wi*wn%P;
35         }
36     }
37     if(is_inv){
38         for(int i=1;i<N/2;++i)std::swap(out[i],out[N-i]);
39         T invn=pow_mod(N,P-2,P);
40         for(int i=0;i<N;++i)out[i]=out[i]*invn%P;
41     }
42 }
43 };
44 #endif

```

6.15 Simplex

```

1 /*target:
2 max \sum_{j=1}^n A_{0,j}*x_j
3 condition:
4 \sum_{j=1}^n A_{i,j}*x_j <= A_{i,0} | i=1~m
5 x_j >= 0 | j=1~n
6 VDB = vector<double>*/
7 template<class VDB>
8 VDB simplex(int m,int n,vector<VDB> a){
9     vector<int> left(m+1), up(n+1);
10    iota(left.begin(), left.end(), n);
11    iota(up.begin(), up.end(), 0);
12    auto pivot = [&](int x, int y){
13        swap(left[x], up[y]);
14        auto k = a[x][y]; a[x][y] = 1;
15        vector<int> pos;
16        for(int j = 0; j <= n; ++j){
17            a[x][j] /= k;
18            if(a[x][j] != 0) pos.push_back(j);
19        }
20        for(int i = 0; i <= m; ++i){
21            if(a[i][y]==0 || i == x) continue;
22            k = a[i][y], a[i][y] = 0;
23            for(int j : pos) a[i][j] -= k*a[x][j];
24        }
25    };
26    for(int x,y;;){
27        for(int i=x+1; i <= m; ++i)

```

```

28     if(a[i][0]<a[x][0]) x = i;
29     if(a[x][0]>=0) break;
30     for(int j=y+1; j <= n; ++j)
31         if(a[x][j]<a[x][y]) y = j;
32     if(a[x][y]>=0) return VDB();//infeasible
33     pivot(x, y);
34 }
35 for(int x,y;;){
36     for(int j=y+1; j <= n; ++j)
37         if(a[0][j] > a[0][y]) y = j;
38     if(a[0][y]<=0) break;
39     x = -1;
40     for(int i=1; i<=m; ++i) if(a[i][y] > 0)
41         if(x == -1 || a[i][0]/a[i][y]
42             < a[x][0]/a[x][y]) x = i;
43     if(x == -1) return VDB();//unbounded
44     pivot(x, y);
45 }
46 VDB ans(n + 1);
47 for(int i = 1; i <= m; ++i)
48     if(left[i] <= n) ans[left[i]] = a[i][0];
49 ans[0] = -a[0][0];
50 return ans;
51 }

```

6.16 Expression

```

1 /**
2  * 支援處理四則運算的工具。給四則運算的字串，檢查格式並計算其
3  * 值。如果
4  * 格式不合法，會丟出錯誤。複雜度 O(字串長度)。支援的符號有
5  * 四則運算
6  * 和求餘數，先乘除後加減。可以使用括號、或前置正負號。數字開
7  * 頭可以為
8  * 零或禁止為零。可以兼容或禁止多重前置號（例如 --1 視為 1、
9  * ++-1
10 * 視為 -1）。空字串視為不合法。運算範圍限於 long long。如果
11 * 試圖除
12 * 以零或對零求餘也會丟出錯誤。
13 */
14 void req(bool b) { if (!b) throw ""; }
15 const int B = 2; // 可以調整成 B 進位
16 class Expr {
17 private:
18     deque<char> src;
19     Expr(const string& s) : src(s.begin(), s.end()) {}
20     inline char top() {
21         return src.empty() ? '\0' : src.front();
22     }
23     inline char pop() {
24         char c = src.front(); src.pop_front(); return c;
25     }
26     ll n() {
27         ll ret = pop() - '0';
28         // 若要禁止數字以 0 開頭，加上這行
29         // req(ret != 0 || !isdigit(top()));
30         while (isdigit(top())) ret = B * ret + pop() - '0';
31         return ret;
32     }
33     ll fac() {
34         if (isdigit(top())) return n();

```

```

35     if (top() == '-') { pop(); return -fac(); }
36     if (top() == '(') {
37         pop();
38         ll ret = expr(1);
39         req(pop() == ')');
40         return ret;
41     }
42     // 若要允許前置正號，加上這行
43     // if(top() == '+') { pop(); return fac(); }
44     throw "";
45 }
46 ll term() {
47     ll ret = fac(); char c = top();
48     while (c == '*' || c == '/' || c == '%') {
49         pop();
50         if (c == '*') ret *= fac();
51         else {
52             ll t = fac(); req(t);
53             if (c == '/') ret /= t; else ret %= t;
54         }
55         c = top();
56     } return ret;
57 }
58 ll expr(bool k) {
59     ll ret = term();
60     while (top() == '+' || top() == '-')
61         if (pop() == '+') ret += term();
62         else ret -= term();
63     req(top() == (k ? ')' : '\0'));
64     return ret;
65 }
66 public:
67 // 給定數學運算的字串，求其值。若格式不合法，丟出錯誤。
68 static ll eval(const string& s) {
69     // 若要禁止多重前置號，加上這四行
70     // req(s.find("--") == -1); // 禁止多重負號
71     // req(s.find("-+") == -1);
72     // req(s.find("+") == -1);
73     // req(s.find("++") == -1);
74     return Expr(s).expr(0);
75 }
76 };

```

6.17 Pick's Theorem

```

1 /* i:number of integer points interior to the polygon
2  b:the number of integer points on its boundary (including
3  both vertices and points along the sides).
4  Then the area A of this polygon is: A = i + b/2 - 1 */
5 pair<ll, ll> operator-(const pair<ll, ll>& a, const pair<ll, ll>& b) {
6     ll& b) {
7     return {a.first - b.first, a.second - b.second};
8 }
9 int n;
10 pair<ll, ll> p[100010];
11 ll Pick() {
12     cin >> n;
13     for(int i = 0; i < n; ++i)
14         cin >> p[i].first >> p[i].second;

```

```

16 p[n] = p[0];
17 ll area = 0;
18 for(int i = 0; i < n; ++i)
19     area += p[i].first * p[i + 1].second - p[i].second * p[i + 1].first;
20 area = abs(area);
21 ll b = 0;
22 for(int i = 0; i < n; ++i) {
23     pair<ll, ll> v = p[i + 1] - p[i];
24     b += abs(__gcd(v.first, v.second));
25 }
26 ll a = (area + 2 - b) / 2;
27 return a;
28 }

```

7 String

7.1 Rolling Hash

```

1 // 問 pat 在 str 第一次出現的開頭 index。-1 表示找不到。
2 int rollhash(string& str, string& pat) {
3     const ll x = 1e6 + 99; // 隨意大質數，建議 1e6
4     const ll m = 1e9 + 9; // 隨意大質數，建議 1e9
5     assert(pat.size()); // pat 不能是空字串
6     ll xx = 1, sh = 0;
7     for (char c : pat)
8         sh = (sh * x + c) % m, xx = xx * x % m;
9     deque<ll> hash = {0};
10    int ret = 0;
11    for (char c : str) {
12        hash.push_back((hash.back() * x + c) % m);
13        if (hash.size() <= pat.size()) continue;
14        ll h = hash.back() - hash.front() * xx;
15        h = (h % m + m) % m;
16        if (h == sh) return ret;
17        hash.pop_front();
18        ret++;
19    } return -1;
20 }

```

7.2 Trie

```

1 class Trie {
2 private:
3     struct Node {
4         int cnt = 0, sum = 0;
5         Node *tr[128] = {};
6         ~Node() {
7             for (int i = 0; i < 128; i++)
8                 if (tr[i]) delete tr[i];
9         }
10    };
11    Node *root;
12 public:
13     void insert(char *s) {
14         Node *ptr = root;
15         for (; *s; s++) {

```

```

16     if (!ptr->tr[*s]) ptr->tr[*s] = new Node();
17     ptr = ptr->tr[*s];
18     ptr->sum++;
19 }
20 ptr->cnt++;
21 }
22 inline int count(char *s) {
23     Node *ptr = find(s);
24     return ptr ? ptr->cnt : 0;
25 }
26 Node *find(char *s) {
27     Node *ptr = root;
28     for (; *s; s++) {
29         if (!ptr->tr[*s]) return 0;
30         ptr = ptr->tr[*s];
31     } return ptr;
32 }
33 bool erase(char *s) {
34     Node *ptr = find(s);
35     if (!ptr) return false;
36     int num = ptr->cnt;
37     if (!num) return false;
38     ptr = root;
39     for (; *s; s++) {
40         Node *tmp = ptr;
41         ptr = ptr->tr[*s];
42         ptr->sum -= num;
43         if (!ptr->sum) {
44             delete ptr;
45             tmp->tr[*s] = 0;
46             return true;
47         }
48     }
49 }
50 Trie() { root = new Node(); }
51 ~Trie() { delete root; }
52 };

```

7.3 AC 自動機

```

1 template<char L='a',char R='z'>
2 class ac_automaton{
3     struct joe{
4         int next[R-L+1], fail, efl, ed, cnt_dp, vis;
5         joe():ed(0),cnt_dp(0),vis(0){
6             for(int i=0; i<=R-L; i++) next[i]=0;
7         }
8     };
9 public:
10     std::vector<joe> S;
11     std::vector<int> q;
12     int qs,qe,vt;
13     ac_automaton():S(1),qs(0),qe(0),vt(0){}
14     void clear(){
15         q.clear();
16         S.resize(1);
17         for(int i=0; i<=R-L; i++) S[0].next[i] = 0;
18         S[0].cnt_dp = S[0].vis = qs = qe = vt = 0;
19     }
20     void insert(const char *s){
21         int o = 0;
22         for(int i=0,id; s[i]; i++){
23             id = s[i]-L;

```

```

24         if(!S[o].next[id]){
25             S.push_back(joe());
26             S[o].next[id] = S.size()-1;
27         }
28         o = S[o].next[id];
29     }
30     ++S[o].ed;
31 }
32 void build_fail(){
33     S[0].fail = S[0].efl = -1;
34     q.clear();
35     q.push_back(0);
36     ++qe;
37     while(qs!=qe){
38         int pa = q[qs++], id, t;
39         for(int i=0;i<=R-L;i++){
40             t = S[pa].next[i];
41             if(!t)continue;
42             id = S[pa].fail;
43             while(~id && !S[id].next[i]) id = S[id].fail;
44             S[t].fail = ~id ? S[id].next[i] : 0;
45             S[t].efl = S[S[t].fail].ed ? S[t].fail : S[S[t].fail]
                ].efl;
46             q.push_back(t);
47             ++qe;
48         }
49     }
50 }
51 /*DP出每個前綴在字串s出現的次數並傳回所有字串被s匹配成功的
    次數O(N*M)*/
52 int match_0(const char *s){
53     int ans = 0, id, p = 0, i;
54     for(i=0; s[i]; i++){
55         id = s[i]-L;
56         while(!S[p].next[id] && p) p = S[p].fail;
57         if(!S[p].next[id])continue;
58         p = S[p].next[id];
59         ++S[p].cnt_dp; /*匹配成功則它所有後綴都可以被匹配(DP計算)*/
60     }
61     for(i=qe-1; i>=0; --i){
62         ans += S[q[i]].cnt_dp * S[q[i]].ed;
63         if(~S[q[i]].fail) S[S[q[i]].fail].cnt_dp += S[q[i]].
            cnt_dp;
64     }
65     return ans;
66 }
67 /*多串匹配走efl邊並傳回所有字串被s匹配成功的次數O(N*M^1.5)*/
68 int match_1(const char *s)const{
69     int ans = 0, id, p = 0, t;
70     for(int i=0; s[i]; i++){
71         id = s[i]-L;
72         while(!S[p].next[id] && p) p = S[p].fail;
73         if(!S[p].next[id])continue;
74         p = S[p].next[id];
75         if(S[p].ed) ans += S[p].ed;
76         for(t=S[p].efl; ~t; t=S[t].efl){
77             ans += S[t].ed; /*因為都走efl邊所以保證匹配成功*/
78         }
79     }
80     return ans;
81 }
82 /*枚舉(s的字子串⊗A)的所有相異字串各恰一次並傳回次數O(N*M
    ^{(1/3)})*/

```

```

83 int match_2(const char *s){
84     int ans=0, id, p=0, t;
85     ++vt;
86     /*把戳記vt+=1，只要vt沒溢位，所有S[p].vis==vt就會變成
        false
87     這種利用vt的方法可以O(1)歸零vis陣列*/
88     for(int i=0; s[i]; i++){
89         id = s[i]-L;
90         while(!S[p].next[id]&&p) p = S[p].fail;
91         if(!S[p].next[id])continue;
92         p = S[p].next[id];
93         if(S[p].ed && S[p].vis!=vt){
94             S[p].vis = vt;
95             ans += S[p].ed;
96         }
97         for(t=S[p].efl; ~t && S[t].vis!=vt; t=S[t].efl){
98             S[t].vis = vt;
99             ans += S[t].ed; /*因為都走efl邊所以保證匹配成功*/
100         }
101     }
102     return ans;
103 }
104 /*把AC自動機變成真的自動機*/
105 void evolution(){
106     for(qs=1; qs!=qe;){
107         int p = q[qs++];
108         for(int i=0; i<=R-L; i++)
109             if(S[p].next[i]==0) S[p].next[i] = S[S[p].fail].next[
                i];
110     }
111 }
112 };

```

7.4 KMP

```

1 // KMP fail function.
2 int* kmp_fail(string& s) {
3     int* f = new int[s.size()]; int p = f[0] = -1;
4     for (int i = 1; s[i]; i++) {
5         while (p != -1 && s[p + 1] != s[i]) p = f[p];
6         if (s[p + 1] == s[i]) p++;
7         f[i] = p;
8     }
9     return f;
10 }
11 // 問 sub 在 str 中出現幾次。
12 int kmp_count(string& str, string& sub) {
13     int* fail = kmp_fail(sub); int p = -1, ret = 0;
14     for (int i = 0; i < str.size(); i++) {
15         while (p != -1 && sub[p + 1] != str[i]) p = fail[p];
16         if (sub[p + 1] == str[i]) p++;
17         if (p == sub.size() - 1) p = fail[p], ret++;
18     }
19     delete[] fail; return ret;
20 }
21 // 問 sub 在 str 第一次出現的開頭 index 。 -1 表示找不到。
22 int kmp(string& str, string& sub) {
23     int* fail = kmp_fail(sub);
24     int i, j = 0;
25     while (i < str.size() && j < sub.size()) {
26         if (sub[j] == str[i]) i++, j++;
27         else if (j == 0) i++;

```

```

28     else j = fail[j - 1] + 1;
29 }
30 delete[] fail;
31 return j == sub.size() ? (i - j) : -1;
32 }

```

7.5 Z

```

1 void z_build(string &s, int *z) {
2     int bst = z[0] = 0;
3     for (int i = 1; s[i]; i++) {
4         if (z[bst] + bst < i) z[i] = 0;
5         else z[i] = min(z[bst] + bst - i, z[i - bst]);
6         while (s[z[i]] == s[i + z[i]]) z[i]++;
7         if (z[i] + i > z[bst] + bst) bst = i;
8     }
9 }
10 // Queries how many times s appears in t
11 int z_match(string &s, string &t) {
12     int ans = 0;
13     int lens = s.length(), lent = t.length();
14     int z[lens + lent + 5];
15     string st = s + "$" + t;
16     z_build(st, z);
17     for (int i = lens + 1; i <= lens + lent; i++)
18         if (z[i] == lens) ans++;
19     return ans;
20 }

```

7.6 BWT

```

1 const int N = 8; // 字串長度
2 int s[N+N+1] = "suffixes"; // 字串，後面預留一倍空間。
3 int sa[N]; // 後綴陣列
4 int pivot;
5 int cmp(const void* i, const void* j) {
6     return strcmp(s+(int*)i, s+(int*)j, N);
7 }
8 // 此處便宜行事，採用 O(N^2 log N) 的後綴陣列演算法。
9 void BWT() {
10     strncpy(s + N, s, N);
11     for (int i=0; i<N; ++i) sa[i] = i;
12     qsort(sa, N, sizeof(int), cmp);
13     // 當輸入字串的所有字元都相同，必須當作特例處理。
14     // 或者改用 stable sort。
15     for (int i=0; i<N; ++i)
16         cout << s[(sa[i] + N-1) % N];
17     for (int i=0; i<N; ++i)
18         if (sa[i] == 0) {
19             pivot = i;
20             break;
21         }
22 }
23 // Inverse BWT
24 const int N = 8; // 字串長度
25 char t[N+1] = "xuffessi"; // 字串
26 int pivot;
27 int next[N];

```

```

28 void IBWT() {
29     vector<int> index[256];
30     for (int i=0; i<N; ++i)
31         index[t[i]].push_back(i);
32     for (int i=0, n=0; i<256; ++i)
33         for (int j=0; j<index[i].size(); ++j)
34             next[n++] = index[i][j];
35     int p = pivot;
36     for (int i=0; i<N; ++i)
37         cout << t[p = next[p]];
38 }

```

7.7 Suffix_Array_LCP

```

1 #define radix_sort(x,y){
2     for(i=0;i<A;++i) c[i] = 0;
3     for(i=0;i<n;++i) c[x[y[i]]]++;
4     for(i=1;i<A;++i) c[i] += c[i-1];
5     for(i=n-1;~i;--i) sa[--c[x[y[i]]]] = y[i];
6 }
7 #define AC(r,a,b) r[a]!r[b]||a+k>n||r[a+k]!r[b+k]
8 void suffix_array(const char *s,int n,int *sa,int *rank,int *
9     tmp,int *c){
10     int A='z'+1,i,k,id=0;
11     for(i=0; i<n; ++i)rank[tmp[i]=i]=s[i];
12     radix_sort(rank,tmp);
13     for(k=1; id<n-1; k<=1){
14         for(id=0,i=n-k; i<n; ++i) tmp[id++] = i;
15         for(i=0; i<n; ++i)
16             if(sa[i]>=k) tmp[id++] = sa[i]-k;
17         radix_sort(rank,tmp);
18         swap(rank,tmp);
19         for(rank[sa[0]]=id=0,i=1; i<n; ++i)
20             rank[sa[i]] = id+=AC(tmp,sa[i-1],sa[i]);
21         A = id+1;
22     }
23 }
24 //h:高度數組 sa:後綴數組 rank:排名
25 void suffix_array_lcp(const char *s,int len,int *h,int *sa,
26     int *rank){
27     for(int i=0; i<len; ++i)rank[sa[i]]=i;
28     for(int i=0,k=0; i<len; ++i){
29         if(rank[i]==0)continue;
30         if(k--<0)
31             while(s[i+k]==s[sa[rank[i]-1]+k])++k;
32         h[rank[i]]=k;
33     }
34 }

```

7.8 LPS

```

1 char t[1001]; // 原字串
2 char s[1001 * 2]; // 穿插特殊字元之後的t
3 int z[1001 * 2], L, R; // 源自Gusfield's Algorithm
4 // 由a往左、由b往右，對稱地作字元比對。
5 int extend(int a, int b) {
6     int i = 0;
7     while (a-i>=0 && b+i<N && s[a-i] == s[b+i]) i++;

```

```

8     return i;
9 }
10 void longest_palindromic_substring() {
11     int N = strlen(t);
12     // t穿插特殊字元，存放到s。
13     // (實際上不會這麼做，都是細算索引值。)
14     memset(s, '.', N*2+1);
15     for (int i=0; i<N; ++i) s[i*2+1] = t[i];
16     N = N*2+1;
17     // s[N] = '\0'; // 可做可不做
18     // Manacher's Algorithm
19     z[0] = 1; L = R = 0;
20     for (int i=1; i<N; ++i) {
21         int ii = L - (i - L); // i的映射位置
22         int n = R + 1 - i;
23         if (i > R) {
24             z[i] = extend(i, ii);
25             L = i;
26             R = i + z[i] - 1;
27         } else if (z[ii] == n) {
28             z[i] = n + extend(i-n, i+n);
29             L = i;
30             R = i + z[i] - 1;
31         } else z[i] = min(z[ii], n);
32     }
33     // 尋找最長迴文子串的長度。
34     int n = 0, p = 0;
35     for (int i=0; i<N; ++i)
36         if (z[i] > n) n = z[p = i];
37     // 記得去掉特殊字元。
38     cout << "最長迴文子串的長度是" << (n-1) / 2;
39     // 印出最長迴文子串，記得別印特殊字元。
40     for (int i=p-z[p]+1; i<=p+z[p]-1; ++i)
41         if (i & 1) cout << s[i];
42 }

```

7.9 Edit Distance

```

1 // 問從 src 到 dst 的最小 edit distance
2 // ins 插入一個字元的成本
3 // del 刪除一個字元的成本
4 // sst 替換一個字元的成本
5 ll edd(string& src, string& dst, ll ins, ll del, ll sst) {
6     ll dp[src.size() + 1][dst.size() + 1]; // 不用初始化
7     for (int i = 0; i <= src.size(); i++) {
8         for (int j = 0; j <= dst.size(); j++) {
9             if (i == 0) dp[i][j] = ins * j;
10            else if (j == 0) dp[i][j] = del * i;
11            else if (src[i - 1] == dst[j - 1])
12                dp[i][j] = dp[i - 1][j - 1];
13            else
14                dp[i][j] = min(dp[i][j - 1] + ins,
15                    min(dp[i - 1][j] + del,
16                        dp[i - 1][j - 1] + sst));
17        }
18    }
19    return dp[src.size()][dst.size()];
20 }

```

8 Geometry

8.1 Geometry

```

1 //Copy from Jinkela
2 const double PI=atan2(0.0,-1.0);
3 template<typename T>
4 struct point{
5     T x,y;
6     point(){ }
7     point(const T&x,const T&y):x(x),y(y){ }
8     point operator+(const point &b)const{
9         return point(x+b.x,y+b.y); }
10    point operator-(const point &b)const{
11        return point(x-b.x,y-b.y); }
12    point operator*(const T &b)const{
13        return point(x*b,y*b); }
14    point operator/(const T &b)const{
15        return point(x/b,y/b); }
16    bool operator==(const point &b)const{
17        return x==b.x&&y==b.y; }
18    T dot(const point &b)const{
19        return x*b.x+y*b.y; }
20    T cross(const point &b)const{
21        return x*b.y-y*b.x; }
22    point normal()const{//求法向量
23        return point(-y,x); }
24    T abs2()const{//向量長度的平方
25        return dot(*this); }
26    T rad(const point &b)const{//兩向量的弧度
27    return fabs(atan2(fabs(cross(b)),dot(b))); }
28    T getA()const{//對x軸的弧度
29        T A=atan2(y,x); //超過180度會變負的
30        if(A<=-PI/2)A+=PI*2;
31        return A;
32    }
33 };
34 template<typename T>
35 struct line{
36     line(){ }
37     point<T> p1,p2;
38     T a,b,c;//ax+by+c=0
39     line(const point<T>&x,const point<T>&y):p1(x),p2(y){ }
40     void pton()const{//轉成一般式
41         a=p1.y-p2.y;
42         b=p2.x-p1.x;
43         c=-a*p1.x-b*p1.y;
44     }
45     T ori(const point<T> &p)const{//點和有向直線的關係，>0左
46         //邊、=0在線上<0右邊
47         return (p2-p1).cross(p-p1);
48     }
49     T btw(const point<T> &p)const{//點投影落在線段上<=0
50         return (p1-p).dot(p2-p);
51     }
52     bool point_on_segment(const point<T>&p)const{//點是否在線段
53         //上
54         return ori(p)==0&&btw(p)<=0;
55     }
56     T dis2(const point<T> &p,bool is_segment=0)const{//點跟直線
57         //線段的距離平方
58         point<T> v=p2-p1,v1=p-p1;
59         if(is_segment){
60             point<T> v2=p-p2;
61             if(v.dot(v1)<=0)return v1.abs2();
62             if(v.dot(v2)>=0)return v2.abs2();
63         }
64         T tmp=v.cross(v1);
65         return tmp*tmp/v.abs2();
66     }
67     T seg_dis2(const line<T> &l)const{//兩線段距離平方
68         return min({dis2(l.p1,1),dis2(l.p2,1),l.dis2(p1,1),l.dis2(
69             (p2,1))});
70     }
71     point<T> projection(const point<T> &p)const{//點對直線的投
72         //影
73         point<T> n=(p2-p1).normal();
74         return p-n*(p-p1).dot(n)/n.abs2();
75     }
76     point<T> mirror(const point<T> &p)const{
77         //點對直線的鏡射，要先呼叫pton轉成一般式
78         point<T> R;
79         T d=a*b+b*b;
80         R.x=(b*b*p.x-a*a*p.x-2*a*b*p.y-2*a*c)/d;
81         R.y=(a*a*p.y-b*b*p.y-2*a*b*p.x-2*b*c)/d;
82         return R;
83     }
84     bool equal(const line &l)const{//直線相等
85         return ori(l.p1)==0&&ori(l.p2)==0;
86     }
87     bool parallel(const line &l)const{
88         return (p1-p2).cross(l.p1-l.p2)==0;
89     }
90     bool cross_seg(const line &l)const{
91         return (p2-p1).cross(l.p1-p1)*(p2-p1).cross(l.p2-p1)<=0;
92         //直線是否交線段
93     }
94     int line_intersect(const line &l)const{//直線相交情況，-1無
95         //限多點、1交於一點、0不相交
96         return parallel(l)?(ori(l.p1)==0?-1:0):1;
97     }
98     int seg_intersect(const line &l)const{
99         T c1=ori(l.p1), c2=ori(l.p2);
100        T c3=l.ori(p1), c4=l.ori(p2);
101        if(c1==0&&c2==0){ //共線
102            bool b1=btw(l.p1)>=0,b2=btw(l.p2)>=0;
103            T a3=l.btw(p1),a4=l.btw(p2);
104            if(b1&&b2&&a3==0&&a4>=0) return 2;
105            if(b1&&b2&&a3>=0&&a4==0) return 3;
106            if(b1&&b2&&a3>=0&&a4>=0) return 0;
107            return -1; //無限交點
108        }else if(c1*c2<=0&&c3*c4<=0)return 1;
109        return 0; //不相交
110    }
111    point<T> line_intersection(const line &l)const{//直線交點*
112    point<T> a=p2-p1,b=l.p2-l.p1,s=l.p1-p1;
113    //if(a.cross(b)==0)return INF;
114    return p1+a*(s.cross(b)/a.cross(b));
115    }
116    point<T> seg_intersection(const line &l)const{//線段交點
117    int res=seg_intersect(l);
118    if(res<=0) assert(0);
119    if(res==2) return p1;
120    if(res==3) return p2;
121    return line_intersection(l);
122    }
123    }
124    template<typename T>
125    struct polygon{
126        polygon(){ }
127        vector<point<T>> p;//逆時針順序
128        T area()const{//面積
129            T ans=0;
130            for(int i=p.size()-1,j=0;j<(int)p.size();i=j++){
131                ans+=p[i].cross(p[j]);
132            }
133            return ans/2;
134        }
135        point<T> center_of_mass()const{//重心
136            T cx=0,cy=0,w=0;
137            for(int i=p.size()-1,j=0;j<(int)p.size();i=j++){
138                T a=p[i].cross(p[j]);
139                cx+=(p[i].x+p[j].x)*a;
140                cy+=(p[i].y+p[j].y)*a;
141                w+=a;
142            }
143            return point<T>(cx/3/w,cy/3/w);
144        }
145        char ahas(const point<T>& t)const{//點是否在簡單多邊形內，
146            //是的話回傳1、在邊上回傳-1、否則回傳0
147            bool c=0;
148            for(int i=0,j=p.size()-1;i<p.size();j=i++){
149                if(line<T>(p[i],p[j]).point_on_segment(t))return -1;
150                else if((p[i].y>t.y)&&
151                    t.x<(p[j].x-p[i].x)*(t.y-p[i].y)/(p[j].y-p[i].y)+p[i].x
152                    )
153                    c=!c;
154                return c;
155            }
156        }
157        char point_in_convex(const point<T>&x)const{
158            int l=1,r=(int)p.size()-2;
159            while(l<r){ //點是否在凸多邊形內，是的話回傳1、在邊上回傳
160                // -1、否則回傳0
161                int mid=(l+r)/2;
162                T a1=(p[mid]-p[0]).cross(x-p[0]);
163                T a2=(p[mid+1]-p[0]).cross(x-p[0]);
164                if(a1>=0&&a2<=0){
165                    T res=(p[mid+1]-p[mid]).cross(x-p[mid]);
166                    return res>0?1:(res>0?-1:0);
167                }else if(a1<0)r=mid-1;
168                else l=mid+1;
169            }
170            return 0;
171        }
172        vector<T> getA()const{//凸包邊對x軸的夾角
173        vector<T>res;//一定是遞增的
174        for(size_t i=0;i<p.size();i++){
175            res.push_back((p[(i+1)%p.size()]-p[i]).getA());
176        }
177        return res;
178    }
179    bool line_intersect(const vector<T>&A,const line<T> &l)
180        const{//0(logN)
181        int f1=upper_bound(A.begin(),A.end(),(l.p1-l.p2).getA())-
182            A.begin();
183        int f2=upper_bound(A.begin(),A.end(),(l.p2-l.p1).getA())-
184            A.begin();
185        return l.cross_seg(line<T>(p[f1],p[f2]));
186    }
187    polygon cut(const line<T> &l)const{//凸包對直線切割，得到直
188        //線l左側的凸包

```



```

172 polygon ans;
173 for(int n=p.size(),i=n-1,j=0;j<n;i=j++){
174     if(1.ori(p[i])>=0){
175         ans.p.push_back(p[i]);
176         if(1.ori(p[j])<0)
177             ans.p.push_back(1.line_intersection(line<T>(p[i],p[
178             j])));
179     }else if(1.ori(p[j])>0)
180         ans.p.push_back(1.line_intersection(line<T>(p[i],p[j
181         ])));
182     return ans;
183 }
184 static bool graham_cmp(const point<T>& a,const point<T>& b)
185 {
186     //凸包排序函數
187     return (a.x<b.x)||((a.x==b.x&&a.y<b.y));
188 }
189 void graham(vector<point<T>> &s){//凸包
190     sort(s.begin(),s.end(),graham_cmp);
191     p.resize(s.size()+1);
192     int m=0;
193     for(size_t i=0;i<s.size();++i){
194         while(m>2&&(p[m-1]-p[m-2]).cross(s[i]-p[m-2])<=0)--m;
195         p[m++]=s[i];
196     }
197     for(int i=s.size()-2,t=m+1;i>0;--i){
198         while(m>=t&&(p[m-1]-p[m-2]).cross(s[i]-p[m-2])<=0)--m;
199         p[m++]=s[i];
200     }
201     if(s.size()>1)--m;
202     p.resize(m);
203 }
204 T diam(){//直徑
205     int n=p.size(),t=1;
206     T ans=0;p.push_back(p[0]);
207     for(int i=0;i<n;i++){
208         point<T> now=p[i+1]-p[i];
209         while(now.cross(p[t+1]-p[i])>now.cross(p[t]-p[i]))t=(t
210         +1)%n;
211         ans=max(ans,(p[i]-p[t]).abs2());
212     }
213     return p.pop_back(),ans;
214 }
215 T min_cover_rectangle(){//最小覆蓋矩形
216     int n=p.size(),t=1,r=1,l;
217     if(n<3)return 0;//也可以做最小周長矩形
218     T ans=1e99;p.push_back(p[0]);
219     for(int i=0;i<n;i++){
220         point<T> now=p[i+1]-p[i];
221         while(now.cross(p[t+1]-p[i])>now.cross(p[t]-p[i]))t=(t
222         +1)%n;
223         while(now.dot(p[r+1]-p[i])>now.dot(p[r]-p[i]))r=(r+1)%n;
224         if(!i)l=r;
225         while(now.dot(p[l+1]-p[i])<=now.dot(p[l]-p[i]))l=(l+1)%n;
226         T d=now.abs2();
227         T tmp=now.cross(p[t]-p[i])*(now.dot(p[r]-p[i])-now.dot(
228         p[l]-p[i]))/d;
229         ans=min(ans,tmp);
230     }
231     return p.pop_back(),ans;
232 }
233 T dis2(polygon &p1){//凸包最近距離平方
234     vector<point<T>> &P=p,&Q=p1.p;
235     int n=P.size(),m=Q.size(),l=0,r=0;
236     for(int i=0;i<n;++i)if(P[i].y<P[l].y)l=i;
237     for(int i=0;i<m;++i)if(Q[i].y<Q[r].y)r=i;
238     P.push_back(P[0]),Q.push_back(Q[0]);
239     T ans=1e99;
240     for(int i=0;i<n;++i){
241         while((P[l]-P[l+1]).cross(Q[r+1]-Q[r])<0)r=(r+1)%m;
242         ans=min(ans,line<T>(P[l],P[l+1]).seg_dis2(line<T>(Q[r],
243         Q[r+1])));
244         l=(l+1)%n;
245     }
246     return P.pop_back(),Q.pop_back(),ans;
247 }
248 static char sign(const point<T>&t){
249     return (t.y==0?t.x:t.y)<0;
250 }
251 static bool angle_cmp(const line<T>& A,const line<T>& B){
252     point<T> a=A.p2-A.p1,b=B.p2-B.p1;
253     return sign(a)<sign(b)||((sign(a)==sign(b)&&a.cross(b)>0));
254 }
255 int halfplane_intersection(vector<line<T>> &s){//半平面交
256     sort(s.begin(),s.end(),angle_cmp);//線段左側為該線段半平
257     面
258     int L,R,n=s.size();
259     vector<point<T>> > px(n);
260     vector<line<T>> > q(n);
261     q[L=R=0]=s[0];
262     for(int i=1;i<n;++i){
263         while(L<R&&s[i].ori(px[R-1])<=0)--R;
264         while(L<R&&s[i].ori(px[L])<=0)++L;
265         q[++R]=s[i];
266         if(q[R].parallel(q[R-1])){
267             --R;
268             if(q[R].ori(s[i].p1)>0)q[R]=s[i];
269         }
270         if(L<R)px[R-1]=q[R-1].line_intersection(q[R]);
271     }
272     while(L<R&&q[L].ori(px[R-1])<=0)--R;
273     p.clear();
274     if(R-L<=1)return 0;
275     px[R]=q[R].line_intersection(q[L]);
276     for(int i=L;i<R;++i)p.push_back(px[i]);
277     return R-L+1;
278 }
279 };
280 template<typename T>
281 struct triangle{
282     point<T> a,b,c;
283     triangle(){
284         triangle(const point<T> &a,const point<T> &b,const point<T>
285         &c):a(a),b(b),c(c){}
286     }
287     T area()const{
288         T t=(b-a).cross(c-a)/2;
289         return t>0?t:-t;
290     }
291     point<T> barycenter()const{//重心
292         return (a+b+c)/3;
293     }
294     point<T> circumcenter()const{//外心
295         static line<T> u,v;
296         u.p1=(a+b)/2;
297         u.p2=point<T>(u.p1.x-a.y+b.y,u.p1.y+a.x-b.x);
298         v.p1=(a+c)/2;
299         v.p2=point<T>(v.p1.x-a.y+c.y,v.p1.y+a.x-c.x);
300         return u.line_intersection(v);
301     }
302 }
303 point<T> incenter()const{//內心
304     T A=sqrt((b-c).abs2()),B=sqrt((a-c).abs2()),C=sqrt((a-b).
305     abs2());
306     return point<T>(A*a.x+B*b.x+C*c.x,A*a.y+B*b.y+C*c.y)/(A+B
307     +C);
308 }
309 point<T> perpencenter()const{//垂心
310     return barycenter()*3-circumcenter()*2;
311 }
312 };
313 template<typename T>
314 struct point3D{
315     T x,y,z;
316     point3D(){
317         point3D(const T&x,const T&y,const T&z):x(x),y(y),z(z){}
318     }
319     point3D operator+(const point3D &b)const{
320         return point3D(x+b.x,y+b.y,z+b.z);
321     }
322     point3D operator-(const point3D &b)const{
323         return point3D(x-b.x,y-b.y,z-b.z);
324     }
325     point3D operator*(const T &b)const{
326         return point3D(x*b,y*b,z*b);
327     }
328     point3D operator/(const T &b)const{
329         return point3D(x/b,y/b,z/b);
330     }
331     bool operator==(const point3D &b)const{
332         return x==b.x&&y==b.y&&z==b.z;
333     }
334     T dot(const point3D &b)const{
335         return x*b.x+y*b.y+z*b.z;
336     }
337     point3D cross(const point3D &b)const{
338         return point3D(y*b.z-z*b.y,z*b.x-x*b.z,x*b.y-y*b.x);
339     }
340     T abs2()const{//向量長度的平方
341         return dot(*this);
342     }
343     T area2(const point3D &b)const{//和b、原點圍成面積的平方
344         return cross(b).abs2()/4;
345     }
346 };
347 template<typename T>
348 struct line3D{
349     point3D<T> p1,p2;
350     line3D(){
351         line3D(const point3D<T> &p1,const point3D<T> &p2):p1(p1),p2
352         (p2){}
353     }
354     T dis2(const point3D<T> &p,bool is_segment=0)const{//點跟直
355     線/線段的距離平方
356     point3D<T> v=p2-p1,v1=p-p1;
357     if(is_segment){
358         point3D<T> v2=p-p2;
359         if(v.dot(v1)<=0)return v1.abs2();
360         if(v.dot(v2)>=0)return v2.abs2();
361     }
362     point3D<T> tmp=v.cross(v1);
363     return tmp.abs2()/v.abs2();
364 }
365 pair<point3D<T>,point3D<T>> closest_pair(const line3D<T> &
366 l)const{
367     point3D<T> v1=(p1-p2),v2=(l.p1-l.p2);
368     point3D<T> N=v1.cross(v2),ab(p1-l.p1);
369     //if(N.abs2()==0)return NULL;平行或重合
370     T tmp=N.dot(ab),ans=tmp*tmp/N.abs2();//最近點對距離
371     point3D<T> d1=p2-p1,d2=l.p2-l.p1,D=d1.cross(d2),G=l.p1-p1
372     ;
373     T t1=(G.cross(d2)).dot(D)/D.abs2();
374     T t2=(G.cross(d1)).dot(D)/D.abs2();
375     return make_pair(p1+d1*t1,l.p1+d2*t2);
376 }

```



```

349 bool same_side(const point3D<T> &a, const point3D<T> &b)
350     const{
351         return (p2-p1).cross(a-p1).dot((p2-p1).cross(b-p1))>0;
352     };
353 template<typename T>
354 struct plane{
355     point3D<T> p0,n; //平面上的點和法向量
356     plane(){
357         plane(const point3D<T> &p0, const point3D<T> &n):p0(p0),n(n)
358     }
359     T dis2(const point3D<T> &p) const { //點到平面距離的平方
360         T tmp=(p-p0).dot(n);
361         return tmp*tmp/n.abs2();
362     }
363     point3D<T> projection(const point3D<T> &p) const {
364         return p-n*(p-p0).dot(n)/n.abs2();
365     }
366     point3D<T> line_intersection(const line3D<T> &l) const {
367         T tmp=n.dot(l.p2-l.p1); //等於0表示平行或重合該平面
368         return l.p1+(l.p2-l.p1)*(n.dot(p0-l.p1)/tmp);
369     }
370     line3D<T> plane_intersection(const plane &p1) const {
371         point3D<T> e=n.cross(p1.n),v=n.cross(e);
372         T tmp=p1.n.dot(v); //等於0表示平行或重合該平面
373         point3D<T> q=p0+(v*(p1.n.dot(p1.p0-p0))/tmp);
374         return line3D<T>(q,q+e);
375     }
376 };
377 template<typename T>
378 struct triangle3D{
379     point3D<T> a,b,c;
380     triangle3D(){
381         triangle3D(const point3D<T> &a, const point3D<T> &b, const
382             point3D<T> &c):a(a),b(b),c(c){}
383     }
384     bool point_in(const point3D<T> &p) const { //點在該平面上的投
385         影在三角形中
386         return line3D<T>(b,c).same_side(p,a)&&line3D<T>(a,c).
387             same_side(p,b)&&line3D<T>(a,b).same_side(p,c);
388     }
389 };
390 template<typename T>
391 struct tetrahedron{ //四面體
392     point3D<T> a,b,c,d;
393     tetrahedron(){
394         tetrahedron(const point3D<T> &a, const point3D<T> &b, const
395             point3D<T> &c, const point3D<T> &d):a(a),b(b),c(c),d(d)
396     }
397     T volume6() const { //體積的六倍
398         return (d-a).dot((b-a).cross(c-a));
399     }
400     point3D<T> centroid() const {
401         return (a+b+c+d)/4;
402     }
403     bool point_in(const point3D<T> &p) const {
404         return triangle3D<T>(a,b,c).point_in(p)&&triangle3D<T>(c,
405             d,a).point_in(p);
406     }
407 };
408 template<typename T>
409 struct convexhull3D{
410     static const int MAXN=1005;
411     struct face{
412         int a,b,c;

```

```

405     face(int a,int b,int c):a(a),b(b),c(c){}
406 };
407 vector<point3D<T>> pt;
408 vector<face> ans;
409 int fid[MAXN][MAXN];
410 void build(){
411     int n=pt.size();
412     ans.clear();
413     memset(fid,0,sizeof(fid));
414     ans.emplace_back(0,1,2); //注意不能共線
415     ans.emplace_back(2,1,0);
416     int ftop = 0;
417     for(int i=3; ftop=1; i<n; ++i, ++ftop){
418         vector<face> next;
419         for(auto &f:ans){
420             T d=(pt[i]-pt[f.a]).dot((pt[f.b]-pt[f.a]).cross(pt[f.
421                 c]-pt[f.a]));
422             if(d<=0) next.push_back(f);
423             int ff=0;
424             if(d>0) ff=ftop;
425             else if(d<0) ff=-ftop;
426             fid[f.a][f.b]=fid[f.b][f.c]=fid[f.c][f.a]=ff;
427         }
428         for(auto &f:ans){
429             if(fid[f.a][f.b]>0 && fid[f.a][f.b]!=fid[f.b][f.a])
430                 next.emplace_back(f.a,f.b,i);
431             if(fid[f.b][f.c]>0 && fid[f.b][f.c]!=fid[f.c][f.b])
432                 next.emplace_back(f.b,f.c,i);
433             if(fid[f.c][f.a]>0 && fid[f.c][f.a]!=fid[f.a][f.c])
434                 next.emplace_back(f.c,f.a,i);
435         }
436         ans=next;
437     }
438     point3D<T> centroid() const {
439         point3D<T> res(0,0,0);
440         T vol=0;
441         for(auto &f:ans){
442             T tmp=pt[f.a].dot(pt[f.b].cross(pt[f.c]));
443             res=res+(pt[f.a]+pt[f.b]+pt[f.c])*tmp;
444             vol+=tmp;
445         }
446         return res/(vol*4);
447     }
448 };

```

8.2 旋轉卡尺

```

1 typedef pair<ll, ll> pii;
2 #define x first
3 #define y second
4 #define ii (i + 1) % n // 打字加速!
5 inline pii operator-(const pii& a, const pii& b) {
6     return {a.x - b.x, a.y - b.y};
7 } // const 不可省略
8 inline ll operator*(const pii& a, const pii& b) {
9     return a.x * b.y - a.y * b.x;
10 }
11 inline ll crzf(const pii& o, const pii& a, const pii& b) {
12     return (a - o) * (b - o)
13 }
14 inline ll dd(const pii& a, const pii& b) {

```

```

15     ll dx = a.x - b.x, dy = a.y - b.y;
16     return dx * dx + dy * dy;
17 }
18 // 給平面上任意個點，求其凸包。返回順序為逆時針。此方法會移除
19 // 重複點。
20 #define jud \
21     crzf(ret[ret.size() - 2], ret.back(), pp[i]) <= 0
22 vector<pii> makepoly(vector<pii>& pp) {
23     int n = pp.size();
24     sort(pp.begin(), pp.end());
25     pp.erase(unique(pp.begin(), pp.end()), pp.end());
26     vector<pii> ret;
27     for (int i = 0; i < n; i++) {
28         while (ret.size() >= 2 && jud) ret.pop_back();
29         ret.push_back(pp[i]);
30     }
31     for (int i = n - 2, t = ret.size() + 1; i >= 0; i--) {
32         while (ret.size() >= t && jud) ret.pop_back();
33         ret.push_back(pp[i]);
34     }
35     if (n >= 2) ret.pop_back();
36     return ret;
37 }
38 // (shoelace formula)
39 // 給凸包，問其面積「的兩倍」。若凸包少於三個點，回傳零。
40 ll area(vector<pii>& poly) {
41     int n = poly.size();
42     ll ret = 0;
43     for (int i = 0; i < n; i++)
44         ret += (poly[i].x * poly[i+1].y);
45     for (int i = 0; i < n; i++)
46         ret -= (poly[i].y * poly[i+1].x);
47     return ret;
48 }
49 // 給凸包，問其兩點最遠距離「的平方」。若要問平面上任意個點的
50 // 兩點最遠
51 // 距離，請先轉成凸包。若凸包少於兩個點，回傳零。
52 #define kk (k + 1) % n
53 ll maxdist(vector<pii>& poly) {
54     int k = 1, n = poly.size();
55     if (n < 2) return 0;
56     if (n == 2) return dd(poly[0], poly[1]);
57     ll ret = 0;
58     for (int i = 0; i < n; i++) {
59         while (abs(crzf(poly[kk], poly[i], poly[ii])) >=
60             abs(crzf(poly[k], poly[i], poly[ii])))
61             k = kk;
62         ret = max(ret, max(dd(poly[i], poly[k]),
63             dd(poly[ii], poly[k])));
64     }
65     return ret;
66 }

```

8.3 最近點對

```

1 typedef pair<ll, ll> pii;
2 #define x first
3 #define y second
4 ll dd(const pii& a, const pii& b) {
5     ll dx = a.x - b.x, dy = a.y - b.y;
6     return dx * dx + dy * dy;
7 }

```

```

8 const ll inf = 1e18;
9 ll dac(vector<pii>& p, int l, int r) {
10     if (l >= r) return inf;
11     int m = (l + r) / 2;
12     ll d = min(dac(p, l, m), dac(p, m + 1, r));
13     vector<pii> t;
14     for (int i = m; i >= l && p[m].x - p[i].x < d; i--)
15         t.push_back(p[i]);
16     for (int i = m + 1; i <= r && p[i].x - p[m].x < d; i++)
17         t.push_back(p[i]);
18     sort(t.begin(), t.end());
19     for (pii& a, pii& b) { return a.y < b.y; };
20     int n = t.size();
21     for (int i = 0; i < n - 1; i++)
22         for (int j = 1; j < 4 && i + j < n; j++)
23             // 這裡可以知道是哪兩點是最小點對
24             d = min(d, dd(t[i], t[i + j]));
25     return d;
26 }
27 // 給一堆點，求最近點對的距離「的平方」。
28 ll closest_pair(vector<pii>& pp) {
29     sort(pp.begin(), pp.end());
30     return dac(pp, 0, pp.size() - 1);
31 }

```

8.4 最小覆蓋圓

```

1 using PT = point<T>;
2 using CPT = const PT;
3 PT circumcenter(CPT &a, CPT &b, CPT &c) {
4     PT u = b - a, v = c - a;
5     T c1 = u.abs2()/2, c2 = v.abs2()/2;
6     T d = u.cross(v);
7     return PT(a.x + (v.y*c1 - u.y*c2)/d, a.y + (u.x*c2 - v.x*c1)/d);
8 }
9 void solve(PT p[], int n, PT &c, T &r2){
10     random_shuffle(p, p+n);
11     c = p[0]; r2 = 0; // c, r2 = 圓心, 半徑平方
12     for(int i=1; i<n; i++)
13         if( (p[i]-c).abs2() > r2) {
14             c=p[i]; r2=0;
15             for(int j=0; j<i; j++)
16                 if( (p[j]-c).abs2() > r2) {
17                     c.x = (p[i].x+p[j].x)/2;
18                     c.y = (p[i].y+p[j].y)/2;
19                     r2 = (p[j]-c).abs2();
20                     for(int k=0; k<j; k++)
21                         if( (p[k]-c).abs2() > r2) {
22                             c = circumcenter(p[i], p[j], p[k]);
23                             r2 = (p[i]-c).abs2();
24                         }
25                 }
26         }
27 }

```

8.5 Rectangle Union Area

```

1 const int maxn = 1e5 + 10;
2 struct rec{

```

```

3     int t, b, l, r;
4 } r[maxn];
5 int n, cnt[maxn << 2];
6 long long st[maxn << 2], ans = 0;
7 vector<int> x, y;
8 vector<pair<pair<int, int>, pair<int, int>>> v;
9 void modify(int t, int l, int r, int ql, int qr, int v) {
10     if (ql <= l && r <= qr) cnt[t] += v;
11     else {
12         int m = (l + r) >> 1;
13         if (qr <= m) modify(t << 1, l, m, ql, qr, v);
14         else if (ql >= m) modify(t << 1 | 1, m, r, ql, qr, v);
15         else modify(t << 1, l, m, ql, m, v), modify(t << 1 | 1, m, r, m, qr, v);
16     }
17     if (cnt[t]) st[t] = y[r] - y[l];
18     else if (r - l == 1) st[t] = 0;
19     else st[t] = st[t << 1] + st[t << 1 | 1];
20 }
21 int main() {
22     cin >> n;
23     for (int i = 0; i < n; i++) {
24         cin >> r[i].l >> r[i].r >> r[i].b >> r[i].t;
25         if (r[i].l > r[i].r) swap(r[i].l, r[i].r);
26         if (r[i].b > r[i].t) swap(r[i].b, r[i].t);
27         x.push_back(r[i].l);
28         x.push_back(r[i].r);
29         y.push_back(r[i].b);
30         y.push_back(r[i].t);
31     }
32     sort(x.begin(), x.end());
33     sort(y.begin(), y.end());
34     x.erase(unique(x.begin(), x.end()), x.end());
35     y.erase(unique(y.begin(), y.end()), y.end());
36     for (int i = 0; i < n; i++) {
37         r[i].l = lower_bound(x.begin(), x.end(), r[i].l) - x.begin();
38         r[i].r = lower_bound(x.begin(), x.end(), r[i].r) - x.begin();
39         r[i].b = lower_bound(y.begin(), y.end(), r[i].b) - y.begin();
40         r[i].t = lower_bound(y.begin(), y.end(), r[i].t) - y.begin();
41         v.emplace_back(make_pair(r[i].l, 1), make_pair(r[i].b, r[i].t));
42         v.emplace_back(make_pair(r[i].r, -1), make_pair(r[i].b, r[i].t));
43     }
44     sort(v.begin(), v.end(), [](pair<pair<int, int>, pair<int, int>> a, pair<pair<int, int>, pair<int, int>> b){
45         if (a.first.first != b.first.first) return a.first.first < b.first.first;
46         return a.first.second > b.first.second;
47     });
48     for (int i = 0; i < v.size(); i++) {
49         if (i) ans += (x[v[i].first.first] - x[v[i - 1].first.first]) * st[1];
50         modify(1, 0, y.size(), v[i].second.first, v[i].second.second, v[i].first.second);
51     }
52     cout << ans << '\n';
53     return 0;
54 }

```

9 Other

9.1 Fastio

```

1 inline ll read(){
2     ll x=0,f=0;
3     char ch = getchar();
4     if(ch==EOF)
5         return 0;
6     while(ch<'0' || ch>'9') f|=ch=='-',ch=getchar();
7     while(ch>='0' && ch<='9') x=(x<<3)+(x<<1)+(ch^48),ch=getchar();
8     return f?-x:x;
9 }
10
11 inline void print(ll x, bool bk = false) {
12     if(x<0){
13         putchar('-');
14         x = -x;
15     }
16     if(x==0){
17         if(!bk) putchar('0');
18         return;
19     }
20     print(x/10, true);
21     putchar((x-10*(x/10))^'0');
22 }

```

9.2 pbds

```

1 #include<bits/extc++.h>
2 using namespace __gnu_pbds;
3
4 // hash_table : 用法和map差不多 //均攤O(1)
5 gp_hash_table <string, int> mp;
6 mp.find(); mp[];
7 mp.insert(make_pair())
8
9 // heaps
10 priority_queue<int, greater<int>, TAG> Q;
11 /*
12 Tag          | push | pop | join | modify |
13 pairing_heap_tag | O(1) | O(lgN) | O(1) | O(lgN) |
14 thin_heap_tag   | O(lgN) | O(lgN) | 慢 | 慢 |
15 binomial_heap_tag | O(1) | O(lgN) | O(lgN) | O(lgN) |
16 rc_binomial_heap_tag | O(1) | O(lgN) | O(lgN) | O(lgN) |
17 binary_heap_tag  | O(1) | O(lgN) | 慢 | O(lgN) |
18 */
19 //可以用迭代器遍歷
20 Q.push(x); Q.pop(); Q.top();
21 Q.join(b); //merge two heap
22 Q.empty(); Q.size();
23 Q.modify(it, 6); Q.erase(it);
24
25 // k-th
26 typedef tree<int, null_type, less<int>, rb_tree_tag,
27     tree_order_statistics_node_update> set_t;
28 set_t s; s.insert(12); s.insert(505);
29 assert(*s.find_by_order(0) == 12);
30 assert(*s.find_by_order(3) == 505);
31 assert(s.order_of_key(12) == 0);

```

```

31 assert(s.order_of_key(505) == 1);
32 s.erase(12);
33 assert(*s.find_by_order(0) == 505);
34 assert(s.order_of_key(505) == 0);

```

9.3 BuiltIn

```

1 //gcc專用
2 //unsigned int ffs
3 //unsigned long ffs1
4 //unsigned long long ffs11
5 unsigned int x; scanf("%u",&x)
6 printf("右起第一個1:的位置");
7 printf("%d\n",__builtin_ffs(x));
8 printf("左起第一個1之前0的個數:");
9 printf("%d\n",__builtin_clz(x));
10 printf("右起第一個1之後0的個數:");
11 printf("%d\n",__builtin_ctz(x));
12 printf("1的個數:");
13 printf("%d\n",__builtin_popcount(x));
14 printf("1的個數的奇偶性:");
15 printf("%d\n",__builtin_parity(x));

```

9.4 莫隊算法-區間眾數

```

1 using namespace std;
2 const int maxn = 1e6 + 10;
3 struct query { int id, bk, l, r; };
4 int arr[maxn], cnt[maxn], d[maxn], n, m, bk, mx;
5 pair<int,int> ans[maxn];
6 vector<query> q;
7 bool cmp(query x, query y) {
8     return (x.bk < y.bk || (x.bk == y.bk) && x.r < y.r);
9 }
10 void add(int pos) {
11     d[cnt[arr[pos]]]--;
12     cnt[arr[pos]]++;
13     d[cnt[arr[pos]]]++;
14     if(d[mx + 1] > 0) mx++;
15 }
16 void del(int pos) {
17     d[cnt[arr[pos]]]--;
18     cnt[arr[pos]]--;
19     d[cnt[arr[pos]]]++;
20     if(d[mx] == 0) mx--;
21 }
22 void mo(int n, int m) {
23     sort(q.begin(), q.end(), cmp);
24     for(int i = 0, cl = 1, cr = 0; i < m; i++) {
25         while(cr < q[i].r) add(++cr);
26         while(cl > q[i].l) add(--cl);
27         while(cr > q[i].r) del(cr--);
28         while(cl < q[i].l) del(cl++);
29         ans[q[i].id] = make_pair(mx, d[mx]);
30     }
31 }
32 int main(){
33     cin >> n >> m;
34     bk = (int)sqrt(n + 0.5);

```

```

35     for(int i = 1; i <= n; i++) cin >> arr[i];
36     q.resize(m);
37     for(int i = 0; i < m; i++) {
38         cin >> q[i].l >> q[i].r;
39         q[i].id = i, q[i].bk = (q[i].l - 1) / bk;
40     }
41     mo(n, m);
42     for(int i = 0; i < m; i++)
43         cout << ans[i].first << ' ' << ans[i].second << '\n';
44     return 0;
45 }

```

9.5 CNF

```

1 #define MAXN 55
2 struct CNF{
3     int s,x,y; //s->xy | s->x, if y==1
4     int cost;
5     CNF(){}
6     CNF(int s,int x,int y,int c):s(s),x(x),y(y),cost(c){}
7 };
8 int state;//規則數量
9 map<char,int> rule;//每個字元對應到的規則，小寫字母為終端字符
10 vector<CNF> cnf;
11 void init(){
12     state=0;
13     rule.clear();
14     cnf.clear();
15 }
16 void add_to_cnf(char s,const string &p,int cost){
17     //加入一個s -> <p>的文法，代價為cost
18     if(rule.find(s)==rule.end())rule[s]=state++;
19     for(auto c:p)if(rule.find(c)==rule.end())rule[c]=state++;
20     if(p.size()==1){
21         cnf.push_back(CNF(rule[s],rule[p[0]],-1,cost));
22     }else{
23         int left=rule[s];
24         int sz=p.size();
25         for(int i=0;i<sz-2;++i){
26             cnf.push_back(CNF(left,rule[p[i]],state,0));
27             left=state++;
28         }
29         cnf.push_back(CNF(left,rule[p[sz-2]],rule[p[sz-1]],cost));
30     }
31 }
32 vector<long long> dp[MAXN][MAXN];
33 vector<bool> neg_INF[MAXN][MAXN]; //如果花費是負的可能會有無限
34     小的情形
35 void relax(int l,int r,const CNF &c,long long cost,bool neg_c
36     =0){
37     if(!neg_INF[l][r][c.s]&&(neg_INF[l][r][c.x]||cost<dp[l][r][
38         c.s])){
39         if(neg_c||neg_INF[l][r][c.x]){
40             dp[l][r][c.s]=0;
41             neg_INF[l][r][c.s]=true;
42         }else dp[l][r][c.s]=cost;
43     }
44 }
45 void bellman(int l,int r,int n){
46     for(int k=1;k<=state;++k)
47         for(auto c:cnf)

```

```

45         if(c.y==1)relax(l,r,c,dp[l][r][c.x]+c.cost,k==n);
46     }
47 void cyk(const vector<int> &tok){
48     for(int i=0;i<(int)tok.size();++i){
49         for(int j=0;j<(int)tok.size();++j){
50             dp[i][j]=vector<long long>(state+1,INT_MAX);
51             neg_INF[i][j]=vector<bool>(state+1,false);
52         }
53         dp[i][i][tok[i]]=0;
54         bellman(i,i,tok.size());
55     }
56     for(int r=1;r<(int)tok.size();++r){
57         for(int l=r-1;l>=0;--l){
58             for(int k=1;k<r;++k)
59                 for(auto c:cnf)
60                     if(~c.y)relax(l,r,c,dp[l][k][c.x]+dp[k+1][r][c.y]+c
61                         .cost);
62             bellman(l,r,tok.size());
63         }
64     }
65 }

```

9.6 提醒事項

```

1 Debug List:
2 1. Long Long !!
3 2. python3 整數除法 "/"
4 3. connected / unconnected
5 4. 範圍看清楚
6 5. eps夠小嗎!!
7 -----
8 Lucas's Theorem
9     For non-negative integer n,m and prime P,
10      $C(m,n) \bmod P = C(m/M,n/M) * C(m\%M,n\%M) \bmod P$ 
11     = mult_i ( C(m_i,n_i) )
12     where m_i is the i-th digit of m in base P.
13 -----
14 Kirchhoff's theorem
15  $A_{ii} = \deg(i), A_{ij} = (i,j) \text{ \in E ? } -1 : 0$ 
16 Deleting any one row, one column, and cal the det(A)
17 -----
18 Nth Catalan recursive function:
19  $C_0 = 1, C_{n+1} = C_n * 2(2n + 1)/(n+2)$ 
20 -----
21 Mobius Formula
22  $u(n) = 1$  , if  $n = 1$ 
23  $(-1)^m$  , 若  $n$  無平方數因數，且  $n = p_1 * p_2 * p_3 * \dots * p_k$ 
24  $0$  , 若  $n$  有大於 1 的平方數因數
25 - Property
26 1. (積性函數)  $u(a)u(b) = u(ab)$ 
27 2.  $\sum_{d|n} u(d) = [n == 1]$ 
28 -----
29 Mobius Inversion Formula
30 if  $f(n) = \sum_{d|n} g(d)$ 
31 then  $g(n) = \sum_{d|n} u(n/d)f(d)$ 
32         =  $\sum_{d|n} u(d)f(n/d)$ 
33 - Application
34 the number/power of gcd(i, j) = k
35 - Trick
36 分塊,  $O(\sqrt{n})$ 
37 -----
38 Chinese Remainder Theorem (m_i 兩兩互質)

```

```

39  x = a_1 (mod m_1)
40  x = a_2 (mod m_2)
41  ....
42  x = a_i (mod m_i)
43  construct a solution:
44  Let M = m_1 * m_2 * m_3 * ... * m_n
45  Let M_i = M / m_i
46  t_i = 1 / M_i
47  t_i * M_i = 1 (mod m_i)
48  solution x = a_1 * t_1 * M_1 + a_2 * t_2 * M_2 + ... + a_n
               * t_n * M_n + k * M
49  = k*M +  $\sum a_i * t_i * M_i$ , k is positive integer.
50  under mod M, there is one solution x =  $\sum a_i * t_i * M_i$ 
51  -----
52  Burnside's lemma
53   $|G| * |X/G| = \sum (|X^g|)$  where g in G
54  總方法數：每一種旋轉下不動點的個數總和 除以 旋轉的方法數
55  -----
56  Linear Algebra
57  trace : tr(A) = 對角線和
58  eigen vector :  $Ax = cx \Rightarrow (A - cI)x = 0$ 
59  -----
60  Josephus Problem
61   $f(n,k) = (f(n-1,k)+k) \pmod n$ 
62   $f(1,k) = 0$ 

```

NTHU-
ELEPHANTGANG

CODEBOOK

Contents