



| REV. | ECN NO | DESCRIPTION | D.B | DATE |
|------|--------|---------------------|--------|----------|
| P0 | | PRELIMINARY RELEASE | Harvey | 19.12.02 |
| | | | | |

PRELIMINARY RELEASE
DATE: 19-12-02

NOTES:

1.ELECTRONIC TEST:

- 1.1.OPEN/SHORT/INTERMITTENCE: 100%.
- 1.2.HI-POT: 300V AC/0.01sec 300V DC/0.01sec
- 1.3.INSULATION RESISTANCE: 10M ohm(MIN)
- 1.4.CONDUCTIVE RESISTANCE: 2 ohm(MAX)

2.CHECK IMPORTANT SIZE Y1-Y2

PIN OUT

| CN1 | | CN2 |
|-----|-------|-----|
| 2 | BLACK | 3 |
| 3 | BROWN | 2 |
| 5 | RED | 5 |

| | | | | |
|-----|-------|---|------|------|
| ⑥ | PVC | V398 45P,BLACK | A/R | KG |
| ⑤ | PE | LD-PE,NATURE | A/R | KG |
| ④ | SCREW | BIG E4*23.5MM #4-40UNC NICKLE PLATED COLOR:BLACK | 4 | PCS |
| ③ | CONN. | RJ45 8P8C PLUG PIN G/F NATURE | 1 | PCS |
| ② | CONN. | DB9P FEMALE INSULATOR BLACK NICKEL PLATED SHELL PIN G/F | 1 | PCS |
| ① | CABLE | UL2464 26AWG*3C+AL OD: 4.0±0.15mm PVC BLACK | A/R | M |
| NO. | NAME | MATERIAL DESCRIPTION | Q'TY | UNIT |

| | | | | | | | |
|------------|--|--------------|--|---|--|---------------|--|
| RoHS | | | | GREATCHINACOM HI-TECH CO.,LTD DONGGUAN FEITAI ELECTRONIC CO.,LTD | | | |
| TOLERANCE | | Approved by: | | Customer P/N: | | | |
| X. ±0.5 | | Qingguo | | | | | |
| .X ±0.3 | | Checked by: | | FEITAI P/N: | | | |
| .XX ±0.15 | | Qingguo | | | | | |
| X* ±2° | | Drawn by: | | Description: | | | |
| .X* ±1° | | Harvey | | DB9P F TO RJ45 8P8C M | | | |
| .XX* ±0.5° | | Date: | | 19.12.02 | | DWG. NO: | |
| | | Scale: 1:1 | | Unit: mm | | SHEET: 1 OF 1 | |
| | | | | | | REV:P0 | |