

Formalizing AMR Inference via Hybrid Logic Tableaux

CL Masters Thesis Defense

Eli Goldner

July 28, 2021

Introduction

- ▶ Semantic representation:
 - ▶ Capture meaning of natural language content.
 - ▶ Designed for manipulation via software.
- ▶ Abstract Meaning Representation (AMR):
 - ▶ Graph-based (DAG), nodes are *concepts*, edges are *relations*.
 - ▶ Built on predicative core of a sentence.
 - ▶ Ignores syntactic differences between equivalent sentences.
 - ▶ PropBank framesets are used for concepts (entities, events, properties, states).

Introduction

(Basic) AMR is reductionistic. This is awesome for:

- ▶ Annotation (esp. by non-experts).
- ▶ Semantic parsing (smaller target space).

This is not awesome for:

- ▶ Representing and recovering fine-grained meaning.
- ▶ Automating reasoning/inference.

Introduction

- ▶ The trade-off between ease of generation/use and rich expressivity/inferentiability is at least as old as computing.
- ▶ AMR has made a choice that works well in data-driven NLP.
- ▶ However AMR can bridge this gap:
- ▶ AMR already does this in a modular way with extensions.
- ▶ Some of these extensions give afford interpretation in first-order logic:
 - ▶ Automated inference for logics is a rich area with lots of tools.
 - ▶ This is where we come in.

Motivation

“Why do we need formal methods? Can’t state-of-the-art language models do this already?”

Short answer: Not really, and even if they could:

- ▶ Statistically driven techniques are unnecessarily expensive for formal inference.
- ▶ Increasing need for ability to guarantee/verify properties of software:
 - ▶ Does the software give us the right *type* of result for an input?
 - ▶ Bias in NLP.
- ▶ Machine learning (by itself) does not lend itself well to this.
- ▶ Hybrid systems and explainable AI.

Approach

AMR with Tense and Aspect

AMR with Scope

Modal Logic

- ▶ Propositional logic lets us form statements like $p \wedge (q \vee \neg r)$.
- ▶ Modal propositional logic extends propositional logic with an operator \Diamond , read as “possible”. i.e. it is not possible that p and $\neg p$ are the case would be:

$$\neg \Diamond(p \wedge \neg p)$$

- ▶ (More) formal meaning of \Diamond : There is a *possible world* where p is true, and this possible world is *accessible* from the current one.
- ▶ The problem: the “current world” is an implicit notion dependent on context. Is there something more expressive?


Hybrid Logic

- ▶ Idea: take propositional modal logic, and add an operator @, that lets us know which world we're referring to.
- ▶ p or r is possible at world i : $@_i \Diamond(p \vee r)$
- ▶ In the above proposition i is called a nominal since it *names*/uniquely picks out some world.
- ▶ Everything true at the world j is true at the world i (they name the same world): $@_{ij}$

Hybrid Logic Variants

First-Order Hybrid Tense Logic

FHTL Tableau Example

(1)	
(2)	$@_s(\exists x)[P((\exists y)[f(x, y) = f(y, x)]) \vee \neg(\exists z)[x = z]]$
(3)	$@_sP((\exists y)[f(s_1, y) = f(y, s_1)]) \vee \neg(\exists z)[s_1 = z]$
	
(4)	$@_sP((\exists y)[f(s_1, y) = f(y, s_1)])$
(5)	$@_s\neg(\exists z)[s_1 = z]$
(6)	$@_sPt$
(7)	$@_s\neg[s_1 = s_1]$
	$@_t(\exists y)[f(s_1, y) = f(y, s_1)]$
	$@_s[s_1 = s_1]$
	\dots
	\otimes

Model Checking Example

- *Every computer will be located at a desk.*

- AMR with quantification and tense:

```
(s / scope
  :pred (b / be-located-at-91 :ongoing -
                                :complete +
                                :time (a / after
                                          :op1 (n / now))
  :ARG0 (c / computer)
  :ARG1 (d / desk
          :quant (e / every)))
:ARG0 d
:ARG1 c)
```

- *FHTL* translation:

$$@_{now}(\forall y)[desk(y) \rightarrow (\exists x)[computer(x) \wedge F(be-located-at-91(x, y))]]$$

Model Checking Example

Define a small *FHTL* model $\mathfrak{M} = (T, \mathcal{R}, (D_t)_{t \in T}, I_{nom}, (I_t)_{t \in T})$ where:

$$T = \{\text{yesterday}, \text{now}, \text{tomorrow}\}$$

$$\mathcal{R} = \{(\text{yesterday}, \text{now}), (\text{now}, \text{tomorrow}), (\text{yesterday}, \text{tomorrow})\}$$

$$I_{nom} = \{(y, \text{yesterday}), (n, \text{now}), (t, \text{tomorrow})\}$$

$$D_{\text{yesterday}} = \{\text{computer}_1, \text{desk}_1\}$$


$$D_{\text{now}} = \{\text{computer}_1, \text{computer}_2, \text{desk}_1, \text{desk}_2, \text{desk}_3\}$$

$$D_{\text{tomorrow}} = \{\text{computer}_1, \text{computer}_2, \text{desk}_1, \text{desk}_2\}$$

Model Checking Example

$$@_n(\forall y)[\text{desk}(y) \rightarrow (\exists x)[\text{computer}(x) \wedge F(\text{located}(x, y))]]$$

$$@_n\text{desk}(n:p_1) \rightarrow (\exists x)[\text{computer}(x) \wedge F(\text{located}(x, n:p_1))]$$



Where we assign $s = t = \text{tomorrow}$, $n:p_2 = \text{computer}_1$ and $n:p_1 = \text{desk}_2$, or $n:p_2 = \text{computer}_2$ and $n:p_1 = \text{desk}_1$ we see that \mathfrak{M} satisfies the *FHTL* sentence.

Extraction

Interpretation

References I