

# Formalization of AMR Inference via Hybrid Logic Tableaux

Eli Goldner

July 23, 2021

## Abstract

AMR and its extensions have become popular in semantic representation due to their ease of annotation by non-experts, attention to the predicative core of sentences, and abstraction away from various syntactic matter. An area where AMR and its extensions warrant improvement is formalization and suitability for inference, where it is lacking compared to other semantic representations, such as description logics, episodic logic, and discourse representation theory. This thesis presents a formalization of inference over a merging of Donatelli et al.’s (2018) AMR extension for tense and aspect and with Pustejovsky et al.’s (2019) AMR extension for quantification and scope. Inference is modeled with a merging of Hansen’s (2007) tableau method for first-order hybrid logic with varying domain semantics (*FHL*) and Blackburn and Jørgensen’s (2012) tableau method for basic hybrid tense logic (*BHTL*). We motivate the merging of these AMR variants, present their interpretation and inference in the combination of *FHL* and *BHTL*, which we will call *FHTL* (first-order hybrid tense logic), and demonstrate *FHTL*’s soundness, completeness, and decidability for finite model checking.

## 1 Introduction

Version 1.2 of the AMR specification states that an AMR does not indicate how it should be processed (?). Indeed, besides concepts that can be interpreted as propositional connectives like `:and`, `:or`, and `:cond`, there is little that can be directly inferred from a basic AMR besides possibly lexical inference on the concepts and relations, and performing lexical inference directly would require extensive hand authoring of relationships between PropBank frames. Pustejovsky et al. (2019) makes direct inference on AMR significantly easier by providing an unambiguous way to interpret an AMR that makes use of quantification, negation, or modality, while retaining the predicative core of AMR. Donatelli et al. (2018) extends AMR with a treatment of tense and aspect which allows for direct inference involving temporal information.

## 2 Related Work

### 2.1 Semantic Features in AMR and Possibility of Inference

Separating argument structure in AMR from logical structure, enables translation from AMR to DRT (Bos, 2020)

AMR expressivity without recurrent variables (and with no more than one universal quantifier per sentence) are in the decidable two-variable fragment of first-order logic (Bos, 2016)

Extension of sentential AMR to incorporate a coarse grained treatment of tense and aspect (Donatelli et al., 2018)

Continuation based semantics for translating AMR into first-order logic in a way that preserves projection phenomena such as quantification, negation, bound variables, and donkey anaphora, which better affords inference than other first-order logic semantics for AMR (Lai et al., 2020). This uses a neo-davidsonian representation for the target first-order logic semantics.

### 2.2 Hybrid Logic and Semantics

Hybrid logic is an extension of the propositional modal logic  $K$  ( $K$  has no conditions on the modal frame of its underlying models) allowing for explicit reference to modal states/worlds through a prefix notation. Where ordinary modal logic writes  $\Diamond p$  to indicate that there is some world where  $p$  holds at some world accessible from that world, hybrid logic by default writes one of  $a\Diamond p$ ,  $a:\Diamond p$ , or  $@_a\Diamond p$  (we use the latter notation from here on), to indicate  $p$  holds at some world accessible from  $a$  specifically.  $a$  in this notation is a *nominal*, which uniquely names a world in the underlying model. A *world* in a modal or hybrid model for us is essentially just a maximal set of sentences in the language, that is for any proposition  $p$  and nominal  $a$  we have either  $@_ap$  or  $@_a\neg p$ . Worlds

are used to model any notion consistent with it, usually possible states of affairs, in particular we will use them to describe states of affairs at different points in time.

### 3 Merging Quantified Hybrid Logic and Indexical Hybrid Tense Logic

#### 3.1 First-order Hybrid Logic

First-order modal logic (or quantified modal logic / QML) extends first-order predicate logic in a way analogous to how propositional modal logic extends first order propositional logic. An introduction to both QML and propositional modal logic can be found in Fitting and Mendelsohn (1998). Hansen (2007)

from  
Blackburn and Marx (2002)

#### 3.2 Basic Hybrid Tense Logic

Blackburn and Jørgensen (2012)

### 4 First-order Hybrid Tense Logic - Syntax and Semantics

The syntax of *FHTL* is identical to *FHL* as given in Hansen (2007) except uses of  $\downarrow$  as in  $\downarrow w.\varphi$  are omitted along with  $\Box$  and  $\Diamond$  as in  $\Box\varphi$  and  $\Diamond\varphi$ .  $\Box$  and  $\Diamond$  are replaced by their semantic equivalents  $F$  and  $G$  and their temporal duals  $P$  and  $H$  are added.

Atomic formulae are the same as in *FHL*, symbols in *NOM* and *SVAR* together with first-order atomic formulae generated from the predicate symbols and equality over the terms. Thus complex formulae are generated from the atomic formulae according to the following rules:

$$\neg\varphi \mid \varphi \wedge \psi \mid \varphi \vee \psi \mid \varphi \rightarrow \psi \mid \exists x\varphi \mid \forall x\varphi \mid F\varphi \mid G\varphi \mid P\varphi \mid H\varphi \mid @_n\varphi$$

Since we want the domain of quantification to be indexed over the collection of nominals/times, we look to Fitting and Mendelsohn's (1998) treatment of first-order modal logic with varying domain semantics and use it to alter the *FHL* model definition to the following:

$$(T, R, D_t, I_{nom}, I_t)_{t \in T}$$

Thus with varying domain semantics a *FHTL* model is identical to the definition for a *FHL* model in that:

- $(T, R)$  is a modal frame.
- $I_{nom}$  is a function assigning members of  $T$  to nominals.

The differences manifest on the level of the model and interpretation. Namely, where  $D = \cup_{t \in T} D_t$ ,  $(D, I_t)$  is a first-order model where:

- $I_t(q) \in D$  where  $q$  is a unary function symbol.
- $I_t(P) \in D^k$  where  $P$  is a  $k$ -ary predicate symbol.

Notice we've relaxed the requirement that  $I_t(c) = I_{t'}(c)$  for  $c$  a constant and  $t, t' \in T$ , since the interpretation of the constant need not exist at both times. This permits us to distinguish between the domain of a frame and the domain of a time/world, in a way that prevents a variable  $x$  from failing to refer at a given time/world, even if it has no interpretation at that time. Intuitively this permits *FHTL* to handle interpretation of entities in natural language utterances, which while reasonable to refer to do not exist at a current time, e.g. previous and future presidents.

Free variables are handled similarly as in *FHL*. Where again  $D = \cup_{t \in T} D_t$ , a *FHTL* assignment is a function:

$$g: \text{SVAR} \cup \text{FVAR} \rightarrow T \cup D$$

Where state variables are sent to times/worlds and first-order variables are sent to  $D$ , the domain of the frame. Thus given a model and an assignment  $g$ , the interpretation of terms  $t$  denoted by  $\bar{t}$  is defined as:

- $\bar{x} = g(x)$  for  $x$  a variable.
- $\bar{c} = I_t(c)$  for  $c$  a constant and some  $t \in T$ .
- For  $q$  a unary function symbol:

- For  $n$  a nominal:

$$\overline{@_n q} = I_{I_{nom}(n)}(q)$$

- For  $n$  a state variable:

$$\overline{@_n q} = I_{g(n)}(q)$$

Finally we say an assignment  $g'$  is an  $x$ -variant of  $g$  if  $g'$  and  $g$  on all variables except possibly  $x$ . In particular, we say  $g'$  is an  $x$ -variant of  $g$  at  $t$ , a time, if  $g'$  and  $g$  on all variables except possibly  $x$  and  $g'(x) \in D_t$ . We omit definitions for  $\wedge$ ,  $\rightarrow$ ,  $H$ ,  $G$ , and  $\forall$ , since they can be defined in terms of the other rules. Given a model  $\mathfrak{M}$ , a variable assignment  $g$ , and a state  $s$ , the inductive definition of  $\mathfrak{M}, s \models_g \varphi$  is:

$$\begin{aligned}
\mathfrak{M}, s \models_g P(t_1, \dots, t_n) &\iff \langle \bar{t}_1, \dots, \bar{t}_n \rangle \in I_s(P) \\
\mathfrak{M}, s \models_g t_i = t_j &\iff \bar{t}_i = \bar{t}_j \\
\mathfrak{M}, s \models_g n &\iff I_{nom}(n) = s, \text{ for } n \text{ a nominal} \\
\mathfrak{M}, s \models_g w &\iff g(w) = s, \text{ for } w \text{ a state variable} \\
\mathfrak{M}, s \models_g \neg \varphi &\iff \mathfrak{M}, s \not\models_g \varphi \\
\mathfrak{M}, s \models_g \varphi \vee \psi &\iff \mathfrak{M}, s \models_g \varphi \text{ or } \mathfrak{M}, s \models_g \psi \\
\mathfrak{M}, s \models_g \exists x \varphi &\iff \mathfrak{M}, s \models_{g'} \varphi \text{ for some } x\text{-variant } g' \text{ of } g \text{ at } s \\
\mathfrak{M}, s \models_g F \varphi &\iff \mathfrak{M}, t \models_g \varphi \text{ for some } t \in T \text{ such that } Rst \\
\mathfrak{M}, s \models_g P \varphi &\iff \mathfrak{M}, t \models_g \varphi \text{ for some } t \in T \text{ such that } Rts \\
\mathfrak{M}, s \models_g @_n \varphi &\iff \mathfrak{M}, I_{nom}(n) \models_g \varphi \text{ for } n \text{ a nominal} \\
\mathfrak{M}, s \models_g @w \varphi &\iff \mathfrak{M}, g(w) \models_g \varphi \text{ for } w \text{ a state variable}
\end{aligned}$$

## 4.1 The Tableau Calculus

Following Fitting and Mendelsohn (1998) we assume for each nominal or state variable  $s$ , there is an infinite list of parameters, where parameters are free variables which are never quantified over, arranged in such a way that different nominals/state variables never share the same parameter. Informally we write  $p_s$  to indicate a parameter is associated with a nominal/state variable  $s$ .

## 4.2 Soundness and completeness

The proof of soundness for *FHTL* follows from the soundness of *FHL* established in Hansen (2007), with additions for the rules  $(P)$ ,  $(\neg P)$ ,  $(P)$ –**bridge**, and  $(P/F)$ –**trans**, the soundness of which is easy to demonstrate. The proof of completeness is the same as the one given in Bolander and Bräuner (2006) for Blackburn's tableau system for standard hybrid logic ( $\mathcal{HL}(@)$ ) with accommodations made for the first order aspects of *FHTL* adapted from Hansen (2007). While Bolander and Bräuner (2006) en route to completeness proves termination for Blackburn's tableau system, we cannot do that for *FHTL*, since a terminating tableau system would be equivalent to a general decision procedure for first-order predicate logic. We will however introduce restrictions on the quantifier and term rules in the next section which will lead to terminating tableau constructions at the cost of general completeness, which will be no real loss since the purpose of our revised terminating tableau system is for finite model checking.

**Definition 4.1 (Closed and open).** If a tableau branch contains a formula  $@_s \varphi$  and its negation  $@_s \neg \varphi$  we say the branch is *closed*. If every branch of the tableau is closed we say the tableau itself is closed. If a tableau or branch is not closed we say it is *open*.

A closed tableau is a proof of the unsatisfiability of the tableau's root formula, i.e. there is no model or assignment of variables in which it holds. The question of when a tableau indicates satisfiability of the root formula leads us to our next definition.

**Definition 4.2 (Quasi-subformula).** A formula  $\varphi$  is a *quasi-subformula* of a formula  $\psi$  if one of the the following is the case:

**Propositional rules:**

$$\frac{\@_s(\varphi \vee \psi)}{\@_s\varphi \mid \@_s\psi} (\vee)$$

$$\frac{\@_s\neg(\varphi \vee \psi)}{\@_s\neg\varphi} (\neg\vee)$$

$$\@_s\neg\psi$$

$$\frac{\@_s\neg\neg\varphi}{\@_s\varphi} (\neg\neg)$$

**Modal rules:**

$$\frac{\@_sF\varphi}{\@_sFa} (F)^{ab}$$

$$\@_a\varphi$$

$$\frac{\@_sP\varphi}{\@_sPa} (P)^{ab}$$

$$\@_a\varphi$$

$$\frac{\@_s\neg P\varphi \quad \@_sPt}{\@_t\neg\varphi} (\neg P)$$

$$\frac{\@_s\neg F\varphi \quad \@_sFt}{\@_t\neg\varphi} (\neg F)$$

**Quantifier rules:**

$$\frac{\@_s\exists x\varphi}{\@_s\varphi[s:p/x]} (\exists)^c$$

$$\frac{\@_s\neg\exists x\varphi}{\@_s\neg\varphi[t/x]} (\neg\exists)^d$$

**Equality rules:**

$$\frac{}{\@_ij:t = j:t} (\text{ref})^e$$

$$\frac{\@_ij:t = k:s \quad \@_i\varphi}{\@_i\varphi[j:t/k:s]} (\text{sub})^f$$

**@ rules:**

$$\frac{\@_s\@_t\varphi}{\@_t\varphi} (@)$$

$$\frac{\@_s\neg\@_t\varphi}{\@_t\neg\varphi} (\neg@)$$

$$\frac{\@_st \quad \@_s\varphi}{\@_t\varphi} (\text{nom})$$

$$\frac{[i \text{ on the branch}]}{\@_ii} (\text{nom ref})$$

$$\frac{\@_sPt}{\@_tFs} (P\text{-trans})$$

$$\frac{\@_sFt}{\@_tPs} (F\text{-trans})$$

$$\frac{\@_sPt \quad \@_tu}{\@_sPu} (P\text{-bridge})$$

$$\frac{\@_sFt \quad \@_tu}{\@_sFu} (F\text{-bridge})$$

**FHTL term rules:**

$$\frac{\@_ik_1:t = k_2:s}{\@_ik_1:t = k_2:s} (:1)$$

$$\frac{\@_ij}{\@_ki:t = j:t} (:2)^e$$

$$\frac{}{\@_ik:j:t = j:t} (:3)^e$$

$$\frac{\@_iR(t_1, \dots, t_n)}{\@_iR(i:t_1, \dots, i:t_n)} (:fix\ 1)$$

$$\frac{\@_i\neg R(t_1, \dots, t_n)}{\@_i\neg R(i:t_1, \dots, i:t_n)} (:fix\ 2)$$

$$\frac{\@_it = s}{\@_ii:t = i:s} (:fix\ 3)$$

$$\frac{\@_i\neg t = s}{\@_i\neg i:t = i:s} (:fix\ 4)$$

$$\frac{}{\@_if(t_1, \dots, t_n) = f(i:t_1, \dots, i:t_n)} (:func)^g$$

<sup>a</sup>The nominal  $a$  is new to the branch.

<sup>b</sup>The formula  $\varphi$  is not a nominal.

<sup>c</sup> $s:p$  is new to the branch.

<sup>d</sup> $p$  is any ground term or parameter which exists at  $s$ .

<sup>e</sup>Where  $t$  is a closed term.

<sup>f</sup> $\varphi[j:t/k:s]$  is  $\varphi$  where some occurrences of  $j:t$  have been replaced by  $k:s$ .

<sup>g</sup> $f$  is an  $n$ -ary function symbol and  $t_1, \dots, t_n$  are closed terms.

1.  $\varphi$  is a subformula of  $\psi$  modulo renaming of free variables and substitution of free variables in  $\varphi$  for grounded

terms.

2.  $\varphi$  is of the form  $\neg\chi$  where  $\chi$  is a subformula of  $\psi$  modulo renaming of free variables in  $\chi$  for grounded terms.

Altering the definition to allow grounded terms being substituted for free variables ensures compatibility of the following proofs with the quantifier and term rules. We say a formula  $@_s\varphi$  on a *FHTL* tableau branch  $\Theta$  is a *root subformula* if  $\varphi$  is a quasi subformula of the root formula of the tableau.

**Lemma 4.1 (Subformula Property).** *If a formula  $@_s\varphi$  occurs in a *FHTL* tableau where  $\varphi$  is not of the form  $a$ ,  $Fa$ , or  $Pa$  for a nominal  $a$ , or  $u = t$  for optionally prefixed closed terms  $t$  and  $u$ , then  $\varphi$  is a (positively occurring) root subformula. If  $@_s\neg\varphi$  occurs in a *FHTL* tableau then  $\varphi$  is a root subformula, but we say it is negatively occurring.*

*Proof.* This is verified by checking the tableau rules.  $\square$

**Definition 4.3.** An occurrence of a nominal in a formula is *equational* if the occurrence is a formula (i.e. not part of a satisfaction operator).

For instance, the occurrence of a nominal  $c$  is equational in the formula  $@_ac \vee \exists x\psi$  but not in the formula  $@_c\exists x\psi$ .

**Theorem 4.2.** *Where  $@_ab$  occurs on a branch  $\Theta$ , if the nominals  $a$  and  $b$  are distinct, then each has the property that it is identical to, or related by  $\sim_\Theta$  to, a nominal with a positive and equational occurrence in the root subformula.*

*Proof.* This is verified by checking each rule, in some cases making use of 4.1. (**nom ref**) might initially appear to be a problem, since we are permitted to apply it for any nominal on the branch, but the nominals in its conclusions are not distinct. For  $F$  and  $P$  we make use of the restriction that they cannot be applied to premises of the form  $@_a(F/P)\varphi$  where  $\varphi$  is a nominal.  $\square$

**Theorem 4.3.** *Let  $@_aFb$  be a formula occurrence on a branch  $\Theta$  of a tableau. Either there is a positively occurring subformula  $Fb'$  of the root formula such that  $b \sim_\Theta^* b'$  or there is an accessibility formula occurrence  $@_{a'}Fb'$  such that  $a \sim_\Theta^* a'$  and  $b \sim_\Theta^* b'$ . Similarly for a formula occurrence  $@_aPb$ .*

*Proof.* This is verified by checking each of the tableau rules, in some cases making use of 4.1.  $\square$

**Definition 4.4** ( $N_\Theta$ ). The set of nominals which occur on  $\Theta$  is written  $N_\Theta$

**Definition 4.5** ( $\subseteq_\Theta$ ). Where  $a$  and  $b$  are nominals occurring on an *FHTL* tableau branch  $\Theta$ ,  $a$  is *included* in  $b$  with respect to  $\Theta$  if for any root subformula  $\varphi$ , if  $@_a\varphi$  occurs on  $\Theta$  then  $@_b\varphi$  also occurs on  $\Theta$ , similarly for their negations. If  $a$  is included in  $b$  with respect to  $\Theta$ , and the first occurrence of  $b$  on  $\Theta$  is before the first occurrence of  $a$  on  $\Theta$ , then we write  $a \subseteq_\Theta b$ .

**Definition 4.6** ( $\sim_\Theta$ ). Where  $\Theta$  is a *FHTL* tableau branch, define a binary relation  $\sim_\Theta$  on  $N_\Theta$  by  $a \sim_\Theta b$  if and only if  $@_ab$  occurs on  $\Theta$ . Let  $\sim_\Theta^*$  be reflexive, transitive, and symmetric closure of  $\sim_\Theta$ .

**Definition 4.7** ( $W, \approx$ ). Let  $W$  be the subset of  $N_\Theta$  containing any nominal  $a$  with the property that there is no nominal  $b$  such that  $a \subseteq_\Theta b$ . Let  $\approx$  be the restriction of  $\sim_\Theta$  to  $W$ .

We can see that  $W$  contains every nominal in the root formula, and since any branch  $\Theta$  is closed under (**nom ref**) and (**nom**) we have that  $\sim_\Theta$  and  $\approx$  are equivalence relations. For a nominal  $a$  in  $W$  we write  $[a]$  to denote the equivalence class of  $a$  and  $W/\approx$  to denote the set of equivalence classes.

**Definition 4.8.** Let  $R$  be the binary relation defined on  $W$  defined by  $Rac$  if and only if there are nominals  $a' \approx a$  and  $c' \approx c$  satisfying one of the following conditions:

1. The formula  $@_{a'}Fc'$  or  $@_{a'}Pc'$  occurs at  $\Theta$  and was introduced to the branch by  $F$  or  $P$  respectively.
2. There is a nominal  $d \in N_\Theta$  such that the formula  $@_{a'}Fd$  or  $@_{a'}Pd$  was introduced to the branch by  $F$  or  $P$  respectively and  $d \subseteq_\Theta c'$
3. The formula  $@_{a'}Fc'$  or  $@_{a'}Pc'$  occurs at  $\Theta$  and  $a'$  or  $c'$  occurs in the root formula.

Note that the nominal  $d$  in the second item is not an element of  $W$  and that the accessibility relation  $R$  is compatible with  $\approx$ . We define  $\bar{R}$  as the binary relation on  $W/\approx$  defined by  $\bar{R}[a][c]$  if and only if  $Rac$ .

$(W, \bar{R})$  are a modal frame, the first step towards constructing a model of an open tableau branch  $\Theta$ . Here we define the analogues of  $D_{[w]}, I_{[w]}$  for  $[w] \in W/\approx$  and  $I_{nom}$ . To start we let  $\mathcal{D}$  be set defined by:

$$\mathcal{D} = \{i:t \mid \text{for some } i \in W \text{ and some closed term of the extended language } t\}$$

Further we define a relation  $\equiv$  on  $\mathcal{D}$  by:  $i:t \equiv j:s \iff @_k i:t \equiv j:s \in \Theta$  for some  $k \in W$ . From the tableau rules **(ref)**, **(sub)**, and **(:1)**, we observe  $\equiv$  is an equivalence relation on  $\mathcal{D}$ . From here we define the domain  $D$  of the model as  $\mathcal{D}/\equiv$ , with the elements written as  $\overline{i:t}$ , for all  $[w] \in W/\approx$  define:

$$D_{[w]} = \{\overline{j:p} \mid j \in [w] \text{ and } p \text{ a parameter}\}$$

For  $a$  a constant or parameter and  $[w] \in W/\approx$  we define  $I_{[w]}(a) = \overline{w:a}$  which is well defined by **(:2)**. For an  $n$ -ary relation symbol  $R$  and  $[w] \in W/\approx$  define  $I_{[w]}(R)$  by:

$$I_{[w]}(R)(\overline{i_1:t_1}, \dots, \overline{i_n:t_n}) \iff @_w R(i_1:t_1, \dots, i_n:t_n) \in \Theta$$

for all  $\overline{i_1:t_1}, \dots, \overline{i_n:t_n} \in D$ . The interpretation is similar for  $n$ -ary function symbols. And naturally for interpretation of nominals, for  $w \in W$  define  $I_{nom}(w) = [w]$ .

Before finally demonstrating that this model  $\mathfrak{M}$  realizes every formula on the tableau branch from which it was constructed we need the following lemma.

**Lemma 4.4.** *If  $t$  is a term of the extended language that contains no variables and  $i$  is a nominal then we have  $\llbracket t \rrbracket_{[i]}^{\mathfrak{M},g} = \overline{i:t}$  for all variable assignments  $g$  in our model  $\mathfrak{M}$ .*

*Proof.* The proof is by induction on the construction of  $t$ . By our assumption  $t$  cannot a first-order variable, and if  $t$  is a constant or a parameter then

$$\llbracket t \rrbracket_{[i]}^{\mathfrak{M},g} = \llbracket t \rrbracket_{[i]}^{\mathfrak{M}} I_{[i]}(t) = \overline{i:t}$$

by definition. Suppose alternatively  $t$  is of the form  $u:s$  for  $u \in W$ , since  $t$  contains no variables neither does  $s$  and consequently:

$$\llbracket u:s \rrbracket_{[i]}^{\mathfrak{M},g} = \llbracket s \rrbracket_{[u]}^{\mathfrak{M},g} * \overline{u:s} \stackrel{(:3)}{=} \overline{i:u:s}$$

Where  $*$  follows from the inductive hypothesis and **(:3)** from **(:3)**. Similarly for the case involving functional symbols.  $\square$

**Lemma 4.5.** *Assuming the branch  $\Theta$  is open, for any formula  $@_a \varphi$  which contains only nominals from  $W$ , the following two statements hold:*

$$\begin{aligned} @_a \varphi \in \Theta &\implies \mathfrak{M}, [a] \models_g \varphi \text{ for some (all) variable assignments } g \\ @_a \neg \varphi \in \Theta &\implies \mathfrak{M}, [a] \not\models_g \varphi \text{ for some (all) variable assignments } g \end{aligned}$$

*Proof.* This is demonstrated by induction on the structure of the formula. We present the most difficult case, namely where  $\varphi$  is of the form  $F\psi$ .

Assume  $@_a F\psi \in \Theta$ . Then we need to show that there is an equivalence class  $[c] \in W/\approx$  such that  $R[a][c]$  and  $\mathfrak{M}, [c] \models_g \psi$  for some variable assignments  $g$ . We have two cases based on the question of whether or not  $\psi$  is a nominal. In the case where

- $\psi$  a nominal Suppose  $\psi$  is some nominal  $b$ , we only need prove  $\bar{R}[a][b]$ . By theorem 4.3 there is either a root nominal  $b'$  such that  $b' \sim_{\Theta} b$  or there is an accessibility formula  $@_{a'} Fb' \in \Theta$  such that  $a' \sim_{\Theta} a$  and  $b' \sim_{\Theta} b$ . In the first case then we have  $@_{a'} Fb' \in \Theta$  and  $b' \in W$  so  $\bar{R}[a][b']$  and since  $b' \approx b$  (since both are in  $W$ ) we have  $[b'] = [b]$  and we are done. In the second case, there are four subcases depending on whether or not  $a'$  and  $a$  are equal and  $b'$  and  $b$  are equal:

- $a' = a$  and  $b' = b$ :

Then we have  $\bar{R}[a][b]$  and are done.

- $a' = a$  and  $b' \neq b$ :

By 4.2 there is a nominal  $c$  occurring in the root formula such that  $b' \sim_{\Theta} c$ . But then  $@_a Fc \in \Theta$  and  $c \in W$  so  $\bar{R}[a][c]$ , and by the definition of  $\approx$  we have  $[c] = [b]$  and are done.

- $a' \neq a$  and  $b' = b$ :

By 4.2 there is a nominal  $c$  occurring in the root formula such that  $a' \sim_{\Theta} c$ . But then  $@_c Fb \in \Theta$  and  $c \in W$  so  $\overline{R}[c][b]$ , and by the definition of  $\approx$  we have  $[c] = [a]$  and are done.

- $a' \neq a$  and  $b' \neq b$ :

By 4.2 there are nominals  $c$  and  $d$  occurring in the root formula such that  $a' \sim_{\Theta} c$  and  $b' \sim_{\Theta} d$ . But then also  $@_c Fd \in \Theta$ , and  $c, d \in W$  so  $\overline{R}[c][d]$  and by definition of  $\approx$  we have  $[c] = [a]$  and  $[d] = [b]$  and are done.

- $\psi$  not a nominal Since  $a \in W$  the application of  $(F)$  to  $@_a \psi$  is not blocked by the loop-check condition of the tableau construction algorithm. From the rule  $(F)$ , there are formulae  $@_a Fc, @_c \psi \in \Theta$  where the nominal  $c$  is new to the branch. If  $c \in W$  then  $\overline{R}[a][c]$  and by induction  $\mathfrak{M}, [c] \models_g \psi$  for some variable assignments  $g$ . If  $c \notin W$  then by the definition of  $W$  there is a nominal  $d$  where  $c \subseteq_{\Theta} d$ . Without loss of generality assume there is no nominal  $e$  such that  $d \subseteq_{\Theta} e$ , this implies  $d \in W$ . Additionally by 4.1  $\psi$  is a root subformula and we have  $@_d \psi \in \Theta$ . By induction we have  $\mathfrak{M}, [d] \models_g \varphi$ , and by the definition of  $W$  and  $\approx$  we have  $\overline{R}[a][d]$ .

Assume  $@_a \neg F\psi \in \Theta$ , we need to show  $\mathfrak{M}, [a] \not\models_g F\psi$  does not hold for any variable assignment  $g$ , i.e. for any  $[c] \in W/\approx$  where  $\overline{R}[a][c]$  that  $\mathfrak{M}, [c] \not\models_g \psi$  for any variable assignment  $g$ . From  $\overline{R}[a][c]$  we have that there are nominals  $a' \approx a$  and  $c' \approx c$  satisfying one of the three conditions of  $R$  in definition 4.8. In the first and third conditions of the definition we have  $@_{a'} Fc' \in \Theta$  and as a result  $@_a Fc \in \Theta$  and in turn by  $(\neg F)$   $@_c \neg \psi \in \Theta$ . By induction we have  $\mathfrak{M}, [c] \not\models_g \psi$  for every variable assignment  $g$ . In the second condition of  $R$  in definition 4.8 there is a nominal  $d \in N_{\Theta}$  such that  $@_{a'} Fd \in \Theta$  and  $d \subseteq_{\Theta} c'$ , consequently  $@_a Fd \in \Theta$  and by  $(\neg F)$   $@_d \neg \psi \in \Theta$ . But by lemma 4.1  $\psi$  is a root subformula, and since  $d \subseteq_{\Theta} c'$  we have  $@_{c'} \neg \psi \in \Theta$ . By induction we have  $\mathfrak{M}, [c'] \not\models_g \psi$  for every variable assignment  $g$  and by the definition of  $\approx$  also  $[c'] = [c]$ .  $\square$

For our task of AMR inference, we are not concerned with the determining the general satisfiability or validity of an AMR formula translated into *FHTL*, but rather whether it holds in a model consistent with an established set of *FHTL* translations of AMR sentences. This model will necessarily be finite, since across any finite number of AMR sentences only a finite number of times (nominals), entities (terms of the extended language), and relationships between entities (function symbols and predicate symbols) can be referenced. In particular, we have a case of a local model-checking problem where given formula  $\varphi$ , a finite *FHTL* model structure  $\mathfrak{M}$ , a time  $t$  in  $\mathfrak{M}$ , and a variable assignment  $g$ , we need to determine whether  $\mathfrak{M}, t \models_g \varphi$  (Müller-Olm et al., 1999).

Here we develop a restriction of our method for tableau construction, which ensures termination at the cost of completeness. This compromise only has positive ramifications for model checking since it does not particularly benefit from completeness of a tableau method but termination is critical to decidability. Our approach to using terminating tableaux as a means of model checking for *FHTL* based on the approach in Bohn et al. (1998), and makes use of the idea of quantifier depth from ?.

### 4.3 Restricted rules

We will show later these new restrictions on these rules ensures that eventually any branch will be saturated, since the amount of times any of the term rules can be applied depends on the number of nominals and terms on the branch. We add the further restriction for universal quantification rules (just  $(\neg \exists)$  in our tableau method) where  $Q$  is a positive natural number:

In first-order tableau systems universal rules are the main culprit for non-termination. Since proofs are finite objects, any tableau proof for a formula involving universal quantification will close for some quantifier depth  $Q$ , the trouble being there is no general way to anticipate the value of  $Q$  as that would constitute a decision procedure for first-order logic. The main function of a universal rule in a tableau proof is to close the branch, so selecting a particular quantifier depth is a way of giving a branch every reasonable chance to close where it has a possible application of a universal rule. While for model checking we actually will not need branches to close so long as they terminate, closed branches are helpful since we automatically do not have to check them for satisfiability.

### 4.4 Systematic tableau construction

**Definition 4.9 (Saturation).** A tableau branch is *saturated* if there are no rules can be applied to the branch in a way that satisfies their constraints or that avoid adding duplicate formulae to the branch. If every branch of the tableau is saturated we say the tableau is saturated.

**Equality rules:**

$$\frac{[i \text{ and } j \text{ on the branch.}]}{\@_i j:t = j:t} \text{ (ref)}^a$$

$$\frac{\@_i j:t = k:s \quad \@_i \varphi}{\@_i \varphi[j:t/k:s]} \text{ (sub)}^b$$

**FHTL term rules:**

$$\frac{\@_i j_1:t = j_2:s}{\@_k j_1:t = j_2:s} \text{ (:1)}^c$$

$$\frac{\@_i j}{\@_k i:t = j:t} \text{ (:2)}^{cd}$$

$$\frac{}{\@_k j:i:t = i:t} \text{ (:3)}^{cd}$$

$$\frac{\@_i R(t_1, \dots, t_n)}{\@_i R(i:t_1, \dots, i:t_n)} \text{ (:fix 1)}^e$$

$$\frac{\@_i \neg R(t_1, \dots, t_n)}{\@_i \neg R(i:t_1, \dots, i:t_n)} \text{ (:fix 2)}^e$$

$$\frac{\@_i t = s}{\@_i i:t = i:s} \text{ (:fix 3)}^e$$

$$\frac{\@_i \neg t = s}{\@_i \neg i:t = i:s} \text{ (:fix 4)}^e$$

$$\frac{[i \text{ and one of the two function terms on the branch}]}{\@_i f(t_1, \dots, t_n) = f(i:t_1, \dots, i:t_n)} \text{ (:func)}^f$$

<sup>a</sup>  $t$  is a closed term on the branch,  $j$  not among its prefixes.

<sup>b</sup>  $\varphi[j:t/k:s]$  is  $\varphi$  where some occurrences of  $j:t$  have been replaced by  $k:s$ .

<sup>c</sup>  $k$  on the branch.

<sup>d</sup>  $t$  is a closed term on the branch, and  $i, j$  are distinct nominals on the branch, not among the prefixes of  $t$ .

<sup>e</sup>  $i$  is not among the prefixes of the terms in the consequent.

<sup>f</sup>  $f$  is an  $n$ -ary function symbol and  $t_1, \dots, t_n$  are closed terms with  $i$  not among their prefixes.

$$\frac{\@_s \neg \exists x \varphi}{\@_s \neg \varphi[s:p/x]} (\neg \exists)^a$$

<sup>a</sup>  $p$  is any parameter and the premise can produce only  $Q$  conclusions.

**Definition 4.10** ( $\prec_\Theta$ ). Where  $\Theta$  is a tableau branch in the *FHTL* calculus, if a nominal  $a$  is introduced to the branch by application of  $F$  or  $P$  to a premise  $\@_s \varphi$ , we say  $a$  is *generated* by  $s$  on  $\Theta$  and write  $s \prec_\Theta a$ . We write  $\prec_\Theta^*$  to denote the reflexive and transitive closure of  $\prec_\Theta$ .

**Lemma 4.6.** Where  $\Theta$  is a tableau branch in the *FHTL* calculus, the graph  $G = (N_\Theta, \prec_\Theta)$  is the disjoint union of a finite set of well-founded and finitely branching trees.

*Proof.* Each aspect is proved below:

- *Wellfoundedness of trees in  $G$*

We have that if  $a \prec_\Theta b$  then the first occurrence of  $a$  on  $\Theta$  is before the first occurrence of  $b$ , thus by induction any subset of  $N_\Theta$  under the relation  $\prec_\Theta$  has a least element and each tree in  $G$  is wellfounded.

- *$G$  is a disjoint union of a set of trees*

This follows from well-foundedness and the fact every nominal in  $N_\Theta$  can be generated by at most one other nominal, and every nominal in  $N_\Theta$  must have one of the finitely many nominals in the root formula as an ancestor.

- *The set of trees is finite*

If a nominal  $c$  occurs on a branch but not in the root formula then there is some nominal  $a$  which generated  $c$ , as a result  $c$  cannot be the root of a tree, and since there are only finitely many nominals in a root formula there can only be finitely many trees.



- *Each tree finitely branching*

We show some tree  $\mathcal{T}$  is finitely branching by showing that given a nominal  $a$ , there can only be finitely many distinct nominals  $b$  such that  $a \prec_{\Theta} b$ . Each nominal  $b$  such that  $a \prec_{\Theta} b$  is generated by applying one of  $F, P$  to a premise of the form  $@_a F\varphi$  or  $@_a P\varphi$  respectively, where by our restrictions  $\varphi$  is not a nominal. Since there can only be finitely many root subformulae of the form of one of the possible premises, where  $a$  is the prefix nominal in each case, only finitely many new nominals have been generated from  $a$ . Thus  $\mathcal{T}$  is finitely branching. □

*Remark 4.1.* In the restricted rules, a term can have no nominal among its prefixes more than once. Consequently where  $n$  is the number of nominals on the branch and  $k$  is the number of prefix strings a term can have ( $k \leq n$ ) the number of possible prefixed versions of a term are

$$\sum_{k=1}^n \frac{n!}{(n-k)!}$$

**Lemma 4.7.** *Using the restricted rules, minus any rules which generate new nominals on a branch ( $F$  and  $P$ ), any FHTL tableau branch  $\Theta$  saturates within a finite number of steps.*

*Proof.* The propositional rules,  $(\neg F/P)$ ,  $(\exists)$  and the  $@$  rules, have only finitely many possible applications before they can no longer be applied on  $\Theta$ . With the quantifier depth restriction  $(\neg\exists)$  can only be applied a finite number of times, and while **(sub)** can generate multiple conclusions since there are multiple partial substitutions for any formula, there are only finitely many partial substitutions possible. For **(ref)** and the term rules, we have at worst cases like **(:3)** and **(ref)** which depend on the number of nominals and terms on the branch for the number of possible applications before a redundant application. There are only finitely many nominals and terms on the branch at any given time, and by our remark, there are finitely many possible prefix strings for a given term. Thus there are only finitely many possible applications of **(ref)** to the branch. □

**Definition 4.11** (*Tableau construction algorithm*). Let  $@_{a_a}\varphi$  be the formula whose validity (or failing that, local satisfiability) we are deciding. We inductively define a sequence of finite tableaux

$$\mathcal{T}_0, \mathcal{T}_1, \mathcal{T}_2, \dots$$

where each element of the sequence is embedded in all of its successors. We let  $\mathcal{T}_0$  be the finite tableau consisting of the formula  $@_a \neg\varphi$ . Assuming the finite tableau  $\mathcal{T}_n$  is defined, apply, where possible according to its restrictions, an arbitrary model checking FHTL tableau rule with the following restrictions.

- **Saturation**

Do not apply a rule to a premise if the resulting conclusion is a formula already on the branch.

- **(Loop check)**

The rule  $(F)$  is not applied to a formula occurrence  $@_a F\varphi$  at a branch  $\Theta$  if there is a nominal  $b$  such that  $a \subseteq_{\Theta} b$ , and similarly for the rule  $(P)$ .

Let  $\mathcal{T}_{n+1}$  be the resulting tableau.

The saturation conditions prevent the algorithm from extending the tableau indefinitely with redundant formulae and forces the algorithm to use every applicable rule the maximum possible amount of times, i.e. this algorithm is “fair” (?)fitting-modal). The loop check condition is in the same spirit, preventing the algorithm from introducing nominals to the branch which would be redundant in their sharing identical information with some ancestor nominal already on the branch. Now we can demonstrate the algorithm always terminates.

**Theorem 4.8.** *The systematic tableau construction algorithm terminates.*

*Proof.* Suppose by contradiction the algorithm does not terminate. Then the tableau is infinite branch  $\Theta$ . By lemma 4.6 the graph  $(N_{\Theta}, \prec_{\Theta})$  is a disjoint union of a finite set of finitely branching trees. Thus it has some infinite branch

$$a_1 \prec_{\Theta} a_2 \prec_{\Theta} \dots \prec_{\Theta} a_i \prec_{\Theta} \dots$$

otherwise by lemmas 4.1 and 4.7 there would only be finitely many formulae on the branch, contradicting that it is infinite. For each  $i$  in the indices of this infinite chain of nominals, let  $\Theta_i$  denote the initial segment of  $\Theta$  up

to but not including the first formula where the nominal  $a_{i+1}$  occurs. Thus one of  $(F)$  or  $(P)$  was applied to a formula in  $\Theta_i$  which generated  $a_{i+1}$ . Let  $\Gamma_i$  be the set of all  $@_{a_i}\varphi \in \Theta_i$  for  $\varphi$  a root subformula and let  $\Delta_i$  be the set of all  $@_{a_i}\neg\varphi \in \Theta_i$  for  $\varphi$  a root subformula. Since there can only be finitely many sets of root subformulae, there are nominals in the infinite chain  $a_j, a_k$  where  $j < k$  and  $\Gamma_j = \Gamma_k$  and  $\Delta_j = \Delta_k$ . Since  $j < k$  the first occurrence of  $a_j$  on  $\Theta_k$  must be before the first occurrence of  $a_k$  on  $\Theta_k$ . Additionally for any root subformula  $\varphi$ , if  $@_{a_k}\varphi \in \Theta_k$  then  $\varphi \in \Gamma_k$  and consequently  $\varphi \in \Gamma_j$ , but then  $@_{a_j}\varphi \in \Theta_j$  which is an initial segment of  $\Theta_k$ . Thus by definition 4.5  $a_k$  is included in  $a_j$  with respect to  $\Theta_k$ , and since the first occurrence of  $a_j$  is before the first occurrence of  $a_k$  we have  $a_k \subseteq_{\Theta} a_j$ . But this contradicts that  $(F)$  or  $(P)$  was applied on  $\Theta_k$  resulting in the first formula containing an occurrence of the nominal  $a_{k+1}$  since  $a_k \subseteq_{\Theta} a_j$  would result in the loop check condition blocking the application. Thus the algorithm terminates.  $\square$

## 4.5 Node Annotation

The approach involves annotating each node of an open branch with the variable assignments in the model which witness the formula at the node, building inductively from the terminal nodes. If the root formula of the tableau with at least one open branch can be annotated with non-empty set of variable assignments, then it is satisfiable in the model. If a tableau is closed then the root formula  $@_s\varphi$  is unsatisfiable. As a result if the root formula is of the form  $@_s\neg\psi$  then this constitutes a proof of the validity of  $@_s\psi$  by contradiction. We now view each node in the tableau graph as a pair  $(@_s\varphi, \mathcal{V})$ , of the formula at the node and the set  $\mathcal{V}$  of variable assignments in our model  $\mathfrak{M}$  which witness the formula. We define an annotation function  $ann(@_s\varphi) = \mathcal{V}$  beginning with terminal nodes:

$$ann(@_s\varphi) = \{g \mid \mathfrak{M}, I_{nom}(s) \models_g \varphi\}$$

If we have a branch that we know to be closed from the tableau construction (or discover it is closed during model checking as we will see) and  $@_t\psi$  is the root of that branch, we define:

$$ann(@_t\psi) = \emptyset$$

For this reason during the annotation process we need not check formulae of the form  $@_i j$  or  $@_i(F/P)j$ , or nodes not involving free variables since their truth or falsehood is independent of variable assignments. Terminal nodes will necessarily not contain quantifiers, double negation, nested prefix/satisfaction operators, or logical connectives, as a result they will consist only of equality or relation statements over extended terms possibly involving free variables. Now we can begin describing the dependency relationships between tableau rule conclusions and their premises.

- **Term rules:** In all cases we can see that for every rule with a premise the same variable assignments which satisfy the conclusion satisfies the premise. This is immediate for  $(:2)$ ,  $(:3)$ , and  $(:func)$ , since they only involve closed terms, and are verified by checking definitions in all other cases.
- **@ rules:** For  $P/F - \text{bridge}$ , and  $P/F - \text{trans}$  all variable assignments trivially satisfy both the conclusions and premises. For **(nom)**, since by the first premise

$$I_{nom}(i) = I_{nom}(j)$$

the variable assignments that witness the conclusion witness the second premise (the first premise being a nominal equivalence is trivially witnessed by all variable assignments). That the premise and conclusion of both  $(@)$  and  $(\neg@)$  are satisfied by the same variable assignments are verified by checking their satisfiability definitions.

- **Equality rules:** The only rule to check is **(sub)**, from which it follows immediately that the premise and conclusion are witnessed by the same variable assignments.
- **Quantifier rules:** For  $(\exists)$ , we let  $C$  be set of variable assignments which satisfy the conclusion. Without loss of generality, where the premise is  $@_s\exists x\varphi$ , we see from the semantics of  $\exists$  that  $P$ , the set of variable assignments which satisfies the premise can be defined as:

$$P = \{g \mid g \in C \text{ such that there is an } x\text{-variant } g' \text{ of } g \text{ at } s \text{ where } \mathfrak{M}, s \models_{g'} \varphi\}$$

Similarly For  $(\neg\exists)$  let  $C$  be the set of variable assignments which satisfy the conclusion. Without loss of generality, where the premise is  $@_s\neg\exists x\varphi$ , we see from the semantics of  $\neg\exists$  that  $P$ , the set of variable assignments which satisfies the premise can be defined as:

$$P = \{g \mid g \in C \text{ such that for every } x\text{-variant } g' \text{ of } g \text{ at } s \text{ we have } \mathfrak{M}, s \models_{g'} \neg\varphi\}$$

- **Modal rules:** For  $F$  and  $P$ , that the the premise and the second conclusion are satisfied by the same variable assignments follows from checking the definitions. Similarly for the first premise and the conclusion of  $\neg P$  and  $\neg F$ .
- **Propositional rules:** For  $(\vee)$  given the semantics of the premise, the union of the sets of variable assignments satisfying each of the conclusions satisfies the premise. Similarly for  $(\neg\vee)$ , except we take the intersection of the variable assignment sets. That the premise and conclusion of  $(\neg\neg)$  are satisfied by the same set of variable assignments follows from checking the semantics.

*Remark 4.2.* We note that any annotation of variable assignments for a node will be finite since any formula will have only finitely many variables, and the model's domain itself is finite.

**Lemma 4.9.** *Node annotation for a model checking tableau over a finite model is decidable.*

*Proof.* First we consider closed terms. Since any model checking tableau is finite, it has only finitely many function symbols, constants, and parameters. Furthermore the model has only finitely many worlds/times and a finite domain for each world/time, consequently computing the value of a closed term is guaranteed to terminate. Similarly, we have terminating computation for relation and equality statements over closed terms. Since the @ rules, modal rules, and equality rules, and  $(\neg\neg)$  merely don't involve any operations on the set of variable assignments satisfying the conclusions, we turn now to the quantifier rules and other propositional rules. Recalling 4.2, we see that  $(\vee)$  and  $(\neg\vee)$  involve only union and intersection of finite sets, both being terminating processes. For the annotation set of the premise in  $(\exists)$  we are selecting from a finite set of variable assignments which satisfy the conclusion based on whether they have a , and for  $(\neg\exists)$   $\square$

**Theorem 4.10.** *Finite model checking for FHTL is decidable.*

*Proof.* This follows immediately from theorem 4.8 and lemma 4.9.  $\square$

## 5 AMR Interpretation in FHTL

### 5.1 Examples

Easier examples:

- (1) a. Every computer will be located at a desk.  
b.

```

(s / scope
  :pred (b / be-located-at-91 :ongoing - :complete + :time (a / after :op1 (n
/ now))
    :ARG0 (c / computer)
    :ARG1 (d / desk
      :quant (e / every)))
  :ARG0 d
  :ARG1 c)
c. @now  $\forall y[\text{desk}(y) \rightarrow \exists[\text{computer}(x) \wedge F\text{be-located-at-91}(x, y)]]$ 
d. Also acceptable @now  $F\forall y[\text{desk}(y) \rightarrow \exists[\text{computer}(x) \wedge \text{be-located-at-91}(x, y)]]$ 

```

Harder examples:

- (2) a. Carl filled out the forms and everyone will submit them tomorrow.  
b.

```

(a / and
  :op1 (s / scope
    :pred (f / fill-out-03 :ongoing - :complete + :time (b / before :op1 (n / now))
      :ARG0 (p / person
        :name (n2 / name
          :op "Carl"))
      :ARG1 (f2 / form))
    :ARG0 p
    :ARG1 f2)
  :op2 (s2 / scope
    :pred (m / submit-01 :ongoing - :complete + :time (a2 / after :op1 n)
      :ARG0 (p2 / person
        :mod (a3 / all))
      :ARG1 f2)
    :ARG0 f2
    :ARG1 p2))
c. Technically correct:

```

$@_{now} \exists x [\text{form}(x) \wedge P_{\text{fill-out-03}}(\text{Carl}, x)] \wedge @_{now} \exists x [\text{form}(x) \wedge \forall y [\text{person}(y) \rightarrow F_{\text{submit-01}}(y, x)]]$   
 d. Correct with regard to reentrance (maybe requires the passive for singular case?):  
 $@_{now} \exists x [\text{form}(x) \wedge P_{\text{fill-out-03}}(\text{Carl}, x) \wedge \forall y [\text{person}(y) \rightarrow F_{\text{submit-01}}(y, x)]]$

The difficulty of the following is due to requiring inference of absent arguments.

(3) a. It was impossible not to notice the car.

b.

```

(s / scope
  :pred (p / possible-01
    :ARG0 (n / notice-01 :ongoing - :complete + :time (b / before :op1 (n2 /
now) )
    :polarity (n3 / not)
    :ARG1 (c / car)
    :polarity (n4 / not))
  :ARG0 n4
  :ARG1 p) )

```

c. Incorrect, since notice-01 is a two-place predicate:

$@_{now} \neg \text{possible-01}(\exists x [\text{car}(x) \wedge \neg P_{\text{notice-01}}(x)])$

d. Correct:

$@_{now} \neg \text{possible-01}(\exists x [\text{car}(x) \wedge \neg \forall y [\text{person}(y) \rightarrow P_{\text{notice-01}}(x, y)]])$

e. Alternative, the particular car as a constant:

$@_{now} \neg \text{possible-01}(\neg \forall x [\text{person}(y) \rightarrow P_{\text{notice-01}}(\text{car}, y)])$

## 5.2 Extraction Steps

With the chosen annotation, the root node can consist of either a logical connective (and, or, or cond) linking two AMR graphs, or a *scope* node with its following predicate and arguments.

## 5.3 General Extraction Algorithm

---

**Algorithm 1:** Basic transformation into *FHTL* clauses and connectives.

---

**Input:** AMR sentence

**Output:** *FHTL* formula

**Def** InterpretEntry (AMR) :

```

root = Root(AMR)
now = current date/time
if root ∈ {and, or, cond} then
  connective = filter(root, {∧, ∨, →})
  clauses = []
  for op ∈ Children(root) do
    | append(clauses, InterpretClause (op))
  end
  return @now join(connective, clauses)
end
return @now InterpretClause (root)

```

**Def** InterpretClause (AMR) :

```

time = Time (AMR)
nominal = Reference (time)
tense = Tense (time)
pred = Pred (AMR)(tense)
Arg0, Arg1 = GetArgs (AMR)
return @nominal Apply (Arg0, Apply (Arg0, pred))

```

---

---

**Algorithm 2:** Supporting definitions.

---

**Input:** AMR sentence

**Output:** *FHTL* formula

**Def** `Apply(pred1, pred2) :`

| **return**  $\lambda\varphi.\text{pred}_1(\lambda\psi.\text{pred}_2(\lambda\gamma.\varphi(\psi(\gamma))))$

**Def** `InterpretPred(UnaryPred) :`

```
/* Propositional modifiers are handled differently than predicates. */
if isPropMod(name(UnaryPred)) then
| return InterpPropMod(UnaryPred)
end
if hasMods(UnaryPred) then
| mods = [name(UnaryPred)]
| for mod ∈ Children(UnaryPred) do
| | append(mods, name(mod)(x))
| end
| FinalPred = λx. join(mods, ∧)
end
else
| FinalPred = λx.name(UnaryPred)(x)
end
if Quant(UnaryPred) == :all then
| return  $\lambda k.\forall x[\text{FinalPred}(x) \rightarrow k(x)]$ 
end
else
| return  $\lambda k.\exists x[\text{FinalPred}(x) \wedge k(x)]$ 
end
```

**Def** `InterpPropModPropMod:`

```
if PropMod == not then
| return  $\lambda p.\lambda k.\neg p(k)$ 
end
/* Given the new semantics of  $F/\Diamond$  */
/* we adopt the naïve way of treating possible-01 */
/* as a predicate symbol. */
if PropMod == possible-01 then
| return  $\lambda p.\lambda k.\text{possible-01}(p(k))$ 
end
```

---

## 6 Future Work

### 6.1 $\downarrow$ and Quantification over Nominals

Main points, at the cost of undecidability with adding  $\downarrow$  some additional things can be done, and at the cost of the integration of generalized quantifiers you can ostensibly handle even things like habitual aspect.

### 6.2 AMR Reentrancy and Non-Temoral Nominals

There are some difficulties with maintaining the usual notion of possible worlds being maximal with this idea, but there seems to be a direct sympathy between the predicative core of an AMR sentence and in general reentrancy of the nodes with the idea of a nominal as a “point of view” rather than the “name” of a world. Maybe things like epistemic logic could be helpful here.

### 6.3 Automated Inference and HTab

HTab (Hoffmann and Areces, 2009) provides an implementation of  $\mathcal{H}(@, \mathbf{A})$ , which does not natively provide a way to reason with  $P$ ,  $H$ , or first-order quantification. The effort required in making the needed changes to handle these remains to be determined.

## 6.4 The Future of AMR and Parsing for Semantic Features

To what extent can current AMR parsers extract the needed semantic features to make full use of automated inference? Of UMR, Dialogue-AMR, and the AMR annotation variants we’ve used, which logistically has the best outlook?

## 7 Conclusion

We have demonstrated how the core aspects of AMR along with annotations for scope, quantification, and tense, can be accommodated in first-order hybrid tense logic, and that *FHTL* better affords reasoning and inference than AMR, given its general tableau method which acts as a proof procedure for *FHTL* sentences and its terminating tableau method which acts as a model checker.

## References

- Laura Banarescu, Claire Bonial, Shu Cai, Madalina Georgescu, Kira Griffitt, Ulf Hermjakob, Kevin Knight, Philipp Koehn, Martha Palmer, and Nathan Schneider. 2012. Abstract meaning representation (amr) 1.0 specification. In *Parsing on Freebase from Question-Answer Pairs. In Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*. Seattle: ACL, pages 1533–1544.
- Patrick Blackburn and Klaus Frovin Jørgensen. 2012. Indexical hybrid tense logic. *Advances in Modal Logic*, 9:144–60.
- Patrick Blackburn and Maarten Marx. 2002. Tableaux for quantified hybrid logic. In *Automated Reasoning with Analytic Tableaux and Related Methods*, pages 38–52, Berlin, Heidelberg. Springer Berlin Heidelberg.
- Jürgen Bohn, Werner Damm, Orna Grumberg, Hardi Hungar, and Karen Laster. 1998. First-order-ctl model checking. In *International Conference on Foundations of Software Technology and Theoretical Computer Science*, pages 283–294. Springer.
- Thomas Bolander and Torben Braüner. 2006. Tableau-based Decision Procedures for Hybrid Logic. *Journal of Logic and Computation*, 16(6):737–763.
- Johan Bos. 2016. Squib: Expressive power of Abstract Meaning Representations. *Computational Linguistics*, 42(3):527–535.
- Johan Bos. 2020. Separating argument structure from logical structure in AMR. In *Proceedings of the Second International Workshop on Designing Meaning Representations*, pages 13–20, Barcelona Spain (online). Association for Computational Linguistics.
- Lucia Donatelli, Michael Regan, William Croft, and Nathan Schneider. 2018. Annotation of tense and aspect semantics for sentential AMR. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 96–108, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Melvin Fitting. 1988. First-order modal tableaux. *Journal of Automated Reasoning*, 4(2):191–213.
- Melvin Fitting and Richard L Mendelsohn. 1998. *First-Order Modal Logic*, volume 277. Springer Science & Business Media.
- Jens Ulrik Hansen. 2007. A tableau system for a first-order hybrid logic. In *Proceedings of the International Workshop on Hybrid Logic (HyLo 2007)*, pages 32–40.
- Guillaume Hoffmann and Carlos Areces. 2009. Htab: a terminating tableaux system for hybrid logic. *Electronic Notes in Theoretical Computer Science*, 231:3–19. Proceedings of the 5th Workshop on Methods for Modalities (M4M5 2007).
- Kenneth Lai, Lucia Donatelli, and James Pustejovsky. 2020. A continuation semantics for Abstract Meaning Representation. In *Proceedings of the Second International Workshop on Designing Meaning Representations*, pages 1–12, Barcelona Spain (online). Association for Computational Linguistics.

- Markus Müller-Olm, David Schmidt, and Bernhard Steffen. 1999. Model-checking. In *International Static Analysis Symposium*, pages 330–354. Springer.
- James Pustejovsky, Ken Lai, and Nianwen Xue. 2019. Modeling quantification and scope in Abstract Meaning Representations. In *Proceedings of the First International Workshop on Designing Meaning Representations*, pages 28–33, Florence, Italy. Association for Computational Linguistics.