

Formalization of AMR Inference via Hybrid Logic Tableaux

Eli Goldner

June 19, 2021

Abstract

AMR and its extensions have become popular in semantic representation due to their ease of annotation by non-experts, attention to the predicative core of sentences, and abstraction away from various syntactic matter. An area where AMR and its extensions warrant improvement is formalization and suitability for inference, where it is lacking compared to other semantic representations, such as description logics, episodic logic, and discourse representation theory. This thesis presents a formalization of inference over a merging of ?'s (?) AMR extension for tense and aspect and with ?'s (?) AMR extension for quantification and scope. Inference is modeled with a merging of ?'s (?) tableau method for first-order hybrid logic with varying domain semantics (*FHL*) and ?'s (?) tableau method for basic hybrid tense logic (*BHTL*). We motivate the merging of these AMR variants, present their interpretation and inference in the combination of *FHL* and *BHTL*, which we will call *FHTL* (first-order hybrid tense logic), and demonstrate *FHTL*'s soundness, completeness, and decidability.

1 Merging Quantified Hybrid Logic and Indexical Hybrid Tense Logic

1.1 Background

1.2 First-order Hybrid Logic

?

from
?

1.3 Basic Hybrid Tense Logic

?

2 First-order Hybrid Tense Logic - Syntax and Semantics

The syntax of *FHTL* is identical to *FHL* as given in ? except uses of \downarrow as in $\downarrow w.\varphi$ are omitted along with \Box and \Diamond as in $\Box\varphi$ and $\Diamond\varphi$. \Box and \Diamond are replaced by their semantic equivalents F and G and their temporal duals P and H are added.

Atomic formulae are the same as in *FHL*, symbols in **NOM** and **SVAR** together with first-order atomic formulae generated from the predicate symbols and equality over the terms. Thus complex formulae are generated from the atomic formulae according to the following rules:

$$\neg\varphi \mid \varphi \wedge \psi \mid \varphi \vee \psi \mid \varphi \rightarrow \psi \mid \exists x\varphi \mid \forall x\varphi \mid F\varphi \mid G\varphi \mid P\varphi \mid H\varphi \mid @_n\varphi$$

Since we want the domain of quantification to be indexed over the collection of nominals/times, we look to ?'s (?) treatment of first-order modal logic with varying domain semantics and use it to alter the *FHL* model definition to the following:

$$(T, R, D_t, I_{nom}, I_t)_{t \in T}$$

Thus with varying domain semantics a *FHTL* model is identical to the definition for a *FHL* model in that:

- (T, R) is a modal frame.
- I_{nom} is a function assigning members of T to nominals.

The differences manifest on the level of the model and interpretation. Namely, where $D = \cup_{t \in T} D_t$, (D, I_t) is a first-order model where:

- $I_t(q) \in D$ where q is a unary function symbol.
- $I_t(P) \in D^k$ where P is a k -ary predicate symbol.

Notice we've relaxed the requirement that $I_t(c) = I_{t'}(c)$ for c a constant and $t, t' \in T$, since the interpretation of the constant need not exist at both times. This permits us to distinguish between the domain of a frame and the domain of a time/world, in a way that prevents a variable x from failing to refer at a given time/world, even if it has no interpretation at that time. Intuitively this permits *FHTL* to handle interpretation of entities in natural language utterances, which while reasonable to refer to do not exist at a current time, e.g. previous and future presidents.

Free variables are handled similarly as in *FHL*. Where again $D = \cup_{t \in T} D_t$, a *FHTL* assignment is a function:

$$g: \text{SVAR} \cup \text{FVAR} \rightarrow T \cup D$$

Where state variables are sent to times/worlds and first-order variables are sent to D , the domain of the frame. Thus given a model and an assignment g , the interpretation of terms t denoted by \bar{t} is defined as:

- $\bar{x} = g(x)$ for x a variable.
- $\bar{c} = I_t(c)$ for c a constant and some $t \in T$.
- For q a unary function symbol:

- For n a nominal:

$$\overline{@_n q} = I_{I_{nom}(n)}(q)$$

- For n a state variable:

$$\overline{@_n q} = I_{g(n)}(q)$$

Finally we say an assignment g' is an x -variant of g if g' and g on all variables except possibly x . In particular, we say g' is an x -variant of g at t , a time, if g' and g on all variables except possibly x and $g'(x) \in D_t$. We omit definitions for \wedge , \rightarrow , H , G , and \forall , since they can be defined in terms of the other rules. Given a model \mathfrak{M} , a variable assignment g , and a state s , the inductive definition of $\mathfrak{M}, s \models_g \varphi$ is:

$$\begin{aligned} \mathfrak{M}, s \models_g P(t_1, \dots, t_n) &\iff \langle \bar{t}_1, \dots, \bar{t}_n \rangle \in I_s(P) \\ \mathfrak{M}, s \models_g t_i = t_j &\iff \bar{t}_i = \bar{t}_j \\ \mathfrak{M}, s \models_g n &\iff I_{nom}(n) = s, \text{ for } n \text{ a nominal} \\ \mathfrak{M}, s \models_g w &\iff g(w) = s, \text{ for } w \text{ a state variable} \\ \mathfrak{M}, s \models_g \neg \varphi &\iff \mathfrak{M}, s \not\models_g \varphi \\ \mathfrak{M}, s \models_g \varphi \vee \psi &\iff \mathfrak{M}, s \models_g \varphi \text{ or } \mathfrak{M}, s \models_g \psi \\ \mathfrak{M}, s \models_g \exists x \varphi &\iff \mathfrak{M}, s \models_{g'} \varphi \text{ for some } x\text{-variant } g' \text{ of } g \text{ at } s \\ \mathfrak{M}, s \models_g F\varphi &\iff \mathfrak{M}, t \models_g \varphi \text{ for some } t \in T \text{ such that } Rst \\ \mathfrak{M}, s \models_g P\varphi &\iff \mathfrak{M}, t \models_g \varphi \text{ for some } t \in T \text{ such that } Rts \\ \mathfrak{M}, s \models_g @_n \varphi &\iff \mathfrak{M}, I_{nom}(n) \models_g \varphi \text{ for } n \text{ a nominal} \\ \mathfrak{M}, s \models_g @_w \varphi &\iff \mathfrak{M}, g(w) \models_g \varphi \text{ for } w \text{ a state variable} \end{aligned}$$

2.1 The Tableau Calculus

For **Nom** we have the constraint that if the premise $@_t \varphi$ are of the form $@_t Xc$ where $X \in \{F, P, \neg G, \neg H\}$ and c is a nominal or state variable, then $@_t \varphi$ is a root subformula. Similarly for **Nom**⁻¹ and the premise $@_s \varphi$.

In all rules in fig. 2, the nominal a is new to the branch. We have the additional constraint that if φ in the premise is a nominal or state variable, then the premise must be a root subformula in order for the rule to be applicable.

$$\begin{array}{c}
\frac{\frac{\textcircled{s}\textcircled{t}\varphi}{\textcircled{t}\varphi} [\textcircled{a}]}{\frac{\textcircled{s}Pt}{\textcircled{t}Fs} [P\text{--Trans}]} \\
\frac{\textcircled{s}Pt \quad \textcircled{t}u}{\textcircled{s}Pu} P\text{--Bridge} \\
\frac{\textcircled{s}t \quad \textcircled{s}\varphi}{\textcircled{t}\varphi} [\text{Nom}]
\end{array}
\qquad
\begin{array}{c}
\frac{\frac{\textcircled{s}\neg\textcircled{t}\varphi}{\textcircled{t}\neg\varphi} [\neg\textcircled{a}]}{\frac{\textcircled{s}Ft}{\textcircled{t}Ps} [F\text{--Trans}]} \\
\frac{\textcircled{s}Ft \quad \textcircled{t}u}{\textcircled{s}Fu} F\text{--Bridge} \\
\frac{[i \text{ on the branch}]}{\textcircled{i}i} [\text{ref}]
\end{array}$$

Figure 1: @ rules

$$\begin{array}{c}
\frac{\frac{\textcircled{s}F\varphi}{\textcircled{s}Fa} [F]}{\textcircled{a}\varphi} \\
\frac{\frac{\textcircled{s}P\varphi}{\textcircled{s}Pa} [P]}{\textcircled{a}\varphi}
\end{array}$$

Figure 2: F and P rules

Following ? we assume for each nominal or state variable s , there is an infinite list of parameters, where parameters are free variables which are never quantified over, arranged in such a way that different nominals/state variables never share the same parameter. Informally we write p_s to indicate a parameter is associated with a nominal/state variable s .

We also introduce the notion of a grounded term. A grounded term is either a first-order constant, a parameter, or a grounded definite description, i.e. a term of the form $\textcircled{n}q$ for n a nominal and q a unary function symbol.

$$\begin{array}{c}
\frac{\textcircled{s}\exists x\varphi}{\textcircled{s}\varphi[s:p/x]} [\exists] \\
\frac{\textcircled{s}\neg\exists x\varphi}{\textcircled{s}\neg\varphi[s:p/x]} [\neg\exists]
\end{array}$$

Figure 3: Quantifiers rules

In the existential rules fig. 3, $s:p$ is a parameter associated with the nominal s , with the requirement that it is new to the branch. Since parameters are never quantified over, $s:p$ is free in $\varphi[s:p/x]$.

In the universal rules ?? $s:p$ is any parameter at s .

$$\begin{array}{c}
\frac{}{\textcircled{i}j:t = j:t} \textbf{(ref)} \\
\frac{\textcircled{i}j:t = k:s \quad \textcircled{i}\varphi}{\textcircled{i}\varphi[j:t//k:s]} \textbf{(sub)}
\end{array}$$

Figure 4: Equality rules

2.2 Soundness and completeness

The proof of soundness and completeness of FHL in ? uses the notions of \diamond -completeness and \exists -completeness. As a result we substitute \diamond -completeness with the equivalent notion F -completeness and add the notion of P -completeness where the \exists -completeness stays the same as before. Thus set of @-formulae (formulae in the extended language (including parameters))

$$\begin{array}{c}
\frac{\textcircled{i}k_1:t = k_2:s}{\textcircled{i}k_1:t = k_2:s} \text{ (:1)} \qquad \frac{\textcircled{i}j}{\textcircled{k}i:t = j:t} \text{ (:2)} \qquad \frac{}{\textcircled{i}k:j:t = j:t} \text{ (:3)} \\
\\
\frac{\textcircled{i}R(t_1, \dots, t_n)}{\textcircled{i}R(i:t_1, \dots, i:t_n)} \text{ (:fix 1)} \qquad \frac{\textcircled{i}\neg R(t_1, \dots, t_n)}{\textcircled{i}\neg R(i:t_1, \dots, i:t_n)} \text{ (:fix 2)} \\
\\
\frac{\textcircled{i}t = s}{\textcircled{i}i:t = i:s} \text{ (:fix 3)} \qquad \frac{\textcircled{i}\neg t = s}{\textcircled{i}\neg i:t = i:s} \text{ (:fix 4)} \qquad \frac{}{\textcircled{i}f(t_1, \dots, t_n) = f(i:t_1, \dots, i:t_n)} \text{ (:func)}
\end{array}$$

Figure 5: *FHTL* term rules

$$\frac{\neg \textcircled{s}\varphi}{\textcircled{s}\neg\varphi} [\neg] \qquad \frac{\textcircled{s}\neg\varphi}{\neg \textcircled{s}\varphi} [\neg^{-1}]$$

Figure 6: Negation rules

of the form $\textcircled{i}\varphi$ is F -complete if:

$$\textcircled{i}F\varphi \in S \implies \textcircled{i}Fj \text{ or } \textcircled{j}Pi, \textcircled{j}\varphi \in S, \text{ for some nominal } j$$

A set of $\textcircled{\cdot}$ -formulae is P -complete if:

$$\textcircled{i}P\varphi \in S \implies \textcircled{i}Pj \text{ or } \textcircled{j}Fi, \textcircled{j}\varphi \in S, \text{ for some nominal } j$$

Soundness and completeness for *FHTL* follows straightforward modification of Hansen's proof of soundness and completeness for *FHL* in a way that reflects the new formulae of the form $\textcircled{i}P\varphi$.

2.3 Decidability

For our task of AMR inference, we are not concerned with the determining the general satisfiability or validity of an AMR formula translated into *FHTL*, but rather whether it holds in the smallest model consistent with an established set of *FHTL* translations of AMR sentences. This model will necessarily be finite, since across any finite number of AMR sentences only a finite number of times and entities can be referenced. In particular, we have a case of a local model-checking problem where given formula φ , a finite *FHTL* model structure \mathfrak{M} , a time t in \mathfrak{M} , and a variable assignment g , we need to determine whether $\mathfrak{M}, t \models_g \varphi$.

The proof of termination for every tableau construction is adapted from the proof given in ? for the termination of the tableau construction algorithm for $\mathcal{H}(\textcircled{\cdot})$.

Definition 2.1. When a formula $\textcircled{s}\varphi$ occurs in a tableau branch Θ we will write $\textcircled{s}\varphi \in \Theta$, and say φ is true at s on Θ or s makes φ true on Θ .

Definition 2.2. Given a tableau branch Θ and a nominal or state variable s the *set of true formulae* at s on Θ , is written $T^\Theta(s)$ and defined as follows:

$$T^\Theta(s) = \{\varphi \mid \textcircled{s}\varphi \in \Theta\}$$

$$\begin{array}{c}
\frac{\textcircled{s}(\varphi \vee \psi)}{\textcircled{s}\varphi \mid \textcircled{s}\psi} [\vee] \qquad \frac{\textcircled{s}\neg(\varphi \vee \psi)}{\textcircled{s}\neg\varphi \mid \textcircled{s}\neg\psi} [\neg\vee] \qquad \frac{\textcircled{s}\neg\neg\varphi}{\textcircled{s}\varphi} [\neg\neg]
\end{array}$$

Figure 7: Propositional rules.

$$\frac{\frac{\textcircled{s} \neg P \varphi \quad \textcircled{s} P t}{\textcircled{t} \neg \varphi} [H] \quad \frac{\textcircled{s} \neg F \varphi \quad \textcircled{s} F t}{\textcircled{t} \neg \varphi} [G]$$

Figure 8: G and H rules

Definition 2.3 (Quasi-subformula). A formula φ is a *quasi-subformula* of a formula ψ if one of the the following is the case:

1. φ is a subformula of ψ modulo substitution of free variables in φ for grounded terms.
2. φ is of the form $\neg \chi$ where χ modulo substitution of free variables in χ for grounded terms.

Altering the definition to allow grounded terms being substituted for free variables ensures compatibility of the following proofs with the universal, existential, and RR rules.

Definition 2.4 (Accessibility formula). A formula of the form $\textcircled{s} F t$ or $\textcircled{s} P t$ on Θ is called an *accessibility formula* if it is the first conclusion of an application of F or P .

Definition 2.5 (Term equality formula). A formula of the form $\textcircled{i} t = s$ where s and t are extended terms is called a term equality formula if it is a an immediate conclusion of (**ref**), (**:3**), or (**:func**), or has such a formula as an ancestor on the branch while being a conclusion of (**:1**), (**:2**), (**:fix 3**), or (**:fix 4**).

Definition 2.6 (Nominal equality formula). A formula of the form $\textcircled{s} t$ where s and t are nominals is a nominal equality formula if it is an immediate conclusion of (**:nom ref**) or has such a formula as an ancestor on the branch while being an immediate conclusion of (**:nom**)

Definition 2.7 (Root-subformula). Where the root formula of a tableau Θ is written root_Θ , a formula $\textcircled{s} \varphi$ occurring on a tableau Θ is called a *root-subformula* on Θ if it is a quasi-subformula of root_Θ .

Lemma 2.1 (Subformula Property). Where Θ is a tableau branch in the FHTL calculus, any formula $\textcircled{s} \varphi$ occurring on Θ is either a root-subformula, accessibility formula, or equality formula.

Proof. This is verified by induction on the tableau rules beginning with root_Θ as a base case. □

Definition 2.8 (\prec_Θ). Where Θ is a tableau branch in the FHTL calculus, if a nominal a is introduced to the branch by application of F , P , $\neg G$, or $\neg H$ to a premise $\textcircled{s} \varphi$, we say a is *generated* by s on Θ and write $s \prec_\Theta a$. We write \prec_Θ^* to denote the reflexive and transitive closure of \prec_Θ .

Definition 2.9 (Nom_Θ). The set of nominals and state variables which occur on Θ is written Nom_Θ

Lemma 2.2. Where Θ is a tableau branch in the FHTL calculus, the graph $G = (\text{Nom}_\Theta, \prec_\Theta)$ is a wellfounded finitely branching tree.

Proof. Each aspect is proved below:

- *Wellfoundedness of trees in G*

We have that if $a \prec_\Theta b$ then the first occurence of a on Θ is before the first occurence of b , thus by induction any subset of Nom_Θ under the relation \prec_Θ has a least element and each tree in G is wellfounded.

- *G is a tree*

Every nominal in Nom_Θ can be generated by at most one other nominal, and every nominal in Nom_Θ must have one of the finitely many nominals in the root formula as an ancestor.

- G is finitely branching

We show G is finitely branching by showing that given a nominal a , there can only be finitely many distinct nominals b such that $a \prec_{\Theta} b$. Each nominal b such that $a \prec_{\Theta} b$ is generated by applying one of the F , P , $\neg H$, $\neg G$ rules to a premise of the form $@_i F\varphi$, $@_i P\varphi$, $@_i \neg H\varphi$, or $@_i \neg G\varphi$ respectively, where by our restrictions, either φ is not a nominal, or the entire premise is a root subformula. Since there can only be finitely many root subformulae of the form of one of the the possible premises, where i is the prefix nominal in each case, only finitely many new nominals have been generated from i . Thus G is finitely branching. □

Lemma 2.3. *Where Θ is a tableau branch in the FHTL calculus, Θ is infinite if and only if there exists an infinite chain of nominals and state variables $a_1 \prec_{\Theta} a_2 \prec_{\Theta} \dots \prec_{\Theta} a_n \prec_{\Theta} \dots$*

Proof. Since the structure of the formulae and tableau rules are not involved in the proof from ? it holds here as well. □

Lemma 2.4. *Where Θ is a tableau branch in the FHTL calculus, if $@_s t \in \Theta$ where s and t are nominals then t is a root nominal.*

Lemma 2.5. *Where Θ is a tableau branch in the FHTL calculus, if $@_s Ft \in \Theta$ or $@_s Pt \in \Theta$ and t is not a root nominal then $s \prec_{\Theta} t$ or s and t denote the same time.*

Definition 2.10 (m_{Θ} and d_{Θ}). *Where Θ is a tableau branch in the FHTL calculus, a is a nominal/state variable occurring on Θ , and $|\@_s \varphi|$ denotes the length of the formula $@_s \varphi$, we define $m_{\Theta}(a)$ as:*

$$m_{\Theta}(a) = \max\{|\@_s \varphi| : @_s \varphi \in \Theta \text{ and } @_s \varphi \text{ is a root subformula}\}$$

If there are no root subformulae $@_a \varphi$ on Θ then $m_{\Theta}(a) = -\infty$. The *depth* of the nominal/state variable a with regard to Θ is the length of the unique path in $(Nom_{\Theta}, \prec_{\Theta})$ which connects the root nominal/state variable to a .

Lemma 2.6. *Where Θ is a tableau branch in the FHTL calculus, for any nominal/state variable on Θ , $m_{\Theta}(a) \leq |root_{\Theta}| - d_{\Theta}(a)$*

Lemma 2.7. *Where Θ is a tableau branch in the FHTL calculus, if for every nominal/state variable a in $root_{\Theta}$:*

$$m_{\Theta}(a) \leq |root_{\Theta}| - d_{\Theta}(a)$$

then Θ is finite.

Lemma 2.8. *Any tableau in the FHTL calculus is finite.*

Theorem 2.9. *The satisfiability of a finite set of FHTL sentences in a FHTL model is decidable.*

3 AMR Interpretation in Hybrid Logic

3.1 Examples

- (1) a. Carl submitted the forms and everyone will sign up again tomorrow.
- b.

```
(a / and
  :op1 (s / scope
    :pred (f / fill-out-03 :ongoing - :complete + :time (b / before :op1 (n / now))
    :ARG0 (p / person
      :name (n2 / name
        :op "Carl"))
    :ARG1 (f2 / form))
  :ARG0 p
  :ARG1 f2)
:op2 (s2 / scope
```

```

:pred (m / submit-01 :ongoing - :complete + :time (a2 / after :op1 n)
      :ARG0 (p2 / person
              :mod (a3 / all))
      :ARG1 f2)
:ARG0 p2
:ARG1 f2))

```

c. It was impossible not to notice the car.

d.

```

(s / scope
 :pred (p / possible-01
       :ARG0 (n / notice-01 :ongoing - :complete + :time (b / before :op1 (n2 / now))
               :polarity (n3 / not)
               :ARG1 (c / car)
               :polarity (n4 / not))
       :ARG0 n4
       :ARG1 p))

```

NB: Will complete these translations in full.

3.2 Extraction Steps

With the chosen annotation, the root node can consist of either a logical connective (and, or, or cond) linking two AMR graphs, or a scope node with its following predicate and arguments.

3.3 General Extraction Algorithm

Algorithm 1: Transform into clauses and connectives.

Input: AMR sentence

Output: *FHTL* formula

Def InterpretEntry (AMR) :

```

  root = Root(AMR)
  now = current date/time
  if root ∈ {and, or, cond} then
    connective = filter(root, {∧, ∨, →})
    clauses = []
    for op ∈ Children(root) do
      append(clauses, InterpretClause (op))
    end
    return @now join(connective, clauses)
  end
  return @now InterpretClause (root)

```

Def InterpretClause (AMR) :

Def Skolemize (UnaryPred) :

Def InferArg (PropBankPred) :

References

Patrick Blackburn and Klaus Frovin Jørgensen. 2012. Indexical hybrid tense logic. *Advances in Modal Logic*, 9:144–60.

- Patrick Blackburn and Maarten Marx. 2002. Tableaux for quantified hybrid logic. In *Automated Reasoning with Analytic Tableaux and Related Methods*, pages 38–52, Berlin, Heidelberg. Springer Berlin Heidelberg.
- Thomas Bolander and Patrick Blackburn. 2009. Terminating tableau calculi for hybrid logics extending k. *Electronic Notes in Theoretical Computer Science*, 231:21–39.
- Lucia Donatelli, Michael Regan, William Croft, and Nathan Schneider. 2018. Annotation of tense and aspect semantics for sentential AMR. In *Proceedings of the Joint Workshop on Linguistic Annotation, Multiword Expressions and Constructions (LAW-MWE-CxG-2018)*, pages 96–108, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Melvin Fitting and Richard L Mendelsohn. 1998. *First-Order Modal Logic*, volume 277. Springer Science & Business Media.
- Jens Ulrik Hansen. 2007. A tableau system for a first-order hybrid logic. In *Proceedings of the International Workshop on Hybrid Logic (HyLo 2007)*, pages 32–40.
- James Pustejovsky, Ken Lai, and Nianwen Xue. 2019. Modeling quantification and scope in Abstract Meaning Representations. In *Proceedings of the First International Workshop on Designing Meaning Representations*, pages 28–33, Florence, Italy. Association for Computational Linguistics.