	Result	Size	Time	Cycles	GPU	SM Frequency	Process	Attributes
Current	680 - brute_force_AL	(1024, 1, 1)x(1024, 1, 1)	1.10 ms	642,614	0 - Tesla T4	584.97 Mhz	[14378] exe	

Summary | Details | Source | Context | Comments | Raw | Session

Compare | Tools | View | Export

GPU Speed Of Light Throughput

All

High-level overview of the throughput for compute and memory resources of the GPU. For each unit, the throughput reports the achieved percentage of utilization with respect to the theoretical maximum. Breakdowns show the throughput for each individual sub-metric of Compute and Memory to clearly identify the highest contributor. High-level overview of the utilization for compute and memory resources of the GPU presented as a roofline chart.

Compute (SM) Throughput [%]	84.28	Duration [ms]	1.10
Memory Throughput [%]	1.14	Elapsed Cycles [cycle]	642,614
L1/TEX Cache Throughput [%]	1.02	SM Active Cycles [cycle]	623,294.78
L2 Cache Throughput [%]	0.45	SM Frequency [Mhz]	584.97
DRAM Throughput [%]	1.14	DRAM Frequency [Ghz]	4.99

High Throughput The kernel is utilizing greater than 80.0% of the available compute or memory performance of the device. To further improve performance, work will likely need to be shifted from the most utilized to another unit. Start by analyzing workloads in the Compute Workload Analysis section.

Roofline Analysis The ratio of peak float (fp32) to double (fp64) performance on this device is 32:1. The kernel achieved 2% of this device's fp32 peak performance and 0% of its fp64 peak performance. See the Kernel Profiling Guide for more details on roofline analysis.

GPU Throughput



Compute Throughput Breakdown

SM: Pipe Alu Cycles Active [%]	84.28
SM: Issue Active [%]	62.26
SM: Inst Executed [%]	62.25
SM: Inst Executed Pipe Adu [%]	38.54
IDC: Request Cycles Active [%]	22.02
SM: Pipe Fma Cycles Active [%]	17.41
SM: Mio Inst Issued [%]	13.02
SM: Mio Pq Read Cycles Active [%]	11.14
SM: Mio Pq Write Cycles Active [%]	11.14
SM: Inst Executed Pipe Cbu Pred On Any [%]	8.42
SM: Mio2rf Writeback Active [%]	5.63
SM: Inst Executed Pipe Lsu [%]	0.51
SM: Inst Executed Pipe Uniform [%]	0.06
SM: Memory Throughput Internal Activity [%]	0
SM: Pipe Tensor Cycles Active [%]	0
SM: Pipe Shared Cycles Active [%]	0
SM: Pipe Fp64 Cycles Active [%]	0
SM: Instruction Throughput Internal Activity [%]	0
SM: Inst Executed Pipe Xu [%]	0
SM: Inst Executed Pipe Tex [%]	0
SM: Inst Executed Pipe Ipa [%]	0
SM: Inst Executed Pipe Fp16 [%]	0

Memory Throughput Breakdown

DRAM: Cycles Active [%]	1.14
DRAM: Dram Sectors [%]	0.83
L1: M L1tex2xbar Req Cycles Active [%]	0.51
L1: Lsuin Requests [%]	0.51
L2: T Sectors [%]	0.45
L2: Xbar2lts Cycles Active [%]	0.44
L1: Data Pipe Lsu Wavefronts [%]	0.26
L2: D Sectors [%]	0.19
L1: Lsu Writeback Active [%]	0.13
GPU: Compute Memory Access Throughput Internal Activity [%]	0.11
L2: T Tag Requests [%]	0.11
L1: Data Bank Reads [%]	0.06
L1: Data Bank Writes [%]	0.06
L2: Lts2xbar Cycles Active [%]	0.00
L2: D Sectors Fill Device [%]	0.00
L1: Texin Sm2tex Req Cycles Active [%]	0.00
L1: F Wavefronts [%]	0.00
L1: M Xbar2l1tex Read Sectors [%]	0
L1: Tex Writeback Active [%]	0
L2: D Atomic Input Cycles Active [%]	0
L2: D Sectors Fill Sysmem [%]	0
L1: Data Pipe Tex Wavefronts [%]	0
GPU: Compute Memory Request Throughput Internal Activity [%]	0

Floating Point Operations Roofline



Floating Point Operations Roofline (Double Precision)



Floating Point Operations Roofline (Half Precision)



Floating Point Operations Roofline (Single Precision)



Tensor Core Operations Roofline



	# Operations	# Operations / Cycle	# Operations / s	Peak % Operations / Cycle	Peak Operations / Cycle	Peak Operations / s
Src:fp16,bf16,tf32 Dst:fp32	0	0	0	0	40,960	23,946.76
Src:fp16 Dst:fp16	0	0	0	0	40,960	23,946.76
Src:int1	0	0	0	0	81,920	47,893.53
Src:int4	0	0	0	0	81,920	47,893.53
Src:int8	0	0	0	0	81,920	47,893.53

GPU and Memory Workload Distribution

Analysis of workload distribution in active cycles of SM, SMP, SMSP, L1 & L2 caches, and DRAM

Average SM Active Cycles [cycle]	623,294.78	Average L1 Active Cycles [cycle]	623,294.78
Average L2 Active Cycles [cycle]	43,810.69	Average SMSP Active Cycles [cycle]	577,727.59
Average DRAM Active Cycles [cycle]	62,425.50	Total SM Elapsed Cycles [cycle]	25,689,640
Total L1 Elapsed Cycles [cycle]	25,689,640	Total L2 Elapsed Cycles [cycle]	30,053,792
Total SMSP Elapsed Cycles [cycle]	102,758,560	Total DRAM Elapsed Cycles [cycle]	43,876,352

Workload Distribution

	Average	Min	Max	Sum
SM Active Cycles	623,294.78	610,094	637,021	24,931,791
SMSP Active Cycles	577,727.59	563,311	592,635	92,436,414
L1 Active Cycles	623,294.78	610,094	637,021	24,931,791
L2 Active Cycles	43,810.69	43,264	44,430	1,401,942
DRAM Active Cycles	62,425.50	61,868	62,932	499,404