	Result	Size	Time	Cycles	GPU	SM Frequency	Process	Attributes
Current	660 - brute_force_AL	(1024, 1, 1)x(1024, 1, 1)	1.51 ms	886,034	0 - Tesla T4	584.98 Mhz	[17816] exe	

Summary | Details | Source | Context | Comments | Raw | Session

Compare | Tools | View | Export

GPU Speed Of Light Throughput

All

High-level overview of the throughput for compute and memory resources of the GPU. For each unit, the throughput reports the achieved percentage of utilization with respect to the theoretical maximum. Breakdowns show the throughput for each individual sub-metric of Compute and Memory to clearly identify the highest contributor. High-level overview of the utilization for compute and memory resources of the GPU presented as a roofline chart.

Compute (SM) Throughput [%]	84.51	Duration [ms]	1.51
Memory Throughput [%]	84.51	Elapsed Cycles [cycle]	886,034
L1/TEX Cache Throughput [%]	86.45	SM Active Cycles [cycle]	866,950.62
L2 Cache Throughput [%]	2.86	SM Frequency [Mhz]	584.98
DRAM Throughput [%]	1.21	DRAM Frequency [Ghz]	5.00

High Throughput The kernel is utilizing greater than 80.0% of the available compute or memory performance of the device. To further improve performance, work will likely need to be shifted from the most utilized to another unit. Start by analyzing workloads in the Compute Workload Analysis section.

Roofline Analysis The ratio of peak float (fp32) to double (fp64) performance on this device is 32:1. The kernel achieved 15% of this device's fp32 peak performance and 0% of its fp64 peak performance. See the Kernel Profiling Guide for more details on roofline analysis.

GPU Throughput



Compute Throughput Breakdown

SM: Inst Executed Pipe Lsu [%]	84.51
SM: Issue Active [%]	62.28
SM: Inst Executed [%]	62.28
SM: Pipe Alu Cycles Active [%]	50.83
SM: Inst Executed Pipe Xu [%]	40.64
SM: Pipe Fma Cycles Active [%]	35.27
SM: Mio Inst Issued [%]	28.30
SM: Mio2rf Writeback Active [%]	19.78
SM: Mio Pq Read Cycles Active [%]	1.96
SM: Mio Pq Write Cycles Active [%]	1.96
SM: Inst Executed Pipe Adu [%]	0.38
SM: Inst Executed Pipe Cbu Pred On Any [%]	0.37
IDC: Request Cycles Active [%]	0.19
SM: Memory Throughput Internal Activity [%]	0
SM: Pipe Tensor Cycles Active [%]	0
SM: Pipe Shared Cycles Active [%]	0
SM: Pipe Fp64 Cycles Active [%]	0
SM: Instruction Throughput Internal Activity [%]	0
SM: Inst Executed Pipe Uniform [%]	0
SM: Inst Executed Pipe Tex [%]	0
SM: Inst Executed Pipe Ipa [%]	0
SM: Inst Executed Pipe Fp16 [%]	0

Memory Throughput Breakdown

L1: Lsuin Requests [%]	84.51
L1: Data Pipe Lsu Wavefronts [%]	43.18
L1: Lsu Writeback Active [%]	39.37
L1: Data Bank Reads [%]	11.63
L1: M L1tex2xbar Req Cycles Active [%]	3.23
L2: T Sectors [%]	2.86
L2: Xbar2lts Cycles Active [%]	2.73
DRAM: Cycles Active [%]	1.21
L1: Data Bank Writes [%]	1.04
DRAM: Dram Sectors [%]	0.89
L2: D Sectors [%]	0.82
GPU: Compute Memory Access Throughput Internal Activity [%]	0.73
L2: T Tag Requests [%]	0.71
L1: M Xbar2l1tex Read Sectors [%]	0.50
L2: Lts2xbar Cycles Active [%]	0.43
L2: D Sectors Fill Device [%]	0.01
L1: F Wavefronts [%]	0.00
L1: Texin Sm2tex Req Cycles Active [%]	0.00
L1: Data Pipe Tex Wavefronts [%]	0
GPU: Compute Memory Request Throughput Internal Activity [%]	0
L1: Tex Writeback Active [%]	0
L2: D Atomic Input Cycles Active [%]	0
L2: D Sectors Fill Sysmem [%]	0

Floating Point Operations Roofline



Floating Point Operations Roofline (Double Precision)



Floating Point Operations Roofline (Half Precision)



Floating Point Operations Roofline (Single Precision)



Tensor Core Operations Roofline



	# Operations	# Operations / Cycle	# Operations / s	Peak %	Peak Operations / Cycle	Peak Operations / s
Src:fp16,bf16,tf32 Dst:fp32	0	0	0	0	40,960	23,982.37
Src:fp16 Dst:fp16	0	0	0	0	40,960	23,982.37
Src:int1	0	0	0	0	81,920	47,964.75
Src:int4	0	0	0	0	81,920	47,964.75
Src:int8	0	0	0	0	81,920	47,964.75

GPU and Memory Workload Distribution

Analysis of workload distribution in active cycles of SM, SMP, SMSP, L1 & L2 caches, and DRAM

Average SM Active Cycles [cycle]	866,950.62	Average L1 Active Cycles [cycle]	866,950.62
Average L2 Active Cycles [cycle]	184,791.12	Average SMSP Active Cycles [cycle]	863,041.50
Average DRAM Active Cycles [cycle]	91,684.50	Total SM Elapsed Cycles [cycle]	35,472,928
Total L1 Elapsed Cycles [cycle]	35,472,928	Total L2 Elapsed Cycles [cycle]	41,438,304
Total SMSP Elapsed Cycles [cycle]	141,891,712	Total DRAM Elapsed Cycles [cycle]	60,534,784

Workload Distribution

	Average	Min	Max	Sum
SM Active Cycles	866,950.62	846,978	881,263	34,678,025
SMSP Active Cycles	863,041.50	841,968	878,992	138,086,640
L1 Active Cycles	866,950.62	846,978	881,263	34,678,025
L2 Active Cycles	184,791.12	160,776	224,715	5,913,316
DRAM Active Cycles	91,684.50	87,036	101,128	733,476