Generation IV Nuclear Reactors: Safety and Efficiency

Vorwissenschaftliche Arbeit verfasst von

Elias Leitinger

Klasse 8B



Betreuer: Patrick Ritt

BRG Steyr Michaelerplatz Michaelerplatz 6 4400 Steyr

Steyr, March 2023

Abstract

This is a placeholder for the abstract. It summarizes the whole thesis to give a very short overview. Usually, this the abstract is written when the whole thesis text is finished.

Contents

Αb	strac	ct	ii					
1.	Basi	ic Concepts of Nuclear Power	1					
	1.1.	Fission	1					
	1.2.	Nuclear Cross Section	2					
	1.3.	Criticality	2					
	1.4.	Safety	3					
	1.5.	Efficiency	3					
		1.5.1. Cogeneration	3					
		1.5.2. Capacity Factor	4					
	1.6.	Fuel Cycle	4					
		1.6.1. Proliferation	4					
	1.7.	Components of Nuclear Reactors	5					
		1.7.1. Fuel	5					
		1.7.2. Moderator	6					
		1.7.3. Control Rods or Blades	7					
		1.7.4. Coolant	7					
2.	Historical Generational Developments of Nuclear Reactors							
	2.1.	Generation I	10					
	2.2.	Generation II	10					
	2.3.	Generation III	11					
	2.4.	Generation III+	11					
3.	Common Nuclear Reactor Types in Current Use							
		* *	12					
	3.2.	BWR – Boiling Water Reactor	13					
		PHWR – Pressurized Heavy Water Reactor	14					

Contents

4.	Generation IV									
	4.1.	Goals		16						
		4.1.1.	Economics	16						
		4.1.2.	Sustainability	17						
		4.1.3.	Safety and Reliability	17						
Α.	Righ	its		19						
	A.1.	Figure	s	19						
			Public Domain							
		A.1.2.	World Nuclear Association	19						
		A.1.3.	Canadian Nuclear Association	19						
	A.2.	Equati	ons	20						
		A.2.1.	Own Creation	20						
Bil	Bibliography									

1. Basic Concepts of Nuclear Power

Nuclear power reactors harness the heat generated by splitting atoms of certain elements in a controlled and predictable way. This heat is used to create electrical power¹.

1.1. Fission

Nuclear fission is the spontaneous or induced reaction, by which an atom is broken up. In the case of nuclear power reactors, these reactions are exothermic. Nuclear radiation such as in equation 1.1 already liberates a large amount of energy.

$$^{238}_{92}\text{U} \to ^{234}_{90}\text{Th} + \alpha, \ P = 8 \cdot 10^{-9} \frac{W}{g}$$
 (1.1)

This power is increased in nuclear reactors by 10 orders of magnitude. Although the effective lifespan is lowered from $4.468 \cdot 10^9$ years to a few months. Therefore fission is the main reaction trough which nuclear reactors generate the majority or their power output. An example of such a reaction is given in equation 1.2.²

$$^{235}_{92}\text{U} + n \rightarrow ^{236}_{92}\text{U}$$

$$^{236}_{92}\text{U} \rightarrow ^{144}_{56}\text{Br} + ^{39}_{36}\text{Kr} + 3n + 177 MeV}$$
(1.2)

It is important to note that 1.2 is a simplification of the actual decay series of $^{236}_{92}$ U into stable end products. 1.2 is sufficient to understand the principle

¹World Nuclear Association, 2022.

²Basdevant, Rich, and Spiro, 2005, p. 286.

behind nuclear fission. A decay series of $^{236}_{\ 92}\mathrm{U}$ with no intermediates removed is given in $1.3.^3$

$$^{236}_{92}U \rightarrow ^{137}_{53}I + ^{96}_{39}Y + 3n$$

$$^{137}I \rightarrow ^{137}Xe + e^{-} + \bar{v}_{e}, \quad t_{1/2} = 24.5s$$

$$^{137}Xe \rightarrow ^{137}Cs + e^{-} + \bar{v}_{e}, \quad t_{1/2} = 3.818min$$

$$^{137}Cs \rightarrow ^{137}Ba + e^{-} + \bar{v}_{e}, \quad t_{1/2} = 30.07a$$

$$^{96}Y \rightarrow ^{96}Zr + e^{-} + \bar{v}_{e}, \quad t_{1/2} = 5.36s$$

$$(1.3)$$

1.2. Nuclear Cross Section

Nuclear cross section describes the probability of a certain nuclear reaction to occur. This aspect needs thorough consideration in the design of nuclear reactors, as the nuclear cross section generally increases with the inverse of the velocities of the reactants⁴.

1.3. Criticality

Criticality is the operating condition of a nuclear reactor, in which the neutrons produced by fission events is sufficient to sustain a chain reaction. It is measured using the multiplication factor k. It is defined as in 1.4. If the factor k equals 1 the reaction is said to be critical. In a critical reaction, the number of neutrons causing a fission event remains constant. If the factor k is less than 1, the number of neutrons is decreasing and the chain reaction is said to be subcritical. If the factor k is grater than 1 the number of neutrons is increasing exponentially and the reaction is supercritical.^{5,6}.

$$k = \frac{number\ of\ neutrons\ involved\ in\ fission\ in\ generation\ n}{number\ of\ neutrons\ involved\ in\ fission\ in\ generation\ n\ -\ 1} \tag{1.4}$$

³Basdevant, Rich, and Spiro, 2005, p. 287.

⁴Basdevant, Rich, and Spiro, 2005, p. 108.

⁵Basdevant, Rich, and Spiro, 2005, p. 308.

⁶Stacey, 2018, p. 39.

In practice the reactivity ρ is used. It describes the change of the reactor away from the critical state. It is calculated using 1.5.

$$\rho = \frac{k-1}{k} \tag{1.5}$$

1.4. Safety

Safety is particularly important for nuclear power reactors, as they contain large amounts of radioactive material, which could be released into the environment in the case of an accident. During the ongoing fission reaction a large amount of radioactive isotopes, of which actinides are the most dangerous. Thus safety in nuclear power plants has three main objectives. Firstly, the reactor needs to operate normally without exposing operators and the environment to dangerous levels of radiation. Secondly, accidents need to be prevented as much as possible. Thirdly, in the case of an accident the consequences need to be minimized. Therefore for each reactors risks need to be carefully evaluated and their probabilities need to be carefully considered.

1.5. Efficiency

Like other power plants, current nuclear power reactors offer efficiencies between 30% and 35%. However with increased heat and cogeneration the efficiency of nuclear power plants could be increased dramatically⁸.

1.5.1. Cogeneration

Usually a large amount of energy is lost to the environment in the form of heat. This is usually destructive towards the environment and results in reduced efficiency. This heat could be used in cogeneration to supply heating to other

⁷Khalil, 2016, p. 793.

⁸Energy Education, 2022.

facilities or private housing, thereby reducing the amount of wasted, unused energy⁹.

1.5.2. Capacity Factor

TODO

1.6. Fuel Cycle

Currently spent fuel from nuclear reactors is sent to reprocessing facilities. There light actinides are separated from the remaining uranium and plutonium. Currently these actinides are treated as waste and stored in facilities to keep them from contaminating the environment. The uranium and plutonium remain in the form of oxides and are reused for mixed oxide fuels $(MOX)^{10}$.

1.6.1. Proliferation

A significant risk in the operation of nuclear power reactors is the proliferation of fission products for use in nuclear weapons. As older fast nuclear reactors produce a great deal of $^{239}_{94}$ Pu. Therefore proliferation resistance is a big consideration in the construction and development of new power reactors and technologies. A possible mitigation is the early removal of fuel, which is only partially spent from the reactor. This fuel contains nearly no $^{239}_{94}$ Pu, but instead contains $^{238}_{94}$ Pu, which cannot be used in weapons and cannot practically be turned into $^{239}_{94}$ Pu 11 .

⁹International Atomic Energy Association, 2018.

 $^{^{10}}$ Schullenberg, 2022, pp. 82–84.

¹¹Schullenberg, 2022, p. 87.

1.7. Components of Nuclear Reactors

1.7.1. Fuel

The reactor fuel is the fissile material used in the fission reaction inside of a reactor. In most cases uranium dioxide UO_2 pressed into pellets is used for this purpose. These pellets are put into tubular fuel rods. The whole fuel assembly inside the reactor consists of many such rods¹².

1.7.1.1. Startup Neutron Source

As the fission of uranium produces on average 2.4 neutrons per reaction, there does not need to be a constant external influx of neutrons. However, to start this chain reaction inside a new reactor equipped with newly made fuel rods a neutron source is needed. Usually beryllium combined with an alpha emitter is used for this purpose, as the collision of an α -particle with 9_4 Be releases a neutron as part of its reaction, as can be seen in equation $1.6^{13,14}$.

$${}_{4}^{9}\text{Be} + {}_{2}^{4}\text{He} \rightarrow {}_{6}^{12}\text{C} + n$$
 (1.6)

¹²World Nuclear Association, 2022.

¹³World Nuclear Association, 2022.

¹⁴Basdevant, Rich, and Spiro, 2005, p. 100.




Figure 1.1.: Nuclear cross section of ²³⁵U in relation to neutron energy

1.7.2. Moderator

Nuclear fission events release neutrons with energies in excess of multiple MeV, or speeds higher than $10^7 \frac{m}{s}$. However at these speeds the nuclear cross section of the fission reaction is quite low as can be seen in figure 1.1.

Therefore the emitted neutrons need to be slowed down in order to be useful. These are called thermal neutrons. This is done using a moderator. When passing through a moderator the neutrons are slowed down through collisions with the aforementioned. Although it is important to note that the moderator should absorb as few neutrons as possible to not hinder the chain reaction. For this reason $\rm H_2O$ and graphite are commonly used. ¹⁵

1.7.2.1. Fast Reactors

However, there is a category of reactors which harness fast neutrons in their nuclear reaction. These have no moderator and instead make use of fuel, which

¹⁵Stacey, 2018, p. 28.

requires a higher share of ²³⁵U as this reduces the chance of neutron capture by ²³⁸U and increases the likelihood of a fission event to occur. As actinides are fissile by fast neutrons, fast reactors may reduce the amount of transuranic nuclear waste generated by nuclear power production. There is still ongoing research regarding fast reactors to make them useful for widespread energy production. ¹⁶

1.7.3. Control Rods or Blades

In order to regulate the reaction speed inside of a nuclear reactor the number of neutrons inducing nuclear fission needs to be regulated. This is accomplished using control rods. As a single control rod with a circular cross section would lead to very nonuniform fission and temperature dynamics, the control rods are either arranged into cruciform blades or evenly spaced across the reactor in the form of clusters. A typical reactor contains around 50 clusters, each made up of 20 control rods^{17,18}.

These rods or blades contain materials which readily absorb neutrons, such as boron or cadmium. They may either be made of steel enriched with boron or hollow tubes filled with a brittle salt like material such as cadmium isotopes. Because the amount of fuel inside reactor steadily decreases, the amount of neutrons absorbed needs to be regulated in order for the chain reaction to continue. Therefore the control rods or blades are mounted on a movable apparatus, which extends or retracts the control rods into or out of the reactor, thereby regulating the amount of neutrons absorbed ¹⁹.

1.7.4. Coolant

The coolant is a liquid which circulates inside the nuclear reactor core to extract the thermal energy generated form the fission reactions. In most cases today this liquid is H_2O . In the case of boiling water reactors the water is boiled

¹⁶World Nuclear Association, 2022.

¹⁷Stacey, 2018, p. 72.

¹⁸Grayson, 2011.

¹⁹Grayson, 2011.

1. Basic Concepts of Nuclear Power

directly inside the core. In all other reactor types, such as pressurized water reactors at least a secondary, separated, coolant circuit is used, which transports the heat away from the primary circuit. When the water is not boiled inside the reactor core, a separate steam generator is used to create the steam, which drives the turbine. The same water which is used as a coolant may also be used as the rector moderator²⁰.

²⁰World Nuclear Association, 2022.

2. Historical Generational Developments of Nuclear Reactors

Nuclear reactors are normally categorised into generations. These generations differentiate reactors based on various technological factors such as cost-effectiveness, safety, commercial applicability and fuel cycle. These generations present a useful tool in categorizing nuclear reactors as multiple factors are combined into one single metric. It is important to not that all designs of generations I to III+ consist mainly of designs first developed in the late fourth decade of the 20th century with various improvements added. Figure 2.1 shows a timeline of nuclear reactor generations along with important notes on the properties of reactors in this generation. The images show representatives of each generation. It is important to note that the example image for gen-




Figure 2.1.: Timeline of nuclear reactor generations

¹Goldberg and R., 2011, pp. 1, 2.

eration IV is not representative, as the reactors of this generation are still in development and have not been built.

2.1. Generation I

The first generation of nuclear reactors consists primarily of research reactors and primitive nuclear power plants. These reactors are regarded as "proof of concept" in the USA. All reactors of this generation have been decommissioned or are undergoing deconstruction as their technological level is far behind that of newer reactors. Therefore they have very low cost-effectiveness and operational safety².

2.2. Generation II

The second generation of nuclear reactors represent the first efforts to produce nuclear reactors primarily designed for commercial viability. The comprise mainly boiling water reactors (BWR), pressurised water reactors (PWR), Canadian deuterium uranium reactors (CANDU) and advanced gas-cooled reactors (AGR). They are designed for an operational lifetime of 40 years. Generation II reactors are the most common generation for boiling water reactors and pressurised water reactors around the world, which can be categorised under the term light water reactor (LWR). These reactors feature more advanced safety features compared to generation I reactors. These safety have the ability to automatically prevent grievous incidents in the operation of a nuclear reactors, as they prevent dangerous incidents in cases such as loss of power or operator error.

Designs from this category require comparatively large electrical power grids. And feature advanced safety envelopes based on western standards. New reactors of this generation are mainly built in China, Russia and the Republic of Korea. Their fuel cycle requires high level waste repositories for ultimate disposition³.

²Goldberg and R., 2011, p. 3.

³Goldberg and R., 2011, pp. 4–6.

2.3. Generation III

In essence nuclear reactors of the third generation are the same designs as in the second generation with evolutionary improvements. These reactors feature improvements to fuel economy, thermal efficiency and and safety. These designs shift away from active safety systems to passive safety systems. They also feature a more standardised design, which leads to more economical construction costs. Designs such as the advanced boiling water reactor (ABWR) belong to this generation⁴.

2.4. Generation III+

As implied by the name nuclear reactors of the III+ generation feature another set of incremental improvements over the third generation. The main focus of these improvements lay in the improved safety of reactor systems as less operator intervention and fewer active components are utilized in reactor safety systems. These new safety systems utilize effects such as gravity to function. This leads to improved safety as a total failure of these safety systems is very unlikely compared to those of earlier generations. These reactors also have a higher expected operating lifetime of up to 60 years. The power plants of this generation also have increased fuel burn up. This has the consequence of reducing fuel consumption and reduced waste generation. Many reactors of this generation of different designs are in operation and construction around the globe⁵.

⁴Goldberg and R., 2011, pp. 5, 6.

⁵Goldberg and R., 2011, pp. 7–11.

3. Common Nuclear Reactor Types in Current Use

3.1. PWR – Pressurized Water Reactor

Pressurized water reactors harness H_2O as coolant and commonly also as moderator. However they have at least two coolant circuits. The water in the primary coolant circuit is under a large pressure in order to still remain liquid even at the high temperatures generated inside the reactor core. Between the primary and secondary coolant circuit lay a steam generator, which turns the cool water supplied in the secondary circuit into steam used to drive turbines. Special attention needs to be drawn to the fact, that primary and secondary circuit are never directly connected and therefore no radioactive material can be passed from inside the reactor core though the steam generator. Therefore only the reactor components which lay before the steam generator need to be under containment. A simplified schematic representation of a pressurized water reactor can be seen in 3.1. The turbine and cooling systems of every schematic are not shown, as this would exceed the scope of the explanations given herein and not contribute to the understanding of the reactor types shown.

¹World Nuclear Association, 2022.

²Khalil, 2016, pp. 14–84.




Figure 3.1.: Schematic representation of a pressurized water reactor

3.2. BWR - Boiling Water Reactor

Boiling water reactors are characterized by their mode of steam production. In comparison to pressurized water reactors, these reactors boil the water directly inside the reactor core. This has the advantage of significantly increasing the simplicity of reactor construction, because there is no need for a steam generator or secondary coolant loop. Like pressurized water reactors, boiling water reactors most commonly employ water as their moderator. Because the coolant water unavoidably comes into direct contact with the fuel rods, radioactive isotopes are leaked into the coolant water and therefore turbines. But as these isotopes almost unanimously consist of ¹⁶N, which has a short half life of 7 seconds. the access radiation is almost completely depleted after power generation. But due to the further spread of radioactive material a greater area of containment needs to be constructed for the nuclear power plant³. A schematic representation of a boiling water reactor is shown in 3.2

³Khalil, 2016, pp. 85–140.




Figure 3.2.: Schematic representation of a boiling water reactor

3.3. PHWR - Pressurized Heavy Water Reactor

Pressurized heavy water reactors also called CANDU for Canadian deuterium uranium reactor, utilize heavy water $\binom{3}{1}H_2O$ – also called D_2O) as coolant and moderator. The cylindrical fuel elements, which consist of multiple small fuel rods welded together, as shown in 3.4, rest inside zirconium alloy pressure tubes, through which the cooling heavy water flows. Many of these tubes are contained inside the calandria. The calandria itself is an enclosed chamber, which contains low pressure, low temperature heavy water used only as moderator. Because only the heavy water inside the zirconium alloy pressure tubes is under high pressure, the calandria need not be able to withstand the pressures, which are exerted upon the vessels housing pressurize water reactors and heavy water reactors. The only parts which need to withstand high mechanical stress are the pressure tubes, which can more easily be mass manufactured, due to their repetitiveness. Another advantage of this design is that single tubes can be refueled during reactor operation, as they can be disconnected, while other reactor designs need to be shut down completely before a change of fuel rods can occur. Pressurized heavy water reactors can also operate on unenriched




Figure 3.3.: Schematic representation of a pressurized heavy water reactor $\,$

natural uranium 4 . For a simplified representation of a reactor of this type see figure 3.3.



Figure 3.4.: Fuel element as used in PHWR $\,$

 $^{^4}$ Khalil, 2016, pp. 141–198.

4. Generation IV

Nuclear reactor systems of the fourth generation are a set of six novel reactor designs created with set goals in mind. This development effort is lead and governed by the Generation IV International Forum (GIF). The GIF has 14 Members: Argentina, Australia, Brazil, Canada, China, Euratom, France, Japan, Korea, the Russian Federation, South Afrika, Switzerland, the United Kingdom and the United States of Amerika. The GIF goal is to motivate research and development on new reactor systems¹.

4.1. Goals

Goals have been defined for nuclear reactor systems of the fourth generation. These goals can be categorised into four sections: Economics, Sustainability, Safety and Reliability and, Proliferation Resistance².

4.1.1. Economics

Generation IV nuclear reactors will have a lower total life-cycle cost when compared to nuclear reactors of previous generations. This means that over the energy produced by these nuclear reactor systems over their lifetime is higher in relation to the cost involved in building such a power plant. Additionally, these reactor systems will have comparable financial risks to other energy projects, which is especially important to make Generation IV systems competitive in

¹Generation IV International Forum, 2021, p. 6.

²Pioro et al., 2016, p. 38.

the marketplace. This also includes viability for a wider range of different ownership models and a wider array of possible energy supply roles³.

4.1.2. Sustainability

It is important for nuclear reactor systems of the fourth generation to make effective use of the resources involved in building and operating such a system. Another area of importance is the reduction and effective management of nuclear waste⁴.

4.1.3. Safety and Reliability

In nuclear reactors of previous generations a compromise between safety and reliability needs to be met, because these designs have not been designed with safety primarily in mind. Therefore an increase in safety mostly coincides with reduced reliability as these measures increase the complexity of the nuclear reactor and also decrease the amount of valid operating states. Because Generation IV nuclear reactors are designed from the ground up with inherent safety systems no compromise needs to be struck. Most of these novel designs feature passive protection against failure modes such as overheating⁵.

³Generation IV International Forum, 2021, p. 6.

⁴Pioro et al., 2016, p. 38.

⁵Generation IV International Forum, 2021, p. 6.

Appendix

Appendix A.

Rights

A.1. Figures

A.1.1. Public Domain

Figure 1.1 is released into the public domain and can therefore be used for any purpose.

A.1.2. World Nuclear Association

Rights are granted for educational use for figures 3.1, 3.2 and 3.3 as per https://www.world-nuclear.org/furniture/masterpage-items/permission-for-use-of-content.aspx

A.1.3. Canadian Nuclear Association

Rights are granted for educational use for figure 3.4 as per https://cna.ca/terms-of-use/

A.2. Equations

A.2.1. Own Creation

Equations 1.1, 1.2, 1.3, 1.4 and 1.6 were typeset by the author with information taken from 1 .

¹Oka and SpringerLink (Online service), 2014.

Bibliography

- Basdevant, J.L., J. Rich, and Michael Spiro (2005). Fundamentals in Nuclear Physics: From Nuclear Structure to Cosmology. Advanced Texts in Physics S. Springer. ISBN: 9780387016726 (cit. on pp. 1, 2, 5).
- Energy Education (2022). Energy Education: Nuclear Power. URL: https://energyeducation.ca/encyclopedia/Nuclear_power_plant (visited on 10/22/2022) (cit. on p. 3).
- Generation IV International Forum (2021). Annual Report. Generation IV International Forum (cit. on pp. 16, 17).
- Goldberg, S. M. and Rosner R. (2011). *Nuclear Reactors: Generation to Generation*. American Academy of Arts and Sciences. ISBN: 0-87724-090-6 (cit. on pp. 9–11).
- Grayson, James (2011). Control Rods in Nuclear Reactors. URL: http://large.stanford.edu/courses/2011/ph241/grayson1/ (visited on 10/11/2022) (cit. on p. 7).
- International Atomic Energy Association (June 2018). Nuclear Power beyond Electricity: towards Greater Efficiency in Energy Production and Water Management. URL: https://www.iaea.org/newscenter/news/nuclear-power-beyond-electricity-towards-greater-efficiency-in-energy-production-and-water-management (visited on 10/22/2022) (cit. on p. 4).
- Khalil, Yehia F. (2016). *Nuclear Engineering Handbook*. CRC Press. DOI: 10.1201/9781315373829-23 (cit. on pp. 3, 12, 13, 15).
- Oka, Yoshiaki. and SpringerLink (Online service) (2014). *Nuclear Reactor Design*. An Advanced Course in Nuclear Engineering, Tokyo: Springer Japan: (cit. on p. 20).
- Pioro, I.L. et al. (2016). *Handbook of Generation IV Nuclear Reactors*. Ed. by Igor L. Pioro. Woodhead Publishing Series in Energy. Woodhead Publishing. ISBN: 978-0-08-100149-3 (cit. on pp. 16, 17).

- Schullenberg, Thomas (2022). The Fourth Generation of Nuclear Reactors -Fundamentals, Types and Benefits Explained. Springer. ISBN: 978-3-662-64918-3 (cit. on p. 4).
- Stacey, Weston M. (2018). *Nuclear reactor physics*. 3rd, revised edition. Weinheim, Germany: Wiley-VCH (cit. on pp. 2, 6, 7).
- World Nuclear Association (Aug. 2022). Nuclear Power Reactors. URL: https://world-nuclear.org/information-library/nuclear-fuel-cycle/nuclear-power-reactors/nuclear-power-reactors.aspx (visited on 09/25/2022) (cit. on pp. 1, 5, 7, 8, 12).

List of Figures

1.1.	Nuclear cross section of ²³⁵ U in relation to neutron energy, CC from: https://en.wikipedia.org/wiki/File:U235_Fission_cross_section.	ion.png 6
2.1.	Timeline of nuclear reactor generations	9
3.1.	Schematic representation of a pressurized water reactor, rights granted from: https://world-nuclear.org/gallery/reactor-diagrams/pwater-reactor.aspx	
3.2.	Schematic representation of a boiling water reactor, rights granted from: https://world-nuclear.org/gallery/reactor-diagrams/boiling-	1.4
3.3.	water-reactor.aspx	14
3.4.	7 0 0	

Eidesstattliche Erklärung

Ich, Elias Leitinger, erkläre hiermit eidesstattlich, dass ich diese vorwissenschaftliche Arbeit selbständig und ohne Hilfe Dritter verfasst habe. Insbesondere versichere ich, dass ich alle wörtlichen und sinngemäßen Übernahmen aus anderen Werken als Zitate kenntlich gemacht und alle verwendeten Quellen angegeben habe.

Steyr, am			
	Datum		Unterschrift