

Implementation Guide

– *Track Shipments* Template App

Contents

0. Prerequisites	2
1. Environment Configuration in SAP Business Network Global Track and Trace	2
1.1 Enable Cloud Foundry and Create Space	2
1.2 Maintain Roles and Users	4
1.3 Maintain Technical User	6
1.4 Maintain Destination of GTT Core Engine Base URL	9
2. Implement <i>Track Shipments</i> Template App	11
2.1 Download Template Code	11
2.2 Download and Setup Tools	11
2.3 Deploy Model	12
2.4 Package and Deploy	13
2.4.1 Login to SAP Cloud Foundry	13
2.4.2 Package and Deploy <i>Track Shipments</i> Frontend App	14
2.4.3 Package and Deploy SAP Fiori Launchpad for <i>Template Applications</i>	16
2.4.4 Package and Deploy <i>Track Shipments</i> Backend Service	24
2.4.5 Check Deployed Apps on SAP Cloud Foundry Cockpit	25
2.4.6 Maintain Destination of Forwarding	26
2.4.7 Maintain Roles and Users	28
2.4.8 Open <i>Track Shipments</i> Template App from SAP Fiori Launchpad	28
3. Implement ERP Extractor	29
4. Other Configuration	30
4.1 Obtain Here Map License	30
4.2 Maintain Location Master	30
4.3 Maintain Data Contributors	31
4.4 Integrate with Visibility Provider	31


0. Prerequisites

- You have an SAP Cloud Platform global account with the entitlement to SAP Business Network Global Track and Trace, and the account is assigned 1 portal service quota and 2 GB Application Runtime quota.
Please refer to the 1st Q&A in “FAQs for Template Code Implementation” for guidance on how to add quotas.


1. Environment Configuration in SAP Business Network Global Track and Trace

1.1 Enable Cloud Foundry and Create Space

- Click “Enable Cloud Foundry” to enable the development landscape



- b. Fill in the Organization Name and click “Create”




Create Cloud Foundry Organization

Organization Name *

GTT_APPS

Create Cancel

- c. Go to “Cloud Foundry” -> “Spaces”
Click “Create Space”
Fill in the Space Name and click “Create”



Cloud Foundry

Spaces

Quota Plans

Org. Members

HTML5 Applications

Connectivity

Destinations

Cloud Connectors

Security

Create Space

Space Name: *

development

Assign space roles to

☒ Space Manager

☒ Space Developer

☐ Space Auditor

Applications

2 Started

2 Stopped

Quota


1.25 of 15GB Memory

5 of 1500 Services

Learn how

1.2 Maintain Roles and Users


1. Go to “Security” -> “Role Collections”



2. Create 2 role collections (You can have user-defined names):

gtt-sample-all

gtt-sample-integration



- Role template “gtt-sample-all” is granted to users who have access to SAP Business Network Global Track and Trace and *Track Shipments* template app.
- Role template “gtt-sample-integration” is granted to technical users only who have access to the global track and trace APIs for development purpose.

- Go to the role of “gtt-sample-all”, and add the following roles:

Role	Application
MessageLogAdminTemplate	lbn_gtt_core
DataModelAdminTemplate	lbn_gtt_core
LocationProcessTemplate	lbnplatform-loc-broker
BPEditTemplate	lbnplatform-bprepo
BusinessPartnerDiscoveryTemplate	lbnplatform-bprepo
InviteBPPProcessTemplate	lbnplatform-bprepo
ManageInvitationsProcessTemplate	lbnplatform-bprepo
BlockStoreProcessTemplate	lbn-retentionmanagement-sb
ReminderTemplateProcessTemplate	lbn-retentionmanagement-sb

- Grant "gtt-sample-all" to your **application** users:
 - Application users are those who have access to SAP Business Network Global Track and Trace and *Track Shipments* template app.

IT Administrator needs to maintain application users in identity provider.

For example, user1@sap.com


Users (51)				
Search				
ID	Identity Provider	E-Mail	First Name	Last Name
[REDACTED]@sap.com	SAP ID Service	[REDACTED]@sap.com	[REDACTED]	[REDACTED]
[REDACTED]@sap.com	SAP ID Service	[REDACTED]@sap.com	[REDACTED]	[REDACTED]
[REDACTED]@sap.com	SAP ID Service	[REDACTED]@sap.com	[REDACTED]	[REDACTED]

Note: The application user in this step should be different from the technical user created in Step 1.3. A user should **never** be assigned to **both** “gtt-sample-all” and “gtt-sample-integration”.

1.3 Maintain Technical User

- a. Go to the SAP Cloud Platform to create the technical user account:
<https://account.hana.ondemand.com/#/home/welcome>

Click "Register"



- b. Fill in the mandatory fields:

Tell us about yourself

E-mail address *	First name *
Last name *	Company *
Country/Region United States	Phone +1 XXX-XXX-XXXX
Department *	Relationship to SAP *
Create password *	Confirm password *

Must have at least 8 characters.


☐ I have read and understood the Terms and Conditions of [SAP.com](#)

SAP will use any of the data provided hereunder in accordance with the [Privacy Statement](#).

This site is protected by reCAPTCHA and the Google [Privacy Policy](#) and [Terms of Service](#) apply.

Submit

- c. Go to the mail inbox to activate the account




- d. As shown in Step 1.2, go to the role of “gtt-sample-integration”, and add the following roles:

Role	Application
EMIDocIntegrationTemplate	lbn_gtt_core
MetadataServiceIntegrationTemplate	lbn_gtt_core
ReadServiceIntegrationTemplate	lbn_gtt_core
WriteServiceIntegrationTemplate	lbn_gtt_core
LocationProcessTemplate	lbnplatform-loc-broker

- e. Grant "gtt-sample-integration" to your **technical** user:


For example, techuser1@techcompany.com



Note:

In the “Identity Provider” field, select “Default identity provider”.

- f. Go to SAP Fiori Launchpad for SAP Business Network Global Track and Trace
Open *Manage Business Profile* app



- g. Add one Alternate Identifier:
Identifier Type: Technical User
ID: the email address of technical user


Email	Phone Number
<input type="text"/>	<input type="text"/>

Alternate Identifiers (1)	
Identifier Type	ID
<input type="text" value="Technical User"/>	<input type="text" value="...@...com"/>

Note: The technical user in this step should be different from the application user in Step 1.2.4. A user should **never** be assigned to **both** "gtt-sample-all" and "gtt-sample-integration".

1.4 Maintain Destination of GTT Core Engine Base URL

- Go to “Destinations”



- Configure Destination of GTT Core Engine Base URL

Name	gtt_core_engine_flp_base_url
Type	HTTP
Description	<optional>
URL	Input the GTT Fiori Launchpad URL and add “/api” at the end of it For example: https://xxxxx.gtt-flp-lbnplatform.cfapps.eu10.hana.ondemand.com/api For the instructions on how to get the GTT Fiori Launchpad URL, see the note under this table
Proxy Type	Internet
Authentication	BasicAuthentication
User	Email of Technical User from Step 1.3
Password	Password of Technical User from Step 1.3

Note:

- On your subaccount page, click “Instances and Subscriptions” in the “Service” tab and click “Global Track and Trace” application. Click “Go to Application”.
- Copy the GTT Fiori Launchpad URL:


[https://\[REDACTED\]gtt-flp-lbnplatform.cfapps.eu10.hana.ondemand.com/cp.portal/site#Shell-home](https://[REDACTED]gtt-flp-lbnplatform.cfapps.eu10.hana.ondemand.com/cp.portal/site#Shell-home)

2. Implement *Track Shipments* Template App

2.1 Download Template Code

Go to <https://github.com/SAP-samples/logistics-business-network-gtt-samples>.

Download and extract, or git clone the template code from SAP-samples on GitHub.



Commented [LS1]: Needs to be replaced

2.2 Download and Setup Tools

a. Install JDK 8 and Maven

JDK 8: <https://www.oracle.com/java/technologies/javase/javase-jdk8-downloads.html>

Maven: <https://maven.apache.org/download.cgi>

b. Install NPM, Node JS, and grunt-cli

Node JS 12: <https://nodejs.org/dist/latest-v12.x/>

For the instructions on how to install Node JS and NOM, see <https://www.saplearners.com/how-to-install-node-js-and-npm/>

Run the following command after NPM is installed:

```
npm config set @sap:registry "https://npm.sap.com" -g
```

c. Install Cloud Foundry Command Line Interface

<https://developers.sap.com/tutorials/cp-cf-download-cli.html>

d. Install MultiApps CF CLI Plugin

<https://github.com/cloudfoundry-incubator/multiapps-cli-plugin>

e. Install Cloud MTA Build Tool (MBT)


<https://sap.github.io/cloud-mta-build-tool/download/>

f. Install MAKE


<https://sap.github.io/cloud-mta-build-tool/makefile/>

2.3 Deploy Model

- Go to the folder *model* with downloaded source code. Make sure you have a JSON file *sof-model-YYYYMMDDxx.json* (e.g. *sof-model-2020091001.json*).
- Open *Manage Models* app on SAP Fiori Launchpad for global track and trace
- Click “Import”
- Click “Browse” to select the *sof-model-YYYYMMDDxx.json* file
- Click “Import” to import the model




- Click “Deploy”
- Write down the model namespace for later use, in this case, “com.lbgnttsamples.gtt.app.sof” in the picture below



- Click “Edit”

- Go to *Event to Action* tab
- Replace all the namespace strings, in this case, “com.lbngttsamples.gtt.app.sof” in *Event to Action* script with the model namespace you wrote down in the previous step
- Click “Save and Deploy” to deploy the model



2.4 Package and Deploy

2.4.1 Login to SAP Cloud Foundry

- Open a command window, *cf login* to SAP Cloud Foundry with your username and password
- Select the organization and space in which you want to deploy the template apps

```
MINGW64
Authenticating...
OK
Select an org:
1. [redacted]
2. [redacted]
3. [redacted]
4. [redacted]
5. [redacted]
6. [redacted]

Org (enter to skip): 6
Targeted org [redacted]

Select a space:
1. acc
2. perf
3. int
4. inthf
5. sbx


Space (enter to skip): 5
Targeted space [redacted]

API endpoint: https://api.cf.sap.hana.ondemand.com (API version: 3.81.0)
User: [redacted]
Org: [redacted]
Space: [redacted]
```

2.4.2 Package and Deploy *Track Shipments* Frontend App

Go to GTT-V2-Sample-TrackShipments-UI directory.


- Open the `./UI/.env` file
- Replace `{tenant-name}` with the middle part of the namespace you got from Step 2.3.



In the command line tool,

- Run the following command to build the MTAR package:
`mbt build`

A MTAR file `./mta_archives/gtt-v2-ui-sample-track-shipments_xxx.mtar` is then generated.



- To deploy the MTAR package in Cloud Foundry, run the following command:

```
cf deploy ./mta_archives/gtt-v2-ui-sample-track-shipments_xxx.mtar
```

The deployment time depends on your network conditions.

2.4.3 Package and Deploy SAP Fiori Launchpad for *Template Applications*

Go to GTT-V2-Sample-App-FLP directory.

- First ensure that at least 1 portal quota is assigned to the subaccount in which apps are deployed.
You can refer to the 1st Q&A in *FAQs for Template Code Implementation* for guidance on how to add quotas.
 - Open the *mta.yaml* file
 - Replace {unique-identifier} with unique information such as your company name or cloud foundry global account name
- Note:
- {unique-identifier} must only contain lowercase letters, numbers and hyphens "-". For example, "company-s01".
 - For the length of "routes", the maximum limit is 63 characters.

```
1 ---
2 ID: lbn-gtt-sample-app-flp
3 _schema-version: "3.1"
4 parameters:
5   deploy_mode: html5-repo
6   enable-parallel-deployments: true
7   append: "${space}"
8   xsappname: tt_sof_${append}
9 version: 2.3.0
10 modules:
11 - name: lbn-gtt-sample-app-appRouter
12   type: approuter.nodejs
13   path: flp_appRouter
14   parameters:
15     disk-quota: 256M
16     memory: 256M
17     routes:
18     - route: lbn-gtt-samples-app-flp-{unique-identifier} ${domain}
19   properties:
20     SAP_JWT_TRUST_ACL:
21     - clientid: "*"
22       identityzone: "*"
23   destinations:
24   - name: lbn-gtt-sof-ani
```



```

resources:
- name: lbn-gtt-sample-app-runtime
  parameters:
    service-plan: app-runtime
    service: html5-apps-repo
  type: org.cloudfoundry.managed-service
- name: lbn-gtt-sample-portal-resources
  parameters:
    service-plan: standard
    service: portal
  type: org.cloudfoundry.managed-service
- name: lbn-gtt-sof-api
  properties:
    url: https://gtt-sample-track-salesorders-service-{unique-identifier}.${default-domain}
- name: lbn-gtt-sst-api
  properties:
    url: https://gtt-sample-track-shipments-service-{unique-identifier}.${default-domain}
- name: lbn-gtt-pof-api
  properties:
    url: https://gtt-sample-track-purchaseorders-service-{unique-identifier}.${default-domain}
- name: lbn-gtt-sample-app-uaa
  type: com.sap.xs.uaa-application
  parameters:

```

This FLP project includes 3 template applications which are Track SO Fulfillment, Track Shipments and Track Purchase Orders. Before you build and deploy it, please deploy all the UI projects you need in advance, otherwise the deploy of this project will fail.

If you only need Track Shipments app, do the following changes:

- Open the *mta.yaml* file
- Delete *lbn-gtt-sof-api* and *lbn-gtt-pof-api* in *lbn-gtt-sample-app-appRouter* and *resources* modules
- Delete *gtt-ui-sample-track-salesorders-app-host* and *gtt-ui-sample-track-purchaseorders-app-host* in *flp* and *resources* module

```

1  ...
2  ID: lbn-gtt-sample-app-flp
3  _schema-version: "3.1"
4  parameters:
5    deploy_mode: html5-repo
6    enable-parallel-deployments: true
7    append: "${space}"
8    xsappname: tt_sof_${append}
9    version: 2.3.0
10 modules:
11   - name: lbn-gtt-sample-app-appRouter
12     type: approuter.nodejs
13     path: flp_appRouter
14     parameters:
15       disk-quota: 250M
16       memory: 250M
17     routes:
18       - route: lbn-gtt-samples-app-flp-{unique-identifier}.${domain}
19     properties:
20       SAP_INT_TRUST_ACL:
21         - clientId: ""
22         identityzone: ""
23     destinations:
24       - name: lbn-gtt-sof-api
25         url: "${lbn-gtt-sof-api/url}"
26         forwardAuthToken: true
27       - name: lbn-gtt-sst-api
28         url: "${lbn-gtt-sst-api/url}"
29         forwardAuthToken: true
30       - name: lbn-gtt-pof-api
31         url: "${lbn-gtt-pof-api/url}"
32         forwardAuthToken: true
33     requires:
34       - name: lbn-gtt-sample-app-uaa
35       - name: lbn-gtt-sample-app-runtime
36       - name: lbn-gtt-sample-portal-resources
37       - name: lbn-gtt-sof-api
38       - name: lbn-gtt-sst-api
39       - name: lbn-gtt-pof-api
40   - name: flp
41     type: com.sap.portal.content
42     path: flp
43     parameters:
44       stack: cflinuxfs3
45       memory: 128M
46       buildpack: https://github.com/cloudfoundry/nodejs-buildpack/releases/download/v1.6.39/nodejs-buildpack-cflinuxfs3-v1.6.39.zip
47     requires:
48       - name: lbn-gtt-sample-app-uaa
49       - name: lbn-gtt-sample-portal-resources
50       - name: gtt-ui-sample-track-salesorders-app-host
51       - name: gtt-ui-sample-track-shiptoorders-app-host
52       - name: gtt-ui-sample-track-purchaseorders-app-host

```

```

53 resources:
54   - name: lbn-gtt-sample-app-runtime
55     parameters:
56       service-plan: app-runtime
57       service: html5-apps-repo
58     type: org.cloudfoundry.managed-service
59   - name: lbn-gtt-sample-portal-resources
60     parameters:
61       service-plan: standard
62       service: portal
63     type: org.cloudfoundry.managed-service
64   - name: lbn-gtt-sof-api
65     properties:
66       url: https://gtt-sample-track-salesorders-service-{unique-identifier}.${default-domain}
67   - name: lbn-gtt-sst-api
68     properties:
69       url: https://gtt-sample-track-shipsments-service-{unique-identifier}.${default-domain}
70   - name: lbn-gtt-pof-api
71     properties:
72       url: https://gtt-sample-track-purchaseorders-service-{unique-identifier}.${default-domain}
73   - name: lbn-gtt-sample-app-uaa
74     type: com.sap.xs.uaa-application
75     parameters:
76       config:
77         xsappname: "${xsappname}"
78         tenant-mode: dedicated
79         oauth2-configuration:
80           system-attributes:
81             - rolecollections
82         description: Security profile of sales order fulfillment application
83       scopes:
84         - name: "XSAPPNAME.sof.r"
85           description: Allow to access sales order fulfillment application
86         - name: "XSAPPNAME.pof.r"
87           description: Allow to access purchase order fulfillment application
88         - name: "XSAPPNAME.sst.r"
89           description: Allow to access standalone shipment tracking application
90         - name: "XSAPPNAME.sst.w"
91           description: Allow to report events in standalone shipment tracking application
92         - name: uaa.user
93           description: UAA
94       authorities:
95         - "XSAPPNAME.sof.r"
96         - "XSAPPNAME.pof.r"
97         - "XSAPPNAME.sst.r"
98         - "XSAPPNAME.sst.w"
99         - uaa.user
100     role-templates:
101       - name: SalesOrderFulfillmentAppUserDisplayTemplate
102         description: Track & Trace Sales Order Fulfillment Template App User Read Access
103         scope-references:
104           - "XSAPPNAME.sof.r"
105           - uaa.user

```

```

88     - name: "SXSAPPNAME.sst.r"
89       description: Allow to access standalone shipment tracking application
90     - name: "SXSAPPNAME.sst.w"
91       description: Allow to report events in standalone shipment tracking application
92     - name: uaa.user
93       description: UAA
94   authorities:
95     - "SXSAPPNAME.sof.r"
96     - "SXSAPPNAME.pof.r"
97     - "SXSAPPNAME.sst.r"
98     - "SXSAPPNAME.sst.w"
99     - uaa.user
100   role-templates:
101     - name: SalesOrderFulfillmentAppUserDisplayTemplate
102       description: Track & Trace Sales Order Fulfillment Template App User Read Access
103       scope-references:
104         - "SXSAPPNAME.sof.r"
105         - uaa.user
106     - name: PurchaseOrderFulfillmentAppUserDisplayTemplate
107       description: Track & Trace Purchase Order Fulfillment Template App User Read Access
108       scope-references:
109         - "SXSAPPNAME.pof.r"
110         - uaa.user
111     - name: StandaloneShipmentTrackingAppUserDisplayTemplate
112       description: Track & Trace Standalone Shipment Tracking Template App User Read Access
113       scope-references:
114         - "SXSAPPNAME.sst.r"
115         - uaa.user
116     - name: StandaloneShipmentTrackingAppUserProcessTemplate
117       description: Track & Trace Standalone Shipment Tracking Template App User Write Access
118       scope-references:
119         - "SXSAPPNAME.sst.w"
120         - uaa.user
121     - name: gtt-ui-sample-track-salesorders-app-host
122       type: org.cloudfoundry.existing-service
123     - name: gtt-ui-sample-track-shipments-app-host
124       type: org.cloudfoundry.existing-service
125     - name: gtt-ui-sample-track-purchaseorders-app-host
126       type: org.cloudfoundry.existing-service
127     - name: lbn-gtt-sample-destination
128       type: org.cloudfoundry.managed-service
129   parameters:
130     service-plan: lite
131     service: destination

```

- Open the *flp/portal-site/CommonDataModel.json* file
- Delete viz items *com.sap.gtt.app.sample.sof* and *com.sap.gtt.app.sample.pof* in *payload/catalogs/payload/viz* array
- Delete groups *salesOrder* and *purchaseOrder* in *payload/groups* array
- Delete orders *salesOrder* and *purchaseOrder* in *payload/sites/payload/groupsOrder* array

```

1 {
2   "_version": "3.0.0",
3   "identification": {
4     "id": "ea7d38d8-c86c-48b1-8f02-c28c4e10f54-1578021444073",
5     "entityType": "bundle"
6   },
7   "payload": {
8     "catalogs": [
9       {
10        "_version": "3.0.0",
11        "identification": {
12          "id": "defaultCatalogId",
13          "title": "({{title}})",
14          "entityType": "catalog",
15          "i18n": "i18n/defaultCatalogId.properties"
16        },
17        "payload": {
18          "viz": [
19            {
20              "id": "com.sap.gtt.app.sample.sof",
21              "vizId": "SalesOrder-track"
22            },
23            {
24              "id": "com.sap.gtt.app.sample.sst",
25              "vizId": "Shipment-track"
26            },
27            {
28              "id": "com.sap.gtt.app.sample.pof",
29              "vizId": "PurchaseOrder-track"
30            }
31          ]
32        }
33      ]
34    },
35    "groups": [
36      {
37        "_version": "3.0.0",
38        "identification": {
39          "id": "salesOrder",
40          "title": "({{title}})",
41          "entityType": "group",
42          "i18n": "i18n/salesOrder.properties"
43        },
44        "payload": {
45          "viz": [
46            {
47              "id": "com.sap.gtt.app.sample.sof",
48              "appId": "com.sap.gtt.app.sample.sof",
49              "vizId": "SalesOrder-track"
50            }
51          ]
52        }
53      ]
54    ]
55  }

```

```

{
  "_version": "3.0.0",
  "identification": {
    "id": "shipment",
    "title": "({{title}})",
    "entityType": "group",
    "i18n": "i18n/shipment.properties"
  },
  "payload": {
    "viz": [
      {
        "id": "com.sap.gtt.app.sample.sst",
        "appId": "com.sap.gtt.app.sample.sst",
        "vizId": "Shipment-track"
      }
    ]
  }
},
{
  "_version": "3.0.0",
  "identification": {
    "id": "purchaseOrder",
    "title": "({{title}})",
    "entityType": "group",
    "i18n": "i18n/purchaseOrder.properties"
  },
  "payload": {
    "viz": [
      {
        "id": "com.sap.gtt.app.sample.pof",
        "appId": "com.sap.gtt.app.sample.pof",
        "vizId": "PurchaseOrder-track"
      }
    ]
  }
},
],
"sites": [
  {
    "_version": "3.0.0",
    "identification": {
      "id": "a3eeeb302-5181-4222-9924-8bde99085f07-1578021444073",
      "entityType": "site",
      "title": "SAP Fiori launchpad site on Cloud Foundry",
      "description": "SAP Fiori launchpad site on Cloud Foundry, deployed from SAP Web IDE"
    },
    "payload": {
      "config": {
        "helloworld": {

```

```

90   },
91   "sites": [
92     {
93       "_version": "3.0.0",
94       "identification": {
95         "id": "a3eee102-5181-4222-9924-8b8e90985f07-1578021444073",
96         "entityType": "site",
97         "title": "SAP Fiori launchpad site on Cloud Foundry",
98         "description": "SAP Fiori launchpad site on Cloud Foundry, deployed from SAP Web IDE"
99       },
100      "payload": {
101        "config": {
102          "ushellConfig": {
103            "renderers": {
104              "fiori2": {
105                "componentData": {
106                  "config": {
107                    "applications": {
108                      "Shell-home": {}
109                    },
110                    "enableHelp": false,
111                    "enableSearch": false,
112                    "sessionTimeoutIntervalInMinutes": 19,
113                    "sessionTimeoutReminderInMinutes": 3
114                  }
115                }
116              }
117            }
118          }
119        },
120        "groupsOrder": [
121          "salesOrder",
122          "shipment",
123          "purchaseOrder"
124        ]
125      }
126    }
127   ]
128 }

```

In the command line tool,

- Run the following command to build the MTAR package:

```
mbt build
```

A MTAR file `./mta_archives/lbn-gtt-sample-app-flp_xxx.mtar` is then generated.


- Deploy the MTAR package in Cloud Foundry by running the following command:

```
cf deploy ./mta_archives/lbn-gtt-sample-app-flp_xxx.mtar
```

2.4.4 Package and Deploy *Track Shipments* Backend Service

Replace User/Password, Here Map License Key and Host Configuration

- Open the file *mta.yaml* under the folder “GTT-V2-Sample-TrackShipments-Service”:



```
1  ---
2  _schema-version: '3.1'
3  ID: gtt-v2-sample-track-shipments-service
4  version: 2.3.0
5  modules:
6  - name: gtt-sample-track-shipments-service
7    type: java
8    path: src/
9    properties:
10     SPRING_PROFILES_ACTIVE: cloud
11     DESTINATION_GTT: gtt_core engine flp_base_url-${space}
12     HERE_MAP_KEY: {here-map-license-key}
13   parameters:
14     buildpack: java_buildpack
15     health-check-timeout: 180
16     host: gtt-sample-track-shipments-service-{unique-identifier}
17   build-parameters:
18     ignore:
19     - "*.md"
20     build-result: target/*.jar
21     timeout: 10m
22   requires:
23   - name: lbn-gtt-sample-app-uaa
24   - name: lbn-gtt-sample-destination
25   resources:
26   - name: lbn-gtt-sample-app-uaa
27     type: org.cloudfoundry.existing-service
28   - name: lbn-gtt-sample-destination
29     type: org.cloudfoundry.existing-service
30
```

- Replace {here-map-license-key} with the license key you can get from step 4.1.

Note: this step is optional, you could ignore this to proceed to verify if application could be built and pushed successfully. After the actual license key is obtained, you could later come back and replace it and execute this step again to build and push the application to cloud so that the map could be shown.

- Replace {unique-identifier} with the unique information such as your company name or cloud foundry global account name.

Note:

- {unique-identifier} must only contain lowercase letters, numbers and hyphens. For example, “company-s01”.
- For the length of “host”, the maximum limit is 63 characters.
- Open the file *./srv/src/main/java/com/sap/gtt/v2/sample/sst/common/constant/Constants.java*
 - Replace “com.lbngttsamples.gtt.app.sof” with the model namespace you got from Step 2.3


```

1 package com.sap.gtt.v2.sample.sst.common.constant;
2
3 import java.math.BigDecimal;
4
5 public class Constants {
6
7     public static final String GTT_MODEL_NAMESPACE = "com.lbngttsamples.gtt.app.sof";
8     public static final String GTT_MODEL_NAMESPACE_WRITE_SERVICE = GTT_MODEL_NAMESPACE + ".sofWriteService";
9     public static final String MODEL_NAMESPACE = GTT_MODEL_NAMESPACE + ".sofService";
10    public static final String ENTITY_CONTAINER_NAME = "EntityContainer";
11    public static final String COMBINED_MODEL_PATH_SEGMENT = "combined-model";
12    public static final String SHIPMENT_MODEL_NAME = "Shipment";
13    public static final String ELEMENTS_PATH_SEGMENT = "elements";
14    public static final String REST_ROOT_URL = "/sap/logistics/gtt/sample/sst/rest/v1";
15    public static final String ODATA_ROOT_URL = "/sap/logistics/gtt/sample/sst/odata/v1";
16    public static final String DATE_TIME_PATTERN = "yyyy-MM-dd'T'HH:mm:ss'Z'";
17    public static final BigDecimal MAX_LONGITUDE = BigDecimal.valueOf(180);
18    public static final BigDecimal MAX_LATITUDE = BigDecimal.valueOf(90);
19 }

```

- Run the following command to build the MTAR package:

```
mbt build
```

A MTAR file `./mta_archives/gtt-v2-sample-track-shipments-service_xxx.mtar` is then generated.

- Deploy the MTAR package in Cloud Foundry by running the following command:

```
cf deploy ./mta_archives/gtt-v2-sample-track-shipments-service_xxx.mtar
```

2.4.5 Check Deployed Apps on SAP Cloud Foundry Cockpit


After operations from Step 2.4.1 to Step 2.4.4, check the deployed apps on SAP Cloud Platform Cockpit.

The screenshot shows the SAP Cloud Platform Cockpit interface. The left sidebar contains navigation options: Applications, Services, SAP HANA Cloud, SAP HANA Cloud Migrations, SAP HANA, Portal, Routes, Security Groups, Events, and Members. The main area displays the 'Space: Applications' with a 'Deploy Application' button. Below this is a table listing the deployed applications.

Requested State	Name	Instances	Disk Quota
Stopped	flp-blue	0/1	1024 MB
Started	gtt-sample-track-purchaseorders-service-green	1/1	1024 MB
Started	gtt-sample-track-salesorders-service-blue	1/1	1024 MB
Started	gtt-sample-track-shipments-service-green	1/1	1024 MB

2.4.6 Maintain Destination of Forwarding

a. Go to “Destinations”



b. Configure Destination of Event to Action

Refer to Chapter 3 of the document *03_Synchronize_Actual_Events_To_TM-TS.pdf*

Note:

Replace "TO_QW9_170_STANDARD" with the destination name that you maintained in Step 2 and replace "QW9CLNT170" with the logical system of shipment tracked process.

Help

```
368 /*-----Forward to TM system begin-----*/
369 //For Track Shipments Application Only
370 var destinationTMName = "TO_QW9_170_STANDARD";
371 var msgObj = toObject("{}");
372 var eventObj = toObject("{}");
373
374 var reportedBy = null;
375 var estimatedArrivalTime = null;
376 var refPlannedEventMatchKey = null;
377 var estimatedArrival = null;
378
379 eventObj.eventReasonCode = "";
380 eventObj.stopId = "";
381
382 if (trackedProcess != null &&
383     "QW9CLNT170" == trackedProcess.logicalSystem &&
384     "SHIPMENT_ORDER" == actualEvent.trackingIdType &&
385     ("com.lbngttsamples.gtt.app.sof.Shipment.Departure" == actualEvent.eventType ||
386      "com.lbngttsamples.gtt.app.sof.Shipment.Arrival" == actualEvent.eventType ||
387      "com.lbngttsamples.gtt.app.sof.Shipment.Delay" == actualEvent.eventType ||
388      "com.lbngttsamples.gtt.app.sof.Shipment.LoadingStart" == actualEvent.eventType ||
389      "com.lbngttsamples.gtt.app.sof.Shipment.LoadingEnd" == actualEvent.eventType ||
390      "com.lbngttsamples.gtt.app.sof.Shipment.POD" == actualEvent.eventType ||
391      "com.lbngttsamples.gtt.app.sof.Shipment.POPU" == actualEvent.eventType ||
392      "com.lbngttsamples.gtt.app.sof.Shipment.Coupling" == actualEvent.eventType ||
393      "com.lbngttsamples.gtt.app.sof.Shipment.Decoupling" == actualEvent.eventType ||
394      "com.lbngttsamples.gtt.app.sof.Shipment.UnloadingStart" == actualEvent.eventType ||
395      "com.lbngttsamples.gtt.app.sof.Shipment.UnloadingEnd" == actualEvent.eventType)) {
396     if (actualEvent.containsProperty("estimatedArrival") && actualEvent.containsProperty("refPlannedEventMatchKey")) {
397         refPlannedEventMatchKey = actualEvent.refPlannedEventMatchKey;
398         estimatedArrival = actualEvent.estimatedArrival;
399         var i = 0;
400         // Get the latest matched estimatedArrivalTime
```

2.4.7 Maintain Roles and Users

As shown in Step 1.2, go to the role of “gtt-sample-all”, and add the following role:

Role	Application
StandaloneShipmentTrackingAppUserDisplayTemplate	tt_sof_{space}
StandaloneShipmentTrackingAppUserProcessTemplate	tt_sof_{space}

Note:


- The role StandaloneShipmentTrackingAppUserDisplayTemplate” can only enable the user to view the Track Shipments app.
- The role “StandaloneShipmentTrackingAppUserProcessTemplate” can only enable the user to report events in Track Shipments app. If the user needs the access to view both the Track Shipments app and report events in the app, then assign both roles to the role template.

If the user needs the access to other template apps such as *Track SO Fulfillment* or *Track PO Fulfillment*, add the following roles:


Role	Application
SalesOrderFulfillmentAppUserDisplayTemplate	tt_sof_{space}
PurchaseOrderFulfillmentAppUserDisplayTemplate	tt_sof_{space}

2.4.8 Open *Track Shipments* Template App from SAP Fiori Launchpad

- Obtain the Application Routes from SAP Cloud Foundry Cockpit



- Click the link of Application Routes
The system browser then navigates to the SAP Fiori Launchpad of *Track Shipments*



- Open the *Track Shipments* template app

SAP Track Shipments

Standard

Shipment Number: Carrier: Process Status: Execution Status: Transportation Mode:

Shipping Type: Vehicle: Planned Departure Location: Planned Arrival Location: Delivery Number:

Adapt Filters Go

Shipments (295)

Shipment Number	Carrier	Planned Departure	Planned Arrival	Execution Status	Process Status
6100062252		MEB_CUS_46 Oct 31, 2018, 5:12:00 PM	Golden Nuts Inc.	Not Started	Overdue
4150002217	10000043	The Cookie Company Shp. Point Feb 2, 2999, 7:00:00 AM	Walmart Inc.	Not Started	As Planned
0000001671	10002419	Golden Nuts Inc.	US HARBOR Dec 20, 2020, 7:00:00 PM	In Transit	Overdue
000000265X	10002418	New York Harbor	Golden Nuts Inc.	In Transit	As Planned
0000002643	10002419	New York Harbor	Golden Nuts Inc.	In Transit	Early

3. Implement ERP Extractor

For ERP extractor implementation, please refer to the following document:

04_Extractor_Creation_Guide-TS.pdf

4. Other Configuration

4.1 Obtain Here Map License

To have the map view, log the incident with the URL of Fiori Launchpad of template apps in SAP support system under component “SBN-LBN-GTT-APP”. Follow the 2 steps below when you create an incident:

- 1) Add logon credentials in the incident to the secure area so that we can provide you the key in a safe way. You can refer to SAP Note 1773689 for reference:
<https://launchpad.support.sap.com/#/notes/0001773689>
- 2) Provide us with the application routes which you get in step 2.4.8 “Obtain the Application Routes from SAP Cloud Foundry Cockpit”


After you get the key, you can use it in Step 2.4.4 to re-deploy the backend service.

For quick validation, you can also use the tile service of other map services.


4.2 Maintain Location Master

To show stops and planned events in the map, you need to maintain location master data with valid geocoordinates in *Manage Locations* app.

- a. Open *Manage Locations* app in your SAP Fiori Launchpad for Global Track and Trace



- b. Click “Create” to create a new location



- c. Maintain location information with valid geocoordinates

To integrate with ERP, you need to keep the “Object Type”, “Source System”, and “External ID” location consistent with ERP location information.

For details, please refer to the following document:

02_Extractor_Creation_Guide-SOF.pdf

SAP Manage Locations Internal Test

Create Location

GENERAL ALTERNATIVE LOCATION IDS

Object Type: *
Logistic Location

Source System/External ID: *
Source System External ID

Description: *

Time Zone:

Country/Region:

State:

City:

District:

Street/House Number:

Zip Code:

Longitude: *
E (East) Example: 000.00000000

Latitude: *
N (North) Example: 00.00000000

4.3 Maintain Data Contributors

To receive actual events from other business partners, you need to invite them to join your business network. For more, search for *Administration Guide for Data Contributors* at help.sap.com/gtt and see the chapters “Onboarding” and “User Management”.

4.4 Integrate with Visibility Provider

To integrate with visibility provider, log your incident in SAP BCP system with the component “SBN-LBN-GTT-APP”.