

# SPEC® CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13


**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017



## Hardware

**CPU Name:** Genuine Intel 0000

**Max MHz.:**

**Nominal:**

**Enabled:** cores, 1 chip, threads/core

**Orderable:**

**Cache L1:**

**L2:**

**L3:**

**Other:**

**Memory:** 15.428 GB fixme: If using DDR3, format is:  
'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)'

**Storage:** 391 GB add more disk info here

**Other:**

## Software

**OS:** Fedora release 32 (Thirty Two)

5.7.0-0.rc6.1.1.cet.fc32.x86\_64

**Compiler:** C/C++: Version 8.1.0 of GNU C/C++

Compiler for Linux;

Fortran: Version 8.1.0 of GNU Fortran

Compiler for Linux

**Parallel:** No

**Firmware:** --

**File System:** ext4

**System State:** Run level 3 (add definition here)

**Base Pointers:** 64-bit

**Peak Pointers:** Not Applicable

**Other:** --

## Errors

'reportable' flag not set during run

602.gcc\_s (base) did not have enough runs!

641.leela\_s (base) did not have enough runs!

623.xalancbmk\_s (base) did not have enough runs!

657.xz\_s (base) did not have enough runs!

620.omnetpp\_s (base) did not have enough runs!

605.mcf\_s (base) did not have enough runs!

648.exchange2\_s (base) did not have enough runs!

631.deepsjeng\_s (base) did not have enough runs!

600.perlbench\_s (base) did not have enough runs!

625.x264\_s (base) did not have enough runs!

(Continued on next page)

# SPEC CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017

## Errors (Continued)

Unknown flags were used! See

<https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl>  
for information about how to get rid of this error.

## Results Table

Benchmark	Base								Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s																
602.gcc_s																
605.mcf_s	1	<b>681</b>	<b>6.93</b>													
620.omnetpp_s																
623.xalancbmk_s																
625.x264_s																
631.deepsjeng_s																
641.leela_s																
648.exchange2_s																
657.xz_s																

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## General Notes

Environment variables set by runcpu before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact"

LD\_LIBRARY\_PATH = "/home/ucsd/SpectreSandboxing/spec2017/lib/ia32:/home/ucsd/SpectreSandboxing/spec2017/lib/intel64"

OMP\_STACKSIZE = "192M"

Binaries compiled on a system with Intel(R) Core(TM) i9-7900X CPU + 32GB RAM  
memory using Redhat Enterprise Linux 7.5  
Transparent Huge Pages enabled by default

## Platform Notes

Sysinfo program /home/ucsd/SpectreSandboxing/spec2017/bin/sysinfo  
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f  
running on tigerlake1-ravi Tue May 26 23:33:06 2020

(Continued on next page)

# SPEC CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017

## Platform Notes (Continued)

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Genuine Intel(R) CPU 0000 @ 2.30GHz

1 "physical id"s (chips)

8 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 4

siblings : 8

physical 0: cores 0 1 2 3

From lscpu:

Architecture: x86\_64

CPU op-mode(s): 32-bit, 64-bit

Byte Order: Little Endian

Address sizes: 39 bits physical, 48 bits virtual

CPU(s): 8

On-line CPU(s) list: 0-7

Thread(s) per core: 2

Core(s) per socket: 4

Socket(s): 1

NUMA node(s): 1

Vendor ID: GenuineIntel

CPU family: 6

Model: 140

Model name: Genuine Intel(R) CPU 0000 @ 2.30GHz

Stepping: 0

CPU MHz: 1790.193

CPU max MHz: 4200.0000

CPU min MHz: 400.0000

BogoMIPS: 4608.00

Virtualization: VT-x

L1d cache: 192 KiB

L1i cache: 128 KiB

L2 cache: 5 MiB

L3 cache: 12 MiB

NUMA node0 CPU(s): 0-7

Vulnerability Itlb multihit: KVM: Mitigation: Split huge pages

Vulnerability L1tf: Not affected

Vulnerability Mds: Vulnerable: Clear CPU buffers attempted, no

microcode; SMT vulnerable

Vulnerability Meltdown: Not affected

Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl and seccomp

(Continued on next page)

# SPEC CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017

## Platform Notes (Continued)

Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and \_\_user pointer sanitization  
Vulnerability Spectre v2: Mitigation; Enhanced IBRS, IBPB conditional, RSB filling  
Vulnerability Tsx async abort: Not affected  
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant\_tsc art arch\_perfmon pebs bts rep\_good nopl xtopology nonstop\_tsc cpuid aperfmperf tsc\_known\_freq pni pclmulqdq dtes64 monitor ds\_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid sse4\_1 sse4\_2 x2apic movbe popcnt tsc\_deadline\_timer aes xsave avx f16c rdrand lahf\_lm abm 3dnowprefetch cpuid\_fault epb invpcid\_single ssbd ibrs ibpb stibp ibrs\_enhanced tpr\_shadow vnmi flexpriority ept vpid ept\_ad fsgsbase tsc\_adjust bmi1 avx2 smep bmi2 erms invpcid avx512f avx512dq rdseed adx smap avx512ifma clflushopt clwb intel\_pt avx512cd sha\_ni avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves dtherm ida arat pln pts hwp hwp\_notify hwp\_act\_window hwp\_epp hwp\_pkg\_req avx512vbmi umip pku ospke avx512\_vbmi2 shstk gfni vaes vpclmulqdq avx512\_vnni avx512\_bitalg tme avx512\_vpopcntdq rdpid movdiri movdir64b fsrm avx512\_vp2intersect ibt flush\_lld arch\_capabilities

/proc/cpuinfo cache data  
cache size : 12288 KB

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

From /proc/meminfo  
MemTotal: 16177588 kB  
HugePages\_Total: 0  
Hugepagesize: 2048 kB

From /etc/\*release\* /etc/\*version\*  
fedora-release: Fedora release 32 (Thirty Two)  
os-release:  
NAME=Fedora  
VERSION="32 (Workstation Edition)"  
ID=fedora  
VERSION\_ID=32  
VERSION\_CODENAME=""  
PLATFORM\_ID="platform:f32"  
PRETTY\_NAME="Fedora 32 (Workstation Edition)"  
ANSI\_COLOR="0;34"  
redhat-release: Fedora release 32 (Thirty Two)  
system-release: Fedora release 32 (Thirty Two)  
system-release-cpe: cpe:/o:fedoraproject:fedora:32

uname -a:  
Linux tigerlake1-ravi 5.7.0-0.rc6.1.1.cet.fc32.x86\_64 #1 SMP Mon May 18 17:21:34 PDT

(Continued on next page)

# SPEC CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017

## Platform Notes (Continued)

2020 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 May 24 15:05

SPEC is set to: /home/ucsd/SpectreSandboxing/spec2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/fedora_localhost--live-home	ext4	391G	127G	244G	35%	/home

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

## Compiler Version Notes

=====  
CC 605.mcf\_s(base)  
=====

clang version 10.0.0 (<https://github.com/llvm/llvm-project>  
d32170dbd5b0d54436537b6b75beaf44324e0c28)

Target: wasm32-unknown-wasi

Thread model: posix

InstalledDir: /opt/wasi-sdk/bin  
=====

## Base Unknown Flags

605.mcf\_s: "/opt/wasi-sdk/bin/clang --sysroot  
/opt/wasi-sdk/share/wasi-sysroot -Wl,--export-all  
-I/opt/wasi-sdk/lib/clang/10.0.0/include/ARRAY(0x823a108)  
"/opt/wasi-sdk/bin/clang --sysroot  
/opt/wasi-sdk/share/wasi-sysroot -Wl,--export-all  
-I/opt/wasi-sdk/lib/clang/10.0.0/include/ARRAY(0x82316b8)  
"-O2ARRAY(0x8252e48)

## Base Runtime Environment

C benchmarks:

605.mcf\_s: No flags used

# SPEC CPU2017 Integer Speed Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

**My Corporation**

(Test Sponsor: Intel Corporation)

SPECspeed2017\_int\_base = 6.93

SPECspeed2017\_int\_peak = Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test Date:** May-2020

**Hardware Availability:**

**Software Availability:** Sep-2017

## Base Compiler Invocation

C benchmarks:

605.mcf\_s: No flags used

## Base Portability Flags

605.mcf\_s: -DSPEC\_LP64

## Base Optimization Flags

C benchmarks:

605.mcf\_s: -Wl,-z,muldefs -fno-strict-aliasing -DSPEC\_SUPPRESS\_OPENMP

## Base Other Flags

C benchmarks:

605.mcf\_s: No flags used

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU2017 v1.0.2 on 2020-05-26 23:33:06-0700.

Report generated on 2020-05-26 23:44:32 by CPU2017 PDF formatter v5748.