SPEC® CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base = 0.7543

SPECrate2017_fp_peak = Not Run

CPU2017 License: 13	**Test Date:** May-2020
Test Sponsor: Intel Corporation	**Hardware Availability:**
Tested by: Intel Corporation	**Software Availability:** Sep-2017

Copies — 0 0.0400 0.0900 0.140 0.180 0.220 0.260 0.300 0.340 0.380 0.420 0.460 0.500 0.540 0.580 0.620 0.660 0.700 0.760

- 503.bwaves_r
- 507.cactuBSSN_r
- 508.namd_r 1 .... 0.754
- 510.parest_r
- 511.povray_r
- 519.lbm_r
- 521.wrf_r
- 526.blender_r
- 527.cam4_r
- 538.imagick_r
- 544.nab_r
- 549.fotonik3d_r
- 554.roms_r

SPECrate2017_fp_base (0.7543)

Hardware

CPU Name: Genuine Intel 0000
Max MHz.:
Nominal:
Enabled: cores, 1 chip, threads/core
Orderable:
Cache L1:
L2:
L3:
Other:
Memory: 15.428 GB fixme: If using DDR3, format is:
'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)'
Storage: 391 GB add more disk info here
Other:

Software

OS: Fedora release 32 (Thirty Two)
5.7.0-0.rc6.1.1.cet.fc32.x86_64
Compiler: C/C++: Version 8.1.0 of GNU C/C++
Compiler for Linux;
Fortran: Version 8.1.0 of GNU Fortran
Compiler for Linux
Parallel: No
Firmware: --
File System: ext4
System State: Run level 3 (add definition here)
Base Pointers: 64-bit
Peak Pointers: 64-bit
Other: --

Errors

'reportable' flag not set during run

526.blender_r (base) did not have enough runs!

503.bwaves_r (base) did not have enough runs!

521.wrf_r (base) did not have enough runs!

508.namd_r (base) did not have enough runs!

507.cactuBSSN_r (base) did not have enough runs!

538.imagick_r (base) did not have enough runs!

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base =   0.7543

SPECrate2017_fp_peak = Not Run

CPU2017 License: 13	**Test Date:** May-2020
Test Sponsor: Intel Corporation	**Hardware Availability:**
Tested by: Intel Corporation	**Software Availability:** Sep-2017

Errors (Continued)

519.lbm_r (base) did not have enough runs!

544.nab_r (base) did not have enough runs!

511.povray_r (base) did not have enough runs!

554.roms_r (base) did not have enough runs!

549.fotonik3d_r (base) did not have enough runs!

510.parest_r (base) did not have enough runs!

527.cam4_r (base) did not have enough runs!

Unknown flags were used! See

   https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl

for information about how to get rid of this error.

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r														
507.cactuBSSN_r														
508.namd_r	1	**1260**	**0.754**											
510.parest_r														
511.povray_r														
519.lbm_r														
521.wrf_r														
526.blender_r														
527.cam4_r														
538.imagick_r														
544.nab_r														
549.fotonik3d_r														
554.roms_r														

SPECrate2017_fp_base =   0.7543

SPECrate2017_fp_peak =   Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runcpu before the start of the run:

KMP_AFFINITY = "granularity=fine,compact"

LD_LIBRARY_PATH = "/home/ucsd/SpectreSandboxing/spec2017/lib/ia32:/home/ucsd/SpectreSandboxing/spec2017/lib/intel64"

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base =   0.7543

SPECrate2017_fp_peak = Not Run

CPU2017 License: 13		**Test Date:**	May-2020
Test Sponsor:	Intel Corporation	**Hardware Availability:**	
Tested by:	Intel Corporation	**Software Availability:**	Sep-2017

General Notes (Continued)

```
OMP_STACKSIZE = "192M"

 Binaries compiled on a system with Intel(R) Core(TM) i9-7900X CPU + 32GB RAM
 memory using Redhat Enterprise Linux 7.5
 Transparent Huge Pages enabled by default
```

Platform Notes

```
 Sysinfo program /home/ucsd/SpectreSandboxing/spec2017/bin/sysinfo
 Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
 running on tigerlake1-ravi Tue May 26 09:20:36 2020

 SUT (System Under Test) info as seen by some common utilities.
 For more information on this section, see
    https://www.spec.org/cpu2017/Docs/config.html#sysinfo

 From /proc/cpuinfo
    model name : Genuine Intel(R) CPU 0000 @ 2.30GHz
       1  "physical id"s (chips)
       8 "processors"
    cores, siblings (Caution: counting these is hw and system dependent. The following
    excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)
       cpu cores : 4
       siblings : 8
       physical 0: cores 0 1 2 3

 From lscpu:
       Architecture:              x86_64
       CPU op-mode(s):            32-bit, 64-bit
       Byte Order:                Little Endian
       Address sizes:             39 bits physical, 48 bits virtual
       CPU(s):                    8
       On-line CPU(s) list:       0-7
       Thread(s) per core:        2
       Core(s) per socket:        4
       Socket(s):                 1
       NUMA node(s):              1
       Vendor ID:                 GenuineIntel
       CPU family:                6
       Model:                     140
       Model name:                Genuine Intel(R) CPU 0000 @ 2.30GHz
       Stepping:                  0
       CPU MHz:                   1841.722
       CPU max MHz:               4200.0000
       CPU min MHz:               400.0000
       BogoMIPS:                  4608.00
```

(Continued on next page)

Standard Performance Evaluation Corporation (info@spec.org)   https://www.spec.org/

SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base =   0.7543

SPECrate2017_fp_peak =   Not Run

CPU2017 License: 13		**Test Date:**	May-2020
Test Sponsor:	Intel Corporation	**Hardware Availability:**	
Tested by:	Intel Corporation	**Software Availability:**	Sep-2017

Platform Notes (Continued)

```
      Virtualization:                   VT-x
      L1d cache:                        192 KiB
      L1i cache:                        128 KiB
      L2 cache:                         5 MiB
      L3 cache:                         12 MiB
      NUMA node0 CPU(s):                0-7
      Vulnerability Itlb multihit:      KVM: Mitigation: Split huge pages
      Vulnerability L1tf:               Not affected
      Vulnerability Mds:                Vulnerable: Clear CPU buffers attempted, no
      microcode; SMT vulnerable
      Vulnerability Meltdown:           Not affected
      Vulnerability Spec store bypass:  Mitigation; Speculative Store Bypass disabled via
      prctl and seccomp
      Vulnerability Spectre v1:         Mitigation; usercopy/swapgs barriers and __user
      pointer sanitization
      Vulnerability Spectre v2:         Mitigation; Enhanced IBRS, IBPB conditional, RSB
      filling
      Vulnerability Tsx async abort:    Not affected
      Flags:                            fpu vme de pse tsc msr pae mce cx8 apic sep mtrr
      pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
      pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology
      nonstop_tsc cpuid aperfmperf tsc_known_freq pni pclmulqdq dtes64 monitor ds_cpl vmx
      smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt
      tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault
      epb invpcid_single ssbd ibrs ibpb stibp ibrs_enhanced tpr_shadow vnmi flexpriority
      ept vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid avx512f
      avx512dq rdseed adx smap avx512ifma clflushopt clwb intel_pt avx512cd sha_ni
      avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves dtherm ida arat pln pts hwp
      hwp_notify hwp_act_window hwp_epp hwp_pkg_req avx512vbmi umip pku ospke avx512_vbmi2
      shstk gfni vaes vpclmulqdq avx512_vnni avx512_bitalg tme avx512_vpopcntdq rdpid
      movdiri movdir64b fsrm avx512_vp2intersect ibt flush_l1d arch_capabilities

  /proc/cpuinfo cache data
     cache size : 12288 KB

From numactl --hardware  WARNING: a numactl 'node' might or might not correspond to a
physical chip.

From /proc/meminfo
    MemTotal:       16177588 kB
    HugePages_Total:       0
    Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
    fedora-release: Fedora release 32 (Thirty Two)
    os-release:
       NAME=Fedora
```

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base = 0.7543

CPU2017 License: 13		**Test Date:**	May-2020
Test Sponsor:	Intel Corporation	**Hardware Availability:**	
Tested by:	Intel Corporation	**Software Availability:**	Sep-2017

Platform Notes (Continued)

```
    VERSION="32 (Workstation Edition)"
    ID=fedora
    VERSION_ID=32
    VERSION_CODENAME=""
    PLATFORM_ID="platform:f32"
    PRETTY_NAME="Fedora 32 (Workstation Edition)"
    ANSI_COLOR="0;34"
  redhat-release: Fedora release 32 (Thirty Two)
  system-release: Fedora release 32 (Thirty Two)
  system-release-cpe: cpe:/o:fedoraproject:fedora:32

 uname -a:
    Linux tigerlake1-ravi 5.7.0-0.rc6.1.1.cet.fc32.x86_64 #1 SMP Mon May 18 17:21:34 PDT
    2020 x86_64 x86_64 x86_64 GNU/Linux

 run-level 3 May 24 15:05

 SPEC is set to: /home/ucsd/SpectreSandboxing/spec2017
    Filesystem                             Type  Size  Used Avail Use% Mounted on
    /dev/mapper/fedora_localhost--live-home ext4  391G  127G  244G  35% /home


 Additional information from dmidecode follows.  WARNING: Use caution when you interpret
 this section. The 'dmidecode' program reads system data which is "intended to allow
 hardware to be accurately determined", but the intent may not be met, as there are
 frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

 (End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
 CXXC 508.namd_r(base)
------------------------------------------------------------------------------
clang version 10.0.0 (https://github.com/llvm/llvm-project
  d32170dbd5b0d54436537b6b75beaf44324e0c28)
Target: wasm32-unknown-wasi
Thread model: posix
InstalledDir: /opt/wasi-sdk/bin
------------------------------------------------------------------------------
```

Base Unknown Flags

```
508.namd_r: "/opt/wasi-sdk/bin/clang --sysroot
/opt/wasi-sdk/share/wasi-sysroot -Wl,--export-all -lstdc++
-I/opt/wasi-sdk/lib/clang/10.0.0/include/ARRAY(0x777e3a8)
```

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base =   0.7543

SPECrate2017_fp_peak =   Not Run

Base Unknown Flags (Continued)

508.namd_r (continued):
```
"/opt/wasi-sdk/bin/clang --sysroot
/opt/wasi-sdk/share/wasi-sysroot -Wl,--export-all -lstdc++
-I/opt/wasi-sdk/lib/clang/10.0.0/include/ARRAY(0x7777830)
"-fno-exceptionsARRAY(0x778d858)
```

Base Runtime Environment

C++ benchmarks:

 508.namd_r: No flags used

Base Compiler Invocation

C++ benchmarks:

 508.namd_r: No flags used

Base Portability Flags

508.namd_r: -DSPEC_LP64

Base Optimization Flags

C++ benchmarks:

 508.namd_r: No flags used

Base Other Flags

C++ benchmarks:

 508.namd_r: No flags used

SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2020 Standard Performance Evaluation Corporation

My Corporation
(Test Sponsor: Intel Corporation)

SPECrate2017_fp_base = 0.7543

SPECrate2017_fp_peak = Not Run

CPU2017 License:	13	**Test Date:**	May-2020
Test Sponsor:	Intel Corporation	**Hardware Availability:**	
Tested by:	Intel Corporation	**Software Availability:**	Sep-2017

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2020-05-26 09:20:36-0700.
Report generated on 2020-05-26 09:41:45 by CPU2017 PDF formatter v5748.