#### SPEC® CPU2017 Floating Point Speed Result Copyright 2017-2020 Standard Performance Evaluation Corporation My Corporation SPECspeed2017\_fp\_base = **5**.10 (Test Sponsor: Intel Corporation) SPECspeed2017\_fp\_peak **M**ot Run Test Date: CPU2017 License: 13 May-2020 Hardware Availability: **Test Sponsor:** Intel Corporation Tested by: Software Availability: Sep-2017 Intel Corporation Threads 0 603.bwaves\_s 607.cactuBSSN\_s 5.10 619.lbm s 1 621.wrf\_s 627.cam4\_s 628.pop2\_s 638.imagick\_s 644.nab s 649.fotonik3d\_s 654.roms\_s SPECspeed2017\_fp\_base (5.10) Hardware Software CPU Name: Genuine Intel 0000 OS: Fedora release 32 (Thirty Two) Max MHz.: 5.7.0-0.rc6.1.1.cet.fc32.x86\_64 C/C++: Version 8.1.0 of GNU C/C++ Nominal: Compiler: Enabled: cores, 1 chip, threads/core Compiler for Linux; Orderable: Fortran: Version 8.1.0 of GNU Fortran Cache L1: Compiler for Linux Parallel: L2: No L3: Firmware: Other: File System: ext4 15.428 GB fixme: If using DDR3, format is: System State: Run level 3 (add definition here) Memory: 'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)' Base Pointers: 64-bit BØ1 GB add more disk info here Peak Pointers: 64-bit Storage: Other: Other: **Errors**

'reportable' flag not set during run 619.lbin s (base) did not have enough runs!

621.wrf\_s (base) did not have enough runs!

638.imagick)s (base) did not have enough runs!

649.fotonik 3d s (base) did not have enough runs!

627.cam4 s (base) did not have enough runs!

628.pop2 s (base) did not have enough runs!

607.cactuBSSN\_s (base) did not have enough runs!

654.roms\_s (base) did not have enough runs!

603.bwaves\_s (base) did not have enough runs!

644.nab s (base) did not have enough runs!

(Continued on next page)

Copyright 2017-2020 Standard Performance Evaluation Corporation

### My Corporation

(Test Sponsor: Intel Corporation)

SPECspeed2017\_fp\_base =

SPECspeed2017\_fp\_peak Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

Test Date: May-2020

**5**.10

Hardware Availability:

Software Availability: Sep-2017

### **Errors** (Continued)

Unknown flags were used! See

https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl for information about how to get rid of this error.

#### Results Table

	Base							\\ \n	Peak						
Benchmark	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	
603.bwaves_s				$\Big)$				7							
607.cactuBSSN_s															
619.lbm_s	1	<u>1027</u>	<u>5.10</u>												
621.wrf_s					_		_								
627.cam4_s							/								
628.pop2_s						)/									
638.imagick_s						) ×									
644.nab_s															
649.fotonik3d_s		(			77	ĺ									
654.roms_s		^	$\cup$ 7												

SPECspeed2017\_fp\_base =

5.10 Not Run

SPECspeed2017\_fp\_peak

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

### **Operating System Notes**

Stack size set to unlimited using "ulimit -s unlimited"

#### **General Notes**

Environment variables set by runcpu before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact"

LD\_LIBRARY\_PATH = //ome/ucsd/SpectreSandboxing/spec2017/lib/ia32:/home/ucsd/SpectreSandboxing/spec2017/lib/intel64"
OMP\_STACKSIZE = "192M"

Binaries compiled on a system with Intel(R) Core(TM) i9-7900X CPU + 32GB RAM memory using Redhat Enterprise Linux 7.5
Transparent Huge Pages enabled by default

#### **Platform Notes**

Sysinfo program /home/ucsd/SpectreSandboxing/spec2017/bin/sysinfo Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f running on tigerlakel-ravi Sat May 30 01:48:24 2020

(Continued on next page)

Page 2

Copyright 2017-2020 Standard Performance Evaluation Corporation

### My Corporation

(Test Sponsor: Intel Corporation)

SPECspeed2017\_fp\_base = 5.10

SPECspeed2017\_fp\_peak Mot Run

CPU2017 License: 13

Tested by:

**Test Sponsor: Intel Corporation**  Test Date:

May-2020

Hardware Availability:

Software Availability: Sep-2017

```
Platform Notes (Continued)
```

```
SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
```

https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From /proc/cpuinfo

model name : Genuine Intel(R) CPU 0000 @ 2.30GHz

1 "physical id"s (chips)

Intel Corporation

8 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo(m)ght not/be reliable/ Use with caution.)

> 32-b1t, 64-bit Little Endian

GenuineIntel

39 bits physical, 48 bits virtual

Genuine Intel(R) CPU 0000 @ 2.30GHz

x86\_

0-72

4

1

6

140

1746.059

400.0000

4608.00

192 KiB

128 KiB

5 MiB 12 MiB

0 - 7

VT-x

4200.0000

cpu cores : 4

siblings : 8

physical 0: cores 0

From lscpu:

Architecture:

CPU op-mode(s): Byte Order:

Address sizes:

CPU(s):

On-line CPU(s) list: Thread(s) per core:

Core(s) per socket:

Socket(s): NUMA node(s):

Vendor In: CPU family:

Model:

Model name:

Stepping:

PU MHz:

CPU max MHz: CPU min MHz:

BogoMIRS: Virtualization: L1d cache:

Mi cache: L2 cache: L3/cache:

NUMA node0 CPU(s):

Vulnerability Itlb multihit:

Vulnerability L1tf: Vulnerability Mds:

microcode; SMT vulnerable Vulnerability Meltdown:

Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl and seccomp

Not affected

Not affected

Vulnerable: Clear CPU buffers attempted, no

KVM: Mitigation: Split huge pages

(Continued on next page)

Page 3

Copyright 2017-2020 Standard Performance Evaluation Corporation

#### My Corporation

(Test Sponsor: Intel Corporation)

SPECspeed2017\_fp\_base =

SPECspeed2017\_fp\_peak Not Run

**CPU2017 License:** 13

**Test Sponsor:** Intel Corporation

Tested by: Intel Corporation

Test Date: May-2020

5.10

Hardware Availability:

Software Availability: Sep-2017

#### Platform Notes (Continued)

Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and \_\_user

pointer sanitization

Vulnerability Spectre v2: Mitigation; Enhanced IBRS/ IBPB conditional, RSB

filling

Vulnerability Tsx async abort: Not affected

fpu wme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts api mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant\_tsc art arch\_perfmon pebs bts rep\_good nopl xtopology nonstop\_tsc cpuid aperfmperf tsc\_known\_freq phi pc/mulqdq dtes64 monitor ds\_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid\_sse4\_1 sse4\_2 x2apic movbe popcnt tsc\_deadline\_timer aes xsave avx f16c rdrand lanf\_lm abm 3dnowprefetch cpuid\_fault epb invpcid\_single ssbd ibrs ibpb stibp ibrs\_enhanced tpr\_shadow vnmi flexpriority ept vpid ept\_ad fsgsbase tsc\_ddjust bmil avx2 smep bmi2 erms invpcid avx512f avx512dq rdseed adx\_emap avx512ifma clflushopt clwb intel\_pt avx512cd sha\_ni avx512bw avx512vl xsaveopt xsavec xgetbyl xsaves dtherm ida arat pln pts hwp hwp\_notify hwp\_act\_window hwp\_epp hwp\_pkg\_req avx512vbmi umip pku ospke avx512\_vbmi2 shstk gfni vaes vpclmulqdq avx512\_vnni avx512\_bitalg tme avx512\_vpopcntdq rdpid movdiri movdir64b fsrm avx512\_vp2inersect ibt flush\_lld arch\_capabilities

/proc/cpuinfo cache data cache size : 12288 KB

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

From /proc/meminfo

MemTotal: 16177588 kB HugePages Total: 0 Hugepagesize: 2048 kB

From /etc/\*release\* /etc/\*version\*

fedora-release Fedora release 32 (Thirty Two)

os-release:

NAME=Fedora

VERSION=/32 (Workstation Edition)"

ID=fedora

VERSION\_ID=32

VERSION\_CODENAME=""

PLATFORM\_ID="platform:f32"

PRETTY\_NAME="Fedora 32 (Workstation Edition)"

ANSI\_COLOR="0;34"

redhat-release: Fedora release 32 (Thirty Two)
system-release: Fedora release 32 (Thirty Two)
system-release-cpe: cpe:/o:fedoraproject:fedora:32

uname -a:

Linux tigerlakel-ravi 5.7.0-0.rc6.1.1.cet.fc32.x86\_64 #1 SMP Mon May 18 17:21:34 PDT

(Continued on next page)

Copyright 2017-2020 Standard Performance Evaluation Corporation

### My Corporation

(Test Sponsor: Intel Corporation)

SPECspeed2017\_fp\_base  $\Rightarrow$  5.10

SPECspeed2017\_fp\_peak Not Run

CPU2017 License: 13

**Test Sponsor:** Intel Corporation

**Tested by:** Intel Corporation

Test Date: May-2020

Hardware Availability:

Software Availability: Sep-2017

#### Platform Notes (Continued)

2020 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 May 28 23:18

SPEC is set to: /home/ucsd/SpectreSandboxing/spec2017
Filesystem
Type Size Used Avail Use% Mounted on
/dev/mapper/fedora\_localhost--live-home ext4 391G 128G 243G 35% /home

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfd program)

### **Compiler Yersion Notes**

------

CC 619.1bm s(base)

------

clang version 10.0.0 (https://github.com/llvm/llvm-project

d32170dbd5b0d54436537b6b75beaf44324e0c28)

Target: wasm32-unknown wasi

Thread model: posix

InstalledDir: opt/wasi-adk/bin

-----

### **Base Unknown Flags**

619.lbm/s:"/opt/wasi\_sdk/bin/clang --sysroot

/opt/wasi-sdk/shart/wasi-sysroot -Wl,--export-all

-I/opt/wasi-sdk/1/1b/clang/10.0.0/include/ARRAY(0x835ac48)

"/opt/wasi-sdk/b/n/clang --sysroot

/opt/wasi-sdk/share/wasi-sysroot -Wl,--export-all

-I/opt/wasi-sdk/lib/clang/10.0.0/include/ARRAY(0x8359eb8)

"-02ARRAX(0x8372938)

#### **Base Runtime Environment**

C benchmarks:

619.lbm\_s: No flags used

Copyright 2017-2020 Standard Performance Evaluation Corporation

### My Corporation

(Test Sponsor: Intel Corporation)

SPECspeed2017\_fp\_base =

SPECspeed2017\_fp\_peak Not Run

CPU2017 License: 13

**Test Sponsor:** Intel Corporation

Tested by: Intel Corporation

Test Date: May-2020

Hardware Availability:

Software Availability: Sep-2017

### **Base Compiler Invocation**

C benchmarks:

619.lbm\_s: No flags used

## Base Portability Flags

619.lbm\_s: -DSPEC\_LP64

### **Base Optimization Flags**

C benchmarks:

619.lbm\_s: -fno-strict-aliasing DSPEC\_SUPPRESS\_OPENMP

### **Base Other Flags**

C benchmarks:

619.lbm\_s: No flags used

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2020-05-30 01:48:24-0700.

Report generated on 2020-05-30 02:05:36 by CPU2017 PDF formatter v5748.