

```
from google.colab import drive
drive.mount('/content/gdrive')
```

Mounted at /content/gdrive

```
import pandas as pd
import numpy as np
import bz2
import re
import matplotlib.pyplot as plt
import seaborn as sns
from tqdm import tqdm
from sklearn.utils import shuffle
from tqdm import tqdm
from keras.layers import *
from keras.models import Model
from keras.preprocessing.text import Tokenizer
from keras.preprocessing.sequence import pad_sequences
```

```
data = pd.read_csv('/content/gdrive/MyDrive/Tweets.csv', encoding="ISO-8859-1")
```

```
data = data.drop(["airline_sentiment_gold", "negativereason_gold", "tweet_coord", "tweet_1
```

```
data = data[data['airline_sentiment_confidence'] >= 0.5][['airline_sentiment', 'text']]
```

```
data.head()
```

	airline_sentiment	text
0	neutral	@VirginAmerica What @dhepburn said.
2	neutral	@VirginAmerica I didn't today... Must mean I n...
3	negative	@VirginAmerica it's really aggressive to blast...
4	negative	@VirginAmerica and it's a really big bad thing...
5	negative	@VirginAmerica seriously would pay \$20 a flight

```
# De dimensies van de dataset
```

```
data.shape
```

```
(14404, 2)
```

```
# Het aantal records
```

```
data.count()
```

```
airline_sentiment 14404
```

Opgeslagen.



```
# Het verwijderen van de stopwoorden
import nltk
nltk.download('stopwords')
from nltk.corpus import stopwords
from nltk.tokenize import word_tokenize
import string
nltk.download('punkt')

def verwijderStopwoorden(text):
    stopwoorden = set(stopwords.words('english'))
    tokens = word_tokenize(text.lower())
    result = [x for x in tokens if x not in stopwoorden and not x.startswith('@')]
    separator = ' '
    return separator.join(result)

data['text'] = data['text'].map(verwijderStopwoorden)
```

```
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Package stopwords is already up-to-date!
[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data] Package punkt is already up-to-date!
```

```
data['airline_sentiment'][data['airline_sentiment']=='negative'] = 0
data['airline_sentiment'][data['airline_sentiment']=='neutral'] = 1
data['airline_sentiment'][data['airline_sentiment']=='positive'] = 2
```

```
data.describe()
```

	airline_sentiment	text
count	14404	14404
unique	3	14157
top	0	united thanks
freq	9115	9


Dubbelklik (of druk op Enter) om te bewerken

```
sns.countplot(data['airline_sentiment'])
plt.title('Labels verdeling')
```

Opgeslagen.



```
/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43: FutureWarning
FutureWarning
Text(0.5, 1.0, 'Labels verdeling')
```



```
data['word_count'] = data['text'].apply(lambda x : len(x.split()))
data['char_count'] = data['text'].apply(lambda x : len(x.replace(" ", "")))
data['word_density'] = data['word_count'] / (data['char_count'] + 1)
```



```
data.head()
```

	airline_sentiment	text	word_count	char_count	word_density
0	1	virginamerica dhepburn said	6	28	0.206897
2	1	virginamerica n't today ... must mean need tak...	12	53	0.222222

```
data.describe()
```

	word_count	char_count	word_density
count	14404.000000	14404.000000	14404.000000
mean	14.647390	67.829631	0.216095
std	5.289233	24.349557	0.036742
min	2.000000	8.000000	0.077778
25%	11.000000	50.000000	0.191011
50%	15.000000	71.000000	0.212766
75%	18.000000	86.000000	0.236842

```
fig, ax = plt.subplots(1, 3, figsize=(16, 6))
dp=sns.distplot(data['word_count'],ax=ax[0])
dp=sns.distplot(data['char_count'],ax=ax[1])
dp=sns.distplot(data['word_density'],ax=ax[2])
plt.show()
```


Opgeslagen.

✕

```

/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2557: FutureWarning: FutureWarning
warnings.warn(msg, FutureWarning)
/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2557: FutureWarning: FutureWarning
warnings.warn(msg, FutureWarning)
/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2557: FutureWarning: FutureWarning
warnings.warn(msg, FutureWarning)

```



```
data['text'].head()
```

```

0          virginamerica dhepburn said .
2  virginamerica n't today ... must mean need tak...
3  virginamerica 's really aggressive blast obnox...
4          virginamerica 's really big bad thing
5  virginamerica seriously would pay $ 30 flight ...
Name: text, dtype: object

```

```
dataRF = data
```

```
dataRF = dataRF.drop(['word_count', 'char_count', 'word_density'], axis=1)
```

```
try:
```

```

    %tensorflow_version 2.x
except Exception:
    pass

```

```

import tensorflow as tf
from tensorflow import keras

```

```
print(tf.__version__)
```

```

import numpy as np
import matplotlib.pyplot as plt
import sklearn as sk

```

Opgeslagen.



```
seed = 2020
```

```
np.random.seed(seed)
```

```
import sklearn as sk
```

```
from sklearn.model_selection import train_test_split
```

```
from tensorflow.keras.datasets import mnist
```

```
from tensorflow.keras.models import Sequential
```

```
from tensorflow.keras.layers import Dense, Dropout, Flatten, Embedding, Conv1D, MaxPoolin
```

```
from tensorflow.keras.optimizers import Adam
```

```
from tensorflow.keras.constraints import max_norm
```

```
from tensorflow.keras.models import load_model
```

```
import nltk
```

VERBORGEN UITVOER WEERGEVEN

```
def plot_history(history):
```

```
    plt.figure(figsize = (12,4))
```

```
    plt.subplot(1,2,1)
```

```
    plt.xlabel('Epoch')
```

```
    plt.ylabel('Nauwkeurigheid')
```

```
    plt.plot(history.epoch, np.array(history.history['accuracy']), 'g-',  
             label='Train dataset nauwkeurigheid')
```

```
    plt.plot(history.epoch, np.array(history.history['val_accuracy']), 'r-',  
             label = 'Validatie dataset nauwkeurigheid')
```

```
    plt.legend()
```

```
    plt.subplot(1,2,2)
```

```
    plt.xlabel('Epoch')
```

```
    plt.ylabel('Verlies')
```

```
    plt.plot(history.epoch, np.array(history.history['loss']), 'g-',  
             label='Train dataset verlies')
```

```
    plt.plot(history.epoch, np.array(history.history['val_loss']), 'r-',  
             label = 'Validatie dataset verlies')
```

```
    plt.legend()
```

```
# De lengte van de woorden in een nieuwe kolom
```

```
dataRF['numberOfWords'] = dataRF.text.str.split().apply(len)
```

```
dataRF.head()
```

	airline_sentiment	text	numberOfWords
0	1	virginamerica dhepburn said .	4
2	1	virginamerica n't today ... must mean need tak...	11
3	0	virginamerica 's really aggressive blast obnox...	17

Opgeslagen.



... ..

~

```
dataRF['numberOfWords'].describe()
```

```
count    14404.000000
mean      13.516523
std        5.242989
min         1.000000
25%        10.000000
50%        14.000000
75%        17.000000
max        39.000000
Name: numberOfWords, dtype: float64
```

```
# Een training dataset opzetten
```

```
from sklearn.model_selection import train_test_split
```

```
X = dataRF.drop(['airline_sentiment','numberOfWords'],axis=1)
```

```
y = dataRF['airline_sentiment']
```

```
X_train, X_test, y_train, y_test = train_test_split(X,y,test_size=0.30)
```

```
X_train = np.asarray(X_train)
```

```
X_test = np.asarray(X_test)
```

```
num_classes = 3
```

```
#De methode utils.to_categorical zet vectors om in binaire matrices
```

```
#De scores (0, 1 of 2) worden omgezet naar een binaire matrix. Het aantal klassen is
```

```
#drie omdat er drie opties zijn: positief, neutraal of negatief
```

```
y_train = keras.utils.to_categorical(y_train, num_classes)
```

```
y_test = keras.utils.to_categorical(y_test, num_classes)
```

```
from tensorflow.keras.layers.experimental.preprocessing import TextVectorization
```

```
#TextVectorization zet een lijst van strings om in een lijst van tokens
```

```
vectorizer = TextVectorization(max_tokens=20000, output_sequence_length=20)
```

```
text_ds = tf.data.Dataset.from_tensor_slices(X_train).batch(128)
```

```
vectorizer.adapt(text_ds)
```

```
voc = vectorizer.get_vocabulary()
```

```
word_index = dict(zip(voc, range(len(voc))))
```

```
#Glove staat voor Global Vector
```

```
glove_file = '/content/gdrive/My Drive/glove.6B.100d.txt'
```

```
#Glove-files bevatten woord vectors. De file die hier gebruikt wordt, bevat 400.000 vector
```

```
embeddings_index = {}
```

```
with open(glove_file) as f:
```

```
    for line in f:
```

```
        values = line.split()
```

```
        woord = values[0]
```

```
        coefs = np.asarray(values[1:], dtype='float32')
```

```
        embeddings_index[woord] = coefs
```

Opgeslagen.



```
missed_words = []
```

```

# Een embedding matrix aanmaken
embedding_matrix = np.zeros((num_tokens, embedding_dim))
for word, i in word_index.items():
    embedding_vector = embeddings_index.get(word)
    if embedding_vector is not None:
        embedding_matrix[i] = embedding_vector
    else:
        missed_words.append(word)

#Het model initialiseren
def initial_model3():
    model = Sequential()

    model.add(Embedding(num_tokens, embedding_dim,
                        embeddings_initializer=keras.initializers.Constant(embedding_matrix)))
    model.add(LSTM(3))

    model.compile(loss='binary_crossentropy',
                  optimizer='adam',
                  metrics=['accuracy'])

    return model

def initial_model2():
    model = Sequential()

    model.add(Embedding(num_tokens, embedding_dim,
                        embeddings_initializer=keras.initializers.Constant(embedding_matrix)))
    model.add(Dropout(0.20))
    model.add(Conv1D(16, activation='relu', kernel_size=3))
    model.add(GlobalMaxPooling1D())
    model.add(Dropout(0.20))
    model.add(Dense(3, activation='sigmoid'))

    model.compile(loss='categorical_crossentropy',
                  optimizer='adam',
                  metrics=['accuracy'])

    return model

#Het model initialiseren
def initial_model4():
    model = Sequential()

    model.add(Embedding(num_tokens, embedding_dim,
                        embeddings_initializer=keras.initializers.Constant(embedding_matrix)))
    model.add(Bidirectional(LSTM(16, dropout=0.2, recurrent_dropout=0.2)))
    model.add(Dense(3, activation='softmax'))

```

Opgeslagen.



```
model.compile(loss='categorical_crossentropy',
              optimizer='adam',
              metrics=['accuracy'])
```

```
return model
```

```
#Het model verwacht een array, dus dit wordt hier omgezet
X_train_final = vectorizer(np.array([s for s in X_train])).numpy()
X_test_final = vectorizer(np.array([s for s in X_test])).numpy()
```

```
y_train_final = np.array(y_train)
y_test_final = np.array(y_test)
```

```
model_1 = initial_model4()
model_1.summary()
batch_size = 128
epochs = 30
```

```
history_1 = model_1.fit(X_train_final, y_train_final,
                        batch_size=batch_size,
                        epochs=epochs,
                        verbose=1,
                        validation_data=(X_test_final, y_test_final)
                        )
```

Model: "sequential_5"

Layer (type)	Output Shape	Param #
embedding_5 (Embedding)	(None, None, 100)	1320400
dropout_5 (Dropout)	(None, None, 100)	0
conv1d_5 (Conv1D)	(None, None, 16)	4816
global_max_pooling1d_5 (Glob	(None, 16)	0
dropout_6 (Dropout)	(None, 16)	0
dense_5 (Dense)	(None, 3)	51
Total params: 1,325,267		
Trainable params: 4,867		
Non-trainable params: 1,320,400		

Epoch 1/30

79/79 [=====] - 2s 13ms/step - loss: 1.1389 - accuracy: 0

Epoch 2/30

79/79 [=====] - 1s 11ms/step - loss: 0.8062 - accuracy: 0

Epoch 3/30

79/79 [=====] - 1s 11ms/step - loss: 0.7325 - accuracy: 0

Epoch 4/30

79/79 [=====] - 1s 11ms/step - loss: 0.6761 - accuracy: 0

Epoch 5/30

Opgeslagen.




```

79/79 [=====] - 1s 11ms/step - loss: 0.6611 - accuracy: 0
Epoch 6/30
79/79 [=====] - 1s 11ms/step - loss: 0.6466 - accuracy: 0
Epoch 7/30
79/79 [=====] - 1s 11ms/step - loss: 0.6430 - accuracy: 0
Epoch 8/30
79/79 [=====] - 1s 11ms/step - loss: 0.6205 - accuracy: 0
Epoch 9/30
79/79 [=====] - 1s 11ms/step - loss: 0.6035 - accuracy: 0
Epoch 10/30
79/79 [=====] - 1s 11ms/step - loss: 0.6130 - accuracy: 0
Epoch 11/30
79/79 [=====] - 1s 11ms/step - loss: 0.5982 - accuracy: 0
Epoch 12/30
79/79 [=====] - 1s 11ms/step - loss: 0.5870 - accuracy: 0
Epoch 13/30
79/79 [=====] - 1s 11ms/step - loss: 0.5910 - accuracy: 0
Epoch 14/30
79/79 [=====] - 1s 11ms/step - loss: 0.5690 - accuracy: 0
Epoch 15/30
79/79 [=====] - 1s 11ms/step - loss: 0.5703 - accuracy: 0
Epoch 16/30
79/79 [=====] - 1s 11ms/step - loss: 0.5723 - accuracy: 0
Epoch 17/30
79/79 [=====] - 1s 11ms/step - loss: 0.5719 - accuracy: 0
Epoch 18/30
79/79 [=====] - 1s 11ms/step - loss: 0.5565 - accuracy: 0
Epoch 19/30
79/79 [=====] - 1s 11ms/step - loss: 0.5490 - accuracy: 0
Epoch 20/30

```

#De resultaten visualiseren



```

[train_loss, train_accuracy] = model_1.evaluate(X_train_final, y_train_final, verbose=0)
print("Nauwkeurigheid training dataset:{:7.2f}".format(train_accuracy))
[val_loss, val_accuracy] = model_1.evaluate(X_test_final, y_test_final, verbose=0)
print("Nauwkeurigheid test dataset:{:7.2f}".format(val_accuracy))
plot_history(history_1)

```

Nauwkeurigheid training dataset: 0.84

Nauwkeurigheid test dataset: 0.78



Opgeslagen.

