Homework Week 9

November 2, 2021

1 Homework Week 9

1.1 Question 1: Lorenz Attractor

```
[10]: import matplotlib.pyplot as plt
      import numpy as np
      import random
      plt.figure(figsize = (15,15))
      ax = plt.axes(projection = "3d")
               = eval(input(" ="))
               = eval(input(" ="))
               = eval(input(" ="))
      b
      for i in range(3):
          x0,y0,z0 = eval(input("x0-{0}, y0-{0}, z0-{0}) = ".format(i)))
          dx
                   = lambda x,y,z: s*(y-x)
                   = lambda x,y,z: r*x-y-x*z
          dy
                   = lambda x,y,z: -b*z+x*y
          dz
                   = 0.0001
          dt
                   = np.arange(0,50,dt)
          Т
          X
                   = [x0 for x in range(len(T))]
                   = [y0 for y in range(len(T))]
          У
                   = [z0 for z in range(len(T))]
          for t in range(len(T)-1): \#len(T)-1 so we stay in range
              x[t+1] = x[t] + dx(x[t], y[t], z[t]) * dt
              y[t+1] = y[t] + dy(x[t], y[t], z[t]) * dt
              z[t+1] = z[t] + dz(x[t], y[t], z[t]) * dt
          ax.plot3D(x,y,z,linewidth=0.5)
      ax.view_init(20,25)
      plt.show()
```


```
= 28

= 8/3

x0-0, y0-0, z0-0 = 1,1,1

x0-1, y0-1, z0-1 = 1.001,1.001,1.001

x0-2, y0-2, z0-2 = 0.999,0.999,0.999
```




1.2 Question 2: SIR with = 1 and = 0.5

```
[7]: import matplotlib.pyplot as plt
import numpy as np

b = 2
g = 0.25
```

```
dt = 0.0001
i0 = float(input('initial percent infectuous: '))/100
s0 = 1-i0
ds = lambda s,i: -b*s*i
di = lambda s,i: b*s*i - g*i
dr = lambda i: g*i
s,i,r = [s0],[i0],[0]
while i[-1] >= (s0+i0)*0.0001:
    s.append(s[-1] + ds(s[-1],i[-1])*dt)
    i.append(i[-1] + di(s[-1],i[-1])*dt)
    r.append(r[-1] + dr(i[-1])*dt)
s = [100*x for x in s]
i = [100*x for x in i]
r = [100*x for x in r]
plt.figure(figsize = (15,10))
plt.plot(range(len(s)),s,label='susceptible')
plt.plot(range(len(i)),i,label='infectuous')
plt.plot(range(len(r)),r,label='recovered')
plt.xlabel('time')
plt.ylabel('percent of people')
plt.legend()
plt.show()
print("max percent infected: ", max(i))
```

initial percent infectuous: 0.1



max percent infected: 61.51453473508214

The simulation isn't perfect, but for small (realistic) initial infection rates, the max percent of people infected is always about 61. In real life, it's usually a small handful of people who begin the disease transmission. If you're over 10 percent, that usually means the disease has already been wreaking havok for some time, and some people have already recovered.

1.3 Question 3 - Curve Fitting an Sir Model


```
import numpy as np
import matplotlib.pyplot as plt
import csv
from lmfit import minimize, Parameters, Parameter, report_fit
from scipy.integrate import odeint

with open('HW9_2021_example.csv') as csvfile:
    data_SIR=[]
    readCSV = csv.reader(csvfile)
    for row in readCSV:
        data_SIR.append(row)

data_SIR = data_SIR[1:]
data_SIR = np.array(data_SIR,dtype = np.float32)
```

```
plt.plot(data_SIR[::,1],'.',label='first')
plt.plot(data_SIR[::,2],'.',label='second')
plt.legend()
plt.show()
# open the file, get the data, plot

t = [x for x in range(len(data_SIR))]
```



```
[72]: data_SIR = np.delete(data_SIR,0,axis=1)

[73]: params = Parameters()
```

```
params.add('i0', value=float(data_SIR[0][1]), min=0, max=1)
params.add('s0', value=float(data_SIR[0][0]), min=0, max=1)
params.add('b', value=1, min=0, max=2)

params.add('g', value=0.5, min=0, max=2)

def SIR_func(xs, t, params):
    try:
        b = params['b'].value
        g = params['g'].value
    except:
        b, g = params

s, i = xs
    return [-b*s*i, b*s*i - g*i]
```

```
X0 = np.array([data_SIR[0][0], data_SIR[0][1]])
[74]: def SciPiSolve(t, X0, params):
          return odeint(SIR_func, XO, t, args=(params,))
[75]: def residual(params, t, data):
          init_conditions = params['s0'].value, params['i0'].value
          model = SciPiSolve(t, init_conditions, params)
          return (model - data).ravel()
[76]: result = minimize(residual, params, args=(t, data_SIR), method='leastsq')
      final = data_SIR + result.residual.reshape(data_SIR.shape)
[77]: # final visualization
      plt.figure(figsize=(13,6))
      plt.plot(t, data_SIR,'.', label='Noisy sol')
      plt.plot(t,final, label='estimated sol')
      plt.legend()
      plt.show()
                                                                               Noisy sol
                                                                               Noisy sol
                                                                               estimated sol
                                                                               estimated sol
          0.8
          0.6
          0.4
```

0.2

0.0