



FF-RFI077I4

FF-RFI078I4

FF-RFI079I4

FlexFi Sub6 O-RU

Key Features

3GPP Release 15 : SA mode
O-RAN option 7.2
Support 64 Active Users
eCPRI and O-RAN Open fronthaul termination
Low-PHY :
 FFT,
 PRACH filtering,
 DFE
RF transceiver
RFFE

Benefits

Highly Flexible
Energy Efficient
Open Architecture
Easy to Install and play
Intelligent & Automation

Applications



Commercial



Industry



Hospitality



IoT

Model	FF-RFI077I4	FF-RFI078I4	FF-RFI079I4
Band	n77 : 3.8~4.2GHz	n78 : 3.3~3.8GHz	n79 : 4.4~5.0GHz
3GPP Compliance	Release 15 5G SA		
Duplex Mode	TDD		
Bandwidth	Up to 100MHz		
Antenna Type	Internal Antenna		
RF Tx Power	1W in total. 24dBm per chain		
MIMO Order	4x4 MIMO		
Tx/Rx Path	4T4R		
Modulation	DL : 256 QAM / UL : 64 QAM		
Timing Source	GNSS, IEEE 1588v2, Sync-E		
Fronthaul Connectivity	10G SFP+, 1G RJ45		
Ingress Protection	Indoor : IP20		
Temperature	-5°C ~ 45°C		
Humidity	5% ~ 95%		
Power Supply	54 Vdc		
Power Consumption	65 W		
Dimensions	252 x 252 x 62.7 mm		
OAM Aspects	with LITEON LiteNetics: FM, CM, AM, PM, SM		
RIC Management	O1 Interface : non-Real Time RIC		
Active Users	Support 64 active users		
Deployment	Indoor		
Mounting	Wall mount or ceiling mount		

Dimension Details



For more product information and sales inquiries :

-  www.liteon.com
-  +886-2-8798-2888
-  +886-2-8793-6849
-  5G-Sales@liteon.com
-  13F, No. 392, Ruiguang Rd., Neihu
Dist., Taipei City



Visit us

Specifications are subject to change without notice.