OPTICAL SORTERS, SORTING COMPLEXES, TRANSPORTATION EQUIPMENT, SERVICE

COMMERCIAL OFFER

№ kY9Ka36HNV 08.12.2025



Новиков Денис
разработчик
ООО 'CSORT'
email: infodasdasdqwedasd@mixar.ru
phone: +7 921 948-93-57

Dear Client

Thank you for your interest in the equipment of the CSort company. We present a specially prepared offer for you for equipment and services, as well as terms of delivery and payment. Please, if you need additional information, be sure to contact us, we will be happy to help you.

Bread robot

The channel where we publish analytical reports and the latest agribusiness news

SPECIFICATION

		Name	Pcs	Price,usd	Amount,usd
1		**SmartSort 3.3 Color Sorter**	1	0	0
2		**Sollant SLT-15V**	1	0	0
		Total:			0.0
		incl. VAT 20%:			

REPORT

Product Report

TERMS OF DELIVERY

Payment

5 working days from the date of contract signing.

Delivery time

Color sorter: delivery time 30 working days, Compressor: delivery time 30 working days

Guarantee

for the color sorter, the warranty period is 24 months, for the compressor, the warranty period is 12 months

Commissioning

For color sorters, commissioning is carried out within 7 working days from the date of receipt of the application and confirmation of the equipment's readiness for launch.

Incoterms

FOB Shanghai

MAIN TECHNICAL CHARACTERISTICS
SmartSort 3.3 Color Sorter

1900 mm 1420 mm 1360 mm

Main features:

1	Number of channels, pcs.	**162**
2	Capacity(wheat), incl., not less than*	**21**
3	Cleaning coefficient, %, not less than*	**99,5**
4	Resolution of the CCD matrix (per chute), pixel	**5400**
5	Supply voltage, V	**230**
6	Frequency of the supply network, Hz	**50**
7	Rated power consumption, kW	**1,8**
8	Air pressure, MPa	**0,6-0,8**
9	Air purity class according to ISO 8573-1:	
	By solid particles	**1**
	By humidity	**4**
	In terms of oil content	**1**
10	Air consumption per technological process (wheat), m3/hour, not less than*:	**120**
11	Maximum air flow (at a pressure of 0.6 MPa), m3/h	**225**
12	Weight, kg, max	**900**
13	Protection class against electric shock according to GOST IEC 61140-2012	**1**
14	The degree of protection of the shell according to GOST 14254	**IP54**
15	Ambient temperature, °C	**5-40**
16	Relative humidity at 25 °C, %	**20-80**
17	service life, years	**10**

* With an initial contamination of no more than 2%, the volume weight of the product is 0.750 t/m3.

MAIN TECHNICAL CHARACTERISTICS
Screw compressor Sollant SLTI-15

1030 mm 1150 mm 820 mm

Main features:

1	Receiver volume, l	**320**
2	Output capacity, l/m	**2300**
3	Operating pressure, bar	**8**
4	Engine power, kW	**15**
5	Supply voltage, V	**380**
6	Frequency of the supply network, Hz	**50**
7	Number of phases	**3**
8	Weight, kg	**390**
9	Air dryer	**Included**
10	Filter	**Included**
11	Receiver	**Included**