OPTICAL SORTERS, SORTING COMPLEXES, TRANSPORTATION EQUIPMENT, SERVICE

COMMERCIAL OFFER

№ R2umckWjvp 28.11.2025

Новиков Денис
разработчик
ООО 'SISORT'
email: infodasdasdqwedasd@mixar.ru
phone: +7 921 948-93-57

Dear Client

Thank you for your interest in the equipment of the CSort company. We present a specially prepared offer for you for equipment and services, as well as terms of delivery and payment. Please, if you need additional information, be sure to contact us, we will be happy to help you.

CoffeeBot

Telegram channel "Bokassa black"

Subscribe to stay up to date with all the coffee trends!

SPECIFICATION

		Name	Pcs	Price,rub	Amount,rub
1		**SmartSort 3.3 Color Sorter**	1	0	0
2		**ASAP.521.0072.00 3 kW compressor on site, with dryer and filters**	1	0	0
		Total:			0.0
		incl. VAT 20%:			

REPORT

Product Report

TERMS OF DELIVERY

Payment

5 working days from the date of contract signing.

Delivery time

Photo separator: delivery time 30 working days, Compressor: delivery time 30 working days

Guarantee

for the photo separator, the warranty period is 26 months, for the compressor, the warranty period is 12 months

Commissioning

For photo separators, commissioning is carried out within 7 working days from the date of receipt of the application and confirmation of the equipment's readiness for launch.

MAIN TECHNICAL CHARACTERISTICS
SmartSort 3.3 Color Sorter

1900 mm 1420 mm 1360 mm

Main features:

1	Number of channels, pcs.	**162**
2	Productivity(coffee), incl., not less than*	**21**
3	Cleaning coefficient, %, not less than*	**99,5**
4	Resolution of the CCD matrix (per tray), pixel	**5400**
5	Supply voltage, V	**230**
6	Frequency of the supply network, Hz	**50**
7	Rated power consumption, kW	**1,8**
8	Air pressure, MPa	**0,6-0,8**
9	Air purity class according to GOST 17433, ISO 8573-1:	
	By solid particles	**1**
	By humidity	**4**
	In terms of oil content	**1**
10	Air consumption per technological process (coffee), m3/hour, not less than*:	**120**
11	Maximum air flow (at a pressure of 0.6 MPa), m3/h	**225**
12	Weight, kg, max	**900**
13	Protection class against electric shock according to GOST IEC 61140-2012	**1**
14	The degree of protection of the shell according to GOST 14254	**IP54**
15	Ambient temperature, °C	**5-40**
16	Relative humidity at 25 °C, %	**20-80**
17	service life, years	**10**

* With an initial contamination of no more than 2%, the volume weight of the product is 0.750 t/m3.

MAIN TECHNICAL CHARACTERISTICS ASAP.521.0072.00 3 kW compressor on site, with dryer and filters

1000 mm 1100 mm 445 mm

Main features:

DXF

LINK TO THE DXF