

# Marked Temporal Point Processes for simulating and capturing coordinated behaviour campaigns

Models for enhancing **disinformation** detection

**Elisa Muratore<sup>1,3</sup>**, Letizia Iannucci<sup>2</sup>, Riccardo Gallotti<sup>3</sup>, Mikko Kivelä<sup>2</sup>, Claudio Agostinelli<sup>1</sup>  
 1. University of Trento 2. AALTO University 3. Bruno Kessler Foundation

## Coordinated behaviour

**Coordinated Inauthentic Behaviour (CIB):** Groups of individuals working together to mislead other users about who they are and what they are doing.

CIBs pose a significant **societal threat** by spreading confusion, division, and fear.

## Research objectives

CIB's systematic and synergistic activities appear anomalous with respect to authentic users' **temporal patterns**.

Exploit *Marked Temporal Point Processes* for modelling social media activities and identify CIB's clusters

The absence of ground truth data and the **wide number of existing strategies** pose serious difficulties for evaluation

Exploit *Marked Temporal Point Processes (MTPP)* for creating a CIB's simulation framework

## Detection

### 1. Co-Activity cascades

Data as MTPPs' realisation  
Preprocess social media data

### 2. AMDN-HAGE extensions:

- Retrieve users' clusters  $U$   
Use MTPP and GMM and DL
- **Clustering techniques**  
On users' embeddings  $E$
- **Exploit influences**  
On users' influences

Date	Content:	Post (P) or Repost (R)	User
September 12, 2022 at 10:57 AM	P Studies show that drinking bleach can cure COVID. Many hospitals are hiding this information to keep their profits up		User A
September 17, 2022 at 05:50 PM	R Studies show that drinking bleach can cure COVID. Many hospitals are hiding this information to keep their profits up		User B
September 20, 2022 at 02:04 AM	R Studies show that drinking bleach can cure COVID. Many hospitals are hiding this information to keep their profits up		User A
November 15, 2022 at 07:05 PM	R Studies show that drinking bleach can cure COVID. Many hospitals are hiding this information to keep their profits up		User C
...			...

$$C_s = [(t_1, u_1 = \text{User A}), (t_2, u_2 = \text{User B}), (t_3, u_3 = \text{User A}), (t_4, u_4 = \text{User C}), \dots]$$

$$\log p_{\theta_a, \theta_b}(C_s, U | E) = \log p_{\theta_a}(C_s | U, E) + \log p_{\theta_b}(U | E)$$

$$\log p(C_s | U, E, \theta_a) = \sum_{i=1}^{|C_s|} [\log p_{E, \theta_a}(t_i | H_{t_i}) + \log p_{E, \theta_a}(m_i | H_{t_i})]$$

$$\log p(U | E, \theta_b) = \sum_{j=1}^{|U|} \log \left[ \sum_{i=1}^N w_i \cdot p(E_{u_j} | \mu_i, \Sigma) \right]$$

## Simulation

### 1. Bayesian Parameters

Authentic users and CIBs

Set up based on real datasets

#### Authentic users      Inauthentic users

$$\begin{aligned} \mu_i &\sim \Gamma(\mu, \sigma_\mu^2) & \mu_i &= c_\mu \mu Z \\ \alpha_{i,j} &\sim \Gamma(\alpha, \sigma_\alpha^2) & \alpha_{i,j} &= c_\alpha \alpha Z \\ \beta_i &\sim \Gamma(\beta, \sigma_\beta^2) & \beta_i &= c_\beta \beta Z \end{aligned}$$

#### Mixed interactions

$$(a_{i,j})_{i,j} = \begin{pmatrix} & \text{authentic} & \text{influencer} \\ \text{authentic} & \alpha_{i,j} & \cdots & \alpha_{i,j} & 0 & \cdots & 0 \\ \vdots & \ddots & \ddots & \vdots & \vdots & \ddots & \vdots \\ \alpha_{i,j} & \cdots & \alpha_{i,j} & 0 & \cdots & 0 & \\ \text{influencer} & c_\alpha \alpha Z & \cdots & c_\alpha \alpha Z & c_\alpha \alpha Z & \cdots & c_\alpha \alpha Z \\ \vdots & \ddots & \ddots & \vdots & \vdots & \ddots & \vdots \\ c_\alpha \alpha Z & \cdots & c_\alpha \alpha Z & c_\alpha \alpha Z & c_\alpha \alpha Z & \cdots & c_\alpha \alpha Z \end{pmatrix}$$


The percentage of mixed interactions is controlled by parameter  $p$

### 2. MTPP model

#### Co-Activity cascades


Generate data

- $\alpha_{k,m}$  excitation rate
- $\beta_{k,m}$  decay rate
- $\mu_k$  baseline rate




$$\begin{aligned} \lambda_k(t | H_t) &:= \frac{\mathbb{E}[dN_t^k | H_t]}{dt} \\ &= \mu_k + \sum_{m=1}^K \sum_{t_{i,m} < t} \alpha_{k,m} e^{-\beta_{k,m}(t - t_{i,m})} \end{aligned}$$

## Results



AMDNHAGE + KMEANS achieves the best performance in all these cases, no matter what value of the excitation parameter  $c_\alpha$  is considered

Changing the interaction level  $p$  has a big effect on the performance: no method outperforms the others in all these scenarios



## Conclusions

### • Detection and simulations:

- Clustering and users' influences for **detection enhancement**
- **Novel suite** for a comprehensive and systematic evaluation

### • Importance of the objective:

- Different methods may excel depending on the **CIBs nature**
- Careful consideration of the **data features and detection goals**

## Main References

- European External Action Service EEAS. 2nd eeas report on foreign information manipulation and interference (fimi) threats. Technical report, 2024. URL: <https://www.eeas.europa.eu/eeas>. Accessed: 2024-09-20.
- Diogo Pacheco, Pik-Mai Hui, Christopher Torres-Lugo, Bao Tran Truong, Alessandro Flammini, and Filippo Menczer. Uncovering coordinated networks on social media: methods and case studies. In Proceedings of the international AAAI conference on web and social media, 2021.
- Daryl J Daley and David Vere-Jones. An introduction to the theory of point processes: volume I: elementary theory and methods. Springer Science and Business Media, 2006.
- Karishma Sharma, Yizhou Zhang, Emilio Ferrara, and Yan Liu. Identifying coordinated accounts on social media through hidden influence and group behaviours. In Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining, 2021.

## Contacts

