

Silk

Luxury Base Coat



Product Attributes



Provides Good Opacity


Low VOC and Smell



Eco-friendly



Reduces Porosity of Surface



Improves Finish Coat Performance



Green Pro Certified



Product Description

Silk Luxury Base Coat is a premium quality water-based acrylic primer for application on masonry surfaces. Silk Luxury Base Coat is Green Label certified by Singapore Environment Council.

Recommended Use

Area of application:



Masonry

Colour Range



White

50% by volume

Recommended Dilution



Dilute 1litre Silk Luxury Base Coat with 500ml potable water and mix well.

Application Method



Brush, Roller & Spray

Flash Point



Above 37° +/- 2°C

Drying Time



SD : 1-2 hrs depending on weather conditions
HD : 4-6hrs depending on weather conditions.
Over coating preferably overnight.

Suitable for:



Interior & Exterior

Finish

MATT ✓

GLOSS

HI-GLOSS

SUPER GLOSS

Coverage



1 COAT : 150 - 180 sq.ft/Lt*
2 COATS : 100 - 120 sq.ft/Lt*
(by Brush Application)

(*Actual coverage may vary from the theoretical coverage due to factors such as method and condition of application, surface roughness, porosity and thickness of the film.)

Viscosity

Brush / Roller :

50-60 sec @ 30°C/Ford Cup B-4

Spraying :

25-35 sec @ 30°C/Ford Cup B-4

Recoating Period



Overnight drying, after applying first coat
(Depending upon ambient temperature & humidity)

Silk

Luxury Base Coat



Packs Available



1 L

4 L

10 L

20 L



Stability Of Thinned Paint

To be used within 24 Hours



Fire Hazard Class

Flammable



Shelf Life

24 months from date of manufacture as long as the container is sealed and kept at normal temperature and away from direct sunlight

Surface Preparation

Surface Inspection:



Before painting, the surface must be free of dirt, oil and grease. Remove grease, oil and other contaminants by using Berger Thinner - 800/T65/03E

Scrapping:



Prepare the surface by scrubbing with wire Brush or Berger Sand Paper No. 150/180 to ensure the surface is clean and smooth. Wipe out Thinner and make sure the surface is fully dry.

Crack Bridging:



Walls : For filling cracks, up to 5mm, use Home Shield Crack Fill Paste. For wider cracks use Home Shield Advance Latex Plus as per product usage guidelines.
Wood : Use Woodkeeper Fill-O-Dent to fill the cracks.

Putty Application :



Apply 1 or 2 Coats of Putty at an interval of 4-6 hours.

Recommended Putty :

Walls
Wood

: HS Waterproof Putty / Bison Wall Putty / Acrylic Putty
: Luxol Knifing Putty / Fill-O-Dent Putty

Primer Application :



After 24 hours of putty application, apply two coats of Silk Luxury Base Coat diluted as recommended. Allow overnight drying time between coats. After the 2nd coat of Primer, the surface should be dry cut with Berger Wet & Dry Sheets No. 320/400 before application of the Top Coat.

Storage

Store in a cool dry place.

Keep away from source of ignition.

Keep container tightly closed, out of children's reach and away from foodstuff.

Disposal

Do not pour left over paint down the drain or any watercourse.

Dispose in accordance with local regulation.

Safety & Precaution

Ensure good ventilation during application and drying of paint.

Wear protective clothes and gloves.

Smoking is prohibited while painting.

Avoid inhaling the vapour. Wear suitable dust nose pad when rubbing the surface.

Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.

Version No: BPP1/09/2023. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com