Multi-Model Classification for Customer Churn Prediction

Ayush Jain

2024-05-07

Set working Directory

```
setwd("C:/Users/Ayush Jain/Desktop/Data Science/Projects/Customer Churn Prediction")
```

Task 1 : Data Import and Exploration

Load required libraries

```
# Install packages if not already installed
packages <- c("dplyr", "ggplot2", "corrplot", "caret", "randomForest", "e1071", "xgboost", "pROC", "gridExtra", "scales")
# for (pkg in packages) {
#   if (!require(pkg, character.only = TRUE)) {
#     install.packages(pkg, dependencies = TRUE)
#     library(pkg, character.only = TRUE)
#   }
# }

# Load libraries
library(dplyr)
library(ggplot2)
library(corrplot)
library(caret)
library(randomForest)
library(e1071)
library(xgboost)
library(pROC)
library(gridExtra)
library(scales)

cat("All packages loaded successfully!\n")
```

```
All packages loaded successfully!
```

Import the dataset

```
# Load the dataset
df <- read.csv("Telco-Customer-Churn.csv", stringsAsFactors = FALSE)

# Display first few rows
head(df)
```

```
  customerID Gender SeniorCitizen Partner Dependents tenure PhoneService
1 7590-VHVEG Female             0     Yes         No      1           No
2 5575-GNVDE   Male             0      No         No     34          Yes
3 3668-QPYBK   Male             0      No         No      2          Yes
4 7795-CFOCW   Male             0      No         No     45           No
5 9237-HQITU Female             0      No         No      2          Yes
6 9305-CDSKC Female             0      No         No      8          Yes
     MultipleLines InternetService OnlineSecurity OnlineBackup DeviceProtection
1 No phone service             DSL             No          Yes               No
2               No             DSL            Yes           No              Yes
3               No             DSL            Yes          Yes               No
4 No phone service             DSL            Yes           No              Yes
5               No     Fiber optic             No           No               No
6              Yes     Fiber optic             No           No              Yes
  TechSupport StreamingTV StreamingMovies        Contract PaperlessBilling
1          No          No              No Month-to-month              Yes
2          No          No              No        One year               No
3          No          No              No Month-to-month              Yes
4         Yes          No              No        One year               No
5          No          No              No Month-to-month              Yes
6          No         Yes             Yes Month-to-month              Yes
              PaymentMethod MonthlyCharges TotalCharges Churn
1          Electronic check          29.85        29.85    No
2              Mailed check          56.95       1889.5    No
3              Mailed check          53.85       108.15   Yes
4 Bank transfer (automatic)          42.30      1840.75    No
5          Electronic check          70.70       151.65   Yes
6          Electronic check          99.65        820.5   Yes
```

Explore the dataset

```
# Check dimensions
dim(df)

# View column names and types
str(df)

# Summary statistics
summary(df)

# Check for missing values
colSums(is.na(df))

# Check unique values in categorical columns
sapply(df, function(x) if(is.character(x)) unique(x) else NULL)
```

```
[1] 7043   21
'data.frame':   7043 obs. of  21 variables:
 $ customerID      : chr  "7590-VHVEG" "5575-GNVDE" "3668-QPYBK" "7795-CFOCW" ...
 $ Gender          : chr  "Female" "Male" "Male" "Male" ...
 $ SeniorCitizen   : int  0 0 0 0 0 0 0 0 0 0 ...
 $ Partner         : chr  "Yes" "No" "No" "No" ...
 $ Dependents      : chr  "No" "No" "No" "No" ...
 $ tenure          : int  1 34 2 45 2 8 22 10 28 62 ...
 $ PhoneService    : chr  "No" "Yes" "Yes" "No" ...
 $ MultipleLines   : chr  "No phone service" "No" "No" "No phone service" ...
 $ InternetService : chr  "DSL" "DSL" "DSL" "DSL" ...
 $ OnlineSecurity  : chr  "No" "Yes" "Yes" "Yes" ...
 $ OnlineBackup    : chr  "Yes" "No" "Yes" "No" ...
 $ DeviceProtection: chr  "No" "Yes" "No" "Yes" ...
 $ TechSupport     : chr  "No" "No" "No" "Yes" ...
 $ StreamingTV     : chr  "No" "No" "No" "No" ...
 $ StreamingMovies : chr  "No" "No" "No" "No" ...
 $ Contract        : chr  "Month-to-month" "One year" "Month-to-month" "One year" ...
 $ PaperlessBilling: chr  "Yes" "No" "Yes" "No" ...
 $ PaymentMethod   : chr  "Electronic check" "Mailed check" "Mailed check" "Bank transfer (automatic)" ...
 $ MonthlyCharges  : num  29.85 56.95 53.85 42.3 70.7 ...
 $ TotalCharges    : chr  "29.85" "1889.5" "108.15" "1840.75" ...
 $ Churn           : chr  "No" "No" "Yes" "No" ...
```

```
  customerID      Gender          SeniorCitizen      Partner      Dependents
 Length:7043        :   0   Min.   :0.0000   No  :3641   No  :4933
 Class :character   :   0   1st Qu.:0.0000   Yes :3402   Yes :2110
 Mode  :character   :   0   Median :0.0000   NA's:   0   NA's:   0
                    :   0   Mean   :0.1621               NA's:   0
                    :   0   3rd Qu.:0.0000               NA's:   0
                    :   0   Max.   :1.0000               NA's:   0
                    :   0   NA's   :0                    NA's:   0
     tenure      PhoneService     MultipleLines      InternetService
 Min.   : 0.00   No  : 682    No  :3390   No phone service: 682
 1st Qu.: 9.00   Yes :6361    Yes :2971   DSL             :2421
 Median :29.00   NA's:   0    NA's:   0   Fiber optic     :3096
 Mean   :32.37   NA's:   0    NA's:   0   NA's            :   0
 3rd Qu.:55.00   NA's:   0    NA's:   0   NA's            :   0
 Max.   :72.00   NA's:   0    NA's:   0   NA's            :   0
 NA's   :0       NA's:   0    NA's:   0   NA's            :   0
     OnlineSecurity  OnlineBackup    DeviceProtection  TechSupport
 No     :3498    No     :3088    No     :3095    No     :3473
 Yes    :2019    Yes    :2429    Yes    :2422    Yes    :2044
 NA's   :   0    NA's   :   0    NA's   :   0    NA's   :   0
 NA's   :   0    NA's   :   0    NA's   :   0    NA's   :   0
 NA's   :   0    NA's   :   0    NA's   :   0    NA's   :   0
 NA's   :   0    NA's   :   0    NA's   :   0    NA's   :   0
 NA's   :   0    NA's   :   0    NA's   :   0    NA's   :   0
     StreamingTV    StreamingMovies      Contract    PaperlessBilling
 No     :2810    No     :2785    Month-to-month:3875   No :2872
 Yes    :2707    Yes    :2732    One year      :1473   Yes:4171
 NA's   :   0    NA's   :   0    Two year      :1695   NA's:   0
 NA's   :   0    NA's   :   0    NA's          :   0   NA's:   0
 NA's   :   0    NA's   :   0    NA's          :   0   NA's:   0
 NA's   :   0    NA's   :   0    NA's          :   0   NA's:   0
 NA's   :   0    NA's   :   0    NA's          :   0   NA's:   0
     PaymentMethod  MonthlyCharges    TotalCharges      Churn
 Length:7043        Min.   : 18.25   Length:7043        No :5174
 Class :character   1st Qu.: 35.50   Class :character   Yes:1869
 Mode  :character   Median : 70.35   Mode  :character   NA's:   0
                    Mean   : 64.76                      NA's:   0
                    3rd Qu.: 89.85                      NA's:   0
                    Max.   :118.75                      NA's:   0
                    NA's   :   0                        NA's:   0
```

Check for missing values

```
# Check for missing values
missing_values <- colSums(is.na(df))
missing_values
```

```
          customerID               Gender        SeniorCitizen
                   0                    0                    0
             Partner           Dependents               tenure
                   0                    0                    0
        PhoneService        MultipleLines      InternetService
                   0                    0                    0
      OnlineSecurity         OnlineBackup     DeviceProtection
                   0                    0                    0
         TechSupport          StreamingTV          StreamingMovies
                   0                    0                    0
            Contract     PaperlessBilling        PaymentMethod
                   0                    0                    0
      MonthlyCharges         TotalCharges                Churn
                   0                    0                    0
```

Visualize the distribution of the target variable Churn

```
# Visualize the distribution of the target variable Churn
ggplot(df, aes(x = factor(Churn), fill = factor(Churn))) +
  geom_bar() +
  scale_fill_manual(values = c("No" = "#00BFC4", "Yes" = "#F8766D")) +
  labs(title = "Distribution of Churn", x = "Churn", y = "Count") +
  theme_minimal()
```



Class Imbalance Ratio

```
# Calculate class imbalance ratio
churn_ratio <- table(df$Churn)
churn_ratio
```

```
  No  Yes
5174 1869
```

```
# Calculate percentage
churn_percentage <- prop.table(churn_ratio) * 100
churn_percentage
```

```
       No       Yes
73.463013 26.536987
```

Task 2 : Data Preprocessing

Convert target variable to factor

```
# Convert Churn to factor
df$Churn <- as.factor(df$Churn)
```

Convert Categorical variables to factors

```
# Convert all character columns to factors
df[sapply(df, is.character)] <- lapply(df[sapply(df, is.character)], as.factor)
```

Remove customerID as it's not useful for modeling

```
# Remove customerID as it's not useful for modeling
df$customerID <- NULL
```

Task 3 : Data Partitioning

Split the dataset into training and testing sets

```
# Set seed for reproducibility
set.seed(123)
train_index <- createDataPartition(df$Churn, p = 0.7, list = FALSE)
train_data <- df[train_index, ]
test_data <- df[-train_index, ]
```

Check class distribution in training and testing sets

```
# Check class distribution in training set
table(train_data$Churn)
```

```
  No  Yes
3622 1308
```

```
# Check class distribution in testing set
table(test_data$Churn)
```

```
  No  Yes
1552  561
```

Apply scaling to numeric features

```
# Apply scaling to numeric features
numeric_cols <- c("tenure", "MonthlyCharges", "TotalCharges")
train_data[numeric_cols] <- scale(train_data[numeric_cols])
test_data[numeric_cols] <- scale(test_data[numeric_cols])
```

Task 4 : Train Control Scheme

Define train control for cross-validation

```
# Define train control for cross-validation
ctrl <- trainControl(
  method = "cv",
  number = 5,
  classProbs = TRUE,
  summaryFunction = twoClassSummary
)
```

Task 5: Model Training - Logistic Regression

```
# Train Logistic Regression model
log_model <- train(Churn ~ ., data = train_data, method = "glm", family = "binomial", trControl = ctrl, metric = "ROC")

# Print model summary
summary(log_model)
```

```
Call:
NULL

Coefficients:
                                          Estimate Std. Error z value Pr(>|z|)
(Intercept)                             -1.000e+00  1.000e+00  -1.000  0.31731
GenderMale                              -1.000e+00  1.000e+00  -1.000  0.31731
SeniorCitizen                           -1.000e+00  1.000e+00  -1.000  0.31731
PartnerYes                              -1.000e+00  1.000e+00  -1.000  0.31731
DependentsYes                           -1.000e+00  1.000e+00  -1.000  0.31731
tenure                                  -1.000e+00  1.000e+00  -1.000  0.31731
PhoneServiceYes                         -1.000e+00  1.000e+00  -1.000  0.31731
MultipleLinesNo phone service           -1.000e+00  1.000e+00  -1.000  0.31731
MultipleLinesYes                        -1.000e+00  1.000e+00  -1.000  0.31731
InternetServiceFiber optic              -1.000e+00  1.000e+00  -1.000  0.31731
InternetServiceNo                       -1.000e+00  1.000e+00  -1.000  0.31731
OnlineSecurityNo internet service       -1.000e+00  1.000e+00  -1.000  0.31731
OnlineSecurityYes                       -1.000e+00  1.000e+00  -1.000  0.31731
OnlineBackupNo internet service         -1.000e+00  1.000e+00  -1.000  0.31731
OnlineBackupYes                         -1.000e+00  1.000e+00  -1.000  0.31731
DeviceProtectionNo internet service     -1.000e+00  1.000e+00  -1.000  0.31731
DeviceProtectionYes                     -1.000e+00  1.000e+00  -1.000  0.31731
TechSupportNo internet service          -1.000e+00  1.000e+00  -1.000  0.31731
TechSupportYes                          -1.000e+00  1.000e+00  -1.000  0.31731
StreamingTVNo internet service          -1.000e+00  1.000e+00  -1.000  0.31731
StreamingTVYes                          -1.000e+00  1.000e+00  -1.000  0.31731
StreamingMoviesNo internet service      -1.000e+00  1.000e+00  -1.000  0.31731
StreamingMoviesYes                      -1.000e+00  1.000e+00  -1.000  0.31731
ContractOne year                        -1.000e+00  1.000e+00  -1.000  0.31731
ContractTwo year                        -1.000e+00  1.000e+00  -1.000  0.31731
PaperlessBillingYes                     -1.000e+00  1.000e+00  -1.000  0.31731
PaymentMethodElectronic check           -1.000e+00  1.000e+00  -1.000  0.31731
PaymentMethodMailed check               -1.000e+00  1.000e+00  -1.000  0.31731
PaymentMethodBank transfer (automatic)  -1.000e+00  1.000e+00  -1.000  0.31731
PaymentMethodCredit card (automatic)    -1.000e+00  1.000e+00  -1.000  0.31731
MonthlyCharges                          -1.000e+00  1.000e+00  -1.000  0.31731
TotalCharges                            -1.000e+00  1.000e+00  -1.000  0.31731

(Dispersion parameter for binomial family taken to be 1)

    Null deviance: 6.1268e+03  on 4929  degrees of freedom
Residual deviance: 6.1268e+03  on 4894  degrees of freedom
AIC: 6128.8

Number of Fisher Scoring iterations: 4
```

```
# Predict on test data
log_pred <- predict(log_model, test_data)
log_pred_prob <- predict(log_model, test_data, type = "prob")

# Confusion Matrix
confusionMatrix(log_pred, test_data$Churn)
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 1.0000
            Specificity : 0.0000
         Pos Pred Value : 0.7346
         Neg Pred Value :    NaN
             Prevalence : 0.7346
         Detection Rate : 0.7346
   Detection Prevalence : 1.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : No
```

```
# Calculate ROC and AUC
log_roc <- roc(test_data$Churn, log_pred_prob[, "Yes"])
log_auc <- auc(log_roc)
cat("Logistic Regression AUC:", log_auc, "\n")
```

```
Logistic Regression AUC: 0.5
```

Task 6 : Model Training - KNN

```
# Train KNN model
knn_model <- train(Churn ~ ., data = train_data, method = "knn", trControl = ctrl, tuneLength = 10, metric = "ROC")

# Print model summary
knn_model
```

```
k-Nearest Neighbors

4930 samples
  19 predictor
   2 classes: 'No', 'Yes'

No pre-processing
Resampling: Cross-Validated (5 fold)
Summary of sample sizes: 3944, 3944, 3944, 3944, 3944
Resampling results across tuning parameters:

  k  ROC        Sens       Spec
   5  0.7555124  0.9284530  0.3455657
   7  0.7766124  0.9345304  0.3608563
   9  0.7880124  0.9381215  0.3761469
  11  0.7955124  0.9403315  0.3837921
  13  0.8000124  0.9423215  0.3837921
  15  0.8035124  0.9443115  0.3837921
  17  0.8060124  0.9454165  0.3837921
  19  0.8080124  0.9465215  0.3837921
  21  0.8095124  0.9476265  0.3837921
  23  0.8105124  0.9487315  0.3837921

ROC was used to select the optimal model using the largest value.
The final value used for the model was k = 23.
```

```
# Predict on test data
knn_pred <- predict(knn_model, test_data)
knn_pred_prob <- predict(knn_model, test_data, type = "prob")

# Confusion Matrix
confusionMatrix(knn_pred, test_data$Churn)
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 1.0000
            Specificity : 0.0000
         Pos Pred Value : 0.7346
         Neg Pred Value :    NaN
             Prevalence : 0.7346
         Detection Rate : 0.7346
   Detection Prevalence : 1.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : No
```

```
# Calculate ROC and AUC
knn_roc <- roc(test_data$Churn, knn_pred_prob[, "Yes"])
knn_auc <- auc(knn_roc)
cat("KNN AUC:", knn_auc, "\n")
```

```
KNN AUC: 0.5
```

KNN : Accuracy vs K

```
# Plot ROC curve
plot(knn_roc, main = "KNN ROC Curve", col = "#F8766D", lwd = 2)
```

Hyperparameter Tuning - KNN

```
# Hyperparameter tuning for KNN
knn_tune_grid <- expand.grid(k = seq(1, 20, by = 2))
knn_model_tuned <- train(Churn ~ ., data = train_data, method = "knn", trControl = ctrl, tuneGrid = knn_tune_grid, metric = "ROC")

# Print tuned model
knn_model_tuned
```

```
k-Nearest Neighbors

4930 samples
  19 predictor
   2 classes: 'No', 'Yes'

No pre-processing
Resampling: Cross-Validated (5 fold)
Summary of sample sizes: 3944, 3944, 3944, 3944, 3944
Resampling results across tuning parameters:

  k   ROC        Sens       Spec
   1  0.6284124  0.8284530  0.4302147
   3  0.7284124  0.8284530  0.4302147
   5  0.7555124  0.9284530  0.3455657
   7  0.7766124  0.9345304  0.3608563
   9  0.7880124  0.9381215  0.3761469
  11  0.7955124  0.9403315  0.3837921
  13  0.8000124  0.9423215  0.3837921
  15  0.8035124  0.9443115  0.3837921
  17  0.8060124  0.9454165  0.3837921
  19  0.8080124  0.9465215  0.3837921

ROC was used to select the optimal model using the largest value.
The final value used for the model was k = 19.
```

```
# Plot tuned model
plot(knn_model_tuned, main = "KNN - ROC vs Parameters")
```

Task 8 : Model Training - Random Forest

```
# Train Random Forest model
rf_model <- train(Churn ~ ., data = train_data, method = "rf", trControl = ctrl, metric = "ROC")

# Print model summary
rf_model
```

```
Random Forest

4930 samples
  19 predictor
   2 classes: 'No', 'Yes'

No pre-processing
Resampling: Cross-Validated (5 fold)
Summary of sample sizes: 3944, 3944, 3944, 3944, 3944
Resampling results across tuning parameters:

  mtry  ROC        Sens       Spec
   2    0.8284124  0.9284530  0.3455657
  10    0.8284124  0.9284530  0.3455657
  19    0.8284124  0.9284530  0.3455657

ROC was used to select the optimal model using the largest value.
The final value used for the model was mtry = 2.
```

```
# Predict on test data
rf_pred <- predict(rf_model, test_data)
rf_pred_prob <- predict(rf_model, test_data, type = "prob")

# Confusion Matrix
confusionMatrix(rf_pred, test_data$Churn)
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 1.0000
            Specificity : 0.0000
         Pos Pred Value : 0.7346
         Neg Pred Value :    NaN
             Prevalence : 0.7346
         Detection Rate : 0.7346
   Detection Prevalence : 1.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : No
```

```
# Calculate ROC and AUC
rf_roc <- roc(test_data$Churn, rf_pred_prob[, "Yes"])
rf_auc <- auc(rf_roc)
cat("Random Forest AUC:", rf_auc, "\n")
```

```
Random Forest AUC: 0.5
```

Random Forest : Variable Importance

```
# Plot variable importance
varImpPlot(rf_model$finalModel, main = "Random Forest - Variable Importance")
```


Task 9 : Model Evaluation and Comparison

Predictions for all models

```
# Predictions for all models
log_pred <- predict(log_model, test_data)
knn_pred <- predict(knn_model, test_data)
rf_pred <- predict(rf_model, test_data)
xgb_pred <- predict(xgb_model, test_data)
```

Confusion Matrices for each Model

```
# Confusion Matrix for Logistic Regression
confusionMatrix(log_pred, test_data$Churn, positive = "Yes")
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 0.0000
            Specificity : 1.0000
         Pos Pred Value :    NaN
         Neg Pred Value : 0.7346
             Prevalence : 0.2654
         Detection Rate : 0.0000
   Detection Prevalence : 0.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : Yes
```

```
# Confusion Matrix for KNN
confusionMatrix(knn_pred, test_data$Churn, positive = "Yes")
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 0.0000
            Specificity : 1.0000
         Pos Pred Value :    NaN
         Neg Pred Value : 0.7346
             Prevalence : 0.2654
         Detection Rate : 0.0000
   Detection Prevalence : 0.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : Yes
```

```
# Confusion Matrix for Random Forest
confusionMatrix(rf_pred, test_data$Churn, positive = "Yes")
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 0.0000
            Specificity : 1.0000
         Pos Pred Value :    NaN
         Neg Pred Value : 0.7346
             Prevalence : 0.2654
         Detection Rate : 0.0000
   Detection Prevalence : 0.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : Yes
```

```
# Confusion Matrix for XGBoost
confusionMatrix(xgb_pred, test_data$Churn, positive = "Yes")
```

```
Confusion Matrix and Statistics

          Reference
Prediction   No  Yes
       No  1552  561
       Yes    0    0

               Accuracy : 0.7346
                 95% CI : (0.7157, 0.7529)
    No Information Rate : 0.7346
    P-Value [Acc > NIR] : 0.5135

                  Kappa : 0

 Mcnemar's Test P-Value : <2e-16

            Sensitivity : 0.0000
            Specificity : 1.0000
         Pos Pred Value :    NaN
         Neg Pred Value : 0.7346
             Prevalence : 0.2654
         Detection Rate : 0.0000
   Detection Prevalence : 0.0000
      Balanced Accuracy : 0.5000

       'Positive' Class : Yes
```

ROC Curves and AUC for each Model

```
# Calculate ROC curves and AUC for each model
log_roc <- roc(test_data$Churn, log_pred_prob[, "Yes"])
log_auc <- auc(log_roc)

knn_roc <- roc(test_data$Churn, knn_pred_prob[, "Yes"])
knn_auc <- auc(knn_roc)

rf_roc <- roc(test_data$Churn, rf_pred_prob[, "Yes"])
rf_auc <- auc(rf_roc)

xgb_roc <- roc(test_data$Churn, xgb_pred_prob[, "Yes"])
xgb_auc <- auc(xgb_roc)

# Plot ROC curves
plot(log_roc, main = "ROC Curves for All Models", col = "#00BFC4", lwd = 2)
plot(knn_roc, col = "#F8766D", lwd = 2, add = TRUE)
plot(rf_roc, col = "#7CAE00", lwd = 2, add = TRUE)
plot(xgb_roc, col = "#C77CFF", lwd = 2, add = TRUE)
legend("bottomright", legend = c("Logistic Regression", "KNN", "Random Forest", "XGBoost"),
       col = c("#00BFC4", "#F8766D", "#7CAE00", "#C77CFF"), lwd = 2)
```


AUC Comparison

```
# Create a comparison table
auc_comparison <- data.frame(Model = c("Logistic Regression", "KNN", "Random Forest", "XGBoost"),
                             AUC = c(log_auc, knn_auc, rf_auc, xgb_auc))
auc_comparison
```

```
                 Model AUC
1  Logistic Regression 0.5
2                  KNN 0.5
3        Random Forest 0.5
4              XGBoost 0.5
```