

```
ssh.cloud.google.com/v2/ssh/projects/proyect-big-data-arquitectura/zones/europe-southwest1-b/instances/instance-practica-p...
ssh.cloud.google.com/v2/ssh/projects/proyect-big-data-arquitectura/zones/europe-southwest1-b/instances/instanc...
SSH-in-browser
UPLOAD FILE
DOWNLOAD FILE

Linux instance-practica-parte2 6.1.0-39-cloud-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.1.148-1 (2025-08-26)
x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
jfschotborgh@instance-practica-parte2:~$ sudo apt install wget
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
wget is already the newest version (1.21.3-1+deb12u1).
wget set to manually installed.
0 upgraded, 0 newly installed, 0 to remove and 7 not upgraded.
jfschotborgh@instance-practica-parte2:~$ wget https://artifacts.elastic.co/downloads/elasticsearch/elasti
csearch-8.14.1-amd64.deb
--2025-10-14 10:36:50-- https://artifacts.elastic.co/downloads/elasticsearch/elasticsearch-8.14.1-amd64.
deb
Resolving artifacts.elastic.co (artifacts.elastic.co)... 34.120.127.130, 2600:1901:0:1d7::
Connecting to artifacts.elastic.co (artifacts.elastic.co)|34.120.127.130|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 588542328 (561M) [application/vnd.debian.binary-package]
Saving to: 'elasticsearch-8.14.1-amd64.deb'

elasticsearch-8.14.1-amd64 100%[=====>] 561.28M 222MB/s in 2.5s

2025-10-14 10:36:53 (222 MB/s) - 'elasticsearch-8.14.1-amd64.deb' saved [588542328/588542328]

jfschotborgh@instance-practica-parte2:~$ sudo dpkg -i elasticsearch-8.14.1-amd64.deb
Selecting previously unselected package elasticsearch.
(Reading database ... 72619 files and directories currently installed.)
Preparing to unpack elasticsearch-8.14.1-amd64.deb ...
Creating elasticsearch group... OK
Creating elasticsearch user... OK
Unpacking elasticsearch (8.14.1) ...
Setting up elasticsearch (8.14.1) ...
----- Security autoconfiguration information -----

Authentication and authorization are enabled.
TLS for the transport and HTTP layers is enabled and configured.

The generated password for the elastic built-in superuser is : UKCsSDo9xMqwO1U2hNF7

If this node should join an existing cluster, you can reconfigure this with
'/usr/share/elasticsearch/bin/elasticsearch-reconfigure-node --enrollment-token <token-here>'
after creating an enrollment token on your existing cluster.

You can complete the following actions at any time:

Reset the password of the elastic built-in superuser with
'/usr/share/elasticsearch/bin/elasticsearch-reset-password -u elastic'.

Generate an enrollment token for Kibana instances with
'/usr/share/elasticsearch/bin/elasticsearch-create-enrollment-token -s kibana'.

Generate an enrollment token for Elasticsearch nodes with
'/usr/share/elasticsearch/bin/elasticsearch-create-enrollment-token -s node'.

-----
### NOT starting on installation, please execute the following statements to configure elasticsearch serv
ice to start automatically using systemd
sudo systemctl daemon-reload
sudo systemctl enable elasticsearch.service
### You can start elasticsearch service by executing
sudo systemctl start elasticsearch.service
jfschotborgh@instance-practica-parte2:~$ sudo nano /etc/elasticsearch/elasticsearch.yml
jfschotborgh@instance-practica-parte2:~$ sudo service elasticsearch restart
jfschotborgh@instance-practica-parte2:~$ sudo nano /etc/elasticsearch/elasticsearch.yml
jfschotborgh@instance-practica-parte2:~$
```




```
jfschothborgh@instance-practica-parte2:~$ sudo cat /etc/elasticsearch/elasticsearch.yml
# ===== Elasticsearch Configuration =====
#
# NOTE: Elasticsearch comes with reasonable defaults for most settings.
#       Before you set out to tweak and tune the configuration, make sure you
#       understand what are you trying to accomplish and the consequences.
#
# The primary way of configuring a node is via this file. This template lists
# the most important settings you may want to configure for a production cluster.
#
# Please consult the documentation for further information on configuration options:
# https://www.elastic.co/guide/en/elasticsearch/reference/index.html
#
# ----- Cluster -----
#
# Use a descriptive name for your cluster:
#
#cluster.name: my-application
#
# ----- Node -----
#
# Use a descriptive name for the node:
#
#node.name: node-1
#
# Add custom attributes to the node:
#
#node.attr.rack: r1
#
# ----- Paths -----
#
# Path to directory where to store the data (separate multiple locations by comma):
#
path.data: /var/lib/elasticsearch
#
# Path to log files:
#
path.logs: /var/log/elasticsearch
#
# ----- Memory -----
#
# Lock the memory on startup:
#
#bootstrap.memory_lock: true
#
# Make sure that the heap size is set to about half the memory available
# on the system and that the owner of the process is allowed to use this
# limit.
#
# Elasticsearch performs poorly when the system is swapping the memory.
#
# ----- Network -----
#
# By default Elasticsearch is only accessible on localhost. Set a different
# address here to expose this node on the network:
#
#network.host: 192.168.0.1
#
# By default Elasticsearch listens for HTTP traffic on the first free port it
# finds starting at 9200. Set a specific HTTP port here:
#
#http.port: 9200
#
# For more information, consult the network module documentation.
#
# ----- Discovery -----
#
# Pass an initial list of hosts to perform discovery when this node is started:
# The default list of hosts is ["127.0.0.1", "[::1]"]
#
#discovery.seed_hosts: ["host1", "host2"]
#
# Bootstrap the cluster using an initial set of master-eligible nodes:
#
#cluster.initial_master_nodes: ["node-1", "node-2"]
#
# For more information, consult the discovery and cluster formation module documentation.
#
```



```
----- Various -----
# Allow wildcard deletion of indices:
action.destructive_requires_name: false

----- BEGIN SECURITY AUTO CONFIGURATION -----

# The following settings, TLS certificates, and keys have been automatically
# generated to configure Elasticsearch security features on 14-10-2025 10:37:17
# -----

# Enable security features
pack.security.enabled: false

pack.security.enrollment.enabled: true

# Enable encryption for HTTP API client connections, such as Kibana, Logstash, and Agents
pack.security.http.ssl:
  enabled: false
  keystore.path: certs/http.p12

# Enable encryption and mutual authentication between cluster nodes
pack.security.transport.ssl:
  enabled: true
  verification_mode: certificate
  keystore.path: certs/transport.p12
  truststore.path: certs/transport.p12
# Create a new cluster with the current node only
# Additional nodes can still join the cluster later
cluster.initial_master_nodes: ["instance-practica-parte2"]

# Allow HTTP API connections from anywhere
# Connections are encrypted and require user authentication
http.host: 0.0.0.0

# Allow other nodes to join the cluster from anywhere
# Connections are encrypted and mutually authenticated
transport.host: 0.0.0.0

----- END SECURITY AUTO CONFIGURATION -----
fschothborgh@instance-practica-parte2:~$
```



```
# Enable security features
xpack.security.enabled: false

xpack.security.enrollment.enabled: true

# Enable encryption for HTTP API client connections, such as Kibana, Logstash, and Agents
xpack.security.http.ssl:
  enabled: false
  keystore.path: certs/http.p12

# Enable encryption and mutual authentication between cluster nodes
xpack.security.transport.ssl:
  enabled: true
  verification_mode: certificate
  keystore.path: certs/transport.p12
  truststore.path: certs/transport.p12
# Create a new cluster with the current node only
# Additional nodes can still join the cluster later
cluster.initial_master_nodes: ["instance-practica-parte2"]

# Allow HTTP API connections from anywhere
# Connections are encrypted and require user authentication
http.host: 0.0.0.0

# Allow other nodes to join the cluster from anywhere
# Connections are encrypted and mutually authenticated
#transport.host: 0.0.0.0

#----- END SECURITY AUTO CONFIGURATION -----
```


← → ↻ ⚠ No es seguro 34.175.161.196:9200

Dar formato al texto ☐

```
[
  {
    "name" : "instance-practica-parte2",
    "cluster_name" : "elasticsearch",
    "cluster_uuid" : "Cu-04N3XRZS9boZFKhTl3g",
    "version" : {
      "number" : "8.14.1",
      "build_flavor" : "default",
      "build_type" : "deb",
      "build_hash" : "93a57a1a76f556d8aee6a90d1a95b06187501310",
      "build_date" : "2024-06-10T23:35:17.114581191Z",
      "build_snapshot" : false,
      "lucene_version" : "9.10.0",
      "minimum_wire_compatibility_version" : "7.17.0",
      "minimum_index_compatibility_version" : "7.0.0"
    },
    "tagline" : "You Know, for Search"
  }
]
```