

ENSEIRB-MATMECA



---

## Solving the linear Boltzmann equation using Monte Carlo methods

---

Project lead by :

C. Aumonier, A. Boucher, G. Doyen, K. El Maddah, G. Rodiere

Project supervised by :

G. Poëtte

January 2024

---

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Transport equations</b>	<b>2</b>
<b>3</b>	<b>The use of Monte Carlo methods to solve the linear Boltzmann equation</b>	<b>2</b>
<b>4</b>	<b>Semi analog MC scheme</b>	<b>3</b>
<b>5</b>	<b>Numerical tests/results</b>	<b>3</b>
<b>6</b>	<b>Conclusion</b>	<b>3</b>

---

## 1 Introduction

\*\*Gabriel

## 2 Transport equations

insérer la partie écrite par Clément \*\*Gabriel traduction

## 3 The use of Monte Carlo methods to solve the linear Boltzmann equation

The transport equation in an infinite medium with its corresponding deterministic collisional component can be expressed as:

$$\partial_t u(x, t, \mathbf{v}) + \mathbf{v} \cdot \nabla u(x, t, \mathbf{v}) + v \sigma_t(x, t, \mathbf{v}) u(x, t, \mathbf{v}) = v \sigma_s(x, t, \mathbf{v}) \int P(x, t, \mathbf{v}, \mathbf{v}') u(x, t, \mathbf{v}') d\mathbf{v}' \quad (1)$$

Where

$$\sigma_s(x, t, \mathbf{v}) = \int \sigma_s(x, t, \mathbf{v}, \mathbf{v}') d\mathbf{v}', \quad P(x, t, \mathbf{v}, \mathbf{v}') = \frac{\sigma_s(x, t, \mathbf{v}, \mathbf{v}')}{\sigma_s(x, t, \mathbf{v})}$$

The approach involves a series of variable changes. The initial step involves re-expressing the transport equation 1 with respect to a characteristic  $x + vt$ . As a result, it transforms into:

$$\partial_s u(x + \mathbf{v}s, s, \mathbf{v}) = -v \sigma_t(x + \mathbf{v}s, s, \mathbf{v}) u(x + \mathbf{v}s, s, \mathbf{v}) + v \sigma_s(x + \mathbf{v}s, s, \mathbf{v}) \int P(x + \mathbf{v}s, s, \mathbf{v}, \mathbf{v}') u(x + \mathbf{v}s, s, \mathbf{v}') d\mathbf{v}' \quad (2)$$

Let's multiply both sides of the equation by:

$$e^{\int_0^s v \sigma_t(x + \mathbf{v}\alpha, \alpha, \mathbf{v}) d\alpha}$$

Following that, we obtain

$$\partial_s [u(x + \mathbf{v}s, s, \mathbf{v}) e^{\int_0^s v \sigma_t(x + \mathbf{v}\alpha, \alpha, \mathbf{v}) d\alpha}] = e^{\int_0^s v \sigma_t(x + \mathbf{v}\alpha, \alpha, \mathbf{v}) d\alpha} v \sigma_s(x + \mathbf{v}s, s, \mathbf{v}) \int P(x + \mathbf{v}s, s, \mathbf{v}, \mathbf{v}') u(x + \mathbf{v}s, s, \mathbf{v}') d\mathbf{v}'$$

We get after integrating the equation 3 between  $[0, t]$ :

$$u(x + \mathbf{v}t, t, \mathbf{v}) = u_0(x, \mathbf{v}) \exp \left( - \int_0^t v \sigma_t(x + \mathbf{v}\alpha, \alpha, \mathbf{v}) d\alpha \right) + \int_0^t \int v \sigma_s(x + \mathbf{v}s, s, \mathbf{v}) u(x + \mathbf{v}s, s, \mathbf{v}') e^{-\int_s^t v \sigma_t(x + \mathbf{v}\alpha, \alpha, \mathbf{v}) d\alpha} P(x + \mathbf{v}s, s, \mathbf{v}, \mathbf{v}') d\mathbf{v}' ds \quad (3)$$

We obtain:

$$u(x, t, \mathbf{v}) = u_0(x - \mathbf{v}t, \mathbf{v}) \exp \left( - \int_0^t v \sigma_t(x - \mathbf{v}(t - \alpha), \alpha, \mathbf{v}) d\alpha \right) + \int_0^t \int v \sigma_s(x - \mathbf{v}(t - s), s, \mathbf{v}) u(x - \mathbf{v}(t - s), s, \mathbf{v}') e^{-\int_s^t v \sigma_t(x - \mathbf{v}(t - \alpha), \alpha, \mathbf{v}) d\alpha} P(x - \mathbf{v}(t - s), s, \mathbf{v}, \mathbf{v}') d\mathbf{v}' ds \quad (4)$$

---

We also have:

$$\begin{aligned} \exp \left( - \int_0^t v \sigma_t (x - \mathbf{v}(t - \alpha), \alpha, \mathbf{v}) d\alpha \right) &= \exp \left( - \int_0^t v \sigma_t (x - \mathbf{v}\alpha, t - \alpha, \mathbf{v}) d\alpha \right) \\ &= \int_t^\infty v \sigma_t (x - \mathbf{v}s, t - s, \mathbf{v}) \exp \left( - \int_0^s v \sigma_t (x - \mathbf{v}\alpha, t - \alpha, \mathbf{v}) d\alpha \right) ds \end{aligned} \quad (5)$$

Then the integral representation of 1 is provided by:

$$\begin{aligned} u(x, t, \mathbf{v}) &= \int_t^\infty u_0(x - \mathbf{v}t, \mathbf{v}) v \sigma_t (x - \mathbf{v}s, t - s, \mathbf{v}) \exp \left( - \int_0^s v \sigma_t (x - \mathbf{v}\alpha, t - \alpha, \mathbf{v}) d\alpha \right) ds \\ &+ \int_0^t \int v \sigma_s (x - \mathbf{v}(t - s), s, \mathbf{v}) u(x - \mathbf{v}(t - s), s, \mathbf{v}') e^{-\int_s^t v \sigma_t (x - \mathbf{v}(t - \alpha), \mathbf{v}) d\alpha} P(x - \mathbf{v}(t - s), s, \mathbf{v}, \mathbf{v}') d\mathbf{v}' ds \end{aligned} \quad (6)$$

## 4 Semi analog MC scheme

Developing a Monte Carlo scheme involves introducing a group of random variables along with their associated probability measure to express 6 as an expectation. The selection of this set of random variables is not unique, resulting in various Monte Carlo schemes with distinct properties.

## 5 Numerical tests/results

à voir

## 6 Conclusion