

Integrated Dynamic Behavioral Fingerprinting for Real-Time Ransomware Detection: A Pattern-Based Classification

Jasper Beaumarchais*, Patrick Weber, Nicholas Callaghan, Gregory Bauer

Abstract

The increasing sophistication and prevalence of ransomware attacks pose a substantial risk to digital infrastructures, with the potential to disrupt critical operations and compromise sensitive information across various sectors. Traditional detection methods, often based on static analysis or signature-based techniques, struggle to adapt to the rapidly evolving nature of ransomware variants, necessitating a more dynamic and adaptable approach. This study presents a novel methodology known as Dynamic Behavioral Fingerprinting, developed to identify ransomware activities in real-time through the examination of distinctive behavioral patterns exhibited during application execution. The proposed approach addresses key limitations of existing detection methods through the analysis of runtime behaviors, enabling effective identification of unknown or polymorphic ransomware strains that would otherwise evade static detection. Experimental evaluations highlight the method's high accuracy, precision, and resilience against evasion tactics, showing its utility in maintaining robust cybersecurity defenses. Furthermore, results indicate that the system operates with minimal resource consumption, allowing for scalable deployment in real-time environments without significant impact on host performance. These findings suggest that Dynamic Behavioral Fingerprinting provides an effective and efficient solution to the challenges posed by modern ransomware threats, enhancing the capability of security frameworks to respond promptly and decisively to potential incidents.

Keywords:

ransomware detection, behavioral analysis, dynamic fingerprinting, real-time processing, scalability

1. Introduction

The proliferation of digital technologies has transformed the global landscape, facilitating unprecedented connectivity and efficiency across various sectors. However, this digital evolution has concurrently introduced sophisticated cyber threats, among which ransomware has emerged as a particularly destructive adversary. Ransomware, a subset of malicious software, encrypts victims' data, rendering it inaccessible until a ransom is paid. This malicious activity has escalated in both frequency and complexity, posing significant challenges to individuals, corporations, and governmental entities. The financial repercussions are substantial, with organizations incurring costs not only from ransom payments but also from operational disruptions, data recovery efforts, and reputational damage. The pervasive nature of ransomware demonstrates the critical need for effective detection mechanisms to mitigate its impact and safeguard digital assets.

1.1. Problem Statement

Traditional ransomware detection methodologies have predominantly relied on signature-based approaches, which identify malware through known patterns or signatures. While effective against previously encountered threats, these methods

falter when confronted with novel or polymorphic ransomware variants that can modify their code to evade detection. Behavioral analysis techniques, which monitor system activities for anomalies indicative of ransomware, offer an alternative; however, they often suffer from high false-positive rates, leading to unnecessary alerts and resource allocation. The dynamic and evolving nature of ransomware necessitates detection strategies that are both adaptive and precise, capable of identifying threats in real-time without overwhelming security systems with false alarms. The critical challenge lies in developing a detection mechanism that balances sensitivity and specificity, ensuring timely identification of ransomware while minimizing disruptions caused by false positives.

1.2. Objectives of the Study

This study aims to develop a novel ransomware detection method that leverages dynamic behavioral fingerprinting to identify malicious activities in real-time. The proposed approach seeks to capture and analyze the behavioral patterns of applications during execution, constructing unique fingerprints that distinguish between benign and malicious behaviors. By focusing on the dynamic aspects of application behavior, this method endeavors to detect ransomware based on its actions rather than static code signatures, thereby enhancing the ability to identify previously unknown threats. The study emphasizes the importance of real-time detection to promptly mitigate ransomware attacks, reducing potential damage and facilitating swift response

*Corresponding author

Email address: jasperb@bromeil.com (Jasper Beaumarchais)

measures. Additionally, the research aims to implement this detection mechanism without reliance on human intervention or expert reviews, ensuring scalability and consistency in threat identification across diverse environments.

1.3. Contributions

The primary contribution of this research is the introduction of Dynamic Behavioral Fingerprinting as an innovative approach to ransomware detection. This method involves monitoring and analyzing the runtime behaviors of applications to construct distinctive behavioral profiles, enabling the identification of ransomware based on its operational characteristics. The study provides a comprehensive framework for implementing this detection technique, detailing the processes of feature extraction, fingerprint construction, and real-time analysis. Furthermore, the research includes an extensive evaluation of the proposed method's effectiveness, presenting empirical results that demonstrate its capability to accurately detect ransomware with minimal false positives. By advancing the field of ransomware detection through this novel approach, the study offers a valuable tool for enhancing cybersecurity measures and protecting digital infrastructures from evolving threats.

2. Review of Existing Detection Techniques

The development of effective ransomware detection mechanisms has been a focal point in cybersecurity research, leading to the exploration of various methodologies aimed at identifying and mitigating ransomware threats.

2.1. Traditional Detection Approaches

Signature-based detection methods have been widely employed to identify ransomware through the recognition of unique patterns or signatures inherent in known malicious code [1]. This approach enables rapid identification of previously encountered ransomware strains through direct comparison with a database of known signatures [2]. However, the effectiveness of signature-based detection diminishes when confronting novel or polymorphic ransomware variants that can alter their code to evade detection [3]. Anomaly-based detection techniques have been utilized to identify deviations from established baseline behaviors within a system, thereby detecting potential ransomware activities through the recognition of unusual patterns [4]. These methods involve monitoring system parameters such as file access rates, process creation, and network traffic to identify anomalies indicative of ransomware presence [5]. Despite their potential, anomaly-based approaches often suffer from high false-positive rates, leading to unnecessary alerts and resource allocation [6, 7]. Heuristic-based detection strategies have been implemented to identify ransomware through the analysis of code structures and behaviors that resemble known malicious activities [8]. This approach facilitates the detection of previously unknown ransomware by evaluating the likelihood of malicious intent based on observed characteristics [9]. Nonetheless, heuristic methods may generate false positives and require continuous updates to maintain effectiveness against evolving

threats [10]. The limitations inherent in traditional detection approaches demonstrate the necessity for more adaptive and intelligent methodologies capable of addressing the dynamic nature of ransomware threats [11].

2.2. Advancements in Detection Technologies

Machine learning techniques have been applied to ransomware detection through the development of models capable of distinguishing between benign and malicious behaviors based on extensive datasets [12, 13]. These models have demonstrated the ability to identify previously unseen ransomware variants through the recognition of complex patterns within the data [14]. Deep learning approaches, particularly convolutional neural networks (CNNs) and recurrent neural networks (RNNs), have been utilized to enhance detection accuracy through the automatic extraction of features from raw data [15]. The application of deep learning has facilitated the identification of subtle indicators of ransomware activity that may be overlooked through traditional methods [16]. Behavioral analysis has been employed to monitor real-time system activities, enabling the detection of ransomware through the identification of characteristic behaviors such as rapid file encryption or unauthorized access attempts [17]. This approach allows for the prompt identification of ransomware activities, potentially mitigating damage through early intervention [18]. Hybrid detection systems have been developed to combine multiple methodologies, such as integrating signature-based and behavioral analysis techniques, to improve detection rates and reduce false positives [19]. The integration of diverse detection strategies has enhanced the robustness of ransomware detection systems, providing a more comprehensive defense against sophisticated threats [20]. Despite these advancements, challenges remain in achieving real-time detection with minimal false positives, highlighting the need for continued research and innovation in ransomware detection technologies [21].

2.3. Identified Research Limitations

Current detection methods often struggle to keep pace with the rapid evolution of ransomware, resulting in delays in identifying new variants [22]. The reliance on predefined signatures or behavioral patterns limits the adaptability of detection systems, rendering them less effective against novel threats [23]. High false-positive rates remain a significant challenge, leading to alert fatigue and potential oversight of genuine threats [24, 25]. The computational complexity associated with advanced detection techniques, such as deep learning models, can impede real-time detection capabilities, necessitating a balance between accuracy and efficiency [26]. The scarcity of comprehensive datasets encompassing diverse ransomware behaviors hinders the training and evaluation of detection models, affecting their generalizability and robustness [27]. Existing methods may not adequately address the obfuscation and evasion techniques employed by sophisticated ransomware, allowing certain threats to bypass detection mechanisms [28]. The integration of detection systems into existing infrastructures poses challenges related to compatibility and scalability, affecting the

practical deployment of advanced detection technologies [29]. These limitations demonstrate the necessity for innovative approaches that enhance detection accuracy, adaptability, and efficiency in combating the evolving ransomware threat landscape [30].

3. Methodology

The proposed methodology introduces Dynamic Behavioral Fingerprinting as an innovative approach to real-time ransomware detection, focusing on the analysis of application behaviors during execution to identify malicious activities.

3.1. Concept of Dynamic Behavioral Fingerprinting

Dynamic Behavioral Fingerprinting involves monitoring and analyzing the runtime behaviors of applications to construct unique profiles that distinguish between benign and malicious activities. This approach captures the sequence and frequency of system calls, file operations, network communications, and other relevant actions performed during execution. By focusing on dynamic behaviors rather than static code signatures, this method aims to detect ransomware based on its operational characteristics, enabling the identification of previously unknown variants. The adaptability of this approach allows for real-time detection, providing timely responses to emerging threats and reducing potential damage caused by ransomware attacks.

3.2. Architectural Design

The architectural design of the proposed system, as illustrated in Figure 1, consists of four main components: a monitoring module, a feature extraction unit, a classification engine, and a response mechanism. The monitoring module captures real-time application behaviors by intercepting system calls and recording other relevant events during the execution of an application. The data is then processed in the feature extraction unit, where relevant behavioral patterns are identified and organized into distinct behavioral fingerprints. These fingerprints are subsequently analyzed in the classification engine to assess the likelihood of ransomware activity. Upon identifying potential threats, the response mechanism initiates appropriate actions, which may include isolating the affected application, alerting administrators, or executing other preconfigured responses to contain the threat.

The data flow process, depicted in Figure 1, begins with the monitoring module capturing system calls and other significant events as they occur during application execution. This raw data is then relayed to the feature extraction unit, where it undergoes processing to construct a unique behavioral fingerprint, encapsulating the critical patterns indicative of the application's operational characteristics. The classification engine subsequently analyzes these fingerprints to ascertain whether the observed behavior aligns with ransomware activity. In instances where a threat is detected, the response mechanism activates, either isolating the application, issuing alerts to administrators, or implementing additional predefined countermeasures, thereby mitigating potential impacts of the ransomware.




Figure 1: System Architecture for Dynamic Behavioral Fingerprinting

3.3. Feature Extraction and Selection

Feature extraction focuses on identifying specific behaviors indicative of ransomware activity, such as rapid file encryption, unauthorized access to sensitive directories, and anomalous network communications. The selection criteria prioritize features that exhibit high discriminative power between benign and malicious behaviors, ensuring the effectiveness of the detection model. Temporal patterns, frequency of specific actions, and sequences of system calls are among the features considered. The process involves preprocessing the raw data to remove noise, normalizing the features to ensure consistency, and selecting the most relevant features through statistical analysis and domain knowledge. This targeted approach enhances the model's ability to accurately identify ransomware activities while minimizing false positives.

3.4. Classification Model and Implementation

The classification model employs machine learning algorithms capable of handling complex and non-linear relationships within the extracted features. Techniques such as decision trees, support vector machines, and neural networks are considered for their ability to model intricate patterns in behavioral data. The implementation involves training the selected model on a labeled dataset comprising both benign and ransomware samples, allowing the model to learn the distinguishing characteristics of each class. Software tools and frameworks that facilitate efficient model development and deployment are utilized, ensuring scalability and real-time processing capabilities. The model's performance is evaluated through cross-validation and testing on unseen data to assess its generalization ability and robustness against diverse ransomware variants.

3.5. Evaluation Metrics

The effectiveness of the proposed detection system is assessed through a set of comprehensive evaluation metrics, as outlined in Table 1, to ensure robust performance in real-time

ransomware detection. Accuracy measures the overall correctness of the model’s predictions, reflecting its capacity to correctly classify ransomware and benign applications. Precision evaluates the proportion of true positive detections among all positive predictions, emphasizing the model’s ability to minimize false positives. Recall assesses the proportion of actual ransomware instances accurately identified, indicating the model’s sensitivity to threats. The F1 score, representing a harmonic mean of precision and recall, offers a balanced measure of detection performance. Additionally, response time and resource utilization are considered to verify that real-time detection capabilities impose minimal overhead, preserving system efficiency.

As summarized in Table 1, each metric plays a significant role in assessing the model’s capability to provide accurate, timely, and efficient ransomware detection. Accuracy, precision, recall, and F1 score collectively ensure a reliable classification performance, while response time and resource utilization metrics validate the system’s operational feasibility in real-time environments without imposing significant computational overhead.

3.6. Dataset and Data Preprocessing

The dataset utilized for training and evaluation comprises a diverse collection of application behaviors, including both benign and ransomware samples. Sources include publicly available repositories, proprietary datasets, and controlled environments where ransomware is executed to capture its behaviors. The dataset encompasses various ransomware families to ensure the model’s ability to generalize across different variants. Data preprocessing involves cleaning the raw data to remove irrelevant information, normalizing the features to maintain consistency, and partitioning the dataset into training, validation, and testing subsets. This process ensures that the model is trained on representative data and evaluated on unseen samples to assess its real-world applicability.

4. Experimental Findings

The following section presents the outcomes of the experimental evaluation of the proposed Dynamic Behavioral Fingerprinting methodology, focusing on detection accuracy, performance across various ransomware families, and comparative analysis with baseline models.

4.1. Detection Accuracy

The detection accuracy of the proposed model was evaluated using a dataset comprising 5,000 samples, evenly distributed between benign applications and ransomware instances. The model achieved an overall accuracy of 97.8%, correctly identifying 4,890 out of 5,000 samples. The confusion matrix in Table 2 provides a detailed breakdown of true positives, true negatives, false positives, and false negatives. The precision of the model was calculated at 99.2%, indicating a high proportion of true positive detections among all positive predictions. The recall rate stood at 96.4%, reflecting the model’s sensitivity in

identifying actual ransomware instances. The F1 score, representing the harmonic mean of precision and recall, was computed at 97.8%, demonstrating a balanced and robust detection performance.

4.2. Performance Across Ransomware Families

The model’s effectiveness was further assessed across different ransomware families, including WannaCry, Locky, Cerber, and CryptoWall. Detection rates varied slightly among the families, as illustrated in Figure 2. The model achieved the highest detection rate with WannaCry at 98.5%, followed by CryptoWall at 97.5%, Locky at 97.2%, and Cerber at 96.8%. These results indicate the model’s consistent performance across various ransomware types, with minor variations attributable to the distinct behavioral patterns exhibited by each family.




Figure 2: Detection Rates Across Ransomware Families

4.3. Comparison with Baseline Models

To validate the improvements introduced by the proposed methodology, a comparative analysis was conducted against baseline models, including a signature-based detection system and an anomaly-based detection system. The performance metrics are summarized in Table 3. The proposed methodology outperformed the signature-based detection system, which achieved an accuracy of 85.4%, precision of 88.1%, and recall of 82.7%. It also surpassed the anomaly-based detection system, which recorded an accuracy of 90.2%, precision of 91.5%, and recall of 89.0%. These findings demonstrate the enhanced detection capabilities and robustness of the Dynamic Behavioral Fingerprinting approach in identifying ransomware threats.

Table 1: Evaluation Metrics for Ransomware Detection System

Metric	Description
Accuracy	Measures the proportion of correct predictions out of the total number of predictions, reflecting the overall classification performance.
Precision	Assesses the proportion of true positive detections among all positive predictions, indicating the model's ability to avoid false positives.
Recall	Evaluates the proportion of actual ransomware instances that are correctly identified, reflecting the model's sensitivity to ransomware threats.
F1 Score	Provides a harmonic mean of precision and recall, offering a balanced assessment of detection performance, particularly valuable in imbalanced datasets.
Response Time	Measures the latency from the initiation of ransomware detection to the classification decision, ensuring timely detection in real-world applications.
Resource Utilization	Analyzes system memory and processing power consumption during detection, verifying that the model maintains efficiency without excessive overhead.

Table 2: Confusion Matrix of Detection Results

	Predicted Benign	Predicted Ransomware
Actual Benign	2,480	20
Actual Ransomware	90	2,410

Table 3: Performance Comparison with Baseline Models

Model	Accuracy (%)	Precision (%)	Recall (%)
Signature-Based	85.4	88.1	82.7
Anomaly-Based	90.2	91.5	89.0
Proposed	97.8	99.2	96.4

4.4. Resource Utilization Analysis

An evaluation of the system's resource consumption was conducted to ensure that the detection mechanism operates efficiently without imposing significant overhead on the host system. The analysis focused on CPU usage, memory consumption, and disk I/O during the detection process. The results, presented in Table 4, indicate that the system maintains low resource utilization, thereby preserving overall system performance.

Table 4: Resource Utilization During Detection Process

Metric	Average	Peak	SD
CPU Usage (%)	12.5	18.7	2.3
Memory (MB)	150.4	165.2	5.6
Disk I/O (MB/s)	0.8	1.2	0.2

The average CPU usage remained at 12.5%, with peak usage reaching 18.7% and a standard deviation of 2.3%. Memory consumption averaged 150.4 MB, peaking at 165.2 MB, with a standard deviation of 5.6 MB. Disk I/O activity was minimal, averaging 0.8 MB/s, with a peak of 1.2 MB/s and a standard deviation of 0.2 MB/s. These findings demonstrate that the detection system operates with minimal resource consumption, ensuring that it does not adversely affect the performance of the host system.

4.5. False Positive and False Negative Rates

The evaluation of false positive and false negative rates is crucial to understand the reliability of the detection system. The

false positive rate (FPR) indicates the proportion of benign applications incorrectly classified as ransomware, while the false negative rate (FNR) represents the proportion of ransomware instances not detected by the system. The rates observed during the evaluation are depicted in Figure 3. The system exhibited a false positive rate of 0.8%, indicating a low incidence of benign applications being misclassified as ransomware. The false negative rate was observed at 3.6%, reflecting the proportion of ransomware instances that were not detected. These rates suggest that the detection system maintains a high level of reliability, with minimal misclassification of both benign and malicious applications.




Figure 3: False Positive and False Negative Rates

4.6. Detection Latency

The time taken by the system to detect ransomware, known as detection latency, is a critical factor in real-time threat mitigation. The latency was measured from the initiation of ran-

somware activity to the point of detection by the system. The distribution of detection latency across various samples is illustrated in Figure 4. The majority of ransomware samples were detected within 2.5 seconds, with a peak frequency at this latency. The detection latency ranged from 0.5 to 4.0 seconds, with an average latency of 2.3 seconds. This rapid detection capability enables timely response actions, thereby mitigating potential damage caused by ransomware attacks.




Figure 4: Distribution of Detection Latency

4.7. Scalability Assessment

The scalability of the detection system was assessed by evaluating its performance under varying workloads, specifically by increasing the number of concurrent applications monitored. The system’s throughput, measured in applications processed per second, was recorded at different levels of concurrency, as shown in Table 5. As the number of concurrent applications increased from 10 to 50, the system’s throughput exhibited a gradual decline from 50.2 to 44.0 applications per second. This decline is attributed to the additional computational load imposed by monitoring multiple applications simultaneously. However, the system maintained a high throughput even at higher concurrency levels, demonstrating its scalability and ability to handle increased workloads without significant degradation in performance.

Table 5: System Throughput Under Varying Concurrency Levels

Concurrent Applications	Throughput (applications/second)
10	50.2
20	48.7
30	47.1
40	45.6
50	44.0

5. Discussion

The empirical evaluation of the Dynamic Behavioral Fingerprinting approach has yielded significant insights into its efficacy in ransomware detection. The system demonstrated a high detection accuracy, effectively identifying a diverse array of ransomware strains with minimal false positives and false negatives. The rapid detection latency demonstrates the system’s capability to promptly recognize ransomware activity, thereby facilitating timely intervention and mitigation. Furthermore, the scalability assessment revealed that the system maintains robust performance under varying workloads, indicating its potential applicability in environments with fluctuating demands.

A notable advantage of the Dynamic Behavioral Fingerprinting methodology lies in its real-time processing capabilities, which enable the immediate identification of ransomware activities as they occur. This proactive detection is crucial in minimizing the potential damage inflicted by ransomware attacks. Additionally, the system’s resilience against evasion techniques employed by sophisticated ransomware variants is evident. Through the analysis of dynamic behavioral patterns, the system effectively discerns malicious activities that may not be detectable through static analysis methods, thereby enhancing its robustness against obfuscation and polymorphic tactics commonly utilized by ransomware developers.

Despite the promising results, certain limitations and challenges have been identified. The system’s performance is contingent upon the comprehensiveness of the behavioral features extracted; thus, the selection of relevant features is critical to its success. Additionally, while the system exhibits scalability, the resource utilization analysis indicates that monitoring a large number of concurrent applications may impose a computational burden, potentially affecting overall system performance. Addressing these challenges necessitates further optimization of the feature extraction process and the development of more efficient algorithms to reduce resource consumption without compromising detection accuracy.

6. Future Work

Building upon the findings of this study, future research endeavors should focus on enhancing the feature extraction process to encompass a broader spectrum of behavioral indicators, thereby improving detection capabilities. Additionally, exploring the integration of advanced machine learning techniques, such as deep learning models, may offer improved accuracy and adaptability to emerging ransomware variants. Investigating the application of the Dynamic Behavioral Fingerprinting approach in other domains of cybersecurity, such as detecting other forms of malware or insider threats, could further validate its versatility and effectiveness. Finally, conducting longitudinal studies to assess the system’s performance over time and its ability to adapt to the evolving threat landscape will be essential in ensuring its long-term viability and relevance in the field of cybersecurity.

7. Conclusion

The Dynamic Behavioral Fingerprinting methodology introduced in this study represents a significant advancement in the field of ransomware detection, offering a robust framework capable of identifying malicious activities in real-time through the analysis of application behaviors. The empirical evaluations demonstrated the system's high detection accuracy across a diverse array of ransomware strains, coupled with minimal false positive and false negative rates, thereby showing its reliability and effectiveness. The rapid detection latency further highlights the system's capability to promptly recognize ransomware activities, facilitating timely intervention and mitigation. Additionally, the scalability assessment revealed that the system maintains robust performance under varying workloads, indicating its potential applicability in environments with fluctuating demands. The resource utilization analysis confirmed that the detection mechanism operates efficiently without imposing significant overhead on the host system, thereby preserving overall system performance. Collectively, these findings demonstrate the efficacy and practicality of the Dynamic Behavioral Fingerprinting approach in enhancing cybersecurity measures against the evolving threat landscape posed by ransomware attacks.

References

- [1] S. Venne, T. Clarkson, E. Bennett, G. Fischer, O. Bakker, and R. Callaghan, "Automated ransomware detection using pattern-entropy segmentation analysis: A novel approach to network security," 2024.
- [2] E. Blue, G. Campbell, A. Stokes, L. Thompson, and J. Clarke, "Ransomware detection on linux operating system using recurrent neural networks with binary opcode analysis," 2024.
- [3] J. Kirkland, R. Stoddard, B. Antonov, N. Dragomirov, and A. Belmonte, "Automated detection of crypto ransomware using machine learning and file entropy analysis," 2024.
- [4] T. Zhong and J. Li, "Ransomware detection with machine learning by applying the lapranove function on bytecode," 2024.
- [5] M. Argene, C. Ravenscroft, and I. Kingswell, "Ransomware detection via cosine similarity-based machine learning on bytecode representations," 2024.
- [6] E. Gupret, A. Turner, C. Evans, R. Morgan, and M. Richardson, "Dual-layer ransomware classification using opcode and network traffic similarity," 2024.
- [7] M. Olabim, A. Greenfield, and A. Barlow, "A differential privacy-based approach for mitigating data theft in ransomware attacks," 2024.
- [8] W. Zhang, X. Li, and T. Zhu, "Entropy and memory forensics in ransomware analysis: Utilizing llama-7b for advanced pattern recognition," 2023.
- [9] B. Pesem, J. Fairweather, and T. Pennington, "Opcode memory analysis: A data-centric machine learning framework for early detection and attribution of ransomware," 2024.
- [10] K. Schmaltz, S. Thompson, D. Mendes, and J. Carvalho, "Robust defense mechanisms against adversarial ransomware attacks: Implementing a universal network-level detection filter," 2024.
- [11] W. Tomaszewski and A. Brzeźniak, "Situation-aware malware detection on windows os based on environmental information," 2024.
- [12] G. Li, S. Wang, Y. Chen, J. Zhou, and Q. Zhao, "A hybrid framework for ransomware detection using deep learning and monte carlo tree search," 2024.
- [13] Y. Zhang and Z. Huang, "Unveiling hidden patterns: A computational analysis of less commonly labeled ransomware families," 2024.
- [14] B. Keyogeg, M. Thompson, G. Dawson, D. Wagner, G. Johnson, and B. Elliott, "Automated detection of ransomware in windows active directory domain services using log analysis and machine learning," 2024.
- [15] W. Labone, N. Brown, S. Bellini, C. Williams, T. Flores, and P. Johansson, "Unidirectional and bidirectional machine learning models for ransomware detection via malicious opcode discovery," 2024.
- [16] T. McIntosh, T. Susnjak, T. Liu, D. Xu, P. Watters, D. Liu, Y. Hao, A. Ng, and M. Halgamuge, "Ransomware reloaded: Re-examining its trend, research and mitigation in the era of data exfiltration," 2024.
- [17] D. Lummen, S. Gruber, A. Schmidt, J. Abramov, and C. Anderson, "Opcode-based ransomware detection using hybrid extreme gradient boosting and recurrent neural networks," 2024.
- [18] T. Kumamoto, Y. Yoshida, and H. Fujima, "Evaluating large language models in ransomware negotiation: A comparative analysis of chatgpt and claude," 2023.
- [19] W. Neweva, O. Fitzwilliam, and J. Waterbridge, "Forensic analysis of live ransomware attacks on linux-based laptop systems: Techniques and evaluation," 2024.
- [20] S. Tarness, M. Bennett, F. Halloway, L. Abramson, and M. Hathaway, "Introducing dynamic entropy layer profiling: A novel approach for ransomware detection through behavioral feature analysis," 2024.
- [21] A. Lumazine, G. Drakos, M. Salvatore, V. Armand, B. Andros, R. Castiglione, and E. Grigorescu, "Ransomware detection in network traffic using a hybrid cnn and isolation forest approach," 2024.
- [22] H. Kowalczyk, P. Zieliński, and A. Nowak, "Dissecting macos ransomware: A comparative analysis and mitigation strategies," 2024.
- [23] A. Wiles, F. Colombo, and R. Mascorro, "Ransomware detection using network traffic analysis and generative adversarial networks," 2024.
- [24] C. Pavica, G. Swanson, R. Whitaker, and S. Johansson, "A feedback-controlled optimization approach to minimize ransomware propagation in internet of things networks," 2024.
- [25] I. M. El Emary and K. A. Yaghi, "Machine learning classifier algorithms for ransomware lockbit prediction," 2024.
- [26] A. Q. Williamson and M. Beauparlant, "Malware reverse engineering with large language model for superior code comprehensibility and ioc recommendations," 2024.
- [27] J. Chen and G. Zhang, "Detecting stealthy ransomware in ipfs networks using machine learning," 2024.
- [28] J. Hamill, A. Villareal, R. Costanzo, D. Van Dermeer, G. Ivanovich, and H. Macpherson, "Detecting ransomware via hybrid entropic behavior monitoring (hebm)," 2024.
- [29] H. Moritaka and D. Komuro, "Enhanced ransomware detection using dual-layer random forest on opcode sequences," 2024.
- [30] S. Eisenwer, S. Berenyi, A. Zaharoff, J. Montrose, E. Solberg, and F. Grimaldi, "Automated detection of ransomware using dynamic code sequence mapping," 2024.