## APP SCORES

Security Score 50/100

Trackers Detection 0/432

## FILE INFORMATION

File Name FireInTheHole.apk

Size 5.68MB

MD5 a24732920ce9847fac207893f081c360

SHA1 9d87f515af4d0bc7167820b4169b266be7da1bb1

SHA256 7ef29fe545103a3862ee8ca0906de030c0cf8c12b1007ecaefa380839756a5d8

## APP INFORMATION

App Name FireInTheHole

Package Name com.PwnSec.fireinthehole

Main Activity com.PwnSec.fireinthehole.MainActivity

Target SDK 34 Min SDK 24 Max SDK

Android Version Name 1.0 Android Version Code 1

2 / 7

EXPORTED ACTIVITIES

View All

1 / 3

EXPORTED SERVICES

View All

1 / 1

EXPORTED RECEIVERS

View All

0 / 2

EXPORTED PROVIDERS

View All

## SCAN OPTIONS

## DECOMPILED CODE

## SIGNER CERTIFICATE

```
Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=PwnSec
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2024-07-22 07:43:24+00:00
Valid To: 2049-07-16 07:43:24+00:00
Issuer: CN=PwnSec
Serial Number: 0x1
Hash Algorithm: sha256
md5: c1cb3683b75b37622b0af69561f12a32
sha1: 0552872559a5e3e0e8d072276fbf8058d1cf6897
sha256: 48612d17dc4db27cdd9e3996ea5f8b55e19dbc2a05b6a6d9e11470ce1f773647
sha512: bdc1c2a8b0dc31ad11dc9009af5bf1f167eb0e16310892261ba1865772d30cf506b7238edcc4105777fdc991b197e67f46c560fccddae099111eee49a401cf00
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: f2a4c5934669fbe84adb1dc872e58f8697789676b0e0e5a7678aaf70e8e5d254
Found 1 unique certificates
```

## APPLICATION PERMISSIONS

Search:

| PERMISSION | STATUS | INFO | DESCRIPTION | CODE MAPPINGS |
|---|---|---|---|---|
| android.permission.ACCESS_NETWORK_STATE | normal | view network status | Allows an application to view the status of all networks. | |
| android.permission.INTERNET | normal | full Internet access | Allows an application to create network sockets. | |

| PERMISSION | STATUS | INFO | DESCRIPTION | CODE MAPPINGS |
|---|---|---|---|---|
| android.permission.READ_EXTERNAL_STORAGE | dangerous | read external storage contents | Allows an application to read from external storage. | |
| android.permission.WRITE_EXTERNAL_STORAGE | dangerous | read/modify/delete external storage contents | Allows an application to write to external storage. | |
| com.google.android.providers.gsf.permission.READ_GSERVICES | unknown | Unknown permission | Unknown permission from android reference | |
| com.PwnSec.fireinthehole.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION | unknown | Unknown permission | Unknown permission from android reference | |

Showing 1 to 6 of 6 entries

Previous 1 Next

## ANDROID API

Search:

| API | FILES |
|---|---|
| Android Notifications | |
| Base64 Decode | |
| Base64 Encode | |
| Crypto | |
| Dynamic Class and Dexloading | |

| API | FILES |
|---|---|
| Get System Service | |
| HTTP Connection | |
| HTTPS Connection | |
| Inter Process Communication | |
| Java Reflection | |

Showing 1 to 10 of 15 entries

Previous 1 2 Next

## BROWSABLE ACTIVITIES

Search:

| ACTIVITY | INTENT |
|---|---|
| com.google.firebase.auth.internal.GenericIdpActivity | **Schemes**: genericidp://,<br>**Hosts:** firebase.auth,<br>**Paths:** /, |
| com.google.firebase.auth.internal.RecaptchaActivity | **Schemes**: recaptcha://,<br>**Hosts:** firebase.auth,<br>**Paths:** /, |

Showing 1 to 2 of 2 entries

Previous 1 Next

## NETWORK SECURITY

Search:

| NO | SCOPE | SEVERITY | DESCRIPTION |
|---|---|---|---|
| No data available in table | | | |

Showing 0 to 0 of 0 entries

Previous Next

## CERTIFICATE ANALYSIS

| HIGH | WARNING | INFO |
|---|---|---|
| 0 | 0 | 1 |

Search:

| TITLE | SEVERITY | DESCRIPTION |
|---|---|---|
| Signed Application | info | Application is signed with a code signing certificate |

Showing 1 to 1 of 1 entries

Previous 1 Next

## MANIFEST ANALYSIS

| HIGH | WARNING | INFO | SUPPRESSED |
|---|---|---|---|
| 1 | 5 | 0 | 0 |

Search:

| NO | ISSUE | SEVERITY | DESCRIPTION | OPTIONS |
|---|---|---|---|---|
| 1 | App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24] | high | This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates. | |
| 2 | Application Data can be Backed up [android:allowBackup=true] | warning | This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device. | |
| 3 | Activity (com.google.firebase.auth.internal.GenericIdpActivity) is not Protected. [android:exported=true] | warning | An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. | |
| 4 | Activity (com.google.firebase.auth.internal.RecaptchaActivity) is not Protected. [android:exported=true] | warning | An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. | |

| NO | ISSUE | SEVERITY | DESCRIPTION | OPTIONS |
|---|---|---|---|---|
| 5 | Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true] | warning | A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission. | |

| NO | ISSUE | SEVERITY | DESCRIPTION | OPTIONS |
|---|---|---|---|---|
| 6 | Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true] | warning | A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission. | |

Showing 1 to 6 of 6 entries

Previous 1 Next

## CODE ANALYSIS

| HIGH | WARNING | INFO | SECURE | SUPPRESSED |
|---|---|---|---|---|
| 2 | 4 | 1 | 1 | 0 |

Search:

| NO | ISSUE | SEVERITY | STANDARDS | FILES | OPTIONS |
|---|---|---|---|---|---|
| 1 | The App logs information. Sensitive information should never be logged. | info | **CWE:** CWE-532: Insertion of Sensitive Information into Log File<br>**OWASP MASVS:** MSTG-STORAGE-3 | | |
| 2 | App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database. | warning | **CWE:** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')<br>**OWASP Top 10:** M7: Client Code Quality | T0/n.java | |
| 3 | The App uses an insecure Random Number Generator. | warning | **CWE:** CWE-330: Use of Insufficiently Random Values<br>**OWASP Top 10:** M5: Insufficient Cryptography<br>**OWASP MASVS:** MSTG-CRYPTO-6 | | |
| 4 | SHA-1 is a weak hash known to have hash collisions. | warning | **CWE:** CWE-327: Use of a Broken or Risky Cryptographic Algorithm<br>**OWASP Top 10:** M5: Insufficient Cryptography<br>**OWASP MASVS:** MSTG-CRYPTO-4 | A0/l.java | |
| 5 | The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks. | high | **CWE:** CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking<br>**OWASP Top 10:** M5: Insufficient Cryptography<br>**OWASP MASVS:** MSTG-CRYPTO-3 | com/PwnSec/fireinthehole/Decrypter.java | |

| NO | ISSUE | SEVERITY | STANDARDS | FILES | OPTIONS |
|---|---|---|---|---|---|
| 6 | Insecure Implementation of SSL. Trusting all the certificates or accepting self signed certificates is a critical Security Hole. This application is vulnerable to MITM attacks | high | **CWE:** CWE-295: Improper Certificate Validation<br>**OWASP Top 10:** M3: Insecure Communication<br>**OWASP MASVS:** MSTG-NETWORK-3 | G0/c.java | |
| 7 | Files may contain hardcoded sensitive information like usernames, passwords, keys etc. | warning | **CWE:** CWE-312: Cleartext Storage of Sensitive Information<br>**OWASP Top 10:** M9: Reverse Engineering<br>**OWASP MASVS:** MSTG-STORAGE-14 | S0/C0599a.java | |
| 8 | This App may have root detection capabilities. | secure | **OWASP MASVS:** MSTG-RESILIENCE-1 | J0/AbstractC0397h.java | |

Showing 1 to 8 of 8 entries

Previous 1 Next

## SHARED LIBRARY BINARY ANALYSIS

Search:

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 1 | arm64-v8a/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 2 | armeabi-v7a/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **True** info The binary has the following fortified functions: ['__vsnprintf_chk'] | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 3 | x86/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 4 | x86_64/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 5 | arm64-v8a/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 6 | armeabi-v7a/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **True** info The binary has the following fortified functions: ['__vsnprintf_chk'] | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 7 | x86/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

| NO | SHARED OBJECT | NX | PIE | STACK CANARY | RELRO | RPATH | RUNPATH | FORTIFY | SYMBOLS STRIPPED |
|---|---|---|---|---|---|---|---|---|---|
| 8 | x86_64/libfrida-detection.so | **True** info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable. | **Dynamic Shared Object (DSO)** info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably. | **True** info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. | **Full RELRO** info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only. | **None** info The binary does not have run-time search path or RPATH set. | **None** info The binary does not have RUNPATH set. | **False** warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries. | **True** info Symbols are stripped. |

Showing 1 to 8 of 8 entries

Previous 1 Next

**NIAP ANALYSIS v1.3**

Search:

| NO | IDENTIFIER | REQUIREMENT | FEATURE | DESCRIPTION |
|---|---|---|---|---|
| No data available in table | | | | |

Showing 0 to 0 of 0 entries

Previous Next

## FILE ANALYSIS

Search:

| NO | ISSUE | FILES |
|---|---|---|
| No data available in table | | |

Showing 0 to 0 of 0 entries

Previous Next

## FIREBASE DATABASE ANALYSIS

Search:

| TITLE | SEVERITY | DESCRIPTION |
|---|---|---|
| Firebase Remote Config disabled | secure | Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/297293106615/namespaces/firebase:fetch?key=AIzaSyCmJQHCQjDByP9FFeTuqm0nEbbrqcF65aY. This is indicated by the response: {'state': 'NO_TEMPLATE'} |
| Open Firebase database | high | The Firebase database at https://fire-in-the-hole-92c34-default-rtdb.firebaseio.com/.json is exposed to internet without any authentication |

Showing 1 to 2 of 2 entries

Previous 1 Next

## MALWARE LOOKUP

VirusTotal Report | Triage Report | MetaDefender Report | Hybrid Analysis Report

## APKiD ANALYSIS

Search:

| DEX | DETECTIONS |
|---|---|
| a24732920ce9847fac207893f081c360.apk | Search:<br>FINDINGS: Manipulator Found<br>DETAILS: Resources Confusion<br>Showing 1 to 1 of 1 entries<br>Previous 1 Next |

| DEX | DETECTIONS |
|---|---|
| classes.dex | Search:<br>FINDINGS \| DETAILS<br>Anti-VM Code \| Build.FINGERPRINT check<br>Build.MANUFACTURER check<br>Build.BRAND check<br>Build.DEVICE check<br>Build.TAGS check<br>Compiler \| r8<br>Showing 1 to 2 of 2 entries<br>Previous 1 Next |

Showing 1 to 2 of 2 entries

Previous 1 Next

## BEHAVIOUR ANALYSIS

Search:

| RULE ID | BEHAVIOUR | LABEL | FILES |
|---|---|---|---|
| 00013 | Read file and put it into a stream | file | b1/e.java |
| 00022 | Open a file from given absolute path of the file | file | X0/f.java |

| RULE ID | BEHAVIOUR | LABEL | FILES |
|---|---|---|---|
| 00036 | Get resource file from res/raw directory | reflection | Q/g.java |
| 00051 | Implicit intent(view a web page, make a phone call, etc.) via setData | control | Q/g.java |
| 00063 | Implicit intent(view a web page, make a phone call, etc.) | control | Q/g.java |
| 00109 | Connect to a URL and get the response code | network command | O/f.java |

Showing 1 to 6 of 6 entries

Previous 1 Next

## ABUSED PERMISSIONS

**Top Malware Permissions** **4**/25

android.permission.INTERNET,
android.permission.ACCESS_NETWORK_STATE,
android.permission.READ_EXTERNAL_STORAGE,
android.permission.WRITE_EXTERNAL_STORAGE

**Other Common Permissions** **0**/44

**Malware Permissions** are the top permissions that are widely abused by known malware.
**Other Common Permissions** are permissions that are commonly abused by known malware.

## SERVER LOCATIONS

This app may communicate with the following OFAC sanctioned list of countries.

Search:

| DOMAIN | COUNTRY/REGION |
|---|---|
| No data available in table | |

Showing 0 to 0 of 0 entries

Previous Next

### DOMAIN MALWARE CHECK

Search:

| DOMAIN | STATUS | GEOLOCATION |
|---|---|---|
| accounts.google.com | ok | **IP:** 74.125.206.84<br>**Country:** United States of America<br>**Region:** California<br>**City:** Mountain View<br>**Latitude:** 37.405991<br>**Longitude:** -122.078514<br>**View:** Google Map |
| console.firebase.google.com | ok | **IP:** 172.217.171.46<br>**Country:** United States of America<br>**Region:** California<br>**City:** Mountain View<br>**Latitude:** 37.405991<br>**Longitude:** -122.078514<br>**View:** Google Map |
| fire-in-the-hole-92c34-default-rtdb.firebaseio.com | ok | **IP:** 35.190.39.113<br>**Country:** United States of America<br>**Region:** Missouri<br>**City:** Kansas City<br>**Latitude:** 39.099731<br>**Longitude:** -94.578568<br>**View:** Google Map |
| firebase.google.com | ok | **IP:** 216.58.205.238<br>**Country:** United States of America<br>**Region:** California<br>**City:** Mountain View<br>**Latitude:** 37.405991<br>**Longitude:** -122.078514<br>**View:** Google Map |

| DOMAIN | STATUS | GEOLOCATION |
|---|---|---|
| github.com | ok | **IP:** 140.82.121.4<br>**Country:** United States of America<br>**Region:** California<br>**City:** San Francisco<br>**Latitude:** 37.775700<br>**Longitude:** -122.395203<br>**View:** Google Map |

Showing 1 to 5 of 5 entries

Previous 1 Next

## URLS

Search:

| URL | FILE |
|---|---|
| https://accounts.google.com/o/oauth2/revoke?token= | O/f.java |
| https://console.firebase.google.com/. | V0/m.java |
| https://fire-in-the-hole-92c34-default-rtdb.firebaseio.com | Android String Resource |
| https://firebase.google.com/docs/database/android/retrieve-data#filtering_data<br>https://firebase.google.com/docs/database/ios/structure-data#best_practices_for_data_structure<br>https://github.com/firebase/firebase-android-sdk | A0/c.java |

Showing 1 to 4 of 4 entries

Previous 1 Next

## EMAILS

Search:

| EMAIL | FILE |
|---|---|
| u0013android@android.com<br>u0013android@android.com0 | Q/s.java |

Showing 1 to 1 of 1 entries

Previous 1 Next

## TRACKERS

Search:

| TRACKER NAME | CATEGORIES | URL |
|---|---|---|
| No data available in table | | |

Showing 0 to 0 of 0 entries

Previous Next

## POSSIBLE HARDCODED SECRETS

▶ Show all **119** secrets

## STRINGS

**From APK Resource**

▶ Show all **9023** strings

**From Code**

▶ Show all **7370** strings

**From Shared Objects**

*lib/arm64-v8a/libfrida-detection.so*

▶ Show all **25** strings

*lib/armeabi-v7a/libfrida-detection.so*

▶ Show all **25** strings

*lib/x86/libfrida-detection.so*

▶ Show all **25** strings

*lib/x86_64/libfrida-detection.so*

▶ Show all **25** strings

*apktool_out/lib/arm64-v8a/libfrida-detection.so*

▶ Show all **25** strings

*apktool_out/lib/armeabi-v7a/libfrida-detection.so*

▶ Show all **25** strings

*apktool_out/lib/x86/libfrida-detection.so*

▶ Show all **25** strings

*apktool_out/lib/x86_64/libfrida-detection.so*

▶ Show all **25** strings

## ACTIVITIES

▼ Showing all **7** activities

com.PwnSec.fireinthehole.MainActivity
com.PwnSec.fireinthehole.Decrypter
com.google.firebase.auth.internal.GenericIdpActivity
com.google.firebase.auth.internal.RecaptchaActivity
androidx.credentials.playservices.HiddenActivity
com.google.android.gms.auth.api.signin.internal.SignInHubActivity
com.google.android.gms.common.api.GoogleApiActivity

## SERVICES

▼ Showing all **3** services

com.google.firebase.components.ComponentDiscoveryService
androidx.credentials.playservices.CredentialProviderMetadataHolder
com.google.android.gms.auth.api.signin.RevocationBoundService

## RECEIVERS

▼ Showing all **1** receivers

androidx.profileinstaller.ProfileInstallReceiver

## PROVIDERS

▼ Showing all **2** providers

com.google.firebase.provider.FirebaseInitProvider
androidx.startup.InitializationProvider

## LIBRARIES

## SBOM

▼ Showing all **47** Versioned Packages

androidx.activity:activity@1.9.0
androidx.annotation:annotation-experimental@1.4.0
androidx.appcompat:appcompat-resources@1.7.0
androidx.appcompat:appcompat@1.7.0
androidx.arch.core:core-runtime@dynamic
androidx.browser:browser@1.4.0
androidx.cardview:cardview@1.0.0
androidx.coordinatorlayout:coordinatorlayout@1.1.0
androidx.core:core-ktx@1.13.0
androidx.core:core@1.13.0
androidx.credentials:credentials-play-services-auth@1.2.0-rc01
androidx.credentials:credentials@1.2.0-rc01
androidx.cursoradapter:cursoradapter@1.0.0
androidx.customview:customview@1.1.0
androidx.databinding:viewbinding@8.5.0
androidx.documentfile:documentfile@1.0.0
androidx.drawerlayout:drawerlayout@1.1.1
androidx.dynamicanimation:dynamicanimation@1.0.0
androidx.emoji2:emoji2-views-helper@1.3.0
androidx.emoji2:emoji2@1.3.0
androidx.fragment:fragment@1.5.4
androidx.interpolator:interpolator@1.0.0
androidx.legacy:legacy-support-core-utils@1.0.0
androidx.lifecycle:lifecycle-livedata-core@dynamic
androidx.lifecycle:lifecycle-livedata@dynamic
androidx.lifecycle:lifecycle-process@dynamic
androidx.lifecycle:lifecycle-runtime@dynamic
androidx.lifecycle:lifecycle-viewmodel-savedstate@dynamic

androidx.lifecycle:lifecycle-viewmodel@dynamic
androidx.loader:loader@1.0.0
androidx.localbroadcastmanager:localbroadcastmanager@1.0.0
androidx.print:print@1.0.0
androidx.profileinstaller:profileinstaller@1.3.1
androidx.recyclerview:recyclerview@1.1.0
androidx.savedstate:savedstate@1.2.1
androidx.startup:startup-runtime@1.1.1
androidx.tracing:tracing@1.0.0
androidx.transition:transition@1.5.0
androidx.vectordrawable:vectordrawable-animated@1.1.0
androidx.vectordrawable:vectordrawable@1.1.0
androidx.versionedparcelable:versionedparcelable@1.1.1
androidx.viewpager2:viewpager2@1.0.0
androidx.viewpager:viewpager@1.0.0
com.google.android.material:material@1.12.0
org.jetbrains.kotlinx:kotlinx-coroutines-android@1.7.3
org.jetbrains.kotlinx:kotlinx-coroutines-core@1.7.3
org.jetbrains.kotlinx:kotlinx-coroutines-play-services@1.7.3

▶ Show all **129** Packages

**FILES**

▶ Show all **1004** files

**© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.** **Version** v4.5.0