


Graphics Programming

1ST WEEK, 2021





Example: Draw a Triangle

- Each application consists of (at least) two files
 - HTML file + a JavaScript file
- HTML
 - Describes page
 - Includes utilities
 - Includes shaders
- Java Script
 - Contains the graphics



Coding in WebGL

- Can run WebGL on any recent browser
 - Chrome
 - Firefox
 - Safari
 - IE
- Code written in JavaScript
- JS runs within browser
 - Use local resources

Install Visual Studio Code



Visual Studio Code - Code Editi +

code.visualstudio.com

Visual Studio Code Docs Updates Blog API Extensions FAQ Learn

Download

Version 1.53 is now available! Read about the new features and fixes from January.

Code editing. Redefined.

Free. Built on open source. Runs everywhere.

Download for Windows
Stable Build

Other platforms and Insiders Edition

By using VS Code, you agree to its [license and privacy statement](#).

File Edit Selection View Go Debug Terminal Help

EXTENSIONS MARKETPLACE

JS serviceWorker.js

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

node

You can now view create-react-app in the browser.

Local: http://localhost:3000/
On Your Network: http://10.211.55.3:3000/
Note that the development build is not optimized.


Lightbulb icon

Play button icon

Share icon

Grid icon

<https://code.visualstudio.com/Download>




triangle.html - Visual Studio Code

File Edit Selection View Go Run Terminal Help

triangle.html X

C: > Users > Sun-Jeong Kim > Desktop > CG > triangle.html > html > body > canvas#gl-canvas

```
1 <!DOCTYPE html>
2 <html>
3 <head>
```





triangle.html X JS triangle.js

C: > Users > Sun-Jeong Kim > Desktop > CG > > triangle.html > html > body > canvas#gl-canvas

```
1 <!DOCTYPE html>
2 <html>
3   <head>
4     <script id="vertex-shader" type="x-shader/x-vertex">
5       attribute vec4 vPosition;
6
7       void main() {
8         gl_Position = vPosition;
9       }
10    </script>
11
12    <script id="fragment-shader" type="x-shader/x-fragment">
13      precision mediump float;
14
15      void main() {
16        gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
17      }
18    </script>
19
20    <script type="text/javascript" src="Common/webgl-utils.js"></script>
21    <script type="text/javascript" src="Common/initShaders.js"></script>
22    <script type="text/javascript" src="triangle.js"></script>
23  </head>
24  <body>
25    <canvas id="gl-canvas" width="512" height="512">
26      Oops... your browser doesn't support the HTML5 canvas element!
27    </canvas>
28  </body>
29 </html>
```





```

1  var gl;
2  var points;
3
4  window.onload = function init()
5  {
6      var canvas = document.getElementById("gl-canvas");
7
8      gl = WebGLUtils.setupWebGL(canvas);
9      if( !gl ) {
10         alert("WebGL isn't available!");
11     }
12
13     var vertices = new Float32Array([-1, -1, 0, 1, 1, -1]);
14
15     // Configure WebGL
16     gl.viewport(0, 0, canvas.width, canvas.height);
17     gl.clearColor(1.0, 1.0, 1.0, 1.0);
18
19     // Load shaders and initialize attribute buffers
20     var program = initShaders(gl, "vertex-shader", "fragment-shader");
21     gl.useProgram(program);
22
23     // Load the data into the GPU
24     var bufferId = gl.createBuffer();
25     gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
26     gl.bufferData(gl.ARRAY_BUFFER, vertices, gl.STATIC_DRAW);
27
28     // Associate our shader variables with our data buffer
29     var vPosition = gl.getAttribLocation(program, "vPosition");
30     gl.vertexAttribPointer(vPosition, 2, gl.FLOAT, false, 0, 0);
31     gl.enableVertexAttribArray(vPosition);
32
33     render();
34 };
35

```

[illegible]



연습 문제 (1)

- 배경색을 변경해보시오.
 - 예) 흰색 → 검정색
- 삼각형의 색상을 변경해보시오.
 - 예) 빨강 → 파랑색

