

Gateways API Reference

Overview

The **Gateways** API returns a list of paths between potential gateway persons and people associated with a prospect company.

Property	Value
API name	Gateways
Type	REST
Method	GET
Version	1.0

Endpoint

```
GET /gateways?prospect_id={prospectID}&potential_gateways={gatewayID}&number_of_path_per_gw_person={numberOfPathPerGWPerson}&number_of_prospect_person={numberOfProspectPersons}&debug={debug}
```

Description

Returns a list of paths between potential gateway persons and the prospect company.

Parameters

Parameter	Type	Required	Default	Description
<code>prospect_id</code>	string	Yes	—	Prospect company ID.
<code>potential_gateways</code>	comma-separated list of strings	Yes	—	IDs of potential gateway persons.
<code>number_of_path_per_gw_person</code>	integer	No	10	Maximum number of paths per gateway person.

Parameter	Type	Required	Default	Description
<code>number_of_gw_person_per_prospect_person</code>	integer	No	<code>10</code>	Maximum number of gateway persons per prospect person.
<code>number_of_prospect_person</code>	integer	No	—	Maximum number of prospect persons.
<code>debug</code>	boolean	No	<code>false</code>	Enables debug mode.

Response

Content type: `application/json`

Success response

Status code: `200 OK`

Returns a list of paths.

The response contains a `list_of_prospects` object with information about prospect persons and their associated paths.

The response structure includes:

- `link` — link to the prospect person
- `score` — score associated with the prospect person
- `paths_string` — formatted path information, available in debug mode
- `gateways_persons` — gateway-person information
- `path_time_in_ms` — path-computation time in milliseconds, available in debug mode

Each gateway person can contain:

- `link` — link to the gateway person
- `score` — score associated with the prospect person
- `paths` — the elements that make up a path

A path can contain links to entities such as a company, job or person.

Response schema

```
{
  "list_of_prospects": {
    "link": "PERSON/{personId}",
    "score": 1,
    "paths_string": [
      "Path information"
    ],
    "gateways_persons": [
      {
        "link": "PERSON/{gatewayPersonId}",
        "score": 1,
        "paths": [
          {
            "link": "Company/{companyId}"
          },
          {
            "link": "JOB/{jobId}"
          },
          {
            "link": "PERSON/{personId}"
          }
        ]
      }
    ],
    "path_time_in_ms": 4567
  }
}
```

The example identifiers and company information in this portfolio version have been replaced with placeholders.

Errors

400 Bad Request

A `400` response occurs when:

- no company exists with the specified `prospect_id`, or
- one or more supplied parameters contain an invalid value.

Example request

```
GET /gateways?prospect_id={prospectId}&potential_gateways={gatewayId1},  
{gatewayId2}&debug=true
```

Example response

```
{
  "list_of_prospects": {
    "link": "PERSON/{personId}",
    "score": 1,
    "paths_string": [
      "Path score: 1.0"
    ],
    "gateways_persons": [
      {
        "link": "PERSON/{gatewayPersonId}",
        "score": 1,
        "paths": [
          {
            "link": "Company/{companyId}"
          },
          {
            "link": "JOB/{jobId}"
          },
          {
            "link": "PERSON/{personId}"
          }
        ]
      }
    ],
    "path_time_in_ms": 4567
  }
}
```

Documentation notes

This reference documents a REST endpoint using a structured API-reference format covering:

- Endpoint and HTTP method
- Request parameters
- Data types and required values
- Default parameter values
- Response content type and status code
- Response structure
- Error conditions
- Request and response examples