



3 tons steam (Split condensing) Quotation

(Quotation valid for three months)



Fangkuai Boiler Co., LTD

16 June 2026



I. Quotation summary table

Code	Item	Specification	Unit	Qty	Unit price (USD)	Total Price (USD)
1	Boiler	WNS3-1.0 - YQ - FL1	set	1	24203	24203
2	Condenser	FCLL-3-L-B2	set	1	2461	2461
3	Burner	RL310 (RIELLO)	set	1	8968	8968
4	Electrical control cabinet	Matching, Siemens PLC, with major electrical components from internationally renowned brands such as ABB/ Schneider	set	1	1867	1867
5	Valves and instruments	Boiler matching	set	1	0	0
6	Chimney	Φ450*8Meter	set	1	1032	1032
7	Fully automatic water softener	3t/h; dual valve, dual tank, one in operation and one on standby	set	1	908	908
8	Cooling sampler	Material: Carbon steel outer shell, stainless steel coil Φ273	Set	1	176	176
9	Stainless steel insulated water tank	Circular, double-layer stainless steel insulation, V=3m ³	set	1	897	897
10	Feed water pump	Q=4m ³ /h, H=140m, P=4kw	set	2	647	1294
11	Steam distributor	System Support	set	1	661	661



	cylinder					
ALL TOTAL	BOBIL BODY+AUXILIARY EQUIPMENTS					42467

II. Product Introduction

- Product Name:** Split Condensing Steam boiler
- Product Model**

WNS	3	—	1.0	—	Y, Q
Horizontal internal combustion chamber combustion	Rated evaporation capacity (t/h)	Delimit er	Rated working pressure (MPa)	Delimiter	Fuel type

Product ModelMain technical data sheet

Se	Name	Unit	Numerical value or
1	Product model	—	WNS3-1.0-Y, Q
2	Structural form	—	Horizontal
3	Rated evaporation capacity	t/h	3
4	Rated steam temperature	°C	184
5	Rated steam pressure	MP	1.0
6	Equipment weight	t	10.14
7	Feed water temperature	°C	20
8	Exhaust gas temperature	°C	69
9	Boiler efficiency (light oil)	%	98.1
10	Boiler efficiency (natural gas)	%	100.07



11	Fuel consumption (light oil)	kg	194.5
12	Fuel consumption (natural gas)	Nm ³	232.7
13	Standards and specifications followed in design and manufacture	—	Boiler Safety Technical Code and professional standards
14	Material of insulation for the furnace	—	Rockwool, aluminosilicate fiber
15	Boiler packaging materials	—	Patterned aluminium sheet
16	Boiler dimensions (L×B×H)	mm	5112×2790×3485

Note: The data in this table is for reference only. The actual data is subject to the shipping drawings and the actual items.

3. Main Uses:

It provides production steam for food processing, printing and dyeing, pharmaceuticals and other industrial enterprises, disinfection steam for medical institutions, heating steam for other enterprises, institutions and hotels, and also provides domestic hot water through heat exchangers.

4. Main Features:

I. Structural Features (Biggest Difference from Integrated Condensation)

1. Three-section, floor-mounted layout: Furnace body + independent high-temperature economizer + independent low-temperature condenser. These three parts are floor-mounted and connected via flue flanges, not welded as a single unit to the boiler tail.

2. Flue Gas Path Sequence: Furnace → Boiler Shell Flue Tubes → Independent Economizer → Independent Condenser → Chimney



Flue gas is cooled in two stages; the low-temperature section is specifically for condensing water vapor and recovering latent heat of vaporization.

3. Water System in Series: Soft water is first preheated in the low-temperature condenser → then enters the high-temperature economizer → finally enters the boiler drum. This reverse heat exchange maximizes heat exchange efficiency.

II. Efficiency and Flue Gas Characteristics

1. Thermal Efficiency: 102% – 108% (lower heating value), conventional boilers 89% – 93%.

2. Flue Gas Temperature: 45 – 60°C (normal temperature condensation), ordinary boilers above 160°C.

3. Acidic condensate is produced; the condenser and low-temperature flue must be made of 316L stainless steel, as carbon steel will corrode.

III. Combustion System Characteristics (Standard Configuration: DB Series Split Burner)

1. Equipped with DB split burners (independent floor-mounted fan, burner head mounted on the furnace inlet), distinguishing it from the RS integrated burner.

2. Generally paired with FGR flue gas external circulation, achieving ultra-low NO_x ≤ 30mg/m³.

3. High tail-end resistance (300 ~ 400Pa), requiring a split high-pressure fan to overcome this resistance.

IV. Installation and Footprint Characteristics

1. The unit is divided into three parts, each lightweight, allowing for easy access even through narrow factory doorways, offering significant advantages for retrofit projects; integrated condensing units are much heavier, limiting hoisting options.

2. The overall length of the equipment is longer than integrated boilers of the



same tonnage, requiring a larger boiler room footprint, but allowing for flexible zoning.

3. Convenient maintenance: The economizer and condenser can be disassembled and maintained separately without moving the boiler body.

V. Water System Characteristics

1. The inlet water is preheated by the condensing flue gas, increasing the inlet water temperature by 30~50°C, reducing fuel consumption.

2. Equipped with a condensate collection system + condensate neutralization device (acidic water requires alkali treatment).

5. PLC full intelligent control system:

Fangkuai Company has fully intellectual property rights to independently design and develop the PLC fully automatic intelligent control system, which adopts the combined control mode of mechatronic control equipment and programmable logic controller (PLC). The advanced programmable logic controller (PLC) serves as the "central processing unit" of the control system. The control system operates via touchscreen, greatly enhancing the degree of automation control and operational reliability of the boiler, and making the operation more straightforward and intuitive.

(PLC)



Color touchscreen



The operation interface is intuitive and simple, and the running status is clear at a glance

- It features a high-resolution color touchscreen.



- It can display the operating status of burners, pumps, etc. and the changing status of the flame in real time and dynamically, at a glance.

- The full Chinese multi-level pop-up menu simplifies, organizes and intelligently monitors the boiler.

- Chinese troubleshooting guide, easy to operate.

Fully automatic operation, easy to operate

- Multiple water level protection: In addition to setting high water level alarm and low water level alarm, the drum is equipped with multiple water level interlock protection function for extremely low water level alarm to ensure the safe operation of the boiler.

- Multiple pressure protection: High-precision pressure gauge, overpressure interlock protection function of imported pressure transmission and pressure control components;

- Precise and convenient pressure control: The pressure transmitter transmits the pressure signal inside the boiler to the control system, and the user can read the current pressure value inside the boiler through the touchscreen and set the steam pressure fluctuation range to achieve precise control of the steam pressure.

- Enable automatic adjustment of boiler load;

- Power supply anomaly protection function: boiler prompt alarm.

- Time setting function: Users can set the start and stop times of the boiler as needed.

- High flue gas temperature alarm function: It can automatically monitor the flue gas temperature of the boiler, making it easier to grasp the combustion situation of the boiler.

- Online monitoring function for scale inside the boiler: Automatically alarm when the thickness exceeds a certain value, and text prompts the user to remove the dirt.

- Ignition program control and flameout protection in the combustion system



- With automatic flame regulation and automatic flame detection.
- Burner pressure protection function;
- Burner power-off self-locking protection function;
- Burner power failure protection function;
- Gas leak detection and other protection features (as the case may be);

High-quality hardware and comprehensive software ensure that the optimized system is efficient and reliable

- With strong anti-interference performance and industrial-grade PLC, it is safe and reliable;
- Multiple interlocking protections coexist, ensuring high reliability and high security of the system;
- It is equipped with a multi-level permission control system. People without permission cannot change the system operation parameters or operate the boiler.

Record fault history for easy maintenance and repair

- Automatically accumulate pump running time and burner running time;
- When a boiler malfunctions, the boiler is safely shut down first and the screen pops up, recording the time and content of the previous dozens of malfunctions. Users can quickly identify the cause of the malfunction according to the maintenance guide;

With a variety of control options and a wealth of extensions, customers have more choices

- PLC block-like expansion modules and ample reserved ports reduce repetitive investment by users for special needs development;
- It can be easily connected to current office automation networks (WINDOWS9X, WINDOWSNT, NOVELL, etc.) and factory automation control networks to enable remote monitoring of boiler water quality and boiler operation status;
- With a standard RS485 interface, using the MODEBUS protocol, it can be



connected to building automation or DCS to achieve group control of multiple boilers. It has a scale detection function to improve the energy-efficient operation of the boiler.

6. Systematic Solutions:

- 1) Adopt a modular design concept, where each part is relatively independent yet unified and coordinated;
- 2) The high-efficiency condensing steam boiler system is uniformly controlled by the boiler controller to fully exert the energy-saving effect;
- 3) While heating the boiler feed water, 80% of the oxygen in the feed water is also removed to increase the boiler's lifespan;



III. Relevant Performance

1. Partial export boiler performance

N O T E	Boiler model	Project Name	Quantity	Notes
1	ZWNSL0.7-1 / G - Q	Tunisian aid project	2	The Republic of Tunisia
2	WNS6-1.25 - YQ - L3	Mher	1	Armenia
3	WNS6-1.25 - YQ - FL1	Yiwu Penglin Import & Export Co., LTD	1	Lunda, Angola, Africa
4	WNS4-1.25-YQ-L4 (G)	Sinopharm 4-ton steam boiler project for export to Uzbekistan	1	Uzbekistan
5	WNS4-1.25 - YQ	Sudan Project	1	Sudan
6	WNS26.7-1.0 - YQ	D F Power Systems Pvt. Ltd	3	India
7	WNS2-1.25 - YQ - FL1	Sinopharm 4-ton steam boiler project for export to Uzbekistan	1	Uzbekistan
8	WNS2-1.25 - YQ	OZIKO CAPITAL&SECURITIES LTD	1	Nigeria
9	WNS2-1.0 - YQ - FBL1	Export fuel oil steam furnace WNS2-1.0-Y to the Philippines	1	Philippines
10	WNS2-1.0 - YQ	Phase I project of Qiaqia Food Co., LTD. (Thailand) factory	1	Thailand
11	WNS2-1.0 - YQ	“UZGERMED PHARM” LLC JV	1	Uzbekistan
12	WNS2.1-1.0/95/70 - YQ	Fuqing Guosheng Steel Structure Trading Co., LTD. (Wuling Indonesia Project)	3	Indonesia
13	WNS1-1-Y	Sichuan Honghua Petroleum Equipment Co., LTD	1	Kazakhstan



14	WNS1-1.0 - YQ	PT green energy	1	Indonesia
15	WNS1-1.0 - YQ	Chongqing Puyu Puxi Environmental Protection Technology Co., Ltd. export ASME steam boiler project for Supporting petrochemical equipment to Alabama, USA	1	USA - Obama
16	WNS1.5-1.25 - Y	PIRELLA	1	Montenegro
17	WNS1.5-1.0 - YQ	Tianjin Dongfang Xianke Company	4	Russia
18	WNS1.5-1.0 - Y	Sichuan Honghua Petroleum Equipment Co., LTD	1	Kazakhstan
19	WDZ1.2-0.7/95/70 - II	North Korea Great Hall of the People	2	North Korea
20	Wdz1.2-0.7/95/70-ii 1200KW	The Great Hall of the Korean People	2	North Korea
21	WDR2.0-1.25 - II - B2	Wuxi Jiateming Environmental Technology Co., Ltd. exports 2-ton electric steam boilers to Thailand	1	Thailand
22	WDR0.5-0.8 - II	Petrochina Bohai Equipment Petroleum Machinery Factory	6	Russia
23	WDR0.5-0.8 - II	1st Machinery	6	Russia
24	WDR0.2-1.0 - II	Nanyang Erji Petroleum Equipment (Group) Co., LTD	8	Kazakhstan
25	WDR0.2-1.0 - II	RG PETRO-MACHINERY (GROUP) CO. LTD	8	Kazakhstan
26	LHS0.5-0.8 - YQ	"CHOCO SOFT" LTD	1	Uzbekistan
27	LHS0.5-0.4 - YQ	Prodkontrakt invest	1	Russia
28	CWNS1.05-95/70 - YQ	GENUINE TRADE	8	Turkmenistan
29	CWDR0.176-95/70 - II	Nanyang Erji Petroleum Equipment (Group) Co., LTD	8	Kazakhstan
30	CWDR0.176-95/70	RG PETRO-MACHINERY (GROUP) CO.	8	Kazakhstan



	- II	LTD		khsta n
31	CLHS0.47-95/70 - YQ	Orica Mongolia LLC	1	Mongolia
32	WNS1-1.0 - YQ - FBL2	Armenian steam boilers for export	1	Armenia
33	CLHS 0.47-95/70-YQ-e N	Qingzhou Xinze Agricultural Science and Technology Co., LTD. CLHS0.47 export	1	
34	WNS1-1.0 - YQ	Export to Indonesia	1	Indonesia
35	WNS1.5-1.0 - YQ - FL2	Export of 1.5-ton fuel oil steam boiler project to Yemen	1	Yemen
36	WNS3-1.25 - YQ	A 3-ton split steam boiler for the export project to Australia	1	Australia
37	WNS6-1.6 - YQ	WNS6-1.6 oil and gas dual-purpose boiler for export to Singapore	1	Singapore
38	WNS6-1.25 - YQ	Shanghai Evan Export 6-ton ASME steam boiler project to the United States	1	USA
39	WNS1-1.0 - YQ - FBL2	Export to Tanzania	2	Tanzania
40	WNS4-1.25 - YQ - NY1	1 4T/H Oil and gas dual-purpose boiler project of Haida Egypt Co., LTD	1	Egypt
41	WNS2-1.25 - YQ	2 ton ASME integrated condensing steam boiler for export to Singapore	1	"Singapore
42	WNS4-1.25 - YQ - FL1	river med	1	Uzbekistan
43	WNS4-1.25 - YQ - NY1	For export to Uzbekistan boilers	1	Uzbekistan
44	NWNS4-2.0 - YQ - NY1	Indonesia Export Project	1	Indonesia
45	WNS6-1.25 - YQ - NY2	Export of 6-ton steam boiler project to Egypt	1	Egypt
46	WNS1-1.0 - YQ - FBL2	1 ton fuel oil boiler for export to Armenia	1	Armenia
47	WNS13-1.6 - YQ	Export of 13-ton ASME+MOM certified steam boiler project to Singapore	1	Singapore
48	WNS4-1.25 - YQ - FL1	Evan Pharmaceutical Equipment Export 4-ton steam boiler project to Laos	1	Laos
49	WNS2.1-1.0/115 (95) /70-YQ (i5-2100Y1P1-1)	China Workers International Asian Youth Games in Uzbekistan	1	Uzbekistan
50	WNS5.6-1.0/115 (95) /70-YQ	China Workers International Asian Youth Games in Uzbekistan	1	Uzbekistan



	(i5-5600Y1P1-1)			
51	WNS1-1.0 - YQ - FBL2	Exported by MILPRO COMPANY, a Thai feed company	1	Thailand
52	WNS2-1.25 - YQ	A 2-ton split steam boiler project for export to the Philippines	1	Philippines
53	WNS6-1.6 - YQ	Export to Singapore ASME6-1.6 Split with overhead condenser Oil and gas dual-purpose boiler project	1	Singapore
54	WNS3-1.25 - YQ	Export to Australia 3-ton boiler project	1	Australia
55	WNS1-1.0 - YQ - FBL2	Compatible with the export of fuel oil steam boilers to Sri Lanka	1	Sri Lanka
56	WNS8-1.25 - YQ - FL1	Export to Saudi Arabia as a set	3	Saudi Arabia
57	NWNS12-1.25 - YQ - NY1	Export to Uzbekistan	1	Uzbekistan
58	CWDR 0.47-95/70-II-E N(480KW)	Procurement of boiler equipment for the Yelizovo Back Street Business Centre Project in Kamchatka, Russia	1	Russia
59	WNS4-1.25 - YQ - FL1	Shanghai Evan export 4-ton split boiler project	1	Egypt
60	NWNS2-1.25 - YQ - TNY2	Chinese medicine exports to Uzbekistan	1	Uzbekistan
61	WNS2-1.25 - YQ	Shandong Kuntai New Materials Technology Co., LTD. Mexico Export Project	1	Mexico
62	FKG - 450 - Q - / - 75/4.0	Export Iran water-tube superheated steam boilers	2	Iran
63	WNS3-1.25 - YQ	Export to Australia 3-ton split boiler project	2	Australia
64	WNS10-1.6 - YQ - FL1	Export to Russia 10-ton split boilers - total number 1.00 - total steam tonnage 10.00	2	Russia
65	WDR2.5-1.25 - II - B1	A steel plant in Ethiopia	2	Ethiopia
66	NWNS10-1.6-Q (07-10000K1L1P3-2)	Tehada export to Belarus project	1	Belarus
67	NWNS10-1.6-Q (07-10000K1L1P3-2)	Tehada export to Belarus project	1	Belarus



68	20 - II LDR0.23-1.0/85 /	The 60kw+250kw electric hot water project of the bath center in North Korea	1	North Korea
69	20 - II LDR0.058-1.0/85 /	North Korean Bath Center 60kw+250kw electric hot Water project	1	North Korea
70	WNS0.7-1.0/95/70-YQ-FBL1 N	Export to Botswana, South Africa	1	South Africa
71	WNS3-1.25-YQ-FL1 (skid-mounted)	Wuhan Jingsheng Paper Engineering Co., LTD. - Venezuela	1	Venezuela
72	WNS4-1.25 - YQ - FL1	Shanghai Wotaien Environmental Protection exports to Chile	2	Chile
73	SZS50-1.25 - YQ - T1	Export to the Red Sea - Yanbu Industrial Park 50-ton steam boiler project in Saudi Arabia	1	Saudi Arabia
74	NWNS8-1.25 - Q (theta I1p2 6-8000-2) F	URS_REKA_MED_ project of the Reka Medical Farm in Uzbekistan	1	Uzbekistan
75	WNS4-1.25 - YQ - NY1	GODAY Indonesia Phase II plant	1	Indonesia
76	WNS6-1.25 - YQ - NY2	GODAY Indonesia Phase II plant	1	Indonesia
77	WNS3-1.25 - YQ - FL1	Export of 1.5-ton fuel oil steam boiler project to Yemen	1	Yemen
78	WNS4-1.25 - YQ - NY1	Export to Uzbekistan 4-ton new integrated project	1	Uzbekistan
79	WNS1.4-1.0/95/70-YQ-FAL1 N	Two 1.4 pressurized hot water boilers for export to Mongolia	2	Mongolia
80	SZS21-70 - Q - / - 1.0/95	Goldsmith undertook the heating project for BYD's Hungarian plant	1	Hungary
81	SZS14-70 - Q - / - 1.0/95	Goldsmith undertook the heating project for BYD's Hungarian plant	5	Hungary
82	WNS2-1.25 - YQ - FL1	Export of 2-ton split steam boiler project to the Philippines	1	Philippines
83	WNS4-1.25 - YQ - NY1	River Sug'D pharm, Tajikistan	1	Tajikistan
84	NWNS6-1.25 - YQ - TFL4	The project of exporting 6-ton split steam boiler bodies to Indonesia	1	Indonesia
85	WNS2-1.25 - YQ - FL1	Export of 6-ton split steam boiler body project to Indonesia	1	Indonesia
86	WNS1.5-1.0 - YQ - FL2	Export of 6-ton split steam boiler body project to Indonesia	1	Indonesia
87	WNS0.5-0.8 - YQ - FBL1	Export Australia 0.5-ton steam boiler project	1	Australia
88	NWNS20-1.25 - Q	Taiwan Jinmei Paper Industry Taiwan	1	Taiwan



		Export Project		n
89	WNS2.8-0.4/90/70-Q (i6-2800L1P0-T1)	China Automotive General Contracting BYD Hungary Paint Heating and Hot Water Project	4	Hung ary
90	WNS7-0.4/90/70-Q (i6-7000L1P0-T1)	China Automotive General Contracting BYD Hungary Paint Heating and Hot Water Project -	5	Hung ary
91	WNS2-1.25 - YQ - FL1	Xiamen Pengwei 2-ton steam boiler	1	Thail and
92	WNS4-1.25 - YQ - FL1	Xiamen Pengwei 2-ton steam boiler	1	Thail and
93	WNS2-1.25 - YQ - FL1	Export of 2-ton split steam boiler project to Yemen	1	Yeme n
94	WNS2.8-70 - Q - / - 0.4/95	Byd Brazil 4 i6s	4	Brazil
95	WNS15-1.25 - YQ - FL1	Export of 15-ton steam boiler project to Kazakhstan	1	Kaza khsta n



2. Some on-site photos of the boiler room

















