Clinic booking API 1.0 OAS 3.0

/assessment-api/openapi.json

The exact contract for Task 1 of the Koya Cohort 4 assessment. Build these endpoints so our checks can talk to your API.

Everything is JSON. Each endpoint says which level it belongs to. Every error response looks like `{"error": "<message>"}`.

Every request needs the `X-API-Key` header (level 2). A missing or wrong key returns **401**.

default

POST `/reset` Level 1 · Replace all slots

Deletes every booking and replaces all slots with the ones you send, including slots in the past.

Parameters

No parameters

Request body required

application/json

Example Value Schema

```
{
  "slots": [
    {
      "id": "s1",
      "provider": "Dr Ade",
      "start": "2026-12-10T09:00:00Z",
      "end": "2026-12-10T09:30:00Z"
    }
  ]
}
```

Responses

Code	Description	Links
200	Done	*No links*

GET `/slots` Level 1 · List slots

Every slot, earliest `start` first.

Parameters

Name	Description
provider `string` *(query)*	Only this provider's slots (exact match) provider

Responses

Code	Description	Links

200	The slots
	Media type
	application/json
	Controls `Accept` header.
	Example Value Schema
	{
	"slots": [
	{
	"id": "s1",
	"provider": "Dr Ade",
	"start": "2026-12-10T09:00:00Z",
	"end": "2026-12-10T09:30:00Z",
	"available": true
	}
	]
	}
		No links

POST `/bookings` Book a slot (levels 1–5)

Level 1: returns 201 with the booking, status `confirmed` .

Level 2: **400** if `slot_id` , `name` or `email` is missing or empty or the email isn't valid. **404** if the slot doesn't exist. **400** if the slot has already started. Trim spaces from `name` and `email` , and store `email` in lower case.

Level 3: a slot that already has a confirmed booking returns **409**. This must hold when many requests arrive at the same moment.

Level 4: the optional `Idempotency-Key` header. The same key with the same body returns the same response (same status code, same booking `id`) and never creates a second booking. The same key with a different body returns **422**.

Level 5: at most 5 attempts per email per minute, failed attempts included. The 6th returns **429** with a `Retry-After` header in whole seconds. Other emails aren't affected.

Parameters

Name	Description
Idempotency-Key `string` *(header)*	Level 4 Idempotency-Key

Request body required

application/json

Example Value Schema

```
{
  "slot_id": "s1",
  "name": "Ada Obi",
  "email": "ada@example.com"
}
```

Responses

Code	Description	Links
201	Booked Media type	*No links*

Code	Description	Links
	application/json Controls `Accept` header. **Example Value** Schema `{ "id": "string", "slot_id": "s1", "name": "Ada Obi", "email": "ada@example.com", "status": "confirmed", "created_at": "2026-11-05T18:34:10.430Z" }`	
400	Missing or invalid field, or the slot has already started (level 2) Media type application/json **Example Value** Schema `{ "error": "slot not found" }`	*No links*
404	The slot doesn't exist (level 2) Media type application/json **Example Value** Schema `{ "error": "slot not found" }`	*No links*
409	Slot already booked (level 3) Media type application/json **Example Value** Schema `{ "error": "slot not found" }`	*No links*
422	Idempotency-Key reused with a different body (level 4) Media type application/json	*No links*

Code	Description	Links

Example Value Schema

```
{
  "error": "slot not found"
}
```

429 Too many attempts for this email (level 5) *No links*

Media type

application/json

Example Value Schema

```
{
  "error": "slot not found"
}
```

Headers:

Name	Description	Type
Retry-After	Seconds to wait	integer

GET /bookings Level 4 · List a person's bookings

That person's bookings, oldest first. The email match ignores case. Use cursor pagination: pass `next_cursor` back as `cursor` to get the next page. The last page has `next_cursor: null`.

Parameters

Name	Description
email * required string *(query)*	email
limit integer *(query)*	1 to 50. Anything else returns 400. *Default value* : 10 10
cursor string	cursor

Name	Description
(query)	

Responses

Code	Description	Links
200	A page of bookings Media type application/json Controls `Accept` header. **Example Value** Schema `{ "bookings": [ { "id": "string", "slot_id": "s1", "name": "Ada Obi", "email": "ada@example.com", "status": "confirmed", "created_at": "2026-11-05T18:34:10.471Z" } ], "next_cursor": "string" }`	*No links*
400	Invalid limit Media type application/json **Example Value** Schema `{ "error": "slot not found" }`	*No links*

GET `/bookings/{id}` Level 1 · Get a booking

Parameters

Name	Description
id * required `string` *(path)*	id

Responses

Code	Description	Links

200	The booking
	
	Media type
	application/json
	Controls `Accept` header.
	
	Example Value Schema
	
	{
	"id": "string",
	"slot_id": "s1",
	"name": "Ada Obi",
	"email": "ada@example.com",
	"status": "confirmed",
	"created_at": "2026-11-05T18:34:10.499Z"
	}
		No links

404	No booking with that id
	
	Media type
	application/json
	
	Example Value Schema
	
	{
	"error": "slot not found"
	}
		No links

DELETE `/bookings/{id}` Level 3 · Cancel a booking

Sets `status` to `cancelled` and frees the slot.

Parameters

Name	Description
id * required `string` *(path)*	id

Responses

Code	Description	Links
200	The cancelled booking Media type application/json Controls `Accept` header. **Example Value** Schema `{ "id": "string", "slot_id": "s1", "name": "Ada Obi", "email": "ada@example.com", "status": "confirmed", "created_at": "2026-11-05T18:34:10.513Z" }`	*No links*
404	No booking with that id Media type application/json **Example Value** Schema `{ "error": "slot not found" }`	*No links*
409	Already cancelled Media type application/json **Example Value** Schema	*No links*

Code	Description	Links
	<pre>{ "error": "slot not found" }</pre>	

Schemas