

Essential Linux Directories & Files (Core)

Linux Commands Course · Section 8

Linux Filesystem Philosophy

Everything in Linux is organized under a **single root directory** `/`.

- No drive letters (like C: or D:)
- All devices, users, and applications live under `/`
- Each directory has a specific purpose

Think of it as a **tree**, with `/` as the root and everything branching from it.

Core Directory Layout Overview

Directory	Purpose
<code>/bin</code>	Essential user binaries (commands needed for all users)
<code>/sbin</code>	System binaries (commands for system administration)
<code>/usr/bin</code>	Most user commands and applications
<code>/usr/sbin</code>	System admin tools not required for booting
<code>/etc</code>	System configuration files
<code>/var</code>	Variable data (logs, mail, cache)
<code>/home</code>	User home directories
<code>/tmp</code>	Temporary files (cleared on reboot)
<code>/dev</code>	Device files (represent hardware or virtual devices)
<code>/proc</code>	Virtual filesystem exposing process and kernel info
<code>/sys</code>	System and hardware information (kernel interface)
<code>/opt</code>	Optional or third-party software packages

/bin and /sbin

Contain the most **fundamental executables**.

Examples:

```
ls /bin  
ls /sbin
```

Typical contents:

- /bin/ls, /bin/cp, /bin/mv, /bin/cat
- /sbin/reboot, /sbin/ifconfig, /sbin/fsck

Used during system boot and single-user recovery mode.

/usr/bin and /usr/sbin

`/usr` = "Unix System Resources."

Holds the **main body of user utilities** and optional system tools.

```
ls /usr/bin | head
ls /usr/sbin | head
```

Applications like `vim`, `python`, `gcc`, `systemctl`, etc., live here.

This is where most installed software resides.

/etc – Configuration Files

Contains **system-wide configuration** for all programs and services.

Examples:

```
ls /etc
```

Subdirectories like `/etc/network`, `/etc/ssh`, `/etc/systemd` hold their respective configs.

These files are usually **plain text**, editable with a text editor.

/var – Variable Data

“Variable” because contents change frequently.

Common uses:

- `/var/log/` → log files (`syslog`, `auth.log`)
- `/var/spool/` → print/mail queues
- `/var/cache/` → cached data
- `/var/lib/` → application state (databases, package info)

Example:

```
ls /var/log
```

Logs are vital for troubleshooting.

/home – User Directories

Each user has a personal workspace under `/home`.

Example structure:

```
/home/alice  
/home/bob
```

Contains personal files, downloads, and shell settings.

```
ls ~
```

The `~` symbol always refers to your current user's home directory.

/tmp – Temporary Storage

Used for short-lived files and data exchange between programs.

```
cd /tmp  
ls
```

Cleared on reboot or after a set time.

Accessible to everyone but protected by the **sticky bit** so users can't delete others' files.

/dev – Devices as Files

Represents hardware and virtual devices as files.

```
ls /dev | head
```

Examples:

- `/dev/sda` – first hard drive
- `/dev/null` – data sink (discards anything written)
- `/dev/tty` – current terminal
- `/dev/random` – random data source

Device files enable programs to interact with hardware using normal file operations.

/proc – Process and Kernel Info

A **virtual filesystem** reflecting live system state.

```
ls /proc | head
```

Contains pseudo-files for each running process (`/proc/<PID>/`).

Key files:

- `/proc/cpuinfo` – CPU details
- `/proc/meminfo` – memory usage
- `/proc/uptime` – uptime information

Read-only for observation; data is generated dynamically.

/sys – Kernel and Device Management

`/sys` is similar to `/proc` but more structured.

Contains live info about devices, drivers, and kernel modules.

Example:

```
ls /sys/class
```

Used by udev and other system components to manage devices dynamically.

/opt – Optional Software

Holds **add-on applications** installed outside the package manager.

Example paths:

- /opt/google/chrome/
- /opt/lampp/

You can place self-contained programs or third-party tools here.

Must-Know System Files

File	Description
<code>/etc/passwd</code>	User account information (username, UID, home, shell)
<code>/etc/shadow</code>	Encrypted passwords and aging info (root-only)
<code>/etc/group</code>	Group membership definitions
<code>/etc/fstab</code>	Filesystems to mount at boot
<code>/etc/hosts</code>	Local hostname-to-IP mapping
<code>/etc/resolv.conf</code>	DNS resolver configuration
<code>/etc/sudoers</code>	sudo access control rules
<code>~/.bashrc</code>	User-specific shell customization
<code>~/.profile</code>	Environment setup on login

/etc/passwd Example

```
cat /etc/passwd | head -3
```

Example line:

```
student:x:1000:1000:Student User:/home/student:/bin/bash
```

Fields (colon-separated):

1. Username
2. Placeholder (historically password, now stored in `/etc/shadow`)
3. UID (User ID)
4. GID (Group ID)
5. Comment / full name
6. Home directory
7. Login shell

/etc/shadow Example

Only readable by root.

```
sudo head /etc/shadow
```

Stores encrypted passwords and password aging information.

Never edit this file manually – use `passwd` command instead.

/etc/group Example

Defines group memberships.

```
cat /etc/group | head
```

Each line: group name, password placeholder, GID, and members.

/etc/fstab – Filesystem Table

Defines which partitions and devices to mount automatically at boot.

Example:

```
UUID=xxxx-xxxx / ext4 defaults 0 1  
UUID=yyyy-yyyy /home ext4 defaults 0 2
```

View safely:

```
cat /etc/fstab
```

`/etc/hosts` and `/etc/resolv.conf`

`/etc/hosts` – manual hostname resolution.

Example:

```
127.0.0.1    localhost
192.168.1.10 server.local
```

`/etc/resolv.conf` – nameserver (DNS) configuration.

Example:

```
nameserver 1.1.1.1
nameserver 8.8.8.8
```

/etc/sudoers

Controls who can run commands as other users (usually root).

Always edit with **visudo** to prevent syntax errors:

```
sudo visudo
```

Example rule:

```
alice ALL=(ALL:ALL) ALL
```

Meaning: Alice can run any command as any user.

User Configuration Files

`~/.bashrc` – executed for interactive non-login shells.
Custom aliases, colors, and shell variables live here.

`~/.profile` – executed for login shells; sets environment variables like `PATH` and `locale`.

```
cat ~/.bashrc | head
```

Keep personal shell tweaks in `.bashrc`, system-wide ones in `/etc/bash.bashrc`.

Recap

- Linux filesystem is a single tree rooted at `/`.
 - Know what each main directory stores.
 - Learn critical system files under `/etc` and your home.
 - Configuration lives in plain text.
 - Reading these files (not editing them blindly) is key to system literacy.
-