



# Data Structures – Overview

Python provides multiple built-in structures for organizing data:

- **Lists**
- **Strings**
- **Tuples**
- **Sets**
- **Dictionaries**
- Choosing the right structure

Each structure has unique properties and use-cases.

---



# List Characteristics

## Advantages:

- Mutable
- Dynamic size
- Supports duplicates

## Use-cases:

- Collections
  - Queues
  - Storing ordered items
-

# Strings

Strings represent **text**.

Properties:

- Ordered
- Immutable
- Indexable
- Iterable

```
s = "Hello"

a = s[0]      # first character
b = s[-1]     # last character
c = s.upper() # all upper chars
d = len(s)    # Length of the string

print(a, b, c, d)
```

---

[finished]

---

```
H o HELLO 5
```

# Tuples

Tuples store **ordered**, **immutable** sequences.

```
point = (10, 20)
```

Benefits:

- Fast
- Secure from modification
- Memory-efficient

Tuple unpacking:

```
x, y = point
```

---

# Tuple vs List

- Need modification → **List**
  - Need fixed, reliable structure → **Tuple**
  - Performance required → **Tuple**
-

# Sets

Sets store **unordered**, **unique** elements.

```
colors = {"red", "blue", "green"}
```

Operations:

```
colors.add("yellow")  
colors.remove("red")
```

Useful for:

- membership checks
  - removing duplicates
  - mathematical operations
-



# Set Operations

```
a = {1, 2, 3}
b = {3, 4, 5}
```

```
x1 = a | b      # union
x2 = a & b      # intersection
x3 = a - b      # difference
x4 = a ^ b      # symmetric difference
```

```
print(x1, x2, x3, x4)
```

---

[finished]

---

```
{1, 2, 3, 4, 5} {3} {1, 2} {1, 2, 4, 5}
```

# Dictionaries

Dictionaries store **key** : **value** pairs.

```
user = {  
    "name": "Alice",  
    "age": 25,  
    "city": "Baku"  
}  
  
# Access:  
n = user["name"]  
print(n)  
print()  
  
# Modify:  
user["age"] = 26  
user["country"] = "Azerbaijan"  
print(user)
```

[finished]

Alice

```
{'name': 'Alice', 'age': 26, 'city': 'Baku', 'country':  
'Azerbaijan'}
```

# Dictionary Operations

```
user = {  
    "name": "Alice",  
    "age": 25,  
    "city": "Baku"  
}  
  
a = user.keys()  
b = user.values()  
c = user.items()  
d = "city" in user # check key existence  
e = "Baku" in user  
  
print(a)  
print(b)  
print(c)  
print(d)  
print(e)
```

————— [finished] —————

```
dict_keys(['name', 'age', 'city'])  
dict_values(['Alice', 25, 'Baku'])  
dict_items([('name', 'Alice'), ('age', 25), ('city',  
    'Baku')])  
True  
False
```

Dictionaries are ideal for structured data.

---

## Example

```
1 student = {  
2     "name": "Elnur",  
3     "scores": [90, 85, 97],  
4     "passed": True  
5 }  
6  
7 average = sum(student["scores"]) / len(student["scores"])  
8  
9 print(student["name"], "average:", average)
```

---

[finished]

```
Elnur average: 90.66666666666667
```

# Choosing the Right Data Structure

Type	Ordered	Mutable	Unique	Best For
<b>String</b>	Yes	No	N/A	Text
<b>List</b>	Yes	Yes	No	General collections
<b>Tuple</b>	Yes	No	No	Fixed data
<b>Set</b>	No	Yes	Yes	Unique items
<b>Dict</b>	Keys no	Yes	Keys unique	Structured data

## Mini Task – Apply Everything

Create a script that:

1. Stores student info in a dictionary
  2. Contains: name, age, list of grades
  3. Calculates average grade
  4. Prints a formatted summary
-