

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

Creating the table

```
MariaDB [22co11]> CREATE TABLE SALES_22co11 (  
->   ord_no INT PRIMARY KEY,  
->   purch_amt DECIMAL(6, 2),  
->   ord_date DATE,  
->   cust_id INT,  
->   salesman_id INT  
-> );  
Query OK, 0 rows affected (0.03 sec)
```

Entering the details

```
MariaDB [22co11]> INSERT INTO SALES_22co11 VALUES  
->   (70001, 150.5, '2012-10-05', 3005, 5002),  
->   (70009, 270.65, '2012-09-10', 3001, 5005),  
->   (70002, 65.26, '2012-10-05', 3002, 5001),  
->   (70004, 110.5, '2012-08-17', 3009, 5003),  
->   (70007, 948.5, '2012-09-10', 3005, 5002),  
->   (70005, 2400.6, '2012-07-27', 3007, 5001),  
->   (70008, 5760, '2012-09-10', 3002, 5001),  
->   (70010, 1983.43, '2012-10-10', 3004, 5006),  
->   (70003, 2480.4, '2012-10-10', 3009, 5003),  
->   (70012, 250.45, '2012-06-27', 3008, 5002),  
->   (70011, 75.29, '2012-08-17', 3003, 5007),  
->   (70013, 3045.6, '2012-04-25', 3002, 5001);  
Query OK, 12 rows affected (0.00 sec)  
Records: 12  Duplicates: 0  Warnings: 0
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

2. Display the contents of the SALES_Rollno

```
MariaDB [22co11]> select * from SALES_22co11;
```

ord_no	purch_amt	ord_date	cust_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70004	110.50	2012-08-17	3009	5003
70005	2400.60	2012-07-27	3007	5001
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005
70010	1983.43	2012-10-10	3004	5006
70011	75.29	2012-08-17	3003	5007
70012	250.45	2012-06-27	3008	5002
70013	3045.60	2012-04-25	3002	5001

```
12 rows in set (0.00 sec)
```

3. Write a SQL statement to find the total purchase amount for all orders.

```
MariaDB [22co11]> select sum(purch_amt) from SALES_22co11;
```

sum(purch_amt)
17541.18

```
1 row in set (0.02 sec)
```

4. Write a SQL statement to find the average purchase amount of all orders.

```
MariaDB [22co11]> select avg(purch_amt) from SALES_22co11;
```

avg(purch_amt)
1461.765000

```
1 row in set (0.00 sec)
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

5. Write a SQL statement to find the distinct salesman from sales

```
MariaDB [22co11]> select count(DISTINCT salesman_id) from SALES_22co11;
+-----+
| count(DISTINCT salesman_id) |
+-----+
| 6 |
+-----+
1 row in set (0.00 sec)
```

6. Write a SQL statement to get the maximum purchase amount of all the orders

```
MariaDB [22co11]> select max(purch_amt) from SALES_22co11;
+-----+
| max(purch_amt) |
+-----+
| 5760.00 |
+-----+
1 row in set (0.00 sec)
```

7. Write a SQL statement to get the minimum purchase amount of all the orders.

```
MariaDB [22co11]> select min(purch_amt) from SALES_22co11;
+-----+
| min(purch_amt) |
+-----+
| 65.26 |
+-----+
1 row in set (0.00 sec)
```

8. Find the highest purchase amount ordered by the each customer

```
MariaDB [22co11]> select cust_id, MAX(purch_amt) as Highest_Purchase_Amount from SALES_22co11 GROUP BY cust_id;
+-----+-----+
| cust_id | Highest_Purchase_Amount |
+-----+-----+
| 3001 | 270.65 |
| 3002 | 5760.00 |
| 3003 | 75.29 |
| 3004 | 1983.43 |
| 3005 | 948.50 |
| 3007 | 2400.60 |
| 3008 | 250.45 |
| 3009 | 2480.40 |
+-----+-----+
8 rows in set (0.00 sec)
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

9. Write a SQL statement to find the highest purchase amount ordered by the each customer on a particular date with their ID, order date and highest purchase amount.

```
MariaDB [22co11]> select cust_id, ord_date, MAX(purch_amt) as Highest_Purchase_Amount from SALES_22co11 GROUP BY cust_id, ord_date;
```

cust_id	ord_date	Highest_Purchase_Amount
3001	2012-09-10	270.65
3002	2012-04-25	3045.60
3002	2012-09-10	5760.00
3002	2012-10-05	65.26
3003	2012-08-17	75.29
3004	2012-10-10	1983.43
3005	2012-09-10	948.50
3005	2012-10-05	150.50
3007	2012-07-27	2400.60
3008	2012-06-27	250.45
3009	2012-08-17	110.50
3009	2012-10-10	2480.40

12 rows in set (0.057 sec)

10. Write a SQL statement to find the highest purchase amount on a date '2012-08-17' for each salesman with their ID

```
MariaDB [22co11]> select salesman_id, MAX(purch_amt) as Highest_Purchase_Amount from SALES_22co11 where ord_date='2012-08-17' GROUP BY salesman_id;
```

salesman_id	Highest_Purchase_Amount
5003	110.50
5007	75.29

2 rows in set (0.068 sec)

11. Write a SQL statement to find the highest purchase amount with their ID and order date, for only those customers who have highest purchase amount in a day is more than 2000

```
MariaDB [22co11]> select cust_id, ord_date, MAX(purch_amt) as Highest_Purchase_Amount from SALES_22co11 GROUP BY cust_id,ord_date having MAX(purch_amt)>2000;
```

cust_id	ord_date	Highest_Purchase_Amount
3002	2012-04-25	3045.60
3002	2012-09-10	5760.00
3007	2012-07-27	2400.60
3009	2012-10-10	2480.40

4 rows in set (0.057 sec)

12. Write a SQL statement to find the highest purchase amount with their ID and order date, for those customers who have a higher purchase amount in a day is within the range 2000 and 6000.

```
MariaDB [22co11]> select cust_id,ord_date, MAX(purch_amt) AS Highest_Purchase_Amount from SALES_22co11 GROUP BY cust_id,ord_date HAVING MAX(purch_amt) BETWEEN 2000 AND 6000;
```

cust_id	ord_date	Highest_Purchase_Amount
3002	2012-04-25	3045.60
3002	2012-09-10	5760.00
3007	2012-07-27	2400.60
3009	2012-10-10	2480.40

4 rows in set (0.01 sec)

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

13. Write a SQL statement to find the highest purchase amount with their ID and order date, for only those customers who have a higher purchase amount in a day is within the list 2000, 3000, 5760 and 6000.

```
MariaDB [22co11]> select cust_id, ord_date, MAX(purch_amt) AS Highest_Purchase_Amount from SALES_22co11 GROUP BY cust_id, ord_date HAVING MAX(purch_amt) IN (2000,3000,5760,6000);
```

cust_id	ord_date	Highest_Purchase_Amount
3002	2012-09-10	5760.00

```
1 row in set (0.00 sec)
```