

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

Consider following Sale table,

oid	oname	previous_balance	customer
11	ord1	2000	Alex
12	ord2	1000	Adam
13	ord3	2000	Abhi
14	ord4	1000	Adam
15	ord5	2000	Alex

Table Sale_22co11

```
SQL> create table Sale_22co11
  2  (oid number(2), oname varchar(5),previous_balance number(6),customer varchar(10));
Table created.
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

```
SQL> insert into Sale_22co11
  2  values(11,'ord1',2000,'Alex');

1 row created.

SQL> insert into Sale_22co11
  2  values(12,'ord2',1000,'Adam');

1 row created.

SQL> insert into Sale_22co11
  2  values(13,'ord3',2000,'Abhi');

1 row created.

SQL> insert into Sale_22co11
  2  values(14,'ord4',1000,'Adam');

1 row created.

SQL> insert into Sale_22co11
  2  values(15,'ord5',2000,'Alex');

1 row created.

SQL> select * from Sale_22co11;
```

OID	ONAME	PREVIOUS_BALANCE	CUSTOMER
11	ord1	2000	Alex
12	ord2	1000	Adam
13	ord3	2000	Abhi
14	ord4	1000	Adam
15	ord5	2000	Alex

1. Create a view "Sale(rollno)1" containing all the details from the sale table.

```
SQL> create VIEW Sale_22co11_1 as
  2  select * from Sale_22co11;

View created.
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

2. Display the contents of "Sale(rollno)1"

```
SQL> select * from Sale_22co11_1;
```

OID	ONAME	PREVIOUS_BALANCE	CUSTOMER
11	ord1	2000	Alex
12	ord2	1000	Adam
13	ord3	2000	Abhi
14	ord4	1000	Adam
15	ord5	2000	Alex

3. Create a view "Sale(rollno)2"; containing order details and customer name from the sale table.

```
SQL> create view Sale_22co11_2 as select OID,ONAME,CUSTOMER from Sale_22co11;
View created.
```

4. Display the contents of "Sale(rollno)02"

```
SQL> select * from Sale_22co11_2;
```

OID	ONAME	CUSTOMER
11	ord1	Alex
12	ord2	Adam
13	ord3	Abhi
14	ord4	Adam
15	ord5	Alex

5. Create a view "Sale(rollno)3"; containing order and previous balance with the amount increased by 1000 from the sale table

```
SQL> create view Sale_22co11_3 AS select OID,PREVIOUS_BALANCE AS PREV_BAL from sale_22co11;
View created.
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

6. Display the contents of Sale(rollno)3

```
SQL> select * from Sale_22co11_3;
```

OID	PREV_BAL
11	2000
12	1000
13	2000
14	1000
15	2000

7. Create a view "Sale(rollno)4" for the sale table having order id as 13 and 14.

Provide with check option clause. Test the clause by using insert and update statement.

```
SQL> create view Sale_22co11_4 as
2   select * from Sale_22co11
3   where OID in(13,14)
4   with CHECK OPTION;

View created.

SQL> insert into Sale_22co11_4 values (13,'ord6',1200,'Jack');

1 row created.

SQL> insert into Sale_22co11_4 values (15,'ord6',1200,'Jack');
insert into Sale_22co11_4 values (15,'ord6',1200,'Jack')
*
ERROR at line 1:
ORA-01402: view WITH CHECK OPTION where-clause violation
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

8. Delete a record in Sale(rollno)1 and then display the contents of sale(rollno)1 and Sales tables.

```
SQL> delete from sale_22co11_1 where oid=13;
2 rows deleted.

SQL> select * from Sale_22co11_1;

  OID ONAME PREVIOUS_BALANCE CUSTOMER
-----
   11 ord1             2000 Alex
   12 ord2             1000 Adam
   14 ord4             1000 Adam
   15 ord5             2000 Alex

SQL> select * from Sale_22co11;

  OID ONAME PREVIOUS_BALANCE CUSTOMER
-----
   11 ord1             2000 Alex
   12 ord2             1000 Adam
   14 ord4             1000 Adam
   15 ord5             2000 Alex
```

9. Create Sale(rollno)5 view for sale table containing all details of sale table. Use read only clause and test by using update statement.

```
SQL> create view Sale_22co11_5 as
  2 select * from Sale_22co11
  3 with READ ONLY;

View created.

SQL> update sale_22co11_5
  2 set oname='Caleb'
  3 where oid=14;
set oname='Caleb'
*
ERROR at line 2:
ORA-42399: cannot perform a DML operation on a read-only view
```

10. Drop view Sale(rollno)5

```
SQL> drop view sale_22co11_5;

View dropped.
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN
