

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
1 create view om as
2 select sch_departure_time from flights
3 where sch_departure_time = '2022-03-24 17:15:31'
4
5 create view next_week as
6 select sch_departure_time from flights
7 where sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
8
9 CREATE OR REPLACE VIEW top5_popular_routes AS
10 SELECT
11     f.departing_airport_id,
12     f.arriving_airport_id,
13     COUNT(DISTINCT b.booking_id) AS bookings_count
14 FROM booking b
15 JOIN booking_flight bf
16     ON b.booking_id = bf.booking_id
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 98 msec.

✓ Query returned successfully in 98 msec. ✕

Total rows: Query complete 00:00:00.098 CRLF Ln 1, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
1 create view om as
2 select sch_departure_time from flights
3 where sch_departure_time = '2022-03-24 17:15:31'
4
5 create view next_week as
6 select sch_departure_time from flights
7 where sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
8
9 CREATE OR REPLACE VIEW top5_popular_routes AS
10 SELECT
11     f.departing_airport_id,
12     f.arriving_airport_id,
13     COUNT(DISTINCT b.booking_id) AS bookings_count
14 FROM booking b
15 JOIN booking_flight bf
16     ON b.booking_id = bf.booking_id
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 55 msec.

✓ Query returned successfully in 55 msec. ✕

Total rows: Query complete 00:00:00.055 CRLF Ln 5, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
9 CREATE OR REPLACE VIEW top5_popular_routes AS
10 SELECT
11     f.departing_airport_id,
12     f.arriving_airport_id,
13     COUNT(DISTINCT b.booking_id) AS bookings_count
14 FROM booking b
15 JOIN booking_flight bf
16     ON b.booking_id = bf.booking_id
17 JOIN flights f
18     ON bf.flight_id = f.flight_id
19 GROUP BY
20     f.departing_airport_id,
21     f.arriving_airport_id
22 ORDER BY
23     bookings_count DESC
24 LIMIT 5;
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 45 msec.

✓ Query returned successfully in 45 msec. ✕

Total rows: Query complete 00:00:00.045 CRLF Ln 25, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
21 f.arriving_airport_id
22 ORDER BY
23 bookings_count DESC
24 LIMIT 5;
25
26
27 create view all_flights as
28 select a.airline_name, f.* from flights f
29 join airline a on f.airline_id = a.airline_id
30 where airline_name = 'Aero India'
31
32
33 create view all_flights_7days as
34 select a.airline_name, f.* from flights f
35 join airline a on f.airline_id = a.airline_id
36 where airline_name = 'Aero India' and sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 35 msec.

✓ Query returned successfully in 35 msec. ✕

Total rows: Query complete 00:00:00.035 CRLF Ln 27, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
28 select a.airline_name, f.* from flights f
29 join airline a on f.airline_id = a.airline_id
30 where airline_name = 'Aero India'
31
32
33 create view all_flights_7days as
34 select a.airline_name, f.* from flights f
35 join airline a on f.airline_id = a.airline_id
36 where airline_name = 'Aero India' and sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
37
38
39 create view delayed_24hours as
40 select * from flights
41 where act_departure_time - sch_departure_time >= interval '24 hours'
42
43
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 39 msec.

✓ Query returned successfully in 39 msec. ✕

Total rows: Query complete 00:00:00.039 CRLF Ln 33, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
29 join airline a on f.airline_id = a.airline_id
30 where airline_name = 'Aero India'
31
32
33 create view all_flights_7days as
34 select a.airline_name, f.* from flights f
35 join airline a on f.airline_id = a.airline_id
36 where airline_name = 'Aero India' and sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
37
38
39 create view delayed_24hours as
40 select * from flights
41 where act_departure_time - sch_departure_time >= interval '24 hours'
42
43
44 CREATE OR REPLACE VIEW skaboo_passengers AS
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 39 msec.

Total rows: Query complete 00:00:00.039 CRLF Ln 39, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
29 join airline a on f.airline_id = a.airline_id
30 where airline_name = 'Aero India'
31
32
33 create view all_flights_7days as
34 select a.airline_name, f.* from flights f
35 join airline a on f.airline_id = a.airline_id
36 where airline_name = 'Aero India' and sch_departure_time >= now() and sch_departure_time < now() + interval '7 days'
37
38
39 create view delayed_24hours as
40 select * from flights
41 where act_departure_time - sch_departure_time >= interval '24 hours'
42
43
44 CREATE OR REPLACE VIEW skaboo_passengers AS
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 39 msec.

Total rows: Query complete 00:00:00.039 CRLF Ln 39, Col 1

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
54
55
56 create view top10 as
57 CREATE OR REPLACE VIEW top10_visited_countries AS
58 SELECT
59     a.country,
60     COUNT(f.flight_id) AS arrival_count
61 FROM flights f
62 JOIN airport a
63     ON f.arriving_airport_id = a.airport_id
64 GROUP BY a.country
65 ORDER BY arrival_count DESC
66 LIMIT 10;
67
68
69 CREATE OR REPLACE VIEW top10_visited_countries AS
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 28 msec.

Total rows: Query complete 00:00:00.028 CRLF Ln 66, Col 10

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
67
68
69 CREATE OR REPLACE VIEW top10_visited_countries AS
70 SELECT
71     a.country,
72     COUNT(f.flight_id) AS arrival_count,
73     COUNT(DISTINCT a.airport_id) AS airport_count,
74     ROUND(COUNT(f.flight_id) * 1.0 / COUNT(DISTINCT a.airport_id),2) AS avg_arrivals_per_airport
75 FROM flights f
76 JOIN airport a
77     ON f.arriving_airport_id = a.airport_id
78 GROUP BY a.country
79 ORDER BY arrival_count DESC
80 LIMIT 10;
81
82 drop view if exists top10_visited_countries, skaboo_passengers, delayed_24hours, all_flights_7days, all_flights, top5_popular_routes, next_week, om
```

Data Output Messages Notifications

CREATE VIEW

Query returned successfully in 28 msec.

Total rows: Query complete 00:00:00.028 CRLF Ln 80, Col 10

pgAdmin 4

File Object Tools Edit View Window Help

Welcome db_course25/postgres@PostgreSQL 17* X

db_course25/postgres@PostgreSQL 17

No limit

Query Query History

```
67
68
69 CREATE OR REPLACE VIEW top10_visited_countries AS
70 SELECT
71     a.country,
72     COUNT(f.flight_id) AS arrival_count,
73     COUNT(DISTINCT a.airport_id) AS airport_count,
74     ROUND(COUNT(f.flight_id) * 1.0 / COUNT(DISTINCT a.airport_id),2) AS avg_arrivals_per_airport
75 FROM flights f
76 JOIN airport a
77     ON f.arriving_airport_id = a.airport_id
78 GROUP BY a.country
79 ORDER BY arrival_count DESC
80 LIMIT 10;
81
82 drop view if exists top10_visited_countries, skaboo_passengers, delayed_24hours, all_flights_7days, all_flights, top5_popular_routes, next_week, om
```

Data Output Messages Notifications

ЗАМЕЧАНИЕ: представление "top10_visited_countries" не существует, пропускается
ЗАМЕЧАНИЕ: представление "delayed_24hours" не существует, пропускается
DROP VIEW

Query returned successfully in 40 msec.

Total rows: Query complete 00:00:00.040 CRLF Ln 82, Col 148