parKVFinder Installation Guide

Download parKVFinder source code

On the terminal, go to the directory containing **KVFinder_linux_distribution.tar.gz**. Then, follow these steps:

- 1) Untar KVFinder linux distribution.tar.gz.
- \$ tar -zxvf KVFinder_linux_distribution.tar.gz
 - 2) Change working directory to KVFinder_linux folder (Note: folder will show after decompression)*.
- \$ cd KVFinder_linux
 - 3) Export $KVFinder_PATH$ variable and add to $\sim/.bashrc$ file.

```
$ export KVFinder_PATH=`pwd`
$ echo "export KVFinder_PATH=`pwd` >> ~/.bashrc
```

- 4) Recompile KVFinder.
- \$ make clean
- \$ make

PyMOL v1.8 Plug-in installation

A graphical interface is available to use KVFinder alongside PyMOL v1.8. To install the plug-in, follow these steps:

- 1) Open PyMOL v1.8
- 2) Go to Plugin menu \rightarrow Plugin Manager.
- 3) Plugin Manager window will open, go to Install New Plugin tab.
- 4) Under Install from local file Group, click in Choose file...
- 5) Install Plugin window will open, go to KVFinder_linux directory and select kvfinder_pymolplugin_linux.py.
- 6) Select plugin directory window will open, select /home/<user>/.pymol/startup and click OK.
- 7) Confirm window will open, click **OK**.
- 8) Sucess window will appear confirming that the plugin has been installed.
- 9) Restart PyMOL v1.8.
- 10) KVFinder plugin is ready to use.