

## ### parKVFinder Installation Guide

Follow these steps to install parKVFinder software on Linux or macOS.

1. Download parKVFinder source code:

Get the latest parKVFinder release from [here](#).

On the terminal, go to the directory containing *parKVFinder.zip* file.

```
$ unzip parKVFinder.zip
$ cd parKVFinder
```

Or, clone the *parKVFinder* repository into a new directory using `git`.

```
$ git clone https://github.com/LBC-LNBio/parKVFinder.git
$ cd parKVFinder
```

2. Export *KVFinder\_PATH* variable and add to `~/.bashrc` file or similar configuration file.

```
$ export KVFinder_PATH=`pwd`
$ echo "export KVFinder_PATH=`pwd`" >> ~/.bashrc
```

3. Compile parKVFinder from source.

Before compiling parKVFinder, check if `gcc` compiler version is equal or greater than 8. If not, check this guide to install earlier versions of `gcc` on Linux and macOS.

```
$ make
```

## PyMOL v1.8 Plug-in installation

A graphical interface is available to use KVFinder alongside PyMOL v1.8. To install the plug-in, follow these steps:

- 1) Open PyMOL v1.8
- 2) Go to **Plugin** menu → **Plugin Manager**.
- 3) **Plugin Manager** window will open, go to **Install New Plugin** tab.
- 4) Under **Install from local file** Group, click in **Choose file...**
- 5) **Install Plugin** window will open, go to **KVFinder\_linux** directory and select **kvfinder\_pymolplugin\_linux.py**.
- 6) **Select plugin directory** window will open, select `/home/<user>/.pymol/startup` and click **OK**.
- 7) **Confirm** window will open, click **OK**.
- 8) **Sucess** window will appear confirming that the plugin has been installed.
- 9) Restart PyMOL v1.8.
- 10) KVFinder plugin is ready to use.