



**AGH**

**AKADEMIA GÓRNICZO-HUTNICZA IM. STANISŁAWA STASZICA W KRAKOWIE**

**FACULTY OF COMPUTER SCIENCE, ELECTRONICS AND TELECOMMUNICATIONS**

DEPARTMENT OF COMPUTER SCIENCE

Master of Science Thesis

*Implementacja algorytmów dla systemów Monroe i  
Chamberlina-Couranta z nieliniową funkcją satysfakcji  
Implementation of algorithms for Monroe and Chamberlin-Courant  
systems under nonlinear satisfaction function*

Author:	<i>Piotr Szmigielski</i>
Degree programme:	<i>Computer Science</i>
Supervisor:	<i>Piotr Faliszewski, PhD</i>

Kraków, 2016

*Oświadczamy, świadomi odpowiedzialności karnej za poświadczenie nieprawdy, że niniejszą pracę dyplomową wykonaliśmy osobiście i samodzielnie (w zakresie wyszczególnionym we wstępie) i że nie korzystaliśmy ze źródeł innych niż wymienione w pracy.*

# Contents

<b>1. Introduction</b>	4
1.1. Results	5
<b>2. Preliminaries</b>	6
2.1. Basic Notions	6
2.2. Monroe and Chamberlin-Courant Rules	8
2.3. Approximate Solutions	8
<b>3. State of the Art</b>	9
<b>4. Implemented Algorithms</b>	10
4.1. Existing Algorithms	10
4.1.1. Algorithms A, B and C	10
4.1.2. Algorithm R	13
4.1.3. Algorithm AR	13
4.1.4. Algorithm GM	14
4.1.5. Algorithm P	14
4.2. New Algorithms	15
4.2.1. Genetic Algorithm	15
4.2.2. Simulated Annealing	16
<b>5. Evaluation Results</b>	18
<b>6. Summary</b>	19
<b>List of Tables</b>	20

# 1. Introduction

We study the effectiveness of algorithms for approximate winner determination under the Monroe [1] and Chamberlin-Courant [2] multiwinner voting rules using nonlinear satisfaction function. The purpose of both these rules is to select a group of candidates that best represent the voters. Having good voting rules and algorithms for them is important, because multiwinner elections are used both in human societies (e.g., for parliament elections) and particular software systems (e.g., in recommendation systems [3]). Rules studied in this paper are exceptionally interesting because they have two desired features of multiwinner rules: they provide accountability (there is a direct connection between the elected candidates and the voters, so each voter has a representative assigned to her and each candidate knows who she represents) and proportional representation of the voters' views.

We assume that candidates participate in the election with multiple winners (a committee with multiple members is selected) and they are elected by voters, each of whom ranks all the candidates (each voter provides a linear order over the set of candidates expressing her preferences). For each voter the Monroe and Chamberlin-Courant rules assign a single candidate as her representative (with some constraints, which are detailed in the further part of the thesis).

The candidates are selected and assigned to the voters optimally, by maximizing the total satisfaction of all the voters. The total satisfaction is calculated as a sum of individual satisfactions of the voters. We assume that there is a satisfaction function that measures how well a voter is represented by the candidate. The function is the same for each voter. It is a decreasing function, so a voter is more satisfied if the candidate assigned to her is ranked higher. In this thesis we study cases in which the satisfaction function is a nonlinear one.

Monroe and Chamberlin-Courant systems may be potentially very useful, because they are one of the few multiwinner election systems that provide both accountability and proportional results. Most of the currently used voting rules lack at least one of these properties. For example, D'Hondt method used to elect members of Polish lower house of parliament lacks accountability (specific parliament members are accountable to the political parties, not to the voters), while single-member constituency plurality system used for United Kingdom parliament elections lacks proportionality.

The main drawback of the aforementioned rules is that their winner determination problems are NP-hard [4, 3, 5] which makes them hard to use in practice, as it would force the use of algorithms that do not provide an optimal result for every data set. Therefore, using these systems for real-life elections may rise some difficulties. However, they can be used for the recommendation systems conveniently,

as a good but not optimal recommendation is still useful. Lu and Boutilier [3] and Skowron et al. [6] provided approximation algorithms for both the rules that return near-optimal results for various test cases (including real-life data and synthetic data), but for linear satisfaction functions only.

In this thesis we focus on providing several algorithms for the Monroe and Chamberlin-Courant rules using nonlinear satisfaction functions and evaluating them empirically against various data sets. For smaller data, results can be easily assessed by comparing them to the optimal result (calculated with the brute-force algorithm). For bigger data, the upper bound of the optimal result must be used for comparison. As finding optimal solution is NP-hard [4, 3, 5], there is a need to provide good algorithms which can compute results that are suboptimal, but still as close to optimal as possible. We implement and evaluate various heuristic algorithms, as well as the existing approximation algorithms for the linear satisfaction function, but applying them to the nonlinear cases.

Skowron et. al [6] have already provided approximation algorithms for these systems, but only under linear satisfaction function. In this thesis we focus on providing algorithms for non-linear satisfaction functions, as they can better reflect real preferences of the voters.

## 1.1. Results

TODO

## 2. Preliminaries

In the first part of this chapter we explain basic notions regarding multiwinner elections. Next, we present definitions of winner determination problems under Monroe and Chamberlin-Courant (abbreviated as CC) voting rules. Finally, we present some notions regarding approximation algorithms for these tasks.

### 2.1. Basic Notions

In these section we present essential definitions and notions concerning multiwinner elections.

**Definition 1: Preferences. [6]** Let's assume we have  $n$  agents (representing voters in the elections) and  $m$  alternatives (representing candidates in the elections). For each agent  $i$ , her *preference order* is a strict linear order  $\succ_i$  over all the alternatives that ranks them from the most to the least desirable one. Collection  $V$  of the preference orders of all the agents is called a *preference profile*.

If  $A$  is the set of all the alternatives and  $B$  is a nonempty strict subset of  $A$ , then by  $B \succ A - B$  we mean that all alternatives in  $B$  are preferred to those outside of  $B$  for the preference order  $\succ$ .

**Definition 2: Positional scoring function. [6]** Let's assume we have  $m$  alternatives. A function  $\alpha^m : \{1, \dots, m\} \rightarrow \mathbb{N}$  that assigns an integer value to each position in the agent's preference order is called a *positional scoring function* (PSF).

If  $\alpha^m$  is a decreasing function (for each  $i, j \in \{1, \dots, m\}, i > j \implies \alpha^m(i) < \alpha^m(j)$ ), it is called a *decreasing positional scoring function* (DPSF) and it can represent an agent's satisfaction when an alternative from a particular position in her preference order is elected. For every DPSF  $\alpha^m(m) = 0$ , so an agent is not satisfied at all with her worst alternative. In some cases, we will write  $\alpha$  instead of  $\alpha^m$  to simplify notation.

A DPSF  $\alpha^m$  is considered a *linear satisfaction function* if for each  $i \in \{1, \dots, m - 1\}$  value  $\alpha^m(i + 1) - \alpha^m(i)$  is constant. Every DPSF not satisfying that constraint is considered a *nonlinear*

*satisfaction function.*

We define a family  $\alpha$  of DPSFs as  $\alpha = (\alpha^m)_{m \in \mathbb{N}}$ , where  $\alpha^m$  is a DPSF on  $\{1, \dots, m\}$ , such that  $\alpha^{m+1}(i+1) = \alpha^m(i)$  for all  $m \in \mathbb{N}$  and  $i \in \{1, \dots, m\}$ . Families of DPSFs are built iteratively by prepending values to functions with smaller domains (smaller  $m$ ), leaving existing values from the previous function (previous family member) unchanged. Such families of DPSFs are called *normal* DPSFs.

**Definition 3: Assignment functions. [6]** Let's assume we have  $n$  agents and  $m$  alternatives. Let  $B$  be a set of all the agents ( $B = \{1, \dots, n\}$ ). A  $K$ -assignment function  $\Phi : B \rightarrow \{a_1, \dots, a_m\}$  is a function that assigns a single alternative to every agent in such way, that no more than  $K$  alternatives are selected ( $\|\Phi(B)\| \leq K$ ). It is called a *Monroe  $K$ -assignment function* if it additionally satisfies the following constraint: For each alternative  $a$  we have that either  $\left\lfloor \frac{\|B\|}{K} \right\rfloor \leq \|\Phi^{-1}(a)\| \leq \left\lceil \frac{\|B\|}{K} \right\rceil$  or  $\|\Phi^{-1}(a)\| = 0$ . It means that for Monroe  $K$ -assignment function, agents are assigned to exactly  $K$  alternatives and each of the alternatives has about  $\frac{\|B\|}{K}$  agents assigned. If we have an assignment function  $\Phi$ , alternative  $\Phi(i)$  is called the *representative* of agent  $i$ .

Additionally, if we allow the  $K$ -assignment function to assign an empty alternative ( $\perp$ ) to the agents, it is called a *partial  $K$ -assignment function*. It is also a *partial Monroe  $K$ -assignment function* if it can be extended to a regular Monroe  $K$ -assignment function by replacing all the empty alternatives with the regular alternatives ( $\{a_1, \dots, a_m\}$ ).

Let  $S$  be a set of alternatives. By  $\Phi^S$  we mean a  $K$ -assignment function (or a partial  $K$ -assignment function) that assigns agents only to alternatives from  $S$ .

**Definition 4: Total satisfaction function. [6]** We assume that  $\alpha$  is a normal DPSF and  $pos_i(x)$  represents position of alternative  $x$  in the  $i$ 'th agent's preference order. Following function assigns a positive integer to a given assignment  $\Phi$ :

$$l_{sum}^\alpha(\Phi) = \sum_{i=1}^n \alpha(pos_i(\Phi(i))) \quad (2.1)$$

This function combines satisfaction of the agents to assess the quality of the assignment for the entire society. It simply calculates the sum of the individual agents' satisfaction value and is used as the *total satisfaction function*.

For each subset of the alternatives  $S \subseteq A$  that satisfies  $\|S\| \leq K$ , by  $\Phi_\alpha^S$  we mean the partial  $K$ -assignment (or the partial Monroe  $K$ -assignment) that assigns agents only to the alternatives from  $S$  and such that  $\Phi_\alpha^S$  maximizes the total satisfaction  $l_{sum}^\alpha(\Phi_\alpha^S)$ .

## 2.2. Monroe and Chamberlin-Courant Rules

We will now define the problems of winner determination under the Monroe and CC rules. The goal is to find an optimal assignment function, where by the optimal function we accept one that maximizes the total satisfaction.

**Definition 5: Chamberlin-Courant and Monroe problems. [6]** Let's assume we have  $n$  agents,  $m$  alternatives, preference profile  $V$ ,  $K \in \mathbb{N}$  ( $K < m$ ) representing committee size and a normal DPSF  $\alpha$ . The goal of the *Chamberlin-Courant problem* is to find a  $K$ -assignment function  $\Phi$  for which the total satisfaction  $l_{sum}^\alpha(\Phi)$  is maximal under preference profile  $V$ . The goal of the *Monroe problem* is similar, but it searches for a Monroe  $K$ -assignment function instead.

Intention of solving these problems is to find a (Monroe)  $K$ -assignment function which returns a set of  $K$  alternatives, who are viewed as the winners of the given multiwinner election (e.g. elected members of a committee).

## 2.3. Approximate Solutions

As for many normal DPSFs multiwinner election problems under both Monroe and CC rules are NP-hard [4, 3, 5], we are looking for approximate solutions.

**Definition 6: Approximation algorithms. [6]** Let  $r$  be a real number such that  $0 < r \leq 1$ , let  $\alpha$  be a normal DPSF. An algorithm is an  *$r$ -approximation algorithm* for CC or Monroe problem if for every correct input it returns an assignment  $\Phi$  such that  $l_{sum}^\alpha(\Phi) \geq r \cdot s_{max}$ , where  $s_{max}$  is the optimal total satisfaction  $l_{sum}^\alpha(\Phi_{max})$ .



### 3. State of the Art

The Chamberlin-Courant and Monroe multiwinner voting rules were introduced by Chamberlin and Courant [2] and Monroe [1] respectively. Despite having desired properties of multiwinner rules when we want to achieve a proportional representation [7], there has not been much research regarding these systems yet.

Complexity of both the systems was studied in the several papers and the conclusion is that they are both NP-hard in general case. Procaccia et al. [5] showed that these systems are NP-hard in the dissatisfaction-based framework in case of approval dissatisfaction function, Lu and Boutilier [3] presented Chamberlin-Courant rule hardness under linear satisfaction function, while Betzler et al. [4] studied the parameterized complexity of the rules. There were also papers that studied the complexity for some specific cases where preferences are either single-peaked (Yu et al. [8]) or single-crossing (Skowron et al. [9]).

Lu and Boutilier [3] were the first to study the approximability of the Chamberlin-Courant rule under linear satisfaction function, they presented an approximation algorithm for this case. Skowron et al. [6] gave more approximation algorithms for both the Monroe and Chamberlin-Courant rules (for the linear satisfaction function) and assessed their effectiveness against various data sets, but there is no work showing results for any nonlinear satisfaction function.

## 4. Implemented Algorithms

In this chapter we present implemented algorithms for the utilitarian versions of Monroe and Chamberlin-Courant multiwinner voting rules in the satisfaction-based framework.

**Proposition 1 (Implicit in the paper of Betzler et al. [4]).** Let  $\alpha$  be a normal DPSF,  $N$  be a set of agents,  $A$  be a set of alternatives,  $V$  be a preference profile of  $N$  over  $A$ , and  $S$  a  $K$ -element subset of  $A$  (where  $K$  divides  $\|N\|$ ). Then there is a polynomial-time-algorithm that computes a (possibly partial) optimal  $K$ -assignment  $\Phi_\alpha^S$  (Monroe  $K$ -assignment  $\Phi_\alpha^S$ ) of the agents to the alternatives from  $S$ .

### 4.1. Existing Algorithms

In this section we present algorithms that already exist, but have never been applied to nonlinear cases before.

#### 4.1.1. Algorithms A, B and C

Algorithm A was first presented by Skowron et al. [6] and tries to solve Monroe problem. It is a greedy algorithm that executes  $K$  iterations (where  $K$  is a size of the elected committee). In every iteration algorithm selects an alternative  $a_i$  that has not been assigned yet and assigns it to  $\frac{N}{K}$  of the remaining agents whose satisfaction of being assigned to  $a_i$  is maximal (criterion for picking an alternative in each step is a sum of satisfaction of  $\frac{N}{K}$  agents selected this way). This algorithm runs in polynomial time [6]. Pseudocode is presented in Algorithm 1.

Algorithm B is an extension to Algorithm A and was presented in the same paper. [6] In the first step, Algorithm B simply executes Algorithm A. Next, it uses algorithm from Proposition 1 to optimally assign alternatives from the winners set to the agents. As both the utilized algorithms run in polynomial time, so does Algorithm B.

Algorithm C is a further extension to Algorithm B, also presented by Skowron et al. [6]. While Algorithm B only keeps one partial assignment function  $\Phi$  that is extended in each step until it

**Algorithm 1** Algorithm A

---

```

1: procedure COMPUTEMONROEPROBLEMSOLUTION
2:    $\Phi \leftarrow$  a map defining a partial assignment, iteratively built by the algorithm
3:    $\Phi^{\leftarrow} \leftarrow$  the set of agents for which the assignment is already defined
4:    $\Phi^{\rightarrow} \leftarrow$  the set of alternatives already used in the assignment
5:    $\Phi = \{\}$ 
6:   for  $i \leftarrow 1$  to  $K$  do
7:      $score \leftarrow \{\}$ 
8:      $bests \leftarrow \{\}$ 
9:     for all  $a_i \in A \setminus \Phi^{\rightarrow}$  do
10:       $agents \leftarrow$  sort  $N \setminus \Phi^{\leftarrow}$  so that if agent  $j$  preceeds agent  $j'$  then  $pos_j(a_i) \leq pos_{j'}(a_i)$ 
11:       $bests[a_i] \leftarrow$  choose first  $\frac{N}{K}$  elements from  $agents$ 
12:       $score[a_i] \leftarrow \sum_{j \in bests[a_i]} (m - pos_j(a_i))$ 
13:       $a_{best} \leftarrow \operatorname{argmax}_{a \in A \setminus \Phi^{\rightarrow}} score[a]$ 
14:      for all  $j \in bests[a_{best}]$  do
15:         $\Phi[j] \leftarrow a_{best}$ 

```

---

becomes a complete solution, Algorithm C stores a list of  $d$  functions ( $d$  is provided as an algorithm parameter). In each step, for each alternative  $a$  with no agent assigned and for each  $\Phi$  of the  $d$  functions stored, algorithm computes a greedy extension to  $\Phi$  that assigns  $\frac{N}{K}$  agents (that are not assigned to any other alternative yet) to  $a$  (the same way as in Algorithm A). For the next step,  $d$  functions that return the highest satisfaction are used. Finally, after the last iteration, winners are reassigned using algorithm from Preposition 1 in each of the stored functions. Function that gives the highest satisfaction is selected. If  $d = 1$ , Algorithm C is identical with Algorithm B. Pseudocode is presented in Algorithm 3.

Unlike previous algorithms, Algorithm C can be used for both Monroe and Chamberlin-Courant rules. To adapt it to the Chamberlin-Courant rule, we have to replace the entire first for all loop with the appropriate code, presented in Algorithm 2.

**Algorithm 2** Algorithm C - CC for all code replacement

---

```

1: for all  $a_i \in A \setminus \Phi^{\rightarrow}$  do
2:    $\Phi' \leftarrow \Phi$ 
3:   for all  $j \in N$  do
4:     if agent  $j$  prefers  $a_i$  to  $\Phi'(j)$  then
5:        $\Phi'(j) \leftarrow a_i$ 
6:    $newPar.push(\Phi')$ 

```

---

**Algorithm 3** Algorithm C

---

```

1: procedure COMPUTEMONROEPROBLEMSOLUTION
2:    $\Phi \leftarrow$  a map defining a partial assignment, iteratively built by the algorithm
3:    $\Phi^{\leftarrow} \leftarrow$  the set of agents for which the assignment is already defined
4:    $\Phi^{\rightarrow} \leftarrow$  the set of alternatives already used in the assignment
5:    $Par \leftarrow$  a list of partial representation functions
6:    $Par = []$ 
7:    $Par.push(//)$ 
8:   for  $i \leftarrow 1$  to  $K$  do
9:      $newPar = []$ 
10:    for  $\Phi \in Par$  do
11:       $bests \leftarrow \{\}$ 
12:      for all  $a_i \in A \setminus \Phi^{\rightarrow}$  do
13:         $agents \leftarrow$  sort  $N \setminus \Phi^{\leftarrow}$  (agent  $j$  preceeds agent  $j'$  implies that  $pos_j(a_i) \leq pos_{j'}(a_i)$ )
14:         $bests[a_i] \leftarrow$  choose first  $\frac{N}{K}$  elements of  $agents$ 
15:         $\Phi' \leftarrow \Phi$ 
16:        for all  $j \in bests[a_i]$  do
17:           $\Phi'[j] \leftarrow a_i$ 
18:         $newPar.push(\Phi')$ 
19:      sort  $newPar$  according to descending order of the total satisfaction of the assigned agents
20:       $Par \leftarrow$  choose first  $d$  elements of  $newPar$ 
21:    for  $\Phi \in Par$  do
22:       $\Phi \leftarrow$  compute the optimal representative function using an algorithm of Betzler et al. [4] for
        the set of winners  $\Phi^{\rightarrow}$ 
23:    return the best representative function from  $Par$ 

```

---

### 4.1.2. Algorithm R

As shown by Skowron et al. [6], algorithms A, B and C are potentially very useful when size of the committee is much lower than the number of alternatives ( $K$  is small compared to  $m$ ), as under this condition they produce results with very high approximation ratio under linear satisfaction function. For the other cases (relatively large committee), a sampling-based randomized algorithm may be used. We call it Algorithm R. We expect that under nonlinear satisfaction function algorithms should behave similarly in relation to each other as under a linear one.

Algorithm R randomly picks  $K$  alternatives and then, using Proposition 1, assigns them to agents optimally. As a single execution of such an algorithm may simply pick only alternatives that are ranked low, random assignment should be computed a given number of times (which is provided as an algorithm parameter), so there is a greater probability to attain a high quality solution. If size of the committee is only slightly lower than the number of alternatives ( $K$  is comparable to  $m$ ) then the probability of finding a solution that is at least close to optimal is high [6]. Algorithm can naturally be used for both Monroe and Chamberlin-Courant systems.

### 4.1.3. Algorithm AR

Algorithm family A-C and Algorithm R are naturally suitable for different cases. Therefore, Skowron et al. [6] proposed to combine algorithms A and R into Algorithm AR. They also showed that under linear satisfaction function, Algorithm AR can achieve approximation ratio of  $0.715 - e$  with probability  $\lambda$ . Both  $e$  and  $\lambda$  are provided as algorithm parameters. Naturally, for different satisfaction functions approximation ratio may vary, but we decided to test the algorithm in an unchanged version for comparison. Pseudocode is presented in Algorithm 4.

---

#### Algorithm 4 Algorithm AR

---

```

1: procedure COMPUTEMONROEPROBLEMSOLUTION
2:    $H_j$  is the  $j$ 'th harmonic number  $H_j = \sum_{i=1}^j (\frac{1}{i})$ 
3:    $\lambda \leftarrow$  probability of achieving the approximation ratio  $0.715 - e$  under linear satisfaction function
4:   if  $\frac{H_K}{K} \geq \frac{e}{2}$  then
5:     compute the optimal solution using an algorithm of Betzler et al. [4] and return
6:   if  $m \leq 1 + \frac{2}{e}$  then
7:     compute the optimal solution using a simple brute force algorithm and return
8:    $\Phi_1 \leftarrow$  solution computed by Algorithm A
9:    $\Phi_2 \leftarrow$  solution computed by Algorithm R (sampled  $\log(1 - \lambda) \cdot \frac{2+e}{e}$  times)
10:  return the better assignment among  $\Phi_1$  and  $\Phi_2$ 

```

---

#### 4.1.4. Algorithm GM

Algorithm GM (greedy marginal improvement) is an algorithm that was introduced by Lu and Boutilier [3] for the Chamberlin-Courant rule only. However, it was later generalized by Skowron et al. [6], so it can be applied to the Monroe rule as well. In the Monroe case, it can be considered as the Algorithm B improvement.

Algorithm starts with an empty set  $S$ . In each iteration of the algorithm an alternative  $a$  ( $a \notin S$ ) is selected and added to  $S$ . Selected  $a$  maximizes the satisfaction value  $l_{sum}^\alpha(\Phi_\alpha^{S \cup \{a\}})$ . Iterations are executed until a complete committee is selected, so  $K$  iterations are required. For Monroe case, computing  $\Phi_\alpha^S$  is slow (it is achieved by using min-cost/max-flow algorithm [4]), which makes the algorithm execute for a relatively long time, as many computations are required. Pseudocode is presented in Algorithm 5.

---

#### Algorithm 5 Algorithm GM

---

```

1: procedure COMPUTECCORMONROEPROBLEMSOLUTION
2:    $\Phi_\alpha^S$  - the partial assignment that assigns a single alternative to at most  $\frac{n}{K}$  agents, that assigns to
      the agents only the alternatives from  $S$ , and that maximizes the utilitarian satisfaction  $l_{sum}^\alpha(\Phi_\alpha^S)$ 
3:    $S \leftarrow \emptyset$ 
4:   for  $i \leftarrow 1$  to  $K$  do
5:      $a \leftarrow \operatorname{argmax}_{a \in A \setminus S} l_{sum}^\alpha(\Phi_\alpha^{S \cup \{a\}})$ 
6:      $S \leftarrow S \cup \{a\}$ 
7:   return  $\Phi_\alpha^S$ 

```

---

#### 4.1.5. Algorithm P

Algorithm P can only be applied to Chamberlin-Courant problem. It was first introduced by Skowron et al. [6]. In the beginning, it computes  $x$  (a non-negative integer). Next, it computes an assignment that should maximize the number of agents that have an alternative from the first  $x$  spots in their preferences assigned to them. This process is executed greedily. Afterwards, if there are still agents with no alternative assigned, the best alternative is picked from the ones already selected for at least one other agent.

$w(x)$  used in the algorithm is a Lambert's W-function, defined to be the solution of the equation  $x = w(x)e^{w(x)}$ . Algorithm runs in polynomial time. Pseudocode of Algorithm P is presented in Algorithm 6.

**Algorithm 6** Algorithm P

---

```

1: procedure COMPUTECCPROBLEMSOLUTION
2:    $\Phi \leftarrow$  a map defining a partial assignment, iteratively built by the algorithm
3:    $\Phi^{\leftarrow} \leftarrow$  the set of agents for which the assignment is already defined
4:    $\Phi^{\rightarrow} \leftarrow$  the set of alternatives already used in the assignment
5:    $num\_pos_x(a) \leftarrow \|\{i \in [n] \setminus \Phi^{\leftarrow} : pos_i(a) \leq x\}\|$  - the number of not-yet assigned agents that
      rank alternative  $a$  in one of their first  $x$  positions
6:    $w(\cdot)$  - Lambert's W-function
7:    $\Phi = \{\}$ 
8:    $x = \left\lceil \frac{mw(K)}{K} \right\rceil$ 
9:   for  $i \leftarrow 1$  to  $K$  do
10:      $a_i \leftarrow argmax_{a \in A \setminus \Phi^{\rightarrow}} num\_pos_x(a)$ 
11:     for all  $j \in [n] \setminus \Phi^{\leftarrow}$  do
12:       if  $pos_j(a_i) < x$  then
13:          $\Phi[j] \leftarrow a_i$ 
14:     for all  $j \in A \setminus \Phi^{\leftarrow}$  do
15:        $a \leftarrow$  such alternative from  $\Phi^{\rightarrow}$  that  $\forall a' \in \Phi^{\rightarrow} pos_j(a) \leq pos_j(a')$ 
16:        $\Phi[j] \leftarrow a$ 
17:   return  $\Phi$ 

```

---

## 4.2. New Algorithms

In this section we present algorithms that have been invented and implemented specifically for the purpose of this thesis.

### 4.2.1. Genetic Algorithm

The idea of our algorithm is loosely based on metaheuristic genetic algorithms [10], such as the Firefly Algorithm [10, 11].

Our Genetic Algorithm starts with an initial set of creatures (each of them presenting a set of possible winners under Chamberlin-Courant or Monroe rule) which are later mutated and crossed over with each other. The best creatures (ones with the highest total satisfaction) are preferred for further mutation and crossover in order to better investigate the neighbourhood of local maxima, but on the other hand algorithm also produces new creatures by crossing over random existing ones to better explore the entire solution space, not limiting to local extrema.

In each iteration of the algorithm creatures are evaluated (winners are assigned using algorithm from Proposition 1 and satisfaction is computed). Best creature in terms of total satisfaction is compared with

currently best found creature and takes its place if it is better. Half of the evaluated creatures (the best ones) are chosen for further propagation. Each of them is then mutated randomly. Remaining creatures are created by crossing over random creatures from the "better" half with each other. Resulting set of creatures is used for the next iteration. Number of iterations and number of creatures are the algorithm parameters. Pseudocode is presented in Algorithm 7.

---

**Algorithm 7** Genetic Algorithm
 

---

```

1: procedure COMPUTECCORMONROEPROBLEMSOLUTION
2:    $I$  - number of iterations
3:    $c$  - number of creatures
4:    $\Phi_{best}$  - best creature (preference profile)
5:    $creatures \leftarrow$  generate initial random set of  $c$  creatures
6:   for  $i \leftarrow 1$  to  $I$  do
7:      $creaturesSorted \leftarrow$  sort  $creatures$  by total satisfaction
8:     if  $satisfaction(creaturesSorted[1]) > satisfaction(\Phi_{best})$  then
9:        $\Phi_{best} = creaturesSorted[1]$ 
10:     $bestCreatures \leftarrow$  choose first  $c/2$  elements from  $creaturesSorted$ 
11:     $mutated \leftarrow$  mutate all creatures from  $bestCreatures$  randomly
12:     $crossed \leftarrow$  crossover random creatures from  $bestCreatures$  to produce  $c/2$ -element set
13:     $newCreatures \leftarrow mutated \cup crossed$ 
14:     $creatures \leftarrow newCreatures$ 
15:  return  $\Phi_{best}$ 

```

---

#### 4.2.2. Simulated Annealing

The Simulated Annealing algorithm is inspired by physical annealing process, used in metallurgy. It involves heating and cooling a material to make it attain specific physical properties. Using simulated annealing for optimization of a complex function depending on many parameters was proposed by Kirkpatrick et al. [12]. We adapt it to the Chamberlin-Courant and Monroe problems.

In simulated annealing we use a temperature variable, which has a high value at the beginning and gets lower ('cools') during the execution. When the temperature is high, algorithm can accept solutions worse than the current one more frequently, so it is possible to leave a local optimum, as the global one may be in totally different area of the search space. When the temperature gets lower, algorithm focuses on the area where solution close to the optimum may lie.

To decide if the new solution should be accepted, the *acceptance function* is used. If the new solution is better, it is always accepted. If it is worse, acceptance function accepts the new solution with probability



$p$ , which is calculated as follows:

$$p = \exp\left(\frac{E_c - E_n}{T}\right) \quad (4.1)$$

$E_c$  is the current solution energy,  $E_n$  is the new solution energy and  $T$  is the temperature. Energy represents quality of the solution and, in our case, is proportional to the total satisfaction value of the solution.

The algorithm proceeds as follows. First, it generates a random initial set of winners. Initial temperature is given as a parameter. Then, in each iteration, a new solution is generated by replacing one of the winners in the current solution with a random alternative that is not a winner in the current solution (every time winners are assigned to agents using algorithm from Proposition 1). The newly created solution is then evaluated by the acceptance function. If it is accepted, it replaces the current solution. Otherwise, the current solution is kept. For the next iteration, temperature is decreased:

$$T \leftarrow T \cdot (1 - c) \quad (4.2)$$

$c$  is the cooling rate, provided as an algorithm parameter. The algorithm stops when  $T \leq 1$ . Pseudocode is presented in Algorithm 8.

---

**Algorithm 8** Simulated Annealing

---

```

1: procedure COMPUTECCORMONROEPROBLEMSOLUTION
2:    $T_{start}$  - initial temperature
3:    $c$  - cooling rate
4:    $\Phi_{curr}$  - current solution
5:    $T$  - current temperature
6:    $E(\Phi)$  - energy of solution  $\Phi$ 
7:    $\Phi_{curr} \leftarrow$  generate initial random solution
8:    $T \leftarrow T_{start}$ 
9:   while  $T > 1$  do
10:     $\Phi_{new} \leftarrow$  perform random replacement on  $\Phi_{curr}$ 
11:     $p \leftarrow \exp\left(\frac{E(\Phi_{curr}) - E(\Phi_{new})}{T}\right)$ 
12:     $r \leftarrow$  generate random number in range  $[0; 1)$ 
13:    if  $E(\Phi_{new}) > E(\Phi_{curr})$  or  $p > r$  then
14:       $\Phi_{curr} \leftarrow \Phi_{new}$ 
15:       $T \leftarrow T \cdot (1 - c)$ 
16:   return  $\Phi_{curr}$ 

```

---

# **5. Evaluation Results**

## **6. Summary**

## References

- [1] B. Monroe. Fully proportional representation. *American Political Science Review*, 89(4):925–940, 1995.
- [2] B. Chamberlin and P. Courant. Representative deliberations and representative decisions: Proportional representation and the borda rule. *American Political Science Review*, 77(3):718–733, 1983.
- [3] T. Lu and C. Boutilier. Budgeted social choice: From consensus to personalized decision making. *IJCAI*, 11:280–286, 2011.
- [4] N. Betzler, A. Slinko, and J. Uhlmann. On the computation of fully proportional representation. *Journal on Artificial Intelligence Research*, 47:475–519, 2013.
- [5] A.D. Procaccia, J.S. Rosenschein, and A. Zohar. On the complexity of achieving proportional representation. *Social Choice and Welfare*, 30(3):353–362, April 2008.
- [6] P. Skowron, P. Faliszewski, and A. Slinko. Achieving fully proportional representation, approximability results. *Artificial Intelligence*, 222:67–103, May 2015.
- [7] E. Elkind, P. Faliszewski, P. Skowron, and A. Slinko. Properties of multiwinner voting rules. *Proceedings of the 13th International Conference on Autonomous Agents and Multiagent Systems*, pages 53–60, May 2014.
- [8] L. Yu, H. Chan, and E. Elkind. Multiwinner elections under preferences that are single-peaked on a tree. *Proceedings of IJCAI-13*, pages 425–431, 2013.
- [9] P. Skowron, L. Yu, P. Faliszewski, and E. Elkind. The complexity of fully proportional representation for single-crossing electorates. *Proceedings of the 6th International Symposium on Algorithmic Game Theory*, pages 1–12, October 2013.
- [10] X.S. Yang. *Nature-inspired Metaheuristic Algorithms*. Luniver Press, 2010.
- [11] S. Łukasik and S. Żak. Firefly algorithm for continuous constrained optimization. *Lecture Notes in Artificial Intelligence*, 5796:97–106, 2009.
- [12] S. Kirkpatrick, C.D. Gelatt, and M. Vecchi. Optimization by simulated annealing. *Science*, 220:671–680, 1983.

## List of Tables