SQL CheatSheet

The Complete SQL Cheat Sheet

1. DDL Commands

Data Definition Language - Defining and optimizing database structure.

Command	Description	Syntax	Example
CREATE	The CREATE command creates a new database and objects, such as a table, index, view, or stored procedure.	`CREATE TABLE table_name (column1 datatype1, column2 datatype2, ...);`	`CREATE TABLE employees (employee_id INT PRIMARY KEY, first_name VARCHAR(50), last_name VARCHAR(50), age INT);`
ALTER	The ALTER command adds, deletes, or modifies columns in an existing table.	`ALTER TABLE table_name ADD column_name datatype;`	`ALTER TABLE customers ADD email VARCHAR(100);`
DROP	The DROP command is used to drop an existing table in a database.	`DROP TABLE table_name;`	`DROP TABLE customers;`
TRUNCATE	The TRUNCATE command is used to delete the data inside a table, but not the table itself.	`TRUNCATE TABLE table_name;`	`TRUNCATE TABLE customers;`

2. DML Commands

Data Manipulation Language Commands - Manipulating data rows.

Command	Description	Syntax	Example
SELECT	The SELECT command retrieves data from a database.	`SELECT column1, column2 FROM table_name;`	`SELECT first_name, last_name FROM customers;`

elvischristian283@gmail.com

INSERT	The INSERT command adds new records to a table.	`INSERT INTO table_name (column1, column2) VALUES (value1, value2);`	`INSERT INTO customers (first_name, last_name) VALUES ('Mary', 'Doe');`
UPDATE	The UPDATE command is used to modify existing records in a table.	`UPDATE table_name SET column1 = value1, column2 = value2 WHERE condition;`	`UPDATE employees SET employee_name = 'John Doe', department = 'Marketing';`
DELETE	The DELETE command removes records from a table.	`DELETE FROM table_name WHERE condition;`	`DELETE FROM employees WHERE employee_name = 'John Doe';`

3. Querying Data Commands

Command	Description	Syntax	Example
SELECT Statement	The SELECT statement is the primary command used to retrieve data from a database	`SELECT column1, column2 FROM table_name;`	`SELECT first_name, last_name FROM customers;`
WHERE Clause	The WHERE clause is used to filter rows based on a specified condition.	`SELECT * FROM table_name WHERE condition;`	`SELECT * FROM customers WHERE age > 30;`
ORDER BY Clause	The ORDER BY clause is used to sort the result set in ascending or descending order based on a specified column.	`SELECT * FROM table_name ORDER BY column_name ASC|DESC;`	`SELECT * FROM products ORDER BY price DESC;`
GROUP BY Clause	The GROUP BY clause groups rows based on the values in a specified column. It is often used with aggregate functions like COUNT, SUM, AVG, etc.	`SELECT column_name, COUNT(*) FROM table_name GROUP BY column_name;`	`SELECT category, COUNT(*) FROM products GROUP BY category;`
HAVING Clause	The HAVING clause filters grouped results based on a specified condition.	`SELECT column_name, COUNT(*) FROM table_name GROUP BY column_name HAVING condition;`	`SELECT category, COUNT(*) FROM products GROUP BY category HAVING COUNT(*) > 5;`

elvischristian283@gmail.com

4. Aggregate Functions Commands

Command	Description	Syntax	Example
COUNT()	The COUNT command counts the number of rows or non-null values in a specified column.	`SELECT COUNT(column_name) FROM table_name;`	`SELECT COUNT(age) FROM employees;`
SUM()	The SUM command is used to calculate the sum of all values in a specified column.	`SELECT SUM(column_name) FROM table_name;`	`SELECT SUM(revenue) FROM sales;`
AVG()	The AVG command is used to calculate the average (mean) of all values in a specified column.	`SELECT AVG(column_name) FROM table_name;`	`SELECT AVG(price) FROM products;`
MIN()	The MIN command returns the minimum (lowest) value in a specified column.	`SELECT MIN(column_name) FROM table_name;`	`SELECT MIN(price) FROM products;`
MAX()	The MAX command returns the maximum (highest) value in a specified column.	`SELECT MAX(column_name) FROM table_name;`	`SELECT MAX(price) FROM products;`

5. Joining Commands

Command	Description	Syntax	Example
INNER JOIN	The INNER JOIN command returns rows with matching values in both tables.	`SELECT * FROM table1 INNER JOIN table2 ON table1.column = table2.column;`	`SELECT * FROM employees INNER JOIN departments ON employees.department_id = departments.id;`
LEFT JOIN/LEFT OUTER JOIN	The LEFT JOIN command returns all rows from the left table (first table) and the matching rows from the right	`SELECT * FROM table1 LEFT JOIN table2 ON table1.column = table2.column;`	`SELECT * FROM employees LEFT JOIN departments ON employees.department_id = departments.id;`

elvischristian283@gmail.com

	table (second table).		
RIGHT JOIN/RIGHT OUTER JOIN	The RIGHT JOIN command returns all rows from the right table (second table) and the matching rows from the left table (first table).	`SELECT * FROM table1 RIGHT JOIN table2 ON table1.column = table2.column;`	`SELECT * FROM employees RIGHT JOIN departments ON employees.department_id = departments.department_id;`
FULL JOIN/FULL OUTER JOIN	The FULL JOIN command returns all rows when there is a match in either the left table or the right table.	`SELECT * FROM table1 FULL JOIN table2 ON table1.column = table2.column;`	`SELECT * FROM employees LEFT JOIN departments ON employees.employee_id = departments.employee_id UNION SELECT * FROM employees RIGHT JOIN departments ON employees.employee_id = departments.employee_id;`
CROSS JOIN	The CROSS JOIN command combines every row from the first table with every row from the second table, creating a Cartesian product.	`SELECT * FROM table1 CROSS JOIN table2;`	`SELECT * FROM employees CROSS JOIN departments;`
SELF JOIN	The SELF JOIN command joins a table with itself.	`SELECT * FROM table1 t1, table1 t2 WHERE t1.column = t2.column;`	`SELECT * FROM employees t1, employees t2 WHERE t1.employee_id = t2.employee_id;`
NATURAL JOIN	The NATURAL JOIN command matches columns with the same name in both tables.	`SELECT * FROM table1 NATURAL JOIN table2;`	`SELECT * FROM employees NATURAL JOIN departments;`

6. Subqueries in SQL

Command	Description	Syntax	Example
IN	The IN command is used to determine whether a	`SELECT column(s) FROM table WHERE`	`SELECT * FROM customers WHERE city IN`

elvischristian283@gmail.com

	value matches any value in a subquery result. It is often used in the WHERE clause.	`value IN (subquery);`	`(SELECT city FROM suppliers);`
ANY	The ANY command is used to compare a value to any value returned by a subquery. It can be used with comparison operators like =, >, <, etc.	`SELECT column(s) FROM table WHERE value < ANY (subquery);`	`SELECT * FROM products WHERE price < ANY (SELECT unit_price FROM supplier_products);`
ALL	The ALL command is used to compare a value to all values returned by a subquery. It can be used with comparison operators like =, >, <, etc.	`SELECT column(s) FROM table WHERE value > ALL (subquery);`	`SELECT * FROM orders WHERE order_amount > ALL (SELECT total_amount FROM previous_orders);`

> *Keep Learning & Keep Exploring!*

elvischristian283@gmail.com