

Using nested classes as associated types.

Authors omitted for double-bind review.

Unspecified Institution.

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent convallis orci arcu, eu mollis dolor. Aliquam eleifend suscipit lacinia. Maecenas quam mi, porta ut lacinia sed, convallis ac dui. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Suspendisse potenti.

2012 ACM Subject Classification Dummy classification

Keywords and phrases Dummy keyword

Digital Object Identifier 10.4230/LIPIcs.CVIT.2016.23

1 Introduction

Associated types are a powerful form of generics, now integrated in both Scala and Rust. They are a new kind of member, like methods fields and nested classes. Associated types behave as 'virtual' types: they can be overridden, can be abstract and can have a default. However, the user has to specify those types and their concrete instantiations manually; that is, the user have to provide a complete mapping from all virtual type to concrete instantiation. When the number of associated types is small this poses no issue, but it hinders designs where the number of associated types is large. In this paper we examine the possibility of completing a partial mapping in a desirable way, so that the resulting mapping is sound and also robust with respect to code evolution.

The core of our design is to reuse the concept of nested classes instead of relying of a new kind of member for associated types. An operation, call Redirect, will redirect some nested classes in some external types. To simplify our formalization and to keep the focus on the core of our approach, we present our system on top of a simple Java like languages, with only final classes and interfaces, when code reuse is obtained by trait composition instead of conventional inheritance. We rely on a simple nominal type system, where subtyping is induced only by implementing interfaces; in our approach we can express generics without having a polymorphic type system. To simplify the treatment of state, we consider fields to be always instance private, and getters and setters to be automatically generated, together with a `static` method `of(..)` that would work as a standard constructor, taking the value of the fields and initializing the instance. In this way we can focus our presentation to just (static) methods, nested classes and implements relationships. Expanding our presentation to explicitly include visible fields, constructors and sub-classing would make it more complicated without adding any conceptual underpinning. In our proposed setting we could write:

```
String=...
SBox={String inner;
  method String inner(){..} //implicit
  static method SBox of(String inner){..} //implicit
myTtrait={
  Box={Elem inner} //implicit Box(Elem inner) and Elem inner()
  Elem={Elem concat(Elem that)}
  static method Box merge(Box b, Elem e){return Box.of(b.inner().concat(e));}
}
Result=myTrait<Box=SBox> //equivalent to trait<Box=SBox, Elem=String>
...Result.merge(SBox.of("hello "), "world");//hello world
```



© Authors omitted for double-bind review.;
licensed under Creative Commons License CC-BY

42nd Conference on Very Important Topics (CVIT 2016).

Editors: John Q. Open and Joan R. Access; Article No. 23; pp. 23:1–23:14

Leibniz International Proceedings in Informatics



LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

23:2 Using nested classes as associated types.

Here class **SBox** is just a container of **Strings**, and **myTrait** is code encoding **Boxes** of any kind of **Elem** with a **concat** method. By instantiating **myTrait<Box=SBox>**, we can infer **Elem=String**, and obtain the following flattened code, where **Box** and **Elem** has been removed, and their occurrences are replaced with **SBox** and **String**.

```
Result={static method SBox merge(SBox b,String e){
return SBox.of(b.inner().concat(e));}}
```

Note how **Result** is a new class that could have been written directly by the programmer, there is no trace that it has been generated by **myTrait**. We will represent trait names with lower-case names and class/interface names with upper-case names. Traits are just units of code reuse, and do not induce nominal types.

We could have just written **Result=myTrait<Elem=String>**, obtaining

```
Result={
Box={String inner}
static method Box merge(Box b,String e){
return Box.of(b.inner().concat(e));}}
```

Note how in this case, class **Result.Box** would exist. Thanks to our decision of using nested classes as associated types, the decision of what classes need to be redirected is not made when the trait is written, but depends on the specific redirect operation. Moreover, our redirect is not just a way to show the type system that our code is correct, but it can change the behaviour of code calling static methods from the redirected classes.

This example shows many of the characteristics of our approach:

- (A) We can redirect mutually recursive nested classes by redirecting them all at the same time, and if a partial mapping is provided, the system is able to infer the complete mapping.
- (B) **Box** and **Elem** are just normal nested classes inside of **myTrait**; indeed any nested class can be redirected away. In case any of their (static) methods was implemented, the implementation is just discarded. In most other approaches, abstract/associated/generic types are special and have some restriction; for example, in Java/Scala static methods and constructors can not be invoked on generic/associated types. With redirect, they are just normal nested classes, so there are no special restrictions on how they can be used. In our example, note how **merge** calls **Box.of(..)**.
- (C) While our example language is nominally typed, nested classes are redirected over types satisfying the same structural shape. We will show how this offers some advantages of both nominal and structural typing.

A variation of redirect, able to only redirect a single nested class, was already presented in literature. While points (B) and (C) already apply to such redirect, we will show how supporting (A) greatly improves their value.

The formal core of our work is in defining

- **ValidRedirect**, a computable predicate telling if a mapping respects the structural shapes and nominal subtype relations.
- A formal definition of what properties a procedure expanding a partial mapping into a complete one should respect.
- **ChoseRedirect**, an efficient algorithm respecting those properties.

We first formally define our core language, then we define our redirect operator and its formal properties. Finally we motivate our model showing how many interesting examples of generics and associated types can be encoded with redirect. Finally, as an extreme application, we show how a whole library can be adapted to be injected in a different environment.

2 Language grammar and well formedness

$e ::= x \mid e.m(es) \mid T.m(es) \mid e.x \mid \text{new } T(es)$	expression	$T ::= \text{This}n.Cs$	types
$L ::= \{\text{interface } Tz; Mz \mid \{Tz; Mz; K\}$	code literal	$Tx ::= T x$	parameter
$M ::= \text{static? } T m(Txs) e? \mid \text{private? } C=E$	member	$D ::= id=E$	declaration
$K ::= \langle Txs \rangle?$	state	$id ::= C \mid t$	class/trait id
$E ::= L \mid t \mid E_1 <+ E_2 \mid E < Cs = T >$	Code Expr.	$v ::= \text{new } T(vs)$	value

We apply our ideas on a simplified object oriented language with nominal typing and (nested) interfaces and final classes. Instead of inheritance, code reuse is obtained by trait composition, thus the source code would be a sequence of top level declarations D followed by a main expression; a lower-case identifier t is a trait name, while an upper case identifier C is a class name. To simplify our terminology, instead of distinguishing between nested classes and nested interfaces, we will call *nested class* any member of a code literal named by a class identifier C . Thus, the term *class* may denote either an *interface class* (interface for short) or a *final class*.

In the context of nested classes, types are paths. Syntactically, we represent them as relative paths of form $\text{This}n.Cs$, where the number n identify the root of our path: $\text{This}0$ is the current class, $\text{This}1$ is the enclosing class, $\text{This}2$ is the enclosing enclosing class and so on. $\text{This}n.Cs$ refers to the class obtained by navigating throughout Cs starting from $\text{This}n$. Thus, $\text{This}0$ is just the type of the directly enclosing class. By using a larger then needed n , there could be multiple different types referring to the same class. Here we expect all types to be in the normalized form where the smallest possible n is used.

Code literals L serve the role of class/interface bodies; they contain the set of implemented interfaces Tz , the set of members Mz and their (optional) state. In the concrete syntax we will use **implements** in front of a non empty list of implemented interfaces and we will omit parenthesis around a non empty set of fields. A class member M can be a (private) nested class or a (static) method. Abstract methods are just methods without a body. Well formed interface methods can only be abstract and non-static. To facilitate code reuse, classes can have (static) abstract methods, code composition is expected to provide an implementation for those or, as we will see, redirect away the whole class. We could easily support private methods too, but to simplify our formalism we consider private only for nested classes. In a well formed code literal, in all types of form $\text{This}n.Cs.C.Cs'$, if C denotes a private nested class, then Cs is empty.

Expressions are used as body of (static) methods and for the main expression. They are variables x (including **this**) and conventional (static) method calls. Field access and **new** expressions are included but with restricted usage: well formed field accesses are of form **this**. x in method bodies and $v.x$ in the main expression, while well formed **new** expressions have to be of form **new This**0(xs) in method bodies and of form v in the main expression. Those restrictions greatly simplify reasoning about code reuse, since they require different classes to only communicate by calling (static) methods. Supporting unrestricted fields and constructors would make the formalism much more involved without adding much of a conceptual difficulty. Values are of form **new** $T(vs)$.

For brevity, in the concrete syntax we assume a syntactic sugar declaring a static of method (that serve as a factory) and all fields getters; thus the order of the fields would induce the order of the factory arguments. In the core calculus we just assume such methods to be explicitly declared.

Finally, we examine the shape of a nested class: **private?** $C=E$. The right hand side is not just a code literal but a code composition expression E . In trait composition, the

23:4 Using nested classes as associated types.

code expression will be reduced/flattened to a code literal L during compilation. Code expressions denote an algebra of code composition, starting from code literal L and trait names t , referring to a literal declared before by $t=E$. We consider two operators: conventional preferential sum $E_1 \leftarrow E_2$ and our novel redirect $E \leftarrow C_s = T$.

The compilation process consists in flattening all the E into L , starting from the innermost leftmost E . This means that sum and redirect work on LV s: a kind of L , where all the nested classes are of form $C=LV$. The execution happens after compilation and consist in the conventional execution of the main expression e in the context of the fully reduced declarations, where all trait composition has been flatted away. Thus, execution is very simple and standard and behaves like a variation of FJ with interfaces instead of inheritance, and where nested classes are just a way to hierarchically organize code names. On the other side, code composition in this setting is very interesting and powerful, where nested classes are much more than name organization: they support in a simple and intuitive way expressive code reuse patterns. To flatten an E we need to understand the behaviour of the two operators, and how to load the code of a trait: since it was written in another place, the syntactic representation of the types need to be updated. For each of those points we will first provide some informal explanation and then we will proceed formalizing the precise behaviour.

2.1 Redirect

Redirect takes a library literal and produce a modified version of it where some nested classes has been removed and all the types referencing such nested classes are now referring to an external type. It is easy to use this feature to encode a generic list:

```
list={
  Elem={}
  static This0 empty()= new This0(Empty.of())
  boolean isEmpty()= this.impl().isEmpty()
  Elem head()= this.impl.asCons().tail()
  This0 tail()=this.impl.asCons().tail()
  This0 cons(Elem e)=new This0(Cons.of(e, this.impl)
  private Impl={interface Bool isEmpty() Cons asCons()}
  private Empty={implements This1
    Bool isEmpty()=true Cons asCons()=../*error*/
    ()//() means no fields
  private Cons={implements This1
    Bool isEmpty()=false Cons asCons()=this
    Elem elem Impl tail }
  Impl impl
}
IntList=list<Elem=Int>
...
IntList.Empty.of().push(3).top()=4 //example usage
```

This would flatten into

```
list={/*as before*/
//IntList=list<Elem=Int>
IntList={
  //Elem={} no more nested class Elem
  static This0 empty()= new This0(Empty.of())
  boolean isEmpty()= this.impl().isEmpty()
  Int head()= this.impl.asCons().tail()
  This0 tail()=this.impl.asCons().tail()
  This0 cons(Int e)=new This0(Cons.of(e, this.impl)
  private Impl={interface Bool isEmpty() Cons asCons()}
  private Empty={/*as before*/}
```

```

198 private Cons={implements This1
199     Bool isEmpty()=false Cons asCons()=this
200     Int elem Impl tail }
201 Impl impl
202 }//everywhere there was "Elem", now there is "Int"

```

Redirect can be propagated in the same way generics parameters are propagate: For example, in Java one could write code as below,

```

206 class ShapeGroup<T extends Shape>{
207     List<T> shapes;
208     ..}
209 //alternative implementation
210 class ShapeGroup<T extends Shape,L extends List<T>>{
211     L shapes;
212     ..}
213

```

to denote a class containing a list of a certain kind of **Shapes**. In our approach, one could write the equivalent

```

217 shapeGroup={
218     Shape={implements Shape}
219     List=list<Elem=Shape>
220     List shapes
221     ..}
222

```

With redirect, `shapeGroup` follow both roles of the two Java examples; indeed there are two reasonable ways to reuse this code

Triangulation=`shapeGroup<Shape=Triangle>`, if we have a **Triangle** class and we would like the concrete list type used inside to be local to the **Triangulation**, or **Triangulation**=`shapeGroup<List=Triangles>`, if we have a preferred implementation for the list of triangles that is going to be used by our **Triangulation**. Those two versions would flatten as follow:

```

230 //Triangulation=shapeGroup<Shape=Triangle>
231 Triangulation={
232     List=/*list with Triangle instead of Elem*/
233     List shapes
234     ..}
235
236 //Triangulation=shapeGroup<List=Triangles>
237 //expands to shapeGroup<List=Triangles,Shape=Triangle>
238 Triangulation={
239     Triangles shapes
240     ..}
241

```

As you can see, with redirect we do not decide a priori what is generic and what is not in a class.

Redirect can not always succeed. For example, if we was to attempt `shapeGroup<List=Int>` the flattening process would fail with an error similar to a invalid generic instantiation. Subtype is a fundamental feature of object oriented programming. Our proposed redirect operator do not require the type of the target to perfectly match the structural type of the internal nested classes; structural subtyping is sufficient. This feature adds a lot of flexibility to our redirect, however completing the mapping (as happens in the example above) is a challenging and technically very interesting task when subtyping is took into account. This is strongly connected with ontology matching and will be discussed in the technical core of the paper later on.

2.2 Preferential sum and examples of sum and redirect working together

The sum of two traits is conceptually a trait with the sum of the traits members, and the union of the implemented interfaces. If the two traits both define a method with the same name, some resolution strategy is applied. In the symmetric sum¹ the two methods need to have the same signature and at least one of them need to be abstract. With preferential sum (sometimes called override), if they are both implemented, the left implementation is chosen. Since in our model we have nested classes, nested classes with the same name will be recursively composed.

We chose preferential sum since is simpler to use in short code examples.¹ Since the focus of the paper is the novel redirect operator, instead of the well known sum, we will handle summing state and interfaces in the simplest possible way: a class with state can only be summed with a class without state, and an interface can only be summed with another interface with identical methods signatures.

In literature it has been shown how trait composition with (recursively composed) nested classes can elegantly handle the expression problem and a range of similar design challenges. Here we will show some examples where sum and redirect cooperate to produce interesting code reuse patterns:

```
listComp=list<+{
  Elem:{ Int geq(Elem e)}//-1/0/1 for smaller, equals, greater
  static Elem max2(Elem e1, Elem e2)=if e1.geq(e2)>0 then e1, else e2
  Elem max(Elem candidate)=
    if This.isEmpty() then candidate
    else this.tail().max(This.max2(this.head(),candidate))
  Elem min(Elem candidate)=...
  This0 sort()=...
}
```

As you can see, we can *extends* our generic type while refining our generic argument: **Elem** of **listComp** now needs a **geq** method.

While this is also possible with conventional inheritance and F-Bound polymorphism, we think this solution is logically simpler than the equivalent Java

```
class ListComp<Elem extends Comparable<Elem>> extends LinkedList<Elem>{
  ../*body as before*/
}
```

Another interesting way to use sum is to modularize behaviour delegation: consider the following (not efficient for the sake of compactness) implementation of **set**, where the way to compare elements is not fixed:

```
set:{
  Elem:{}
  List=list<Elem=Elem>
  static This0 empty()= new This0(List.empty())
  Bool contains(Elem e)=../*uses eq and hash*/
  Int size()=..
  This add(Elem e)=...
  This remove(Elem e)=...
  Bool eq(Elem e1,Elem e2)//abstract
  Int hash(Elem e)//abstract
  List asList //to allow iteration
}
```

¹ symmetric sum is often presented in conjunction with a restrict operator that makes some methods abstract.

```

307 }
308 eqElem={
309   Elem={ Bool equals(Elem e)/*abstract*/}
310   Bool eq(Elem e1,Elem e2)=e1.equals(e2)
311 }
312 hashElem={
313   Elem={ Int hash(Elem e)/*abstract*/}
314   Int hash(Elem e)=e.hash()
315 }
316 Strings=(set<+eqElem<+eqHash)<Elem=String>
317 LongStrings=(set<+eqElem)<Elem=String> <+{
318   Int hash(String e)=e.size()
319 }//for very long strings, size is a faster hash
320

```

321 Note how $(\text{set}\langle +\text{eqElem}\langle +\text{eqHash}\rangle\langle \text{Elem}=\text{String}\rangle)$ is equivalent to $\text{set}\langle \text{Elem}=\text{String}\rangle\langle +\text{eqElem}\langle \text{Elem}=\text{String}\rangle\langle +\text{eqHash}\langle \text{Elem}=\text{String}\rangle\rangle$.

322 Consider now the signature `Bool equals(Elem e)`. This is different from the common signature `Bool equals(Object e)`. What is the best signature for `equals` is an open research question, where most approaches advise either the first or the second one. Our `eqElem`, as I wrote, can support both: `Strings` would be correctly defined both if `String.equals` signature has a `String` or an `Object` parameter. EXPAND on method subtyping.

327 2.3 Moving traits around in the program

328 It is not trivial to formalize the way types like `This1.A.B` have to be adapted so that when code is moved around in different depths of nesting the refereed classes stay the same. This is needed during flattening, when a trait t is reused, but also during reduction, when a method body is inlined in the main expression, and during typing, where a method body is typed depending on the signature of other methods in the system.

329 To this aim we define a concept of program p , as a representation of the code as seen from a certain point inside of the source code.

330 The program p is the most interesting form of the grammar, used for virtually all reduction and typing rules. On the left of the `;` is a stack representing which (nested) declaration is currently being processed, the bottom (rightmost) DL represents the D of the source-program that is currently being processed. The right of the `;` represents the top-level declarations that have already been compiled, this is necessary to look up top-level classes and traits. That is, each of the $DL_0 \dots DL_n$ represents the outer nested level $0..n$, while the DVs component represent the already flattened portion of the program top level, that is the outer nested level $n + 1$

342 $p ::= DLs; DVs$ program

343 $DL ::= id=L$ partially-evaluated-declaration

344 $DV ::= id=LV$ evaluated-declaration

345 $Mid ::= C \mid m$ member-id

346 Thus, for example in the program

```

345 A={()}
346 t={ B={()}   This1.A m(This0.B b)}
347 C={D={E=t}}
348 H=t<B=A>
349
350

```

351 the flattened version for `C.D.E` will be `{ B={()} This3.A m(This0.B b)}`, where the path `This1.A` is now `This3.A` while the path `This0.B` stays the same: types defined internally will stay untouched. The program p in the observation point `E=t` is

```

354 A={()}
355 t={ B={()}   This1.A m(This0.B b)}
356

```


23:8 Using nested classes as associated types.

```

357 C={D={E=t}};
358 C={D={E=t}},//this means, we entered in C
359 D={E=t}//this means, we entered in D
360

```

361 To fetch a trait form a program, we will use notation $p(t) = LV$, to fetch a class we will
362 use $p(T)$.

363 To look up the definition of a class in the program we will use the notation $p(T) = LV$, which
364 is defined by the following:

$$\begin{aligned}
 & (; _, C=L, _)(\text{This}0.C.Cs) := L(Cs) \\
 & (id=L, DLs; DVs)(\text{This}0.Cs) := L(Cs) \\
 & (id=L, DLs; DVs)(\text{This}n+1.Cs) := DLs; DVs(\text{This}n.Cs) \\
 & LV(\emptyset) := LV \\
 & L(C.Cs) := L_0(Cs) \text{ where } L = \text{interface? } \{ _ ; _, C=L_0, _ ; _ \}
 \end{aligned}$$

365 This notation just fetch the referred LV without any modification. To adapt the paths
366 we define $T_0[from T_1]$ and $L[from T]$ as following:

$$\begin{aligned}
 & \text{This}n.Cs[from \text{This}m.C_1 \dots C_k] := \text{This}m.C_1 \dots C_{(k-n)} \quad \text{with } n \leq k \\
 & \text{This}n.Cs[from \text{This}m.C_1 \dots C_k] := \text{This}(m+n-k).C_1 \dots C_{(k-n)}Cs \quad \text{with } n > k \\
 & L[from T] := L[from T]_0 \\
 & \{\text{interface?}Tz; Mz; K\}[from T]_j := \{\text{interface?}Tz[from T]_{j+1}; Mz[from T]_{j+1}; K[from T]_{j+1}\} \\
 & \text{This}(j+n).Cs_0[from T]_j := \text{This}(j+k).Cs_1 \quad \text{with } \text{This}n.Cs_0[from T] = \text{This}k.Cs_1 \\
 & \text{This}n.Cs[from T]_j := \text{This}n.Cs[from T] \quad \text{with } n < j
 \end{aligned}$$

369 Finally, we we combine those to notation for the most common task of getting the value of a
370 literal, in a way that can be understand from the current location: $p[t]$ and $p[T]$:

$$\begin{aligned}
 & (DL_1 \dots DL_n; _, t=LV, _)[t] := LV[from \text{This}n] \\
 & p[T] := p(T)[from T]
 \end{aligned}$$

3 Flattening

377 Aside from the redirect operation itself, compilation/flattening is the most interesting part,
378 it is defined by a reduction arrow $p; id \vdash E \leftarrow E'$, the id represents the id of the type/trait
379 that we are currently compiling, it is needed since it will be the name of $This0$, and we use
380 that fact that that is equal to $This1.id$ to compare types for equality. The $(CtxV)$ rule is
381 the standard context, the (L) rule propegates compilation inside of nested-classes, $(trait)$
382 merely evaluates a trait reference to it's defined body, (sum) and $(redirect)$ perform our two
383 meta-operations.

384 $\mathcal{E}_V ::= \square \mid \mathcal{E}_V <+ E \mid LV <+ \mathcal{E}_V \mid \mathcal{E}_V < Cs = T >$ context of library-evaluation

385 Define $p; id \vdash E \rightarrow E'$

386 =====


```

(TOP)
  a →b c  ∀i < 3a ⊢ b : OK
  -----
  1 + 2 → 3
388
(CtxV)
  p; id ⊢ E ⇒ E'
  -----
  p; id ⊢ EV[E] ⇒ EV[E']
389 p; id ⊢ E --> E'
390 (CtxV) -----
391 p; id ⊢ CtxV[E] --> CtxV[E']
392
393 id = L[C = E], p; C ⊢ E --> E'
394 (L) ----- // TODO use fresh C?
395 p; id ⊢ L[C = E] --> L[C = E']
396
397 (trait) -----
398 p; id ⊢ t -> p[t]
399
400 LV1 <+p' LV2 = LV3                p' = C' = LV3, p
401 (sum) ----- for fresh C'
402 p; id ⊢ LV1 <+ LV2 --> LV3
403
404 // TODO: Inline and de-42 redirect formalism
405 (redirect) -----LV'=redirect(p, LV, Cs, P)
406 p; id ⊢ LV(Cs=P) -> LV'

```

4 The Sum operation

The sum operation is defined by the rule $L1 < +pL2 = L3$, it is unconventional as it assumes we already have the result ($L3$), and simply checks that it is indeed correct. We believe (but have not proved) that this rule is unambiguous, if $L1 < +pL2 = L3$ and $L1 < +pL2 = L3'$, then $L3 = L3'$ (since the order of members does not matter for Ls).

The main rule for summing of non-interfaces, sums the members, unions the implemented interfaces (and uses *minimize* to remove any duplicates), it also ensures that at most one of them has a constructor. For summing an interface with a interface/class we require that an interface cannot 'gain' members due to a sum. The actual L42 implementation is far less restrictive, but requires complicated rules to ensure soundness, due to problems that could arise if a summed nested-interface is implemented. Summing of traits/classes with state is a non-trivial problem and not the focus of our paper, there are many prior works on this topic, and our full L42 language simply uses ordinary methods to represent state, however this would take too much effort to explain here.

```

421 Define L1 <+p L2 = L3
422 =====
423 {Tz1; Mz1; K?1} <+p {Tz2; Mz2; K?2} = {Tz; Mz; K?}
424 Tz = p.minimize(Tz1 U Tz2)
425 Mz1 <+p Mz1 = Mz
426 {empty, K?1, K?2} = {empty, K?} //may be too sophisticated?

```

23:10 Using nested classes as associated types.

```

427
428 interface{Tz1; amtz,amtz';} <+p interface?{Tz2;amtz;} = interface {Tz;amtz,amtz';}
429 Tz = p.minimize(Tz1 U Tz2)
430 if interface? = interface then amtz'=empty

```

431 The rules for summing member are simple, we take two sets of members collect all the
 432 oness with unique names, and sum those with duplicates. To sum nested classes we merely
 433 sum their bodies, to sum two methods we require their signatures to be identical, if they
 434 both have bodies, the result has the body of the RHS, otherwise the result has the body (if
 435 present) of the LHS.

```

436 Define Mz <+p Mz' = Mz"
437 -----
438 M, Mz <+p M', Mz' = M <+p M', Mz <+p Mz
439 //note: only defined when M.Mid = M'.Mid
440
441 Mz <+p Mz' = Mz, Mz':
442 dom(Mz) disjoint dom(Mz')
443
444 Define M <+p M' = M"
445 -----
446 T' m(Txs') e? <+p T m(Txs) e = T m(Txs) e
447 T', Txs'.Ts =p Ts, Txs
448
449 T' m(Txs') e? <+p T m(Txs) = T m(Txs) e?
450 T', Txs'.Ts =p Ts, Txs
451
452 (C = L) <+p (C = L') = L <+p.push(C) L'

```

453 We have two-top level reduction rules defining our language, of the form $Dse^{\sim\sim} > Ds'e$
 454 which simply reduces the source-code. The first rule (*compile*) ‘compiles’ each top-level
 455 declaration (using a well-typed subset of already compiled top-level declarations), this
 456 reduces the defining expression. The second rule, (*main*) is executed once all the top-level
 457 declarations have compiled (i.e. are now fully evaluated class literals), it typechecks the
 458 top-level declarations and the main expression, and then proceeds to reduce it. In principle
 459 only one-typechecking is needed, but we repeat it to avoid declaring more rules.

```

460 Define Ds e --> Ds' e'
461 =====
462 DVs' |- Ok
463 empty; DVs'; id | E --> E'
464 (compile)----- DVs' subsetof DVs
465 DVs id = E Ds e --> DVs id = E' Ds e
466
467 DVs |- Ok
468 DVs |- e : T
469 DVs |- e --> e'
470 (main)----- for some type T
471 DVs e --> DVs e'

```

```

472   gff
       $L[C=E'] := \text{interface? } \{Tz; MVs C=E' Ms; K?\}$ 
473   where  $L = \text{interface? } \{Tz; MVs C=_ Ms; K?\}$ 
       $Ts \in p := \forall T \in Ts \bullet p(T)$  is defined
474    $\mathcal{E}_V ::= \square \mid \mathcal{E}_V \leftarrow E \mid LV \leftarrow \mathcal{E}_V \mid \mathcal{E}_V \leftarrow Cs=T >$  context of library-evaluation
475    $\mathcal{E}_v ::= \square \mid \mathcal{E}_v.m(es) \mid v.m(vs \mathcal{E}_v es) \mid T.m(vs \mathcal{E}_v es)$ 

```

5 Type System

The type system is split into two parts: type checking programs and class literals, and the typechecking of expressions. The latter part is mostly conventional, it involves typing judgments of the form $p; Txs \vdash e : T$, with the usual program p and variable environment Txs (often called Γ in the literature). rule (*Dsok*) type checks a sequence of top-level declarations by simply push each declaration onto a program and typecheck the resulting program. Rule *pok* typechecks a program by check the topmost class literal: we type check each of it's members (including all nested classes), check that it properly implements each interface it claims to, does something weird, and finanly check check that it's constructor only referenced existing types,

```

486
487
488 Define p |- Ok
489 =====
490
491 D1; Ds |- Ok ... Dn; Ds|- Ok
492 (Ds ok) ----- Ds = D1 ... Dn
493 Ds |- Ok
494
495 p |- M1 : Ok .... p |- Mn : Ok
496 p |- P1 : Implemented .... p |- Pn : Implemented
497 p |- implements(Pz; Ms) /*WTF?*/ if K? = K: p.exists(K.Txs.Ts)
498 (p ok) ----- p.top() = interface? {P1...Pn; M1, ..., Mn; K?
499 p |- Ok
500
501 p.minimize(Pz) subseteq p.minimize(p.top().Pz)
502 amt1 _ in p.top().Ms ... amtn _ in p.top().Ms
503 (P implemented) ----- p[P] = interface {Pz; amt1 ... an
504 p |- P : Implemented
505
506 (amt-ok) ----- p.exists(T, Txs.Ts)
507 p |- T m(Tcs) : Ok
508
509 p; This0 this, Txs |- e : T
510 (mt-ok) ----- p.exists(T, Txs.Ts)
511 p |- T m(Tcs) e : Ok
512
513 C = L, p |- Ok
514 (cd-Ok) -----

```

23:12 Using nested classes as associated types.

```

515 p |- C = L : OK
516

```

517 Rule (*Pimplemented*) checks that an interface is properly implemented by the program-
 518 top, we simply check that it declares that it implements every one of the interfaces super-
 519 interfaces and methods. Rules (*amt - ok*) and (*mt - ok*) are straightforward, they both
 520 check that types mentioned in the method signature exist, and ofcourse for the latter case,
 521 that the body respects this signature.

522 To typecheck a nested class declaration, we simply push it onto the program and typecheck
 523 the top-of the program as before.

524 The expression typesystem is mostly straightforward and similar to feartherwieght Java,
 525 notable we use $p[T]$ to look up information about types, as it properly 'from's paths, and
 526 use a classes constructor definitions to determine the types of fields.

```

527 Define p; Txs |- e : T
528 =====
529 (var)
530 ----- T x in Txs
531 p; Txs |- x : T
532
533 (call)
534 p; Txs |- e0 : T0
535 ...
536 p; Txs |- en : Tn
537 ----- T' m(T1 x1 ... Tn xn) _ in p[T0].Ms
538 p; Txs |- e0.m(e1 ... en) : T'
539
540 (field)
541 p; Txs |- e : T
542 ----- p[T].K = constructor(_ T' x _)
543 p; Txs |- e.x : T'
544
545
546 (new)
547 p; Txs |- e1 : T1 ... p; Txs |- en : Tn
548 ----- p[T].K = constructor(T1 x1 ... Tn xn)
549 p; Txs |- new T(e1 ... en)
550
551
552 (sub)
553 p; Txs |- e : T
554 ----- T' in p[T].Pz
555 p; Txs |- e : T'
556
557
558 (equiv)
559 p; Txs |- e : T
560 ----- T =p T'
561 p; Txs |- e : T'

```

6 Graph example

We now consider an example where Redirect simplifies the code quite a lot: We have a **Node** and **Edge** concepts for a graph. The **Node** have a list of **Edges**. A **isConnected** function takes a list of **Nodes**. A **getConnected** function takes **Node** and return a set of **Nodes**.

```

566 graphUtils={
567   Edges:list<+{Node start() Node end()}
568   Node:{Edges connections()}
569   Nodes:set<Elem=Node> //note that we do not specify equals/hash
570   static Bool isConnected(Nodes nodes)=
571     if(nodes.size()==0) then true
572     else getConnected(nodes.asList().head()).size()==nodes.size()
573   static Nodes getConnected(Node node)=getConnected(node,Nodes.empty())
574   static Nodes getConnected(Node node,Nodes collected)=
575     if(collected.contains(node)) then collected
576     else connectEdges(node.connections(),collected.add(node))
577   static Nodes connectEdges(Edges e,Nodes collected)=
578     if( e.isEmpty()) then collected
579     else connectEdges(e.tail(),collected.add(e.head().end()))
580 }
581

```

We have shown the full code instead of omitting implementations to show that the code inside of an highly general code like the former is pretty conventional. Just declare nested classes as if they was the concrete desired types. Note how we can easily create a new Nodes@ by doing **Nodes.empty()**.

Here we show how to instantiate **graphUtils** to a graph representing cities connected by streets, where the streets are annotated with their length, and **Edges** is a priority queue, to optimize finding the shortest path between cities.

```

590 Map:{
591   Street:{City start, City end, Int size}
592   City:{}
593   Streets:priorityQueue<Elem=Street><+{
594     Int geq(Street e1, Street e2)=e1.size()-e2.size()
595   }<+{
596   Streets:{}
597   City:{Streets connections, Int index} //index identify the node
598   Cities:set<Elem=City><+{
599     Bool eq(City e1, City e2) e1.index==e2.index
600     Int hash(City e) e.index
601   }
602   Cities cities
603   //more methods
604 }
605 MapUtils=graphUtils<Nodes=Map.Cities>
606 //infers Nodes.List, Node, Edges, Edge
607

```

In Appending 2 we will show our best attempt to encode this graph example in Java, Rust and Scala. In short, we discovered... - towel1:.. //Map: towel2:.. //Map: lib: T:towel1 f1 ... fn
MyProgram: T:towel2 Lib:lib[T=This0.T] ... -

7 extra

Features: Structural based generics embedded in a nominal type system. Code is Nominal, Reuse is Structural. Static methods support for generics, so generics are not just a trik to make the type system happy but actually change the behaviour Subsume associate types.

617 After the fact generics; redirect is like mixins for generics Mapping is inferred-> very large
 618 maps are possible -> application to libraries

619 In literature, in addition to conventional Java style F-bound polymorphism, there is
 620 another way to obtain generics: to use associated types (to specify generic paramaters) and
 621 inheritance (to instantiate the paramaters). However, when parametrizing multiple types,
 622 the user to specify the full mapping. For example in Java interface A B m(); inteface
 623 BString f(); class G<TA extends A<TB>, TB> //TA and TB explicitly listed String g(TA
 624 a TB b) return a.m().f(); class MyA implements A<MyB>.. class MyB implements B ..
 625 G<MyA,MyB> //instantiation Also scala offers genercs, and could encode the example in
 626 the same way, but Scala also offers associated types, allowing to write instead...

627 Rust also offers generics and associated types, but also support calling static methods
 628 over generic and associated types.

629 We provide here a foundational model for genericity that subsume the power of F-bound
 630 polimorphims and associated types. Moreover, it allows for large sets of generic parameter
 631 instantiations to be inferred starting from a much smaller mapping. For example, in our
 632 system we could just write g= A= method B m() B= method String f() method String g(A a
 633 B b)=a.m().f() MyA= method MyB m()= new MyB(); .. MyB= method String f()="Hello";
 634 .. g<A=MyA> //instantiation. The mapping A=MyA,B=MyB

635 We model a minimal calculus with interfaces and final classes, where implementing an
 636 interface is the only way to induce subtyping. We will show how supporting subtyping
 637 constitute the core technical difficulty in our work, inducing ambiguity in the mappings.
 638 As you can see, we base our generic matches the structor of the type instead of respect-
 639 ing a subtype requirement as in F-bound polymorphis. We can easily encode subtype
 640 requirements by using implements: Print=interface method String print(); g= A:implements
 641 Print method A printMe(A a1,A a2) if(a1.print().size())>a2.print.size())return a1; return a2;
 642 MyPrint=implements Print .. g<A=MyPrint> //instantiation g<A=Print> //works too
 643 ————— example showing ordering need to strictly improve EI1: interface EA1: imple-
 644 ments EI1

645 EI2: interface EA2: implements EI2
 646 EB: EA1 a1 EA1 a1
 647 A1: A2: B: A1 a1 A2 a2 [B = EB] // A1 -> EI1, A2 -> EA2 a // A1 -> EA1, A2 ->
 648 EI2 b // A1 -> EA1, A2 -> EA2 c
 649 a <= b b <= a c <= a, b a <= c

650 hi Hi class $a ::= b \quad c$

651 aa hi Hi class qq a $a ::= b \quad c$
 $a ::= b \quad c$

652 } } [()]
 (TOP)

653
$$\frac{a \xrightarrow{b} c \quad \forall i < 3a \vdash b : \text{OK}}{1 + 2 \rightarrow 3} \begin{matrix} a \\ b \\ c \end{matrix}$$