

Separating Use and Reuse to Improve Both

Hrshikesh Arora ¹
Marco Servetto ¹
Bruno C. d. S. Oliveira ²

¹Victoria University of Wellington

²The University of Hong Kong

Subtyping and Subclassing

- ▶ Subtyping without subclassing; easy: Java interfaces
- ▶ Subclassing without subtyping; hard:

```
class A{ int ma(){ return Utils.m(this); } }  
class Utils{ static int m(A a){..} }  
class B extends A{ int mb(){return this.ma();} }  
..  
new B().mb();
```

This-leaking problem: **this** written in class **A** is of type **A**. when **B** inherits the code of **A**, code **Utils.m(this)** would pass a **this** as an **A**. To be sound, $B \leq A$ must hold.

Reusing code without inducing subtyping

Three different approaches separating subtyping and subclassing:

- ▶ DeepFJig
- ▶ TraitRecordJ
- ▶ PackageTemplate

Widely different approaches, similar core ideas that we synthesize and improve: *separating code from use and code for reuse*

42_μ: our approach:

We synthesize the best from these 3 approaches.

Traits! (inspired from the original approach, not Scala/Rust traits).

- ▶ **Traits** for Code Reuse: traits can be reused to produce more code.
 - ▶ **Classes** for Code Use: classes can be instantiated.
 - ▶ **Types**: classes and interface names can be used as a types.
 - ▶ **Exact types**: all classes are final; inheritance by reusing traits.
 - ▶ **Sub types**: interfaces are the only way to induce subtyping.
 - ▶ **Not a type**: trait names can not be used as types.
- This** can be used to refer to the eventual class of the code.
- ▶ **State**: No explicit constructors/fields; state is implicitly defined.
 - ▶ **Composition**: traits code can be composed to obtain more code.

This leaking in our approach

```
IA={interface
  method Int ma ()
}
Utils={
  static method Int m(IA a){return ...}
}
ta={implements IA
  method Int ma () {return Utils.m(this);}
}
A=Use ta
B=Use ta
```

this written in trait **ta** is of type **This** and **IA**. when **B** inherits the code of **ta**, code **Utils.m(this)** would pass a **this** as an **IA**. In this way, even if **B** and **A** share the same code, there are not in a subtype relation. (Note that **ta** is not a valid typename)

Trait composition

The composed code contains all members from the used traits. Methods with same name and type signature are summed into a single one. At most one of those summed methods can have a body, which will be propagated into the result.

```
t1={  
  method String hello();  
  method String helloWorld(){return hello()+" World";}  
}
```

```
t2={ method String hello(){return "Hi";} }
```

```
t3= Use t1,t2
```

```
//-- flatten to -----
```

```
t3= {  
  method String hello(){return "Hi";}  
  method String helloWorld(){return hello()+" World";}  
}
```

Handling State

How to make this process work with constructors and fields while achieving the following goals:

- ▶ managing fields in a way that borrows the elegance of summing methods;
- ▶ actually initializing objects, leaving no **null** fields;
- ▶ making it easy to add new fields;
- ▶ allowing self instantiation: a trait method can instantiate the class using it.

Abstract State Operations

Idea: use abstract methods as getters, setters and factory methods.
Conventionally, an abstract class is a class with some abstract method.
Here, a class whose abstract methods can be seen as state operations is a concrete coherent class.

For example, Java:

```
class A{  
    int x;  
    A(int x){this.x=x;}  
    int x(){return this.x;}  
    void x(int that){this.x=that;}  
}
```

Equivalent code in 42_μ:

```
A={  
    static method This of (Int x)  
    method Int x()  
    method Void x(Int that)  
}
```


Coherent class

- ▶ A class with no abstract methods is coherent (just like Java **Math**, for example). Such classes have no instances and are only useful for calling static methods.
- ▶ A class with a single abstract **static** method returning **This** and with parameters $T_1\ x_1, \dots, T_n\ x_n$ is coherent if all the other abstract methods can be seen as *abstract state operations* over one of x_1, \dots, x_n . That is:
 - ▶ A method $T_i\ x_i\ ()$ is interpreted as an abstract state method: a *getter* for x_i .
 - ▶ A method **void** $x_i\ (T_i\ \text{that})$ is a *setter* for x_i .

Example: **Point**s with algebraic operations

static factory method:

```
Point p=Point.of(3,4)
```

getters:

```
p.x()==3,    p.y()==4
```

summing points:

```
p.sum(Point.of(10,20)) equivalent to Point.of(13,24)
```

NOTE: sum operation creates a new point

If no code reuse is desired, it is easy to use Java to encode such **Point** class. However, we would like to define operations `sum`, `mul`, `div` and `sub` independently and compose them to create classes with the operations we want, so that it is easy to have points with `sum` and `mul`, points with just `sum` or points with just `mul`.

For example, we expect **PointSum**.sum(**PointSum**) : **PointSum**
but we also **PointSumMul**.sum(**PointSumMul**) : **PointSumMul**.
This breaks subtyping: **PointSumMul** $\not\leq$ **PointSum**.

Abstract state

```
p= { //point trait with abstract state
  method Int x() //getter for field x
  method Int y() //getter for field y
  static method This of(Int x,Int y) //factory method
}

Point= Use p //this is a concrete coherent class
...
.. Point.of(3,7).x() ..//valid code
```

Abstract state

```
p={ method Int x()   method Int y()  
    static method This of(Int x,Int y)  
}
```

```
pointSum= Use p, {  
    method This sum(This that){  
        return This.of(this.x()+that.x(),this.y()+that.y());  
    }}
```

```
pointMul= Use p, {  
    method This mul(This that){  
        return This.of(this.x()*that.x(),this.y()*that.y());  
    }}
```

```
pointDiv= ...
```

```
MyPoint= Use pointSum,pointMul,pointDiv,...
```

Case study 1: **Points** with algebraic operations

Encoding the point example above, with the 4 arithmetic operations, and instantiating all the 16 possible permutations as separate classes:

Language	Lines of code	members	classes/traits
Java7	115	50	16
Classless Java	82	34	16
Scala	81	40	21
42_{μ}	32	7	21

State extensibility

```
p={ method Int x() method Int y()  
  static method This of(Int x,Int y)  
}  
pointSum= Use p, {  
  method This sum(This that){  
    return This.of(  
      this.x()+that.x(),this.y()+that.y());  
  }}  
  
colored= { method Color color() }  
  
CPoint= Use pointSum,colored,{  
  static method This of(Int x,Int y,Color color)  
  
  static method This of(Int x,Int y){  
    return This.of(x,y,Color.of(/*red*/));  
  } }//Now CPoint.sum return read points
```

State extensibility, with withers

A wither is like a field setter, but creates a new copy of the object

```
p= { method Int x() method Int y()
    method This withX(Int that)
    method This withY(Int that)
    method This merge(This that)
  }
pointSum= Use p, {
  method This sum(This that){
    return this.merge(that)
      .withX(this.x()+that.x())
      .withY(this.y()+that.y());
  }}
colored= { method Color color()
  method This withColor(Color that)
  method This merge(This that){
    return this.withColor(this.color().mix(that.color()));
  }}
CPoint= Use pointSum,colored,{
  static method This of(Int x, Int y, Color color) }
```

Independent extensibility

```
flavored= {  
  method Flavor flavor()  
  method This withFlavor(Flavor that)  
  method This merge(This that){  
    return this.withFlavor(that.flavor());  
  }  
}  
FCPoint= Use //aliasing conflicting implementations  
  colored[super merge as m1],  
  flavored[super merge as m2],  
  pointSum,{  
    method This merge(This that){  
      return this.m1(that).m2(that);  
    }  
    static method  
    This of(Int x, Int y, Color color, Flavor flavor)  
  }
```


More in the paper

- ▶ Transparent handling of nested classes
- ▶ **This** type generalized for family polymorphism
- ▶ A very natural encoding of the Expression Problem
- ▶ Simple formalization of our language

Thanks

Questions?