



Lecture 7

Abstract data types
Mutable Values



Some slides were borrowed from CS88, Berkeley



Abstract Data Types




Slides were borrowed from cs88, berkeley.

Data abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as *units*
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- **Data abstraction:** A methodology by which functions enforce an abstraction barrier between *representation* and *use*

Abstract Data Type



Data Types You have seen

- **Lists**

- **Constructors:**

- » `list(...)`

- » `[<exprs>, ...]`

- » `[<exp> for <var> in <list> [if <exp>]]`

- **Selectors:** `<list> [<index or slice>]`

- **Operations:** `in, not in, +, *, len, min, max`

- » Mutable ones too

- **Tuples**

- **Constructors:**

- » `tuple(...)`

- » `(<exprs>, ...)`

- **Selectors:** `<tuple> [<index or slice>]`

- **Operations:** `in, not in, +, *, len, min, max`

More “Built-in” Examples

- **Strings**

- **Constructors:**

- » `str(...)`

- » `"<chars>", '<chars>'`

- **Selectors:** `<str> [<index or slice>]`

- **Operations:** `in, not in, +, *, len, min, max`

- **Range**

- **Constructors:**

- » `range(<end>), range(<start>,<end>),`
`range(<start>,<end>,<step>)`

- **Selectors:** `<range> [<index or slice>]`

- **Operations:** `in, not in, len, min, max`

(Demo)



Abstraction Barriers



Abstraction Barriers

Parts of the program that...

Treat city as

Using ...

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat
Implement selectors and constructor for cities	three-element lists	list literals and element selection

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat
Implement selectors and constructor for cities	three-element lists	list literals and element selection

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat
Implement selectors and constructor for cities	three-element lists	list literals and element selection

Implementation of lists

Abstraction Barriers

Parts of the program that...	Treat city as	Using ...
Use cities to perform computation	whole data values	distance, closer_city
Create cities or implement cities operations	combination of 3 elements	make_city, get_lon, get_lat
Implement selectors and constructor for cities	three-element lists	list literals and element selection

Implementation of lists



Violating Abstraction Barriers

```
closer_city(34, 67, ['Moscow', 45, 43], ['Paris', 65, 78])
```

```
def distance(x, y):  
    return sqrt((x[1] - y[1])** 2 + (x[2] - y[2])**2))
```

How many violations can you spot?

A: 0

B: 1

C: 2

D: 3

E: 4



Violating Abstraction Barriers

```
closer_city(34, 67, ['Moscow', 45, 43], ['Paris', 65, 78])
```

Does not use
constructors

Does not use
constructors

```
def distance(x, y):  
    return sqrt((x[1] - y[1])** 2 + (x[2] - y[2])**2))
```

How many violations can you spot?

A: 0

B: 1

C: 2

D: 3

E: 4



Violating Abstraction Barriers

```
closer_city(34, 67, ['Moscow', 45, 43], ['Paris', 65, 78])
```

Does not use
constructors

Does not use
constructors

```
def distance(x, y):
```

```
    return sqrt((x[1] - y[1])**2 + (x[2] - y[2])**2)
```

No selectors!

No selectors!

How many violations can you spot?

A: 0

B: 1

C: 2

D: 3

E: 4



Violating Abstraction Barriers

```
closer_city(34, 'Paris', 65, 78])
```

```
def distance(x, y):  
    return sqrt((x[2] - y[2])**2)
```

How many violations?

A: 0 B: 1



Does not use
constructors

No selectors!

Violating Abstraction Barriers

(Thank you, John. It was fun :))



Time for fun!



Check point

```
lst = [1, -2, -3, 4, 5]
def func1(x):
    return x < 2

it = filter(func1, lst)
print(list(it))
```

What is the output of the code shown?

A: [1, 4, 5]

B: Error

C: [-2, -3]

D: [1, -2, -3, None, None]

E: None of the above



Check point

```
lst = [1, -2, -3, 4, 5]
```

```
def func1(x):  
    return x < -1
```

```
it = map(func1, lst)  
print(list(it))
```

What is the output of the code shown?

A: [False, False, False, False, False]

B: [False, True, True, False, False]

C: [True, False, False, True, True]

D: [True, True, True, True, True]

E: None of the above



Questions from last week video lecture

```
d = { (1,2):1, (2,3):2 }
```

```
print(d[1,2])
```

What Will Be The Output

A: `KeyError`

B: `1`

C: `{(2,3):2}`

D: `{(1,2):1}`

E: `None of the above`



Question based on last week video lecture

```
basket = {}
```

```
def addone(index):  
    if index in basket:  
        basket[index] += 1  
    else:  
        basket[index] = 1
```

```
addone('Apple')  
addone('Banana')  
addone('apple')  
addone('Apple')  
print (len(basket))
```

What Will Be The Output

A: 1

B: 2

C: 3

D: 4

E: None of the above



Question based on last week video lecture

```
def problem(lst, index):  
    try:  
        average = sum(lst)/len(lst)  
        last_elem = lst[index]  
    except IndexError as e:  
        print('Index is wrong')  
    except ZeroDivisionError as e:  
        print("Can't divide by a 0")  
  
    print("I'm safe")  
  
problem( [1, 2, 3], 3)
```

- A: Index is wrong
- B: Can't divide by a 0
- C: Can't divide by a 0
I'm safe
- D: Index is wrong
I'm safe
- E: None of the above



Question based on last week video lecture

```
def problem(lst, index):  
    try:  
        average = sum(lst)/len(lst)  
        last_elem = lst[index]  
    except IndexError as e:  
        print('Index is wrong')  
    except ZeroDivisionError as e:  
        print("Can't divide by a 0")  
  
    print("I'm safe")  
  
problem ( [], 17)
```

- A: Index is wrong
- B: Can't divide by a 0
- C: Can't divide by a 0
I'm safe
- D: Index is wrong
I'm safe
- E: None of the above

Question

- Is there a way in Python to call filter on a list where the filtering function has a *number of formal parameters* **bound** during the call ?

```
def func (a, b, c):  
    return a + b < c
```

```
lst = [10, 20, 30, 40]  
filter(func(a=10, c=35), lst) #Want to happen
```

```
def make_filter(a, c):  
    def my_filter(b):  
        return a + b < c  
    return my_filter  
  
filt = make_filter(10, 35)  
lst = [10, 20, 30, 40]  
  
list(filter(filt, lst))
```

```
def func (a, b, c):  
    return a + b < c  
  
lst = [10, 20, 30, 40]  
  
list(filter(lambda x: func(10, x, 35), lst))
```

Mutable Data

Mutability

- **Immutable** – the value of the object cannot be changed:
 - integers, floats, booleans
 - strings, tuples
- **Mutable** – the value of the object can be changed:
 - Lists
 - Dictionaries

Mutability

- **Immutable** – the value of the object cannot be changed:
 - integers, floats, booleans
 - strings, tuples
- **Mutable** – the value of the object can be changed:
 - Lists
 - Dictionaries

```
>>> alist = [1,2,3,4]
>>> alist
[1, 2, 3, 4]
>>> alist[2]
3
>>> alist[2] = 'elephant'
>>> alist
[1, 2, 'elephant', 4]
```


Mutability

- **Immutable** – the value of the object cannot be changed:
 - integers, floats, booleans
 - strings, tuples
- **Mutable** – the value of the object can be changed:
 - Lists
 - Dictionaries

```
>>> alist = [1,2,3,4]
>>> alist
[1, 2, 3, 4]
>>> alist[2]
3
>>> alist[2] = 'elephant'
>>> alist
[1, 2, 'elephant', 4]
```

```
>>> adict = {'a':1, 'b':2}
>>> adict
{'b': 2, 'a': 1}
>>> adict['b']
2
>>> adict['b'] = 42
>>> adict['c'] = 'elephant'
>>> adict
{'b': 42, 'c': 'elephant', 'a': 1}
```


From value to storage ...

- A variable assigned a compound value (object) is a **reference** to that object.
- Mutable object can be *changed* but the variable(s) still refer to it

From value to storage ...


- A variable assigned a compound value (object) is a **reference** to that object.
- Mutable object can be *changed* but the variable(s) still refer to it

```
x = [1, 2, 3]  
y = 6  
x [1] = y  
x [1]
```



From value to storage ...

- A variable assigned a compound value (object) is a **reference** to that object.
- Mutable object can be *changed* but the variable(s) still refer to it



Examples

```
x = [1, 2, 3]
y = x
print (y)
x[1] = 11
print (y)
```

```
x = [1, 2]
y = [x, x, x]
print (y)
x[1] = 3
print (y)
y[2] = [1, 3]
print (y[0] == y[2])
print (y[0] is y[2])
```

Copies, 'is' and '=='

```
>>> alist = [1, 2, 3, 4]
```

```
>>> alist == [1, 2, 3, 4] # Equal values?
```

True

```
>>> alist is [1, 2, 3, 4] # same object?
```

False

```
>>> blist = alist # assignment refers
```

```
>>> alist is blist # to same object. Shallow copy
```

True

```
>>> blist = list(alist) # type constructors copy
```

```
>>> blist is alist # Deep copy
```

False

Copies, 'is' and '=='

```
>>> alist = [1, 2, 3, 4]
```

```
>>> alist == [1, 2, 3, 4] # Equal values?
```

True

```
>>> blist = alist[ : ] # so does slicing
```

```
>>> blist is alist
```

False

```
>>> blist
```

```
[1, 2, 3, 4]
```

```
>>>
```

Identity Operators: is is not

Identity

`<exp0> is <exp1>`

evaluates to `True` if both `<exp0>` and `<exp1>` evaluate to the same object

Identity Operators

Identity

`<exp0> is <exp1>`

evaluates to `True` if both `<exp0>` and `<exp1>` evaluate to the same object

Equality

`<exp0> == <exp1>`

evaluates to `True` if both `<exp0>` and `<exp1>` evaluate to equal values

Identity Operators

Identity

`<exp0> is <exp1>`

evaluates to `True` if both `<exp0>` and `<exp1>` evaluate to the same object

Equality

`<exp0> == <exp1>`

evaluates to `True` if both `<exp0>` and `<exp1>` evaluate to equal values

Identical objects are always equal values

Parameter passing: Output?

```
def test (x):  
    x = x + 1  
  
y = 10  
  
test(y)  
  
print(y)
```

A: 10

B: 11

C: None

D: Error

E: I do not know

Parameter passing: Output?

```
def test (x):  
    x[0] = x[0] + 1  
  
y = [1, 2, 3]  
  
test(y)  
  
print(y)
```

A: [1, 2, 3]

B: [2, 2, 3]

C: None

D: Error

E: I do not know