

Problem Solving with AI Techniques

Reasoning under Uncertainty

Paul Weng

UM-SJTU Joint Institute

VE593, Fall 2018



JOINT INSTITUTE
交大密西根学院

- 1 Reasoning under Uncertainty
- 2 Example
- 3 Graphical Models
- 4 Applications

Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions

Why Reasoning under Uncertainty?


- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:

Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world


Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world
 - Observation comes from imperfect sensors




Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world
 - Observation comes from imperfect sensors
 - Data often imprecise, missing or contradictory




Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world
 - Observation comes from imperfect sensors
 - Data often imprecise, missing or contradictory
 - World is stochastic?




Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world
 - Observation comes from imperfect sensors
 - Data often imprecise, missing or contradictory
 - World is stochastic?
- Uncertainty can be handled with probability distribution



Why Reasoning under Uncertainty?

- Previous search algorithms requires full observability of states and generally deterministic actions
- Knowledge is generally uncertain:
 - Partial/non observable world
 - Observation comes from imperfect sensors
 - Data often imprecise, missing or contradictory
 - World is stochastic?
- Uncertainty can be handled with probability distribution
- Previous search algos are therefore not directly applicable anymore



What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation
 - **Diagnostic:** Given some effect, what are the probable cause?

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation
 - **Diagnostic:** Given some effect, what are the probable cause?
 - **Prediction:** Given some cause, what are the probable consequence?

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation
 - **Diagnostic:** Given some effect, what are the probable cause?
 - **Prediction:** Given some cause, what are the probable consequence?
 - **Intercausal:** Given some cause & effect, what about other causes?

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation
 - **Diagnostic:** Given some effect, what are the probable cause?
 - **Prediction:** Given some cause, what are the probable consequence?
 - **Intercausal:** Given some cause & effect, what about other causes?
 - **Mixed:** Combination of two or more of the above

What is Reasoning under Uncertainty?

- A state is an assignment of $X_{1:n} = (X_1, \dots, X_n)$
- Probability distribution $\mathbb{P}(X_{1:n})$ represents uncertainty about possible states
- Given \mathbb{P} , we can obtain the probability of any event
- We can also compute the conditional probability of any event, i.e., we can update our belief after some observation
 - **Diagnostic:** Given some effect, what are the probable cause?
 - **Prediction:** Given some cause, what are the probable consequence?
 - **Intercausal:** Given some cause & effect, what about other causes?
 - **Mixed:** Combination of two or more of the above
- **Issue:** memory requirement to store \mathbb{P}

1 Reasoning under Uncertainty

2 Example

3 Graphical Models

4 Applications

Medical Diagnosis of Lung Cancer

| Variables | Type | Values |
|---------------------------|---------|---------------|
| Pollution (P) | Binary | {Low, High} |
| Smoker (S) | Boolean | {True, False} |
| Cancer (C) | Boolean | {True, False} |
| Dyspnoea ¹ (D) | Boolean | {True, False} |
| X-ray (X) | Binary | {Pos., Neg.} |

- Assume we have probability distribution $\mathbb{P}(P, S, C, D, X)$ (e.g., obtained from data).

¹Short breath

Medical Diagnosis of Lung Cancer

| Variables | Type | Values |
|---------------------------|---------|---------------|
| Pollution (P) | Binary | {Low, High} |
| Smoker (S) | Boolean | {True, False} |
| Cancer (C) | Boolean | {True, False} |
| Dyspnoea ¹ (D) | Boolean | {True, False} |
| X-ray (X) | Binary | {Pos., Neg.} |

- Assume we have probability distribution $\mathbb{P}(P, S, C, D, X)$ (e.g., obtained from data).
- We can then easily compute probabilities for any event:
e.g., $\mathbb{P}(C = \text{True})$, $\mathbb{P}(D = \text{True})$, $\mathbb{P}(C = \text{True}, S = F)$...

¹Short breath

Medical Diagnosis of Lung Cancer

| Variables | Type | Values |
|---------------------------|---------|---------------|
| Pollution (P) | Binary | {Low, High} |
| Smoker (S) | Boolean | {True, False} |
| Cancer (C) | Boolean | {True, False} |
| Dyspnoea ¹ (D) | Boolean | {True, False} |
| X-ray (X) | Binary | {Pos., Neg.} |

- Assume we have probability distribution $\mathbb{P}(P, S, C, D, X)$ (e.g., obtained from data).
- We can then easily compute probabilities for any event:
e.g., $\mathbb{P}(C = \text{True})$, $\mathbb{P}(D = \text{True})$, $\mathbb{P}(C = \text{True}, S = F)$...
- Even better, we can compute conditional probabilities:
e.g., $\mathbb{P}(C = \text{True} \mid D = \text{True})$, $\mathbb{P}(C = \text{False} \mid X = \text{True})$,
 $\mathbb{P}(C = \text{True} \mid S = \text{True}, X = \text{False})$...

¹Short breath

Memory Requirement

- How many values do we need to store $\mathbb{P}(P, S, C, D, X)$?

Memory Requirement

- How many values do we need to store $\mathbb{P}(P, S, C, D, X)$?
- In general, $2^n - 1$ for n boolean variables

Memory Requirement

- How many values do we need to store $\mathbb{P}(P, S, C, D, X)$?
- In general, $2^n - 1$ for n boolean variables
- We can exploit (conditional) independences to reduce this requirement
e.g., Assume:

$$\mathbb{P}(P, S, C, D, X) = \mathbb{P}(P) \times \mathbb{P}(S) \times \mathbb{P}(C | P, S) \times \mathbb{P}(D | C) \times \mathbb{P}(X | C)$$

what is the space requirement now?

Memory Requirement

- How many values do we need to store $\mathbb{P}(P, S, C, D, X)$?
- In general, $2^n - 1$ for n boolean variables
- We can exploit (conditional) independences to reduce this requirement e.g., Assume:

$$\mathbb{P}(P, S, C, D, X) = \mathbb{P}(P) \times \mathbb{P}(S) \times \mathbb{P}(C | P, S) \times \mathbb{P}(D | C) \times \mathbb{P}(X | C)$$


what is the space requirement now?

- Huge saving in large domains with many (conditional) independences


- 1 Reasoning under Uncertainty
- 2 Example
- 3 Graphical Models**
- 4 Applications

Graphical Models

- What is a **graphical model**?
 - Graphical notation to express all the (random) variables and their (conditional) (in)dependencies
 - (Compact) representation of a joint distributions over the variables
- Two basic variants:
 - Directed model: Bayesian network or belief network
 - Undirected model: factor graph or Markov random field



$$P(x_{1:6}) = P(x_1) P(x_2|x_1) P(x_3|x_1) P(x_4|x_2) P(x_5|x_3) P(x_6|x_2, x_5)$$



$$P(x_{1:6}) = f_1(x_1, x_2) f_2(x_3, x_1) f_3(x_2, x_4) f_4(x_3, x_5) f_5(x_2, x_5, x_6)$$

From Marc Toussaint

Why are Graphical Models Useful?

- Why do we need graphical models?
 - Real problems have many variables
 - Real problems have some structure (i.e., conditional probabilistic independences)
- What can we do with graphical models?
 - Are two variables independent given a third one?
 - What is the probability of some event?
 - What is the probability of some event given some observation?

- 1 Reasoning under Uncertainty
- 2 Example
- 3 Graphical Models
- 4 Applications**

Diagnostics

- Medical diagnosis
- Printer troubleshooting




Heckerman and Breese, 1996

- Equipment failure
- Intelligent tutoring

Prediction and decision-making

- Failure prediction in satellite




Bottone et al., 2008

- Disease prediction
- Price evolution in stockmarket
- With utilities, optimal decisions with influence diagrams
- More about this, in the last part of this course

Anomaly Detection

- Software health management in UAVs




Schumann et al., 2013

- Breakdown detection
- Fraud detection in banking and finance
- Spam detection

Machine Learning Models

- Any probabilistic ML model could exploit Bayes net
- Many applications in computer vision, speech recognition, bioinformatics...
- e.g., Latent Dirichlet Allocation in NLP



α parameter of Dirichlet prior of per-document topic distribution

β parameter of Dirichlet prior of per-topic word distribution

θ_m topic distribution for document m

ϕ_k word distribution for topic k

z_{mn} topic for n -th word for document m

w_{mn} n -th word for document m