

Build LP Panel — Direct-From-Raw Strategy & Stepwise Debug Plan

This report documents **exactly how** we will construct the six LP time series directly from the three raw data sources (no intermediate “normalization” layer). It also lays out a **stepwise build-and-debug plan** so we only proceed to the next phase when the current one passes deterministic QA gates.

1) Objective

Construct six LP series that respect the pre/post-reform data grain while keeping the economic definition $LP = w \times \Pi$ intact:

1. **Haifa (port) — Monthly:** 2018-01 → 2021-08
2. **Ashdod (port) — Monthly:** 2018-01 → 2021-08
3. **Haifa-Legacy (terminal) — Quarterly:** 2021-Q3 → 2024-Q4
4. **Haifa-SIPG/Bayport (terminal) — Quarterly:** 2021-Q3 → 2024-Q4
5. **Ashdod-Legacy (terminal) — Quarterly:** 2021-Q3 → 2024-Q4
6. **Ashdod-HCT/ACH/TIL (terminal) — Quarterly:** 2021-Q3 → 2024-Q4

Ignore all rows for **Eilat** and **All Ports** everywhere.

2) Inputs (no normalization layer)

A) Monthly tons (ports & terminals)

Path: Data/Output/monthly_output_by_1000_tons_ports_and_terminals.tsv

Columns: PortOrTerminal, Month-Year, tons_k

- $PortOrTerminal \in \{Ashdod, Haifa\} \rightarrow$ **port-level** monthly tons.
- $PortOrTerminal \in \{Ashdod\ HCT, Haifa\ SIPG\} \rightarrow$ **terminal-level** monthly tons.
- $PortOrTerminal = All\ Ports \rightarrow$ drop.
- **Units:** tons = $tons_k \times 1000$.
- **Port-month precedence rule:** if *any* terminal rows exist for $(port, year, month)$, define $tons_port_m = \sum_terminal\ tons_i_m$; otherwise $tons_port_m = tons_portrow_m$ (the single port row).

B) TEU mixed frequency (monthly & quarterly in one file)

Path: Data/Output/teu_monthly_plus_quarterly_by_port.tsv

Columns: Port, Period, Freq, Year, MonthIndex, TEU_thousands, TEU

- Use TEU when present; otherwise $TEU := TEU_thousands \times 1000$.
- **Monthly TEU (pre-reform ports):** $Freq = 'Monthly' \ \& \ Port \in \{Ashdod, Haifa\} \rightarrow (port, year, month, TEU_port_m)$.
- **Quarterly TEU (post-reform terminals):** $Freq = 'Quarterly' \ \& \ Port \in \{Haifa, Haifa\ SIPG, Ashdod, Ashdod\ HCT\} \rightarrow$ map to terminal names (see below) and parse $(port, terminal, year, quarter, TEU_i_q)$.
- **Port-quarter TEU:** $TEU_port_q = \sum_{terminal} TEU_i_q$ within $(port, year, quarter)$.

C) Terminal×month Labor & Π

Path: Data/L_proxy/L_Proxy.tsv

Key columns: port, terminal, year, month, quarter, L_hours_i_m, Pi_teu_per_hour_i_y, plus TEU_i_m, share_i_p_q for mix computation.

- Grain is **terminal × month**.
- Π_{iy} (Pi_teu_per_hour_i_y) is terminal-year intrinsic productivity.
- **Port labor** at month = $\sum_i L_hours_i_m$ across terminals.

Terminal name mapping (ensure consistent joins)

- TEU Port='Haifa SIPG' \rightarrow L_Proxy terminal='Haifa-Bayport'
- TEU Port='Ashdod HCT' \rightarrow L_Proxy terminal='Ashdod-HCT'
- TEU Port='Haifa' (Quarterly) \rightarrow L_Proxy terminal='Haifa-Legacy'
- TEU Port='Ashdod' (Quarterly) \rightarrow L_Proxy terminal='Ashdod-Legacy'

3) LP math (unchanged)

3.1 Monthly port LP (pre-reform)

- **Ratio:** $r_{\{p,m\}} = tons_{\{p,m\}} / TEU_{\{p,m\}}$.
- **Winsorize & Rebase by (port,year):** winsorize r to $[1\%, 99\%]$; rebase to mean 1 $\Rightarrow w_{\{p,m\}}$.
- **Mix base Π (month):** quarter-constant terminal shares ($shares_{\{i,p,q\}}$ from TEU_i_m or $share_i_p_q$) times Π_{iy} , broadcast to months $\Rightarrow \Pi_{\{p,m\}}$.
- **LP:** $LP_{\{p,m\}} = w_{\{p,m\}} \times \Pi_{\{p,m\}}$.
- **Diagnostic identity:** $LP_id = TEU_{\{p,m\}} / \sum_i L_hours_{\{i,m\}}$ when both positive.

3.2 Quarterly terminal LP (post-reform)

- **Port ratio per quarter:** $r_{\{p,q\}} = (\sum_{m \in q} tons_{\{p,m\}}) / TEU_{\{p,q\}}$ where $TEU_{\{p,q\}} = \sum_i TEU_{\{i,q\}}$.

- Winsorize & Rebase by (port,year): $\Rightarrow w_{\{p,q\}}$.
- Terminal LP: $LP_{\{i,q\}} = w_{\{p(i),q\}} \times \Pi_{iy}$.

4) Output artifacts (six atomic series + optional long panel)

- 1) LP_Haifa_port_month.tsv (2018-01..2021-08)
- 2) LP_Ashdod_port_month.tsv (2018-01..2021-08)
- 3) LP_Haifa_Legacy_quarter.tsv (2021-Q3..2024-Q4)
- 4) LP_Haifa_SIPG_quarter.tsv (2021-Q3..2024-Q4)
- 5) LP_Ashdod_Legacy_quarter.tsv (2021-Q3..2024-Q4)
- 6) LP_Ashdod_HCT_quarter.tsv (2021-Q3..2024-Q4)

Each row includes: port, terminal (if any), year, month (if monthly), month_index (if monthly), quarter (if quarterly), TEU, tons, w, w_source $\in \{\text{monthly, quarterly}\}$, Pi, LP, and provenance (tons_source).

Optional convenience: LP_panel_long.tsv stacking the six with series_id and freq $\in \{M, Q\}$.

5) Stepwise Build-and-Debug Plan (gated progression)

We move in **four gated stages**. Each stage writes its own outputs and a QA report. We proceed **only if the QA passes**. If a stage fails, we fix inputs/logic and re-run that stage; later stages never run on bad prerequisites.

Stage 0 — Configuration & Guards

- Set constants: cutover month (2021-09 \rightarrow monthly ends at 2021-08), ranges, winsor bounds (1%, 99%).
- Define terminal mapping dictionary.
- **Guardrails activated:** drop Eilat & All Ports; enforce month $\in [1..12]$, quarter $\in \{Q1..Q4\}$.
- **Deliverables:** _meta_config.json (params), _stage0_ok marker.

QA-0 (must-pass): - Terminal mapping covers all terminals seen in TEU quarterly and L_Proxy.
- No unexpected ports/terminals after filtering.

Stage 1 — Build tons tables (from monthly tons file only)

- Parse Month-Year \rightarrow (year, month); month_index = year*12 + month.
- Build **terminal-month tons** for {Ashdod-HCT, Haifa-SIPG}.
- Build **port-month tons** with precedence: sum terminals if present else port row.
- Aggregate **port-quarter tons**: tons_port_q = $\sum_{m \in q} \text{tons_port_m}$.
- **Deliverables:**

- `S1_port_month_tons.tsv` (unique `(port, year, month)`)
- `S1_port_quarter_tons.tsv` (unique `(port, year, quarter)`)
- `S1_terminal_month_tons.tsv` (unique `(port, terminal, year, month)`)
- `S1_qa.tsv`

QA-1 (must-pass): - Keys unique at their grains.

- No Eilat / All Ports rows.

- For months with terminal tons present, port-month tons equals the sum of terminals.

Stage 2 — Build TEU tables (from TEU mixed-frequency file only)

- **Monthly port TEU:** `Freq='Monthly'` & `Port ∈ {Ashdod, Haifa}`, keep only months $\leq 2021-08$.
- **Quarterly terminal TEU:** `Freq='Quarterly'` & `Port ∈ {Haifa, Haifa SIPG, Ashdod, Ashdod HCT}`, map to terminals.
- **Build port-quarter TEU:** `TEU_port_q = \sum_i TEU_i_q` per `(port, year, quarter)`.
- **Deliverables:**
 - `S2_port_month_teu.tsv` (pre-reform monthly)
 - `S2_terminal_quarter_teu.tsv` (post-reform quarterly)
 - `S2_port_quarter_teu.tsv` (sum of terminals)
 - `S2_qa.tsv`

QA-2 (must-pass): - Keys unique at their grains.

- For each `(port, year, quarter)` in terminal TEU, the port-quarter TEU equals the sum of terminals.

- No unexpected terminals after mapping.

Stage 3 — Load L_Proxy (terminal×month labor & Π)

- Standardize terminals via mapping; enforce `year, month` Int64; add `quarter` if missing.
- **Deliverables:**
 - `S3_lproxy_clean.tsv` (selected columns only)
 - `S3_qa.tsv`

QA-3 (must-pass): - Keys unique at `(port, terminal, year, month)`.

- Π available for expected terminal-years; basic coverage table printed by `(port, terminal, year)`.

Stage 4 — Build LP series

4A. Monthly port LP (Haifa & Ashdod, 2018-01..2021-08)

- Merge `S1_port_month_tons` with `S2_port_month_teu` for months $\leq 2021-08$.
- Compute `r_{p,m} = tons/TEU` → winsorize & rebase by `(port, year)` $\Rightarrow w_{p,m}$.
- Build monthly `$\Pi_{p,m}$` from `S3_lproxy_clean`: quarter-constant terminal shares $\times \Pi_{iy}$.
- `LP_{p,m} = w \times \Pi`; compute optional `LP_id = TEU / \sum_i L_hours`.

- **Deliverables:** LP_Haifa_port_month.tsv, LP_Ashdod_port_month.tsv, S4A_qa.tsv.

QA-4A (must-pass): - Keys unique.

- Annual preservation: within (port, year), $|\text{mean}(\text{LP}) - \text{mean}(\Pi)| \leq \epsilon$ for years with Π coverage.
- Winsorized w has mean 1 by (port, year).

4B. Quarterly terminal LP (2021-Q3..2024-Q4)

- From S1_port_quarter_tons & S2_port_quarter_teu: $r_{\{p,q\}} = \text{tons_port_q} / \text{TEU_port_q} \rightarrow$ winsorize & rebase by (port, year) $\Rightarrow w_{\{p,q\}}$.
- For each terminal (Legacy/HCT/SIPG): $\text{LP}_{\{i,q\}} = w_{\{p,q\}} \times \Pi_{iy}$ (Π_{iy} from S3_lproxy_clean by terminal-year of q).
- **Deliverables:**
 - LP_Haifa_Legacy_quarter.tsv
 - LP_Haifa_SIPG_quarter.tsv
 - LP_Ashdod_Legacy_quarter.tsv
 - LP_Ashdod_HCT_quarter.tsv
 - S4B_qa.tsv

QA-4B (must-pass): - Keys unique.

- w mean 1 by (port, year) on the quarterly groups.
- If $\text{TEU_port_q} \leq 0$ or missing $\rightarrow w$ NA \rightarrow LP NA (and logged).
- Coverage table lists counts per terminal by year.

6) Error Handling & Guardrails

- **Drop** any row with port='Eilat' or PortOrTerminal='All Ports'.
- **No double-counting:** port-month tons via precedence rule (sum terminals if present).
- **TEU value** selection: use TEU; fallback to $1000 \times \text{TEU_thousands}$ only if TEU is missing.
- **DTypes:** keep year, month as Int64; quarter $\in \{Q1..Q4\}$; ratios as float64.
- **Key uniqueness** enforced at each stage; failure stops the pipeline and writes a small error sample to the stage QA.
- **Winsorization:** [1%, 99%] default (configurable), per (port, year); **Rebase** makes $\text{mean}(w)=1$ within group.
- **NA logic:** ratios set to NA when numerator/denominator invalid; LP NA when either w or Π NA.

7) Deliverables & Naming

- Stage outputs: S1_*.tsv, S2_*.tsv, S3_*.tsv, S4A_qa.tsv, S4B_qa.tsv.
- Final six LP files named exactly as listed in Section 4.
- Optional: LP_panel_long.tsv stacking all six with series_id and freq.
- Per-run metadata in _meta_lp_build.json (row counts, parameter hash, input hashes).

8) CLI & Config (suggested)

```
python Build_LP_Panel.py
--tons "Data/Output/monthly_output_by_1000_tons_ports_and_terminals.tsv"
--teu "Data/Output/teu_monthly_plus_quarterly_by_port.tsv"
--lproxy "Data/L_proxy/L_Proxy.tsv"
--out "Data/LP"
--cutover_month 2021-09
--winsor_low 0.01 --winsor_high 0.99
```

9) Why this plan avoids prior pitfalls

- **No schema inference** from ambiguous columns (e.g., `Freq`, `MonthIndex`) — we read exactly what we need, with explicit filters.
- **No quarter inference** — we only use rows declared `Quarterly` for terminal TEU and build port quarters by summing terminals.
- **No double counting** of tons — port months are built from terminals when present.
- **Strict gates** at each stage — we never build LP on top of misaligned inputs.

This plan keeps the economics ($LP = w \times \Pi$) intact and gives us **deterministic checkpoints** so we can debug issues immediately at their source before propagating them into the LP series.