

In []:

```
import h5py

import numpy as np
import scipy
import matplotlib.pyplot as plt
from scipy import signal
import pandas as pd
import scipy.sparse as sparse
import os

indir_name = "C:/CSES/file/"

outdir_name = "C:/CSES/plot/"

ext = ('.h5')

def getData(data):
    Bw = 51200 * 2 / 1024
    data = pd.DataFrame(data)

    matrix = []
    for i in range(len(data)):
        matrix.append(data.iloc[i])
    matrix = np.array(matrix)
    data_t = np.empty(shape=(matrix.shape[0], matrix.shape[1]))
    for i in range(0, matrix.shape[0]):
        meanX_b = np.mean(matrix[i])
        data_t[i] = matrix[i] - meanX_b

    M_b = data_t.shape[1]
    hamming_b = signal.get_window("hamming", M_b)
    FFT_low = np.array([scipy.fft.fft(data_t[i] * hamming_b) for i in range(0, data_t.shape[0])])
    out = np.abs(FFT_low.T[:1024]) ** 2
    outX_b = 400 + 20 * np.log10(out / Bw)

    return outX_b

def powerSpectrum(pow):
    powerX = 400 + 20 * np.log10(pow)

    return powerX

def tempArray(data):
    temp_df_x = []
    for i in range(len(df)):
        if (df.iloc[i].WORKMODE == 2):
            temp_df_x.append(df[data].iloc[i])
        else:
            temp_df_x.append(np.empty(np.array(df[data].iloc[i]).shape))
            temp_df_x[i][:] = np.NaN
    temp_df_x = np.array(temp_df_x)
    return temp_df_x

def Amplitude(arr):
    mask = ~np.isnan(arr[row])
    dataX = arr[row][mask]
    for i in range(0, arr.shape[0]):
        if i != row:
            mask = ~np.isnan(arr[i])
            arr[i][mask] = np.nan
    return arr

def dataframeBurstBuild(arrX, arrY, arrZ):
    df_burst = pd.DataFrame(list(zip(arrX[row, :], arrY[row, :], arrZ[row, :], GEO_LAT, GEO_LON)),
                             columns=['arrXb',
                                      'arrYb',
                                      'arrZb', 'GEO_LAT',
                                      'GEO_LON'])

    df_burst['DATE2'] = DATE2

    arraysXb.append([df_burst['arrXb'].to_numpy(),
                    OrbitNumber + '_' + DATE[0]])

    arraysYb.append([df_burst['arrYb'].to_numpy(),
                    OrbitNumber + '_' + DATE[0]])

    arraysZb.append([df_burst['arrZb'].to_numpy(),
                    OrbitNumber + '_' + DATE[0]])

    return arraysXb, arraysYb, arraysZb, df_burst

def dataframeBuild(arrX, arrY, arrZ):
    df['arrX'] = arrX.T[row, :].tolist()
    df['arrY'] = arrY.T[row, :].tolist()
    df['arrZ'] = arrZ.T[row, :].tolist()

    arraysX.append([df['arrX'].to_numpy(), OrbitNumber + '_' + DATE[0]])

    arraysY.append([df['arrY'].to_numpy(), OrbitNumber + '_' + DATE[0]])

    arraysZ.append([df['arrZ'].to_numpy(), OrbitNumber + '_' + DATE[0]])
    return arraysX, arraysY, arraysZ, df

def readFile(f):
    UTC_TIME = f["UTC_TIME"]()[0][:, 0]
    GEO_LAT = f["GEO_LAT"]()[0][:, 0]
    GEO_LON = f["GEO_LON"]()[0][:, 0]
    #ALT = f["ALTITUDE"]()[0][:, 0]
    Workmode = f["WORKMODE"]()[0][:, 0]
    #MAG_LAT = f["MAG_LAT"]()[0][:, 0]
    #MAG_LON = f["MAG_LON"]()[0][:, 0]
    #VERSE_TIME = f["VERSE_TIME"]()[0][:, 0]
    A131_W = f["A131_W"]()[0]
    A132_W = f["A132_W"]()[0]
    A133_W = f["A133_W"]()[0]
    A131_P = f["A131_P"]()[0]
    A132_P = f["A132_P"]()[0]
    A133_P = f["A133_P"]()[0]
    columns = list(f.keys())
    df = pd.DataFrame({})
    for column in columns:
        try:
```

```

data = np.array(f[column])
if data.shape[1] == 1:
    df[column] = data.flatten()
elif column.endswith('.P'):
    mat = sparse.coo_matrix(data, shape=data.shape)
    df[column] = mat.toarray().tolist()
elif column == "A131_W":
    selected_data = np.array(data[0:len(Workmode), :])
    mat = sparse.coo_matrix(selected_data, shape=selected_data.shape)
    df[column] = mat.toarray().tolist()
elif column == "A132_W":
    selected_data = np.array(data[0:len(Workmode), :])
    mat = sparse.coo_matrix(selected_data, shape=selected_data.shape)
    df[column] = mat.toarray().tolist()
elif column == "A133_W":
    selected_data = np.array(data[0:len(Workmode), :])
    mat = sparse.coo_matrix(selected_data, shape=selected_data.shape)
    df[column] = mat.toarray().tolist()
else:
    print(column + ' skipped')
except Exception as e:
    pass
S_burst = df[df.WORKMODE == 2]
df['DATE_TIME'] = pd.to_datetime(df.UTC_TIME, format='%Y%m%d%H%M%S%f')
DATE = df.DATE_TIME.map(lambda x: x.strftime('%Y-%m-%d'))
DATE2 = df.DATE_TIME.map(lambda x: x.strftime('%Y-%m'))
#df['DATE2'] = df.DATE_TIME.map(lambda x: x.strftime('%Y-%m'))

return GEO_LAT, GEO_LON, A131_W, A132_W, A133_W, A131_P, A132_P, A133_P, DATE, df, S_burst, DATE2

```

```

In [ ]:
def minmax(array):
    vals_mean = []
    arraysXdf = pd.DataFrame(array)

    for i, date in enumerate(df_complete.DATE2.unique()):

        arraysXdf_sel = arraysXdf[arraysXdf[1].str.contains(date)]

        arraysX_table = pd.DataFrame()
        for j in arraysXdf_sel.index:
            row = pd.DataFrame(arraysXdf_sel[0][j]).transpose()
            arraysX_table = pd.concat([arraysX_table, row], axis=0)

        arraysX_table.reset_index()

        vals_mean = arraysX_table.mean().transpose().to_numpy() + (i + 1) * (-50)

        max_globalX=(np.nanmax(arraysX_table.transpose()).max()
max_global_meanX=(np.nanmax(vals_mean)).max()
min_globalX = (np.nanmin(arraysX_table.transpose()).min()
min_global_meanX = (np.nanmin(vals_mean)).min()

return max_globalX,max_global_meanX,min_globalX,min_global_meanX

```

```

In [ ]:
arraysX = []

arraysY = []

arraysZ = []

arraysXb = []

arraysYb = []

arraysZb = []

dir_name = ""
file_name = dir_name + indir_name
ext = ('.h5')

sampleFreq=51200
nRow=1024
maxFreq=sampleFreq/2
freqRow=maxFreq/nRow
freq_array=np.arange(100,2600,100)
for i in freq_array:
    for path, dir, files in os.walk(file_name):
        for name in files:
            if name.endswith('.h5'):
                OrbitNumber = name.split("_")[6]
                with h5py.File(str(file_name) + str(name), "r") as f:

                    GEO_LAT, GEO_LON, A131_W, A132_W, A133_W, A131_P, A132_P, A133_P, DATE, df, S_burst, DATE2 = readFile(f)
                    f.close()

                    row=int(i/freqRow)
                    powerX = powerSpectrum(A131_P)
                    powerY = powerSpectrum(A132_P)
                    powerZ = powerSpectrum(A133_P)

                    temp_df_x=tempArray('A131_W')
                    outX_b = getData(temp_df_x)

                    temp_df_y=tempArray('A132_W')

                    outY_b = getData(temp_df_y)

                    temp_df_z=tempArray('A133_W')

                    outZ_b = getData(temp_df_z)

                    outX_b = Amplitude(outX_b)
                    outY_b = Amplitude(outY_b)
                    outZ_b = Amplitude(outZ_b)

                    arraysX,arraysY,arraysZ,df=dataframeBuild(powerX,powerY,powerZ)

                    arraysXb,arraysYb,arraysZb,df_burst=dataframeBurstBuild(outX_b,outY_b,outZ_b)

```

```

In [ ]:
max_globalX,max_global_meanX,min_globalX,min_global_meanX=minmax(arraysX)
max_globalY,max_global_meanY,min_globalY,min_global_meanY=minmax(arraysY)
max_globalZ,max_global_meanZ,min_globalZ,min_global_meanZ=minmax(arraysZ)
max_globalXb,max_global_meanXb,min_globalXb,min_global_meanXb=minmax(arraysXb)
max_globalYb,max_global_meanYb,min_globalYb,min_global_meanYb=minmax(arraysYb)
max_globalZb,max_global_meanZb,min_globalZb,min_global_meanZb=minmax(arraysZb)

```